




## Balanced Trees

Section 3.3




## 2-3 Trees

Balance using really big nodes

## Binary Search Tree Issues

- Binary Search Trees have the ability to find data in  $O(\log n)$
- This is incredibly more efficient than a linear search of  $O(n)$
- However, internal nodes never change and have a huge impact on the tree




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

3

## Binary Search Tree Issues

- There are cases where the tree is **unbalanced** – one particular path contains all the data
- In this case, the time complexity slowly deteriorates to  $O(n)$




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

4

## Very Unbalanced Tree



Our tree is no better than a linked list!


6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

5

## 2-3 Trees

- The *2-3 Tree* is a special type of BST invented by *John Hopcroft* in 1970
- It automatically maintains **balance** as it grows!
- It does this by using a clever variation of the node that can contain multiple values




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

6

## 2-3 Trees

- **2-Nodes** contain 1 values and two children: left and right
- **3-Nodes** contains 2 values and three children: left, middle and right
- Both are easy to code and traversal logic is straight forward



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

7

## Searching a 2-3 tree



- Searching a 2-3 Tree is very similar to a Binary Search Tree, but with a minor difference
- **2-nodes** are treated the same as they are in BSTs:
  - if less than, go left
  - if greater than, go right

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

8

## Searching a 2-3 tree




- **3-nodes** are a bit different
- Since they have 2 values, *a* and *b*, we do the following:
  - if less than *a*, go left
  - if between *a* and *b*, go middle
  - if greater than *b*, go right

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

9

## Search for 8: Go Left




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

10

## Search for 8: Go Middle




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

11

## Search for 8: Found




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

12

## Adding to a 2-3 tree

- For BSTs, when a value is added, it will search and then **create** a new left or right leaf
- 2-3 Trees, however, will **merge** the value into the bottom node (rather than creating a new node)




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

13

## Adding to a 2-3 tree

- This will convert a 2-Node into a 3-Node (it now has two values and three links)
- A 3-Node will convert into a **temporary** structure called a 4-Node... but we will get to that later




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

14

## Add 25: Go Right




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

15

## Add 25: Go Left




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

16

## Add 25: Can't go further




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

17

## Add 25: Convert 2-Node to 3-Node



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

18

## Adding to a 2-3 tree



- Notice, when the value was added to the 2-3 Tree, that the height of the tree *did not change*
- Binary Search Tree would have added another child node and the height *would have changed*


6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

19

## The 4-Node

- So, what happens when we add a value to a 3-node?
- It becomes a *4-Node*, which has 3 values and 4 children
- This is temporary**, it will be converted




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

20

## The 4-Node

- When a 4-Node is created, the 2-3 Tree algorithm will *split* it into other nodes
- Given that 4 is a nice even number, we can split equally
- ... and balanced!




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

21

## One Way to Split a 4-Node




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

22

## The Types of Splits

- There are a total of six different splits that can occur in a 2-3 tree
- In each split, the **middle** value **ascends** up to the parent node




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

23

## The Types of Splits

- This will change a parent from a 2-Node to 3-Node
- ... or from 3-Node to 4-Node
  - then, the parent will split
  - it continues to bubble up – possibly all the way to the root
  - this is  $O(\log n)$



6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

24

## The Six Splits


- Parent is 2-Node:
  - node is the left child of the parent (1)
  - node is the right child of the parent (2)
- Parent is 3-Node:
  - node is the left child of the parent (3)
  - node is the middle child of the parent (4)
  - node is the right child of the parent (5)
- Node is the root (6)

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

25

## 2-Node Parent, Left Child




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

26

## 2-Node Parent, Right Child




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

27

## 3-Node Parent, Left Child




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

28

## 3-Node Parent, Middle Child




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

29

## 3-Node Parent, Right Child




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

30

## Node is a the root



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

31

## Why Does This Work?



- Notice that, of the six splits, only one created a new node and changed the height
- So, *a 2-3 tree grows in depth only when the root is split*
- ... and it splits balanced on the left and right side!

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

32

## Why Does This Work?



- 2-3 Trees grow from the top rather than from the bottom like Binary Search Trees
- And, the tree auto-balances do to the very nature of how the nodes split
- They are always  $O(\log n)$

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

33

## Why Does This Work?



- Additional, 2-3 Trees are *incredibly* easy to write
- When a recursive call completes, in the case of a split, you can return the middle value
- So, as recursion bubbles up, you can handle all splits

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

34

## Let's Try Some...




- Let's try two sets of numbers inserted into a Binary Search Tree and 2-3 Tree
- This will allow us to contrast the difference

1. Numbers: 6, 2, 1, 3, 5, 4, 7	<input type="radio"/>
2. Numbers: 1, 2, 3, 4, 5, 6, 7	<input type="radio"/>

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

35




Red-Black  
Trees

Bringing Balance with Ease

## Red-Black Trees

- 2-3 Trees are re-mark-a-ble!
- However, the nodes are a tad complex
- Can we implement the same concept by using the Binary Search Tree's basic 2-Node?
- The answer is: **yes!**




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

37

## Red-Black Trees

- The *Red-Black Tree* is ADT that implements a 2-3 tree using strictly 2-nodes
- However, this does add some complexity to our balancing logic... but we will get the same results




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

38

## Red-Black Trees




- So, let's look a 2-3 tree and make some modifications
- First, we will convert all of our 3-nodes into a chain of two 2-Nodes
- So we know that they belong together, let's make the branch as **red**

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

39

## Basic 2-3 Tree




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

40

## Represented with only 2-Nodes

These represent a 3-Node




These too

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

41

## Red-Black Trees




- Of course, we don't typically represent trees using horizontal links
- So, let's rearrange the nodes into a typical tree structure

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

42

## Same tree – normal layout




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

43

## Coloring the node




- Naturally, we can't color branches (which are just links) in Java
- ... or any major language
- We can color the nodes, that are children of the red-branch, as **red**

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

44

## Coloring the Nodes Red




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

45

## Red-Black Tree Definition

- In a *Red-Black Tree*, every node is marked as either **Red** or **Black**
- Colors were arbitrarily chosen
  - there is no metaphor
  - they looked best on laser printers at the time




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

46

## Red-Black Tree Definition

- If a node is **Red** then both children are **Black**
- That makes sense, or it would be representing a 4-Node (or something even larger)




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

47

## Red-Black Tree Definition

- The root considered **Black**
- Null pointers are considered **Black** nodes
  - even though they are not
  - the algorithm uses this logic



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

48



## The Black-Height


- *Black-height* of a node is the number of **Black** nodes on any path to a null
- We don't count red nodes since they represent part of a 3-Node
- We also don't count the root
- Every path from any node to a null contains the same number of **Black** nodes

6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

49

## Black-heights




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

50

## Balancing the tree

- Balancing the Red-Black tree is done in the same manner as a 2-3 tree
- However, because we use 2-Nodes, we use a series of *rotations* to get the same effect as splits




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

51

## Balancing the tree


- They are tad more complicated
- Unfortunately, we don't have time to cover them this Summer, but they are cool



6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

52




## AVL Trees

Bringing balance... aggressively

## AVL Trees

- *AVL Tree* is a height-balanced binary search tree invented by Adelson-Velskii and Landis
- The ADT keeps track of the height of each subtree and reorders the data as needed




6/26/2019

Sacramento State - Summer 2019 - CS130 - Cook

54

## AVL Trees

- AVL Trees aggressively balance the nodes – which ensures the  $O(\log n)$  search
- So, searching is optimized
- However, these steps require considerable work and hurts efficiency



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

55

## AVL Trees


- Each subtree has a "height" property
  - it is the maximum between the height of the left and right subtree + 1
  - leaves have a height of zero
- As long as the right and left branches only differ by 1, the AVL Tree is sufficiently balanced
- If not, they are balanced by "rotating"

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

56

## Subtree Heights



Each subtree differs only by 1

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

57

## Inserting Nodes


- Unless values are inserted in a very specific order, the tree will, naturally, become unbalanced
- Imbalance falls into two distinct categories
  - Left-Left (or Right-Right) imbalance
  - Left-Right (or Right-Left) imbalance

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

58

## Left-Left Imbalance




Left of X and Left of Y

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

59

## Left-Right Imbalance



Left of X and Right of Y

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

60

## Insert and Rotate

- Only nodes on the path from insertion point to root node have possibly changed in height
- So after the Insert...
  - start balancing starting at the lowest node
  - recurse back up to the root rotating *as needed*


6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

61

## Left-Left Imbalance

- B and C have the same height
- A's height is 1 larger than B and C
- Rotate right...
  - make Y the new root
  - X its right child of Y
  - B and C subtrees of X




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

62

## Left-Left Imbalance

- B and C have the same height
- A's height is 1 larger than B and C
- Rotate right...
  - make Y the new root
  - X its right child of Y
  - B and C subtrees of X




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

63

## Left-Left Rebalance




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

64

## Example: Left-Left Unbalance

Children differ by more than 1. Rotate here




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

65

## Example: Left-Left Unbalance

(1) This becomes the new root




6/26/2019


Sacramento State - Summer 2019 - CSc 130 - Cook

66


## Example: Left-Left Unbalance




## Example: Left-Left Unbalance



## Example: Left-Left Unbalance




## Example: Left-Left Unbalance




## Left-Right Imbalance

- Can't use the Left-Left balance trick - because now it's the *middle subtree*, i.e. B, that's too deep.
- Instead consider what's inside B...




## Left-Right Imbalance

- B will have two subtrees containing at least one item (just added)
- We do not know which is too deep - set them both to 0.5 levels below subtree A



## Left-Right Imbalance

- Neither X nor Y worked as root node so make Z the root
- Rearrange the subtrees in the correct order
- No matter how deep  $B_1$  or  $B_2$  ( $\pm 0.5$  levels) we get a legal AVL tree again




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

73

## Left-Right Rebalance



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

74