




$O(n \log n)$ Sorting

Section 2.2 – 2.3




Merging Arrays

Quite easy... and quite common

Merging Arrays

- It is a common task in Computer Science to combine two different arrays into one
- If both arrays are unsorted...
 - the task is fairly simple $O(n)$
 - just add one onto the end of the other




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

3

Merging Arrays

- However, often two sorted arrays are combined
- ...and the resulting array must be sorted



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

4

Merging Arrays

- The algorithm for merging two sorted arrays is very simple
- The resulting time complexity is $O(n)$
- However, it requires auxiliary storage of $O(n)$

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

5

Merge Algorithm


- Keep two counters – one for each array
- Loop while both arrays have data
 - take the smaller element and put it in the auxiliary array
 - increment the array's counter (which just lost an element)
- After the loop
 - one array will still have elements
 - append them to the auxiliary array

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

6

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

7

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

8

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

9

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

10

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

11

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

12

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

13

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

14

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

15

Sorted Array Merge Example




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

16

Dump the Rest of the Array




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

17

Dump the Rest of the Array




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

18


Merge Sort



Divide and conquer!

Merge Sort

- *Merge Sort* is a divide-and-conquer approach to sorting arrays
- It is based on the idea of cutting the array into smaller and smaller sublists until sorting them is arbitrary
- This approach ultimately results in $O(n \log n)$



6/26/2019 Sacramento State - Summer 2019 - CSc 130 - Cook 20

Merge Sort

- Because Merge-Sort defines a dividing the list into a list into smaller instances of itself, it naturally is solved using recursion
- Each recursive step cuts the lists into 2 until the list is either 1 element – which is, well, obviously sorted


6/26/2019 Sacramento State - Summer 2019 - CSc 130 - Cook 21

Merge Sort

- As the recursion bubbles up, each sub list is merged using the algorithm we just discussed
- Since an auxiliary array is required for the merge process, Merge-Sort, while fast, has $O(n)$ auxiliary storage requirements


6/26/2019 Sacramento State - Summer 2019 - CSc 130 - Cook 22

Merge Sort Example: Recurse down



6/26/2019 Sacramento State - Summer 2019 - CSc 130 - Cook 23

Merge Sort Example: Merge Up



6/26/2019 Sacramento State - Summer 2019 - CSc 130 - Cook 24


Merge Sort Summary

Merge Sort	
Time Average	$O(n \log n)$
Time Best	$O(n \log n)$
Time Worst	$O(n \log n)$
Auxiliary space	$O(n)$
Stable	Yes – Equal element order preserved
Online?	Yes – New data → new sublist

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

25




Quick Sort

Oh, I am getting dizzy....

Quick Sort

- *Quick-Sort* is a divide-and-conquer algorithm that rotates values around a *pivot*
- Even faster than both Merge Sort and Heap Sort
- ... but does have its weaknesses




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

27

How it Works

- Like Merge-Sort, the array is broken down into smaller and smaller sub-lists
- However, before recursion
 - an value *p* is chosen in the sub-list as the *pivot* value
 - smaller items are moved before it
 - larger items are moved after it



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

28

Choosing a Pivot

- The pivot can be any element in the sub-list – we just need one real value to compare
- This value is used to *partition* the values
- Different versions use different pivots
 - first item in the sub-list
 - end item in the sub-list
 - the midpoint of the sub-list
 - random value in the sub-list


6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

29

Partitioning the Values

- After the pivot is selected, all elements are moved
- Two loops move through the elements swapping elements less than/greater than the pivot



6/26/2019


Sacramento State - Summer 2019 - CSc 130 - Cook

30

Partitioning the Values

The result is...

- sub-list **L** that contains items less than P and
- sub-list **G** that contains items greater than P
- The sub-lists are stored in the original data array




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

31

Partitioning the Values

- **Note:** neither L or G is sorted yet
- These will be called **recursively** by Quick-Sort
- Moving the elements, in-place, can look a tad ugly code-wise, but the logic is straight forward



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

32

Partition Algorithm

- The algorithm maintains two pointers
 - first moves left to right and keeps track of the values that are **too big**
 - second moves right to left and keeps track of the values that are **too little**
- Each moves independently

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

33

Partition Algorithm

- First move the **Too Big** pointer until a value is found that is bigger than the pivot
- Then move the **Too Little** pointer until a value is found that is smaller than Pivot
- Then, these values are swapped
- When the two pointers collide, we are done

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

34

Example Partition

- In this example, we pivot at the **start** of the array
- **Any** value can be used...
 - but it will have to be swapped to the start before the algorithm runs
 - this "saves" the pivot for later



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

35

Quick Sort Algorithm

```
while (tooBig < tooSmall)
{
    while (array[tooBig] <= array[pivot])
    {
        tooBig++;
    }

    while (array[tooSmall] > array[pivot])
    {
        tooSmall--;
    }

    if (tooBig < tooSmall)
    {
        //swap array[tooBig] and array[tooSmall]
    }


    //swap array[tooSmall] and array[pivot]
    //Recurse QuickSort on both L and G
}
```

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

36

Example: Pivot is First




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

37

Move Too Big




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

38

Move Too Big



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

39

Move Too Big: Found!




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

40

Now, Move Too Small




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

41

Move Too Small: Found!




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

42

Swap these two




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

43

Keep going... Move Too Big




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

44

Move Too Big: Found




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

45

Move Too Small




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

46

Move Too Small: Found




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

47

Swap




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

48

Still going... Move Too Big




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

49

Move Too Big




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

50

Move Too Big: Found




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

51

Move Too Small




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

52

Move Too Small: Found




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

53

Swap




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

54

And again... Move Too Big




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

55

Move Too Big: Found




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

56

Move Too Small




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

57

Move Too Small




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

58

Pointers Passed Each Other!




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

59

Finally, Swap Pivot and Too Small



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

60

Done (with this pass)




6/26/2019

Sacramento State - Summer 2019 - CSIS 130 - Cook

61

Recursion Time!

- Notice: all the items **before** the pivot are **smaller** and all the items **after** are a **larger**
- Now, we can recurse both sides
- The end result is a sorted array




6/26/2019

Sacramento State - Summer 2019 - CSIS 130 - Cook

62

Quick Sort Example




6/26/2019

Sacramento State - Summer 2019 - CSIS 130 - Cook

63

Quick Sort Example



6/26/2019

Sacramento State - Summer 2019 - CSIS 130 - Cook

64

Quick Sort: Worst Case



- Assume we get array that is already sorted
- This can cause huge problems!
- Shockingly, the efficiency of this sort can degenerate if we are not careful

6/26/2019

Sacramento State - Summer 2019 - CSIS 130 - Cook

65

Quick Sort: Worst Case


- If the first item is the pivot
 - a reverse sorted list will cause both the pointers to simply pass each other
 - one sublist will be empty, the second will contain **ALL** the elements – 1
- If the last item is the pivot
 - a sorted array will have the same effect

6/26/2019

Sacramento State - Summer 2019 - CSIS 130 - Cook

66

Quick Sort: Worst Case




6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

67

Quick Sort: Worst Case



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

68

Quick Sort Analysis

- So, in the worst case, Quick Sort is $O(n^2)$
- ... and, given all the work it has to do with the pointers, it gets beat by Bubble Sort



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

69

How Can We Avoid This?

- If you don't know if the array is randomized, *manually randomize the values*
- $O(n)$ – run i from first to last element and swap $\text{array}[i]$ and $\text{array}[\text{random}]$



6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

70

Quick Sort Summary

Quick Sort	
Time Average	$O(n \log n)$
Time Best	$O(n \log n)$
Time Worst	$O(n^2)$
Auxiliary space	$O(1)$
Stable	No – Equal element order not preserved
Online?	No

6/26/2019

Sacramento State - Summer 2019 - CSc 130 - Cook

71