




## Queues & Stacks in Practice

### Section 1.3




## The System Stack and Heap

How it works? ...um, I forgot

## The System Stack and Heap

- Your computer maintains two distinct types of memory for running programs: the stack and heap
- The **stack** is used to ...
  - store function states
  - this includes local variables




9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

3

## The Heap

- **Heap** is used to store dynamic allocation
- ... not to be confused with the Heap Data Structure (which we will cover later)



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

4

## The Heap

- Anytime you create objects using **"new"**...
  - the heap is used to allocate storage
  - system performs garbage cleanup after the memory is no longer needed
- Unlike the stack, data persists regardless of function calls

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

5

## Garbage Collection

- Programming languages use **garbage collection** to reclaim unused data from the heap
- Policy is to reclaim the memory used by objects that **can no longer be accessed** (i.e. **no references**)




9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

6

## Loitering

- It is possible to "remove" an item from the ADT, but accidentally keep a reference (link) to it
- The item is effectively an *orphan* - it will be never be accessed again by the ADT




9/8/2019

Sacramento State - Fall 2019 - CS130 - Cook

7

## Loitering

- The garbage collector has no way to know unless it's overwritten
- So, under this condition, the object is said to *loiter* – stay in memory with no purpose




9/8/2019

Sacramento State - Fall 2019 - CS130 - Cook

8

## Array Storing a List (partially filled)




9/8/2019

Sacramento State - Cook - CS130 - Fall 2019

9

## Delete Last – Move End




9/8/2019

Sacramento State - Cook - CS130 - Fall 2019

10


## Dobby is still linked...



9/8/2019

Sacramento State - Cook - CS130 - Fall 2019

11




Cursors

Okay, now its getting weird

## Cursors

- *Cursors* are a melding of the idea of arrays and linked lists
- Cursors want to minimize the constant creation and deletion of new nodes
- So, it maintains an array of unused nodes




9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

13

## Cursors

- Multiple nodes are allocated early - called a *pool*
- If a node is needed, one is removed from the pool
- If a node is removed, and the array has room, it is placed back in the array



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

14

## The Reason

- Arrays can be wasteful ...
  - **in space** – when there are partially filled arrays
  - **in time** – created and destroyed frequently
- Linked lists can be wasteful...
  - require memory to be allocated each time a node is created
  - puts a lot of work on the heap

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

15

## Even more approaches

- You can also use another "pool" linked list
- So, your Linked List class
  - would have a linked list of valid nodes
  - and another list of unused nodes
  - the danger here is that you don't limit the size of the pool – and it grows **forever**
  - so, if you use two linked lists, keep a pool member count

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

16



## Queues & Stacks in Practice

1001 Uses!  
(I meant 1,001 – not 9)

## HTML Tag Matching

- HTML is a hierarchical structure
- HTML consists of tags
  - each tag can also embed other tags
  - allows text to be aligned, made bold, etc...



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

18

## HTML Tag Matching

- Web browsers read the text and apply a tag depending if it is active
- They maintain a stack...
  - push a start tag, pop and end tag
  - if the HTML is correct, they should match
  - ... with the exception of the unary tags

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

19

## HTML Tag Matching

```
<html>
<body>
<center>
<h1>Banks of Sacramento</h1>
</center>
A bully ship and a bully crew,<br>
<i>Doo-da! Doo-da!</i><br>
A bully mate and a captain
too,<br>
<i>Doo-da! Doo-da-day!</i><br>
<i>And it's blow, ye winds,
blow,<br>
For Californi-o.<br>
For there's plenty of gold,<br>
So I've been told,<br>
On the banks of the
Sacramento.</i><br>
</body>
</html>
```

### Banks of Sacramento

A bully ship and a bully crew,  
*Doo-da! Doo-da!*  
 A bully mate and a captain too,  
*Doo-da! Doo-da-day!*  
  
*Then blow, ye winds, blow,*  
*For Californi-o.*  
*For there's plenty of gold,*  
*So I've been told,*  
*On the banks of the Sacramento.*

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

20

## Balanced Parentheses

- When analyzing arithmetic expressions...
  - it is important to determine whether it is balanced with respect to parentheses
  - otherwise, the expression is incorrect
- A great solution is a stack
  - push each ( and pop each )
  - at the end, the stack should be empty
  - also, if you attempt to pop on an empty stack, the expression is invalid

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

21

## Balanced Parenthesis Examples

( a + b )

Balanced

( a + b ) )

Pop empty stack

) a + b (

Pop empty stack

( a + ( b + 1 ) \* c ) / e

Balanced

( a \* ( b + ( ( d + e ) \* f ) )

Stack has 1 left

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

22

## Balanced Parentheses

- But wait...*
  - can we just use a "parenthesis level" counter?
  - if it is  $\geq 1$  at the end or it ever is  $< 0$ , the expression is invalid
- Sorry, it won't work
  - some expressions allow { } and [ ]
  - a simple counter is insufficient
  - stack can check if the pop'd item matches

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

23

## Balanced Parenthesis Examples

[ a + b ]

Balanced

( a + b )

Mismatch

{ [ a + b ] }

Mismatch

( a + ( b + 1 ) \* c / e

Unbalanced


( a \* [ b + { c + d } \* e ] )

Balanced

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

24




## Evaluating Expressions

A Stack and Queue working together!

## Evaluating Expressions


- It is a common task in programs to **evaluate** mathematical expressions and get a result
- Computers can perform this task using an algorithm *created by Dijkstra*, but we will get into that later



9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 26

## Evaluating Expressions

- First, we need to look at mathematical expressions
- We commonly use **infix** notation which is not stack or queue "friendly"
  - there are, however, two alternative notations
  - one of which is stack friendly*



9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 27

## Infix Notation

- Using *infix notation*, we put the operator in between the two operands
- This is the standard format used today

To add the numbers <i>a</i> and <i>b</i> , we type:	<b><math>a + b</math></b>
To divide <i>a</i> by <i>b</i> , we type:	<b><math>a / b</math></b>

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 28

## Prefix Notation

- Prefix notation*, rather than putting the operator between the operands, puts it first
- It is also called "*Polish Notation*"
- Used by the LISP programming language

To add the numbers <i>a</i> and <i>b</i> , we type:	<b><math>+ a b</math></b>
To divide <i>a</i> by <i>b</i> , we type:	<b><math>/ a b</math></b>

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 29

## Postfix Notation

- Postfix notation* puts the operator at the end
- Also called "*Reverse Polish Notation*" (*RPN*)
- Since the operator is last, we can also use it as a "trigger" to perform math

To add the numbers <i>a</i> and <i>b</i> , we type:	<b><math>a b +</math></b>
To divide <i>a</i> by <i>b</i> , we type:	<b><math>a b /</math></b>

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 30

## Where are My Parenthesis?

Infix	Prefix	Postfix
$a + b * c$	$+ a * b c$	$a b c + *$
$(a - b) * c$	$- a b * c$	$a b - c *$
$(a / (b - c) + d)$	$+ / a - b c d$	$a b c - / d +$
$(a + b / (c - d))$	$+ a / b - c d$	$a b c d - / +$

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

31

## Where are My Parenthesis?

- Infix is the only notation that needs parentheses to change precedence
- The order of operators handles precedence in prefix and postfix



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

32

## Converting to Prefix or Postfix

- Why are learning this... *be patient!*
- Converting from infix to postfix or prefix notation is easy to do by hand
- Did you notice that the operands did not change order? They were always *a, b, c...*
- We just need to rearrange the operators

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

33

## Convert Infix to Prefix / Postfix


1. Make it a *fully parenthesized expression (FPE)* - one pair of parentheses enclosing each operator and its operands
2. Move the operators to the start (prefix) or end (postfix) of each sub-expression
3. Finally, remove all the parenthesis

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

34

## Infix to Postfix



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

35

## Compute Postfix Algorithm

- Computing a postfix expression is unbelievably easy
- All you need is:
  - one queue of values & operators
  - and one stack
- In fact, on classic Hewlett Packard calculators, all operations are stack based



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

36

## Compute Postfix Pseudo-code

```
while there is data in the input queue
  read a token (value or operator) from queue
  if it's a value, push it on the stack
  if it's an operator
    pop two numbers from the stack
    compute the result (using the operator)
    push the result on the stack
  end if
end while

//Afterwards, the final result is on the stack
```

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook


37

## Compute Postfix Demo

Input Queue



Stack



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

38

## Compute Postfix Demo

Input Queue



Stack



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

39

## Compute Postfix Demo

Input Queue



Stack



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

40

## Compute Postfix Demo

Input Queue



Stack



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

41

## Compute Postfix Demo

Input Queue



Stack



9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

42

## Compute Postfix Demo

Input Queue

Stack

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 43

## Compute Postfix Demo

Input Queue

Stack

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 44

## Compute Postfix Demo

Input Queue

Stack

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 45

## Compute Postfix Demo

Input Queue

Stack

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 46

## Compute Postfix Demo

Input Queue

Stack

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 47


## Compute Postfix Demo

Input Queue

Stack

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 48






## Infix to Postfix Algorithm

Let the computer do the work...

## Edsger Dijkstra


- Edsger Dijkstra is a World famous computer scientist
- He invented a wealth of algorithms that we use today
- For his contributions, he received the Turing Award



9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 50

## Infix to Postfix Algorithm


- Infix expressions need to be converted to postfix to be evaluated
- Dijkstra's *Shunting-yard algorithm* performs this task



9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 51


## Shunting-yard algorithm

- Named after railroad shunting yards – which move trains onto different tracks
- Dijkstra's solution uses an input queue, operator stack, and output queue




9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 52

## Shunting-yard Algorithm



9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 53

## Shunting-yard Algorithm



- The most basic version of this algorithm requires *Fully-Parenthesized Expression (FPE)*
- This means, there is no precedence and parenthesis are put around every operator

9/8/2019 Sacramento State - Fall 2019 - CSc 130 - Cook 54

## FPE Shunting-yard Algorithm

```

while the input queue has tokens
  read a token from the input queue
  if the token is a...
    operand : add it to output queue
    operator : push it on the stack
    '(' : push it onto the stack
    ')' :
      while the top of stack isn't a '('
        pop an operator
        add it to the output queue
      end while
      pop and discard the extra '('
    end if
  end if
end while

```

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

55

## FPE Shunting-yard Algorithm

Input Queue  $((a * (b + c)) / d)$

Operator Stack

Output Queue

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

56

## FPE Shunting-yard Algorithm

Input Queue  $(a * (b + c)) / d)$

Operator Stack  $($

Output Queue

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

57

## FPE Shunting-yard Algorithm

Input Queue  $a * (b + c)) / d)$

Operator Stack  $(($

Output Queue

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

58

## FPE Shunting-yard Algorithm

Input Queue  $* (b + c)) / d)$

Operator Stack  $(($

Output Queue  $a$

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

59

## FPE Shunting-yard Algorithm

Input Queue  $(b + c)) / d)$

Operator Stack  $(( *$

Output Queue  $a$

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

60

## FPE Shunting-yard Algorithm

Input Queue **b + c ) ) / d )**

Operator Stack **( ( \* (**

Output Queue **a**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

61

## FPE Shunting-yard Algorithm

Input Queue **+ c ) ) / d )**

Operator Stack **( ( \* (**

Output Queue **a b**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

62

## FPE Shunting-yard Algorithm

Input Queue **c ) ) / d )**

Operator Stack **( ( \* ( +**

Output Queue **a b**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

63

## FPE Shunting-yard Algorithm

Input Queue **) ) / d )**

Operator Stack **( ( \* ( +**

Output Queue **a b c**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

64

## FPE Shunting-yard Algorithm

Input Queue **) / d )**

Operator Stack **( ( \***

Output Queue **a b c +**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

65

## FPE Shunting-yard Algorithm

Input Queue **/ d )**

Operator Stack **(**

Output Queue **a b c + \***

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

66

## FPE Shunting-yard Algorithm

Input Queue **d )**

Operator Stack **( /**

Output Queue **a b c + \***

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

67

## FPE Shunting-yard Algorithm

Input Queue **)**

Operator Stack **( /**

Output Queue **a b c + \* d**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

68

## FPE Shunting-yard Algorithm

Input Queue

Operator Stack

Output Queue **a b c + \* d /**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

69

## Too Many Paranthesis!

- FPE's are **rarely** used in real-World examples
- In fact, we use precedence rules to simplify expressions
- Fortunately, the algorithm can be modified, **very easily**, to handle precedence!

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

70

## FPE Shunting-yard Algorithm

```
while the input queue has tokens
  read a token from the input queue
  if the token is a...
    operand : add it to output queue
    operator : new rules - see next slide
    '(' : push it onto the stack
    ')' :
      while the top of stack isn't a '('
        pop an operator
        add it to the output queue
      end while
      pop and discard the '('
  end if
end while
```

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

71

## Operator: New Rules

- When you read an operator from the input queue....
- ... go into a loop that looks at the top of the stack and compares its precedence to the current operator
- If the current operator is ...
  - left-associative, pop while the top is **>=**
  - right-associative, pop while the top is **>**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

72

## Shunting-yard Algorithm Operators

- Stop if you hit a '('
- Each pop'd operator is put directly on the output queue
- Finally, push the current operator onto the stack

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

73

## Operator Associativity

Operator	Associativity
+ - * /	Left
^ (exponent)	Right

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

74

## Shunting-yard Algorithm Example 1

Input Queue **a - b \* c + d**

Operator Stack

Output Queue

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

75

## Shunting-yard Algorithm Example 1

Input Queue **- b \* c + d**

Operator Stack

Output Queue **a**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

76

## Shunting-yard Algorithm Example 1

Input Queue **b \* c + d**

Operator Stack **-**

Output Queue **a**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

77

## Shunting-yard Algorithm Example 1

Input Queue **\* c + d**

Operator Stack **-**

Output Queue **a b**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

78

## Shunting-yard Algorithm Example 1

Input Queue **c + d**

Operator Stack **- \***

Output Queue **a b**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

79

## Shunting-yard Algorithm Example 1

Input Queue **+ d**

Operator Stack **- \***

Output Queue **a b c**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

80

## Shunting-yard Algorithm Example 1

Input Queue **d**

Operator Stack **- \* +**

Output Queue **a b c**

The precedence of \* - are both  $\geq$  than +

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

81

## Shunting-yard Algorithm Example 1

Input Queue **d**

Operator Stack **+**

Output Queue **a b c \* -**

The precedence of \* - are both  $\geq$  than +

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

82

## Shunting-yard Algorithm Example 1

Input Queue

Operator Stack **+**

Output Queue **a b c \* - d**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

83

## Shunting-yard Algorithm Example 1

Input Queue

Operator Stack

Output Queue **a b c \* - d +**

Remaining stack items pop'd

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

84

## Shunting-yard Algorithm Example 2

Input Queue **a + (b - c \* d) / e - f**

Operator Stack

Output Queue

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

85

## Shunting-yard Algorithm Example 2

Input Queue **+ (b - c \* d) / e - f**

Operator Stack

Output Queue **a**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

86

## Shunting-yard Algorithm Example 2

Input Queue **(b - c \* d) / e - f**

Operator Stack **+**

Output Queue **a**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

87

## Shunting-yard Algorithm Example 2

Input Queue **b - c \* d) / e - f**

Operator Stack **+ (**

Output Queue **a**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

88

## Shunting-yard Algorithm Example 2

Input Queue **- c \* d) / e - f**

Operator Stack **+ (**

Output Queue **a b**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

89

## Shunting-yard Algorithm Example 2

Input Queue **c \* d) / e - f**

Operator Stack **+ ( -**

Output Queue **a b**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

90

## Shunting-yard Algorithm Example 2

Input Queue    **\* d) / e - f**

Operator Stack    **+ ( -**

Output Queue    **a b c**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

91

## Shunting-yard Algorithm Example 2

Input Queue    **d) / e - f**

Operator Stack    **+ ( - \***

- has a lower precedence than \*

Output Queue    **a b c**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

92

## Shunting-yard Algorithm Example 2

Input Queue    **) / e - f**

Operator Stack    **+ ( - \***

Output Queue    **a b c d**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

93

## Shunting-yard Algorithm Example 2

Input Queue    **/ e - f**

Operator Stack    **+**

) was read.  
All items are pop'd until matching ( found

Output Queue    **a b c d \* -**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

94

## Shunting-yard Algorithm Example 2

Input Queue    **e - f**

Operator Stack    **+ /**

Output Queue    **a b c d \* -**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

95

## Shunting-yard Algorithm Example 2

Input Queue    **- f**

Operator Stack    **+ /**

Output Queue    **a b c d \* - e**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

96



## Shunting-yard Algorithm Example 2

Input Queue **f**

Operator Stack **+ / -**

Output Queue **a b c d \* - e**

The precedence of both / and + are >= than -

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

97

## Shunting-yard Algorithm Example 2

Input Queue **f**

Operator Stack **-**

Output Queue **a b c d \* - e / +**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

98

## Shunting-yard Algorithm Example 2

Input Queue

Operator Stack **-**

Output Queue **a b c d \* - e / + f**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

99

## Shunting-yard Algorithm Example 2

Input Queue

Operator Stack

Output Queue **a b c d \* - e / + f -**

Remaining stack items pop'd

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

100

## Testing Our Result

**a + (b - c \* d) / e - f**

1. **((a + ((b - (c \* d)) / e)) - f)**

2. **((a ((b (c d \*) -) e /) +) f -)**

3. **a b c d \* - e / + f -**

9/8/2019

Sacramento State - Fall 2019 - CSc 130 - Cook

101