
Practical- 5

Aim: To Implementation of a knapsack problem using dynamic programming.

Knapsack

Algorithm:



Input :

* number of items n
* weight w[i] and value v[i] of each item
* knapsack capacity w

output :

* maximum value that can be obtained
* selected items.

step 1 : start

step 2 : Read the number of item n and knapsack capacity w.

step 3 : Read the weight w[i] and value v[i] of each item.

step 4 : Initialize the first row and first column of the DP table to 0.

step 5 : for each item i = 1 to n, repeat step 6.

step 6 : for each capacity j = 1 to w;

if w[i] <= j ; calculate :

dp[i][j] = max(v[i] + dp[i-1][j-w][i]], dp[i-1][j])

otherwise :

dp[i][j] = dp[i-1][j]

step 7 : the maximum value is stored in dp[n][w]

step 8 : trace the DP table from dp[n][w] backward to find the selected items

step 9 : Display the DP table, maximum value and selected item.

step 10 : stop

NAME:Hima sankar
Enrollment Number:92460118218

Program:

```
#include<iostream>
using namespace std;
class Knapsack {
private:
   int w[10];
   int v[10];
   int n;
   int W;
   int dp[10][100];
public:
   void getInput() {
      cout << "Enter number of items   : ";
      cin  >> n;
      cout << "Enter knapsack capacity : ";
      cin  >> W;
      for(int i = 1; i <= n; i++) {
         cout << "Item " << i << " weight and value : ";
         cin  >> w[i] >> v[i];
      }
   }
   void solve() {
      for(int i = 0; i <= n; i++) dp[i][0] = 0;
      for(int j = 0; j <= W; j++) dp[0][j] = 0;
      for(int i = 1; i <= n; i++) {
         for(int j = 1; j <= W; j++) {
            if(w[i] <= j) {
               dp[i][j] = max(
                  v[i] + dp[i-1][j-w[i]],
                  dp[i-1][j]
               );
            } else {
               dp[i][j] = dp[i-1][j];
```

```
            }
        }
    }
}
void printTable() {
    cout << "\nDP Table:" << endl;
    cout << "     ";
    for(int j = 0; j <= W; j++)
        cout << j << "  ";
    cout << endl;
    for(int i = 0; i <= n; i++) {
        cout << "i=" << i << "  ";
        for(int j = 0; j <= W; j++)
            cout << dp[i][j] << "  ";
        cout << endl;
    }
}
void findItems() {
    cout << "\nSelected Items:" << endl;
    int j = W;
    for(int i = n; i >= 1; i--) {
        if(dp[i][j] != dp[i-1][j]) {
            cout << "Item " << i
                 << " (w=" << w[i]
                 << ", v=" << v[i]
                 << ") TAKEN " << endl;
            j = j - w[i];
        } else {
            cout << "Item " << i
                 << " (w=" << w[i]
                 << ", v=" << v[i]
                 << ") NOT taken " << endl;
        }
```

```
        }
    }
    void showResult() {
        cout << "\nMaximum Value = "
             << dp[n][W] << endl;
    }
};
int main() {
    Knapsack k;
    k.getInput();
    k.solve();
    k.printTable();
    k.showResult();
    k.findItems();
    return 0;
}
```

Output:


```
PS C:\MinGW\bin> & "C:\Users\chinn\Downloads\dsa in c++\practical-5\knapsnack.exe"
Enter number of items   : 4
Enter knapsack capacity : 8
Item 1 weight and value : 2
1
Item 2 weight and value : 3
2
Item 3 weight and value : 4
5
Item 4 weight and value : 5
6

DP Table:
      0  1  2  3  4  5  6  7  8
i=0   0  0  0  0  0  0  0  0  0
i=1   0  0  1  1  1  1  1  1  1
i=2   0  0  1  2  2  3  3  3  3
i=3   0  0  1  2  5  5  6  7  7
i=4   0  0  1  2  5  6  6  7  8

Maximum Value = 8

Selected Items:
Item 4 (w=5, v=6) TAKEN
Item 3 (w=4, v=5) NOT taken
Item 2 (w=3, v=2) TAKEN
Item 1 (w=2, v=1) NOT taken
PS C:\MinGW\bin>
```

Time complexity:



Conclusion: The 0/1 Knapsack Problem was successfully implemented using Dynamic Programming. The algorithm efficiently finds the maximum value that can be obtained within the given knapsack capacity by considering whether each item should be selected or not selected. The time complexity of the algorithm is O(nW) and the space complexity is O(nW).

NAME:Hima sankar
Enrollment Number:92460118218