


Part I

The Structure of Programs

The Elements

- Question: What are the basic elements that make up a computer program?
- Can you deconstruct a program down into a basic collection of objects?
- In essence: A data model



Primitives

- There are primitive values

34	# Integer
3.4	# Float
'T'	# Character
True	# Boolean

- The primitives are the most basic things
- Indivisible
- The foundation of all else

Types

- There is usually an underlying type system

```
int  
float  
char  
bool
```

- Values always have an associated "type"
- Required to map operations onto actual hardware (e.g., integer operations vs floating point operations).

Names

- You can name things

```
var r = 2.0;  
const pi = 3.14159;  
var area = pi * r * r;
```

- You don't hardcode values, use a name
- New names often introduced by "declarations"
- Example: "var", "const", etc.
- Naming -> "Abstraction"

Expressions

- There are operators (often on hardware)

$3 + 4 * 5$
 $\text{tau} = 2 * \text{pi}$

- And rules for evaluation order (left-right)

$3 - 4 - 5$ $\# \rightarrow (3 - 4) - 5$

- And rules for precedence (from math)

$3 - 4 * 5$ $\# \rightarrow 3 - (4 * 5)$

- An expression always produces a value

Assignment

- Computers have memory

- Load/store operations

```
3 + x;          // Value is read from "x"  
x = 4 + 5;      // Value is stored in "x"
```

- A "storage location" is a complex concept

```
x           // Simple value  
x[n]        // Indexing (arrays)  
x.attr      // Attribute (structures)
```

- Locations can appear on either side of =

```
x[n] = y.attr;
```

- Also: Mutable vs Immutable

Control Flow

- You can make decisions

```
if a > b {  
    m = a;  
} else {  
    m = b;  
}
```

- And perform repeated operations

```
while n > 0 {  
    print('T-minus', n);  
    n = n - 1;  
}
```


Functions/Procedures


- Defining a function

```
func square(x float) float {  
    return x*x;  
}
```

- Applying a function (produces a value)


```
3 + square(10)
```

- How does it work? ("substitute the x")



Environments/Scopes

- Definitions are part of environments (scopes)




- Scopes may be nested (e.g., notion of "locality").

Problem: Representation


- How do you represent a computer program as a proper data structure?
- Not as text, but as concrete objects
- Like in a database
- Or as a diagram you would draw on the screen

Problem: Representation




```
const pi = 3.14159;
```

Program Elements



Elements Have Parts

```
const pi = 3.14159;
```



Program elements are built
from more basic primitives
(names, types, etc.)

const

name :


"pi"

value :

3.14159

Collections

```
var r = 2.0;  
const pi = 3.14159;  
var area = pi * r * r;
```



statements

```
var r = 2.0;
```



```
const pi = 3.14159;
```



```
var area = pi * r * r;
```



...

Multiple statements


Multiple structure fields

Multiple function arguments

Many multiples!

Nesting


```
statement1;  
if test {  
    statement3;  
    statement4;  
} else {  
    statement5;  
    statement6;  
}  
statement7;
```





Programs are filled with nested structure

Programs as Objects

- Program elements can be defined by classes

23  `class Integer:`
 `def __init__(self, value):`
 `self.value = value`

`location = value;`  `class Assignment:`
 `def __init__(self, location, value):`
 `self.location = location`
 `self.value = value`

`left + right;`  `class BinOp:`
 `def __init__(self, op, left, right):`
 `self.op = op`
 `self.left = left`
 `self.right = right`

Programs as Objects

- Example

```
x = 23 + 42;
```

```
Assignment(  
    NamedLocation('x'),  
    BinOp('+', Integer(23), Integer(42))  
)
```

- Commentary: A major part of writing a compiler is in designing and building the data model. It directly reflects the structure and features of the language that's being compiled.
- Sometimes known as Abstract Syntax Tree (AST)

Commentary

- Programs are not necessarily "text"



Commentary

- A structurally correct program is not necessarily a correct program

```
const pi = "three";  
pi = pi + .14159;
```

- The syntax might be fine
- The meaning might be gibberish
- Don't confuse program semantics with program structure. They are two different problems.
- Right now: Structure.

Project I

Find the files

- `wabbit/model.py`
- `script_models.py`

Follow the instructions inside (with guidance)