

# REASONING UNDER UNCERTAINTY

Universidad Carlos III de Madrid

AI



# Outline

- 1 Introduction
- 2 Probabilistic reasoning
- 3 Bayesian networks
- 4 Markov Models
- 5 Fuzzy logic

# Outline

- 1 Introduction
- 2 Probabilistic reasoning
- 3 Bayesian networks
- 4 Markov Models
- 5 Fuzzy logic

# Uncertainty in AI

## Uncertainty

- In classic logic we express **absolute certainty**: true or false
  - *Ann works for Google*  $\rightsquigarrow$  *works(Ann, Google)*
  - Production Systems (PS) use assertions considered as true

# Uncertainty in AI

## Uncertainty

- In classic logic we express **absolute certainty**: true or false
  - *Ann works for Google*  $\rightsquigarrow$  *works(Ann, Google)*
  - Production Systems (PS) use assertions considered as true
- **Uncertainty** over some assertion
  - *weather tomorrow, traffic today, vehicle position*
- Simple **solutions**:

# Uncertainty in AI

## Uncertainty

- In classic logic we express **absolute certainty**: true or false
  - *Ann works for Google*  $\rightsquigarrow$  *works(Ann, Google)*
  - Production Systems (PS) use assertions considered as true
- **Uncertainty** over some assertion
  - *weather tomorrow, traffic today, vehicle position*
- Simple **solutions**:
  - omit it
  - represent different results as a disjunction
    - assert (*good weather OR bad weather*)
    - we would need new algorithms
    - (*good weather OR bad weather*)  
*if good weather then play tennis*  $\rightsquigarrow$  ???
- **Problem**: utility of the PS decreases

# Uncertainty

## Handling uncertainty

- **Probability:**
  - example: there is a 90% of chance that tomorrow rains
  - solution: probabilistic reasoning, bayesian networks
- **Vagueness:**
  - example: X is tall/short, it is cold
  - solution: fuzzy logic

# Reasoning under uncertainty

## Short history

- Bayes theorem (1763)
- Fuzzy logic (Zadeh, 1965)
- Certainty factors in expert systems: MYCIN (1976), PROSPECTOR (1979)
- Dempster-Schafer (1976)
- Bayesian networks (Pearl, 1986)
- Sequences of decisions: MDP, HMM, POMDP



# Outline

- 1 Introduction
- 2 Probabilistic reasoning
  - Probabilities
  - Reasoning
- 3 Bayesian networks
- 4 Markov Models
- 5 Fuzzy logic

# Outline

- 1 Introduction
- 2 Probabilistic reasoning  
Probabilities  
Reasoning
- 3 Bayesian networks
- 4 Markov Models
- 5 Fuzzy logic

# Probabilities

- **Probability** can be interpreted as a measure of:
  - **proportion of times** something is true
    - *20 students passed the exam out of 22*
    - a physical phenomenon
    - can be experimentally measured

# Probabilities

- **Probability** can be interpreted as a measure of:
  - **proportion of times** something is true
    - *20 students passed the exam out of 22*
    - a physical phenomenon
    - can be experimentally measured
  - **degree of belief** over something
    - *I think Real Madrid will win the Liga with a 80%*
    - can vary over people
    - or intelligent system

# Probabilities

- **Probability** can be interpreted as a measure of:
  - **proportion of times** something is true
    - *20 students passed the exam out of 22*
    - a physical phenomenon
    - can be experimentally measured
  - **degree of belief** over something
    - *I think Real Madrid will win the Liga with a 80%*
    - can vary over people
    - or intelligent system
- **Probability calculus** does not depend on the interpretation
  - Probabilities range in  $[0.0..1.0]$
  - Probability=0: false
  - Probability=1: true

# Random variables

## Propositional logic

- we describe states as sets of **boolean variables**:  $p, q, r$
- an interpretation is a **truth assignment** to those variables:  
 $p = V, q = F, r = V$

# Random variables

## Propositional logic

- we describe states as sets of **boolean variables**:  $p, q, r$
- an interpretation is a **truth assignment** to those variables:  
 $p = V, q = F, r = V$

## Probability theory

- we use a set of **random variables** that can take values on a given **domain**:
  - one die:  $X \in \{1, 2, 3, 4, 5, 6\}$
  - two dice:  $X \in \{1, 2, 3, 4, 5, 6\}, Y \in \{1, 2, 3, 4, 5, 6\}$

# Random variables

## Propositional logic

- we describe states as sets of **boolean variables**:  $p, q, r$
- an interpretation is a **truth assignment** to those variables:  
 $p = V, q = F, r = V$

## Probability theory

- we use a set of **random variables** that can take values on a given **domain**:
  - one die:  $X \in \{1, 2, 3, 4, 5, 6\}$
  - two dice:  $X \in \{1, 2, 3, 4, 5, 6\}, Y \in \{1, 2, 3, 4, 5, 6\}$
- the associated **value** to a random variable is **unknown**
- we can assign a **probability** to each value
  - die:  $P(X = 1) = \frac{1}{6}, \dots, P(X = 6) = \frac{1}{6}$
- these probabilities define a **probability distribution**



# Example

- Given a robot in a  $100 \times 100$  grid with a given orientation
- Define its random variables and domains

# Example

- Given a robot in a  $100 \times 100$  grid with a given orientation
- Define its random variables and domains
  - Random variables

$$X \in \{0, \dots, 99\}, Y \in \{0, \dots, 99\}, \theta \in \{0, \dots, 359\}$$

- what would be the random variables of two robots?

# Events

- Probability is defined for a **sample space**  $\Omega$ , domain of a random variable
  - $X$ : unknown position
  - $\Omega$ : values  $0, \dots, 99$

# Events

- Probability is defined for a **sample space**  $\Omega$ , domain of a random variable
  - $X$ : unknown position
  - $\Omega$ : values  $0, \dots, 99$
- An **atomic event**  $e \in \Omega$  is a possible situation (world)
  - $e_0 : X = 0, e_1 : X = 1, \dots e_{99} : X = 99$

# Events

- Probability is defined for a **sample space**  $\Omega$ , domain of a random variable
  - $X$ : unknown position
  - $\Omega$ : values  $0, \dots, 99$
- An **atomic event**  $e \in \Omega$  is a possible situation (world)
  - $e_0 : X = 0, e_1 : X = 1, \dots, e_{99} : X = 99$
- A **probability distribution** assigns a number  $P(e)$  to each  $e \in \Omega$ , such that
  - $0 \leq P(e) \leq 1$       and       $\sum_{e \in \Omega} P(e) = 1$
  - $P(e_0) = P(e_1) = \dots = P(e_{99}) = \frac{1}{100}$

# Events

- Probability is defined for a **sample space**  $\Omega$ , domain of a random variable
  - $X$ : unknown position
  - $\Omega$ : values  $0, \dots, 99$
- An **atomic event**  $e \in \Omega$  is a possible situation (world)
  - $e_0 : X = 0, e_1 : X = 1, \dots, e_{99} : X = 99$
- A **probability distribution** assigns a number  $P(e)$  to each  $e \in \Omega$ , such that
  - $0 \leq P(e) \leq 1$       and       $\sum_{e \in \Omega} P(e) = 1$
  - $P(e_0) = P(e_1) = \dots = P(e_{99}) = \frac{1}{100}$
- An **event**  $A$  is a set of atomic events:  $A \subseteq \Omega$ 
  - $P(A) = \sum_{e \in A} P(e)$
  - $P(\text{robot is on one of the first four columns}) = P(e_0) + P(e_1) + P(e_2) + P(e_3) = \frac{4}{100} = \frac{1}{25}$

# Events

- Probability is defined for a **sample space**  $\Omega$ , domain of a random variable
  - $X$ : unknown position
  - $\Omega$ : values  $0, \dots, 99$
- An **atomic event**  $e \in \Omega$  is a possible situation (world)
  - $e_0 : X = 0, e_1 : X = 1, \dots, e_{99} : X = 99$
- A **probability distribution** assigns a number  $P(e)$  to each  $e \in \Omega$ , such that
  - $0 \leq P(e) \leq 1$       and       $\sum_{e \in \Omega} P(e) = 1$
  - $P(e_0) = P(e_1) = \dots = P(e_{99}) = \frac{1}{100}$
- An **event**  $A$  is a set of atomic events:  $A \subseteq \Omega$ 
  - $P(A) = \sum_{e \in A} P(e)$
  - $P(\text{robot is on one of the first four columns}) =$   
 $P(e_0) + P(e_1) + P(e_2) + P(e_3) = \frac{4}{100} = \frac{1}{25}$
  - what is the probability that the robot is in the first row?

# “A priori” probability

- The probability distribution of a random variable is usually represented as a  $\langle \text{vector} \rangle$
- Example:
  - $P(X) = \langle P(X = 0), \dots, P(X = 99) \rangle$
- The **joint probability distribution** is the distribution for several variables. E.g.  $P(X, Y)$ ,  $P(X, Y, \theta)$

$$\begin{aligned} P(X, Y) &= \langle P(X = 0, Y = 0), P(X = 0, Y = 1), \dots, P(X = 99, Y = 99) \rangle \\ &= \langle P(X = 0, Y = 0), P(X = 0, Y = 1), \dots, P(X = 99, Y = 99) \rangle \\ &= \left\langle \frac{1}{10000}, \frac{1}{10000}, \dots, \frac{1}{10000} \right\rangle \end{aligned}$$

- This distribution is **“a priori” or unconditional**, since it does not depend on any condition



# Example

- Given a robot in a  $100 \times 100$  grid with a given orientation
- Define its random variables, domains, and probability distribution

# Example

- Given a robot in a  $100 \times 100$  grid with a given orientation
- Define its random variables, domains, and probability distribution
  - Random variables

$$X \in \{0, \dots, 99\}, Y \in \{0, \dots, 99\}, \theta \in \{0, \dots, 359\}$$

- Probability distribution (*unknown position*):

$$\begin{aligned} P(X = 0, Y = 0) &= P(X = 0, Y = 1) = \dots = \\ P(X = 0, Y = 99) &= P(X = 1, Y = 0) = \dots = \\ P(X = 99, Y = 99) &= \frac{1}{100 \times 100} \end{aligned}$$

# Example

- Given a robot in a  $100 \times 100$  grid with a given orientation
- Define its random variables, domains, and probability distribution

- Random variables

$$X \in \{0, \dots, 99\}, Y \in \{0, \dots, 99\}, \theta \in \{0, \dots, 359\}$$

- Probability distribution (*unknown position*):

$$\begin{aligned} P(X = 0, Y = 0) &= P(X = 0, Y = 1) = \dots = \\ P(X = 0, Y = 99) &= P(X = 1, Y = 0) = \dots = \\ P(X = 99, Y = 99) &= \frac{1}{100 \times 100} \end{aligned}$$

- Probability distribution (*unknown position and orientation*):

# Example

- Given a robot in a  $100 \times 100$  grid with a given orientation
- Define its random variables, domains, and probability distribution
  - Random variables

$$X \in \{0, \dots, 99\}, Y \in \{0, \dots, 99\}, \theta \in \{0, \dots, 359\}$$

- Probability distribution (*unknown position*):

$$\begin{aligned} P(X = 0, Y = 0) &= P(X = 0, Y = 1) = \dots = \\ P(X = 0, Y = 99) &= P(X = 1, Y = 0) = \dots = \\ P(X = 99, Y = 99) &= \frac{1}{100 \times 100} \end{aligned}$$

- Probability distribution (*unknown position and orientation*):

$$\begin{aligned} P(X = 0, Y = 0, \theta = 0) &= \dots \\ P(X = 100, Y = 100, \theta = 360) &= \frac{1}{100 \times 100 \times 360} \end{aligned}$$

# Example

- Given a robot in a  $100 \times 100$  grid with a given orientation
- Define its random variables, domains, and probability distribution

- Random variables

$$X \in \{0, \dots, 99\}, Y \in \{0, \dots, 99\}, \theta \in \{0, \dots, 359\}$$

- Probability distribution (*unknown position*):

$$\begin{aligned} P(X = 0, Y = 0) &= P(X = 0, Y = 1) = \dots = \\ P(X = 0, Y = 99) &= P(X = 1, Y = 0) = \dots = \\ P(X = 99, Y = 99) &= \frac{1}{100 \times 100} \end{aligned}$$

- Probability distribution (*unknown position and orientation*):

$$\begin{aligned} P(X = 0, Y = 0, \theta = 0) &= \dots \\ P(X = 100, Y = 100, \theta = 360) &= \frac{1}{100 \times 100 \times 360} \end{aligned}$$

- what would be the probability distribution of unknown position and orientation of two robots?

# Conditional probability

$$P(A|B) = \frac{P(A, B)}{P(B)} \text{ if } P(B) \neq 0$$

- $P(A|B)$  can be interpreted as the **updated** probability of  $A$ , once  $B$  has been observed
- Examples
  - $P(X = 0)$ ?
  - $P(X = 0|X < 10)$ ?
  - $P(X = 0|Y = 0)$ ?

# Conditional distribution

- **Conditional distribution** is a vector of vectors (array)
- Example:

$$\begin{aligned}P(X|Y) &= \langle P(X|Y=0), \dots, P(X|Y=99) \rangle \\ &= \langle \langle \frac{1}{10000}, \dots, \frac{1}{10000} \rangle, \dots, \langle \frac{1}{10000}, \dots, \frac{1}{10000} \rangle \rangle\end{aligned}$$

# Law of total probability

- Given a set of pairwise disjoint events  $A_i$  such that their union is the whole sample space and another event  $B$ :

$$P(B) = \sum_{i=1}^n P(B, A_i) = \sum_{i=1}^n P(B|A_i)P(A_i)$$



# Law of total probability

- Given a set of pairwise disjoint events  $A_i$  such that their union is the whole sample space and another event  $B$ :

$$P(B) = \sum_{i=1}^n P(B, A_i) = \sum_{i=1}^n P(B|A_i)P(A_i)$$

- Thus, if we have a random variable  $A$  with possible disjoint values  $a_1, \dots, a_n$  and an event  $B$ :

$$P(B) = \sum_{i=1}^n P(B, A = a_i) = \sum_{i=1}^n P(B|A = a_i)P(A = a_i)$$

# Law of total probability

- Given a set of pairwise disjoint events  $A_i$  such that their union is the whole sample space and another event  $B$ :

$$P(B) = \sum_{i=1}^n P(B, A_i) = \sum_{i=1}^n P(B|A_i)P(A_i)$$

- Thus, if we have a random variable  $A$  with possible disjoint values  $a_1, \dots, a_n$  and an event  $B$ :

$$P(B) = \sum_{i=1}^n P(B, A = a_i) = \sum_{i=1}^n P(B|A = a_i)P(A = a_i)$$

- Example

$$\begin{aligned} P(X = 0) &= \sum_{i=0}^{99} P(X = 0, Y = i) \\ &= P(X = 0, Y = 0) + P(X = 0, Y = 1) + \dots + P(X = 0, Y = 99) \\ &= \frac{1}{10000} + \frac{1}{10000} + \dots + \frac{1}{10000} = \frac{100}{10000} = \frac{1}{100} \end{aligned}$$

# Conditional probability

- Conditional probability

$$P(A|B) = \frac{P(A, B)}{P(B)} \text{ if } P(B) \neq 0$$

- Product rule

$$P(A, B) = P(A \wedge B) = P(A|B)P(B) = P(B|A)P(A)$$

- Bayes rule

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)} = \alpha P(B|A)P(A)$$

# Conditional probability

- Conditional probability

$$P(A|B) = \frac{P(A, B)}{P(B)} \text{ if } P(B) \neq 0$$

- Product rule

$$P(A, B) = P(A \wedge B) = P(A|B)P(B) = P(B|A)P(A)$$

- Bayes rule

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)} = \alpha P(B|A)P(A)$$

- Sometimes obtaining  $P(A|B)$  is easier than  $P(B|A)$

$$P(\text{Cause}|\text{Effect}) = \frac{P(\text{Effect}|\text{Cause})P(\text{Cause})}{P(\text{Effect})}$$

it is usually easier to ask an expert  $P(\text{Effect}|\text{Cause})$  than  $P(\text{Cause}|\text{Effect})$

# Chain rule

- Product rule  $P(X_1, X_2) = P(X_1)P(X_2|X_1)$
- Recursive application: **chain rule**

$$\begin{aligned}P(X_1, \dots, X_n) &= P(X_1, \dots, X_{n-1})P(X_n|X_1, \dots, X_{n-1}) \\&= P(X_1, \dots, X_{n-2})P(X_{n-1}|X_1, \dots, X_{n-2})P(X_n|X_1, \dots, X_{n-1}) \\&= \dots \\&= P(X_1)P(X_2|X_1)P(X_3|X_1, X_2) \dots P(X_n|X_1, \dots, X_{n-1}) \\&= P(X_1) \times \prod_{i=2}^n P(X_i|X_1, \dots, X_{i-1})\end{aligned}$$

- **Crucial for AI:** we can compute joint probabilities only using conditional probabilities

# Outline

- 1 Introduction
- 2 Probabilistic reasoning  
Probabilities  
Reasoning
- 3 Bayesian networks
- 4 Markov Models
- 5 Fuzzy logic

# Use of probabilities in AI

Typical tasks: decision making, classification, prediction, . . .

- What is true?
  - use of classic logic: propositional satisfaction, circuit verification, production systems, shortest path, chess, . . .

# Use of probabilities in AI

Typical tasks: decision making, classification, prediction, ...

- What is true?
  - use of classic logic: propositional satisfaction, circuit verification, production systems, shortest path, chess, ...
- vs. what is more probable?
  - use of probabilities: bayesian networks, sequences prediction (speech recognition), classification (of language), weather forecast, videogames, ...



# Use of probabilities in AI

Typical tasks: decision making, classification, prediction, ...

- What is true?
  - use of classic logic: propositional satisfaction, circuit verification, production systems, shortest path, chess, ...
- vs. what is more probable?
  - use of probabilities: bayesian networks, sequences prediction (speech recognition), classification (of language), weather forecast, videogames, ...
- What if the selected model is wrong?
  - In classic logic
    - incomplete model  $\rightarrow$  ok
    - incorrect model  $\rightarrow$  problem
  - In probabilities
    - it is usually more interesting to know the relation among probabilities than the exact numbers:  $P(e) > P(e')$ ?
    - it could be more robust

# Inference

- Main task:

Compute probabilities of events  $e$  given some evidence  $o$ :

$$P(e|o)$$

- Inference tasks:
  - compute **posterior distribution** given evidence
  - **choose an action** to **achieve high reward** given some evidence
  - decision making with **optimal utility**
  - **classification**
  - **diagnosis**

# Inference

Compute posterior distribution given evidence  $P(X|o)$


$1/8$	$1/8$	$1/8$	$1/8$	$1/8$	$1/8$	$1/8$	$1/8$
-------	-------	-------	-------	-------	-------	-------	-------



$$P(X) = \langle \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8} \rangle$$

# Inference


Compute posterior distribution given evidence  $P(X|o)$



What is the probability distribution of the position of the robot ( $X$ ) given that it observed a door ( $o = \text{door}$ ),  $P(X|o = \text{door})$ ?

# Inference

Compute posterior distribution given evidence  $P(X|o)$




What is the probability distribution of the position of the robot ( $X$ ) given that it observed a door ( $o = \text{door}$ ),  $P(X|o = \text{door})$ ?

$$P(X|o = \text{door}) = \langle 0, 0, \frac{1}{2}, 0, 0, 0, 0, \frac{1}{2} \rangle$$

# Inference

Compute posterior distribution given evidence  $P(X|o)$



What is the probability distribution of the position of the robot ( $X$ ) given that it observed a door ( $o = \text{door}$ ),  $P(X|o = \text{door})$ ?


$$P(X|o = \text{door}) = \langle 0, 0, \frac{1}{2}, 0, 0, 0, 0, \frac{1}{2} \rangle$$

$$P(X = 0|o = \text{door}) = \frac{P(\text{door}|X = 0)P(X = 0)}{P(\text{door})} = \frac{0 \times \frac{1}{8}}{\frac{2}{8}} = 0$$

$$P(X = 2|o = \text{door}) = \frac{P(\text{door}|X = 2)P(X = 2)}{P(\text{door})} = \frac{1 \times \frac{1}{8}}{\frac{2}{8}} = \frac{1}{2}$$

# Inference

Compute posterior distribution given evidence  $P(X|o)$



What is the probability distribution of the position of the robot ( $X$ ) given that it did not observe a door ( $o = \text{not-door}$ ),  $P(X|o = \text{not-door})$ ?

# Inference

Choose an action to achieve high reward ( $R = 1$ ) given that variable  $X$  has a value

- if I can take Action=1 or Action=2, I choose Action=1 if  $P(R = 1 | \text{Action} = 1, X = v) > P(R = 1 | \text{Action} = 2, X = v)$
- example:



$P(X=3)=1$



- $R = 1$ : find a door
- Actions: *Left* or *Right*



# Inference

Choose an action to achieve high reward ( $R = 1$ ) given that variable  $X$  has a value



$$P(X=3)=1$$



$$P(R = 1 | \text{Action}=\text{Left}, X = 3) = 1$$

$$P(R = 1 | \text{Action}=\text{Right}, X = 3) = 0$$

Then, select **Left**

# Inference

Choose an action to achieve high reward ( $R = 1$ ) given that variable  $X$  has a value



$$P(X=3)=1$$



$$P(R = 1 | \text{Action}=\text{Left}, X = 3) = 1$$

$$P(R = 1 | \text{Action}=\text{Right}, X = 3) = 0$$

Then, select **Left**

Similar task: Choose an action to achieve high reward ( $R = 1$ ) given some evidence  $o$

# Inference

Choose an action to achieve high reward ( $R = 1$ ) given that variable  $X$  has a value



$$P(X=3)=1$$



$$P(R = 1 | \text{Action}=\text{Left}, X = 3) = 1$$

$$P(R = 1 | \text{Action}=\text{Right}, X = 3) = 0$$

Then, select **Left**

Similar task: Choose an action to achieve high reward ( $R = 1$ ) given some evidence  $o$   
What would happen if  $X = 1$ ? And if  $X = 7$ ?


# Inference

## Decisions with optimal utility

- Choose action  $a_j$  with best **expected utility**

ExpectedUtility(Action =  $a_j$ )

$$= \sum_i P(\text{Output} = i | \text{Action} = a_j, \text{evidence}) \times \text{ExpectedUtility}(\text{Output} = i)$$




# Inference

## Decisions with optimal utility

- Choose action  $a_j$  with best **expected utility**

ExpectedUtility(Action =  $a_j$ )

$$= \sum_i P(\text{Output} = i | \text{Action} = a_j, \text{evidence}) \times \text{ExpectedUtility}(\text{Output} = i)$$



- Output:** see door or book
- Action:** Left or Right
- Evidence:** robot position
- Utility:** see door=3.88, see book=20

# Inference

## Decisions with optimal utility

- Choose action  $a_j$  with best **expected utility**

ExpectedUtility(Action =  $a_j$ )

$$= \sum_i P(\text{Output} = i | \text{Action} = a_j, \text{evidence}) \times \text{ExpectedUtility}(\text{Output} = i)$$



ExpectedUtility(Action=Left)=

$$\begin{aligned} & \sum_i P(\text{Output} = i | \text{Action}=\text{Left}, X) \times \text{ExpectedUtility}(\text{Output} = i) = \\ & P(\text{Output}=\text{door} | \text{Action}=\text{Left}, X = 3) \times \text{ExpectedUtility}(\text{Output}=\text{door}) + \\ & P(\text{Output}=\text{book} | \text{Action}=\text{Left}, X = 3) \times \text{ExpectedUtility}(\text{Output}=\text{book}) = \\ & 1 \times 3.88 + 0 \times 20 = 3.88 \end{aligned}$$


# Inference

## Decisions with optimal utility

- Choose action  $a_j$  with best **expected utility**

ExpectedUtility(Action =  $a_j$ )

$$= \sum_i P(\text{Output} = i | \text{Action} = a_j, \text{evidence}) \times \text{ExpectedUtility}(\text{Output} = i)$$



ExpectedUtility(Action=Left)=3.88

ExpectedUtility(Action=Right)=

$$\begin{aligned} & \sum_i P(\text{Output} = i | \text{Action} = \text{Right}, X) \times \text{ExpectedUtility}(\text{Output} = i) = \\ & P(\text{Output} = \text{door} | \text{Action} = \text{Right}, X = 3) \times \text{ExpectedUtility}(\text{Output} = \text{door}) + \\ & P(\text{Output} = \text{book} | \text{Action} = \text{Right}, X = 3) \times \text{ExpectedUtility}(\text{Output} = \text{book}) = \\ & 0 \times 3.88 + 1 \times 20 = 20 \end{aligned}$$

# Inference

- Classification

- given some observations  $o$  to what class they belong?
- compare  $P(\text{Class} = 1|o)$  vs.  $P(\text{Class} = 2|o)$
- examples:
  - given some client data (average money on bank, location of house, monthly earnings),  
determine whether s/he will correctly return a mortgage (Class=1) or not (Class=2)
  - given some image (number of pixels of a given luminosity, number of lines),  
determine whether it belongs to a cat (Class=cat), a dog (Class=dog), or something different (Class=other)
- computation (Naïve Bayes)
  - $\text{Class} = \arg \max_{c \in \text{Classes}} P(\text{Class}=c|o)$
  - $P(\text{Class} = c|o) = \frac{P(o|\text{Class}=c) \times P(\text{Class}=c)}{P(o)}$



# Inference

- Classification

- given some observations  $o$  to what class they belong?
- compare  $P(\text{Class} = 1|o)$  vs.  $P(\text{Class} = 2|o)$
- examples:
  - given some client data (average money on bank, location of house, monthly earnings),  
determine whether s/he will correctly return a mortgage (Class=1) or not (Class=2)
  - given some image (number of pixels of a given luminosity, number of lines),  
determine whether it belongs to a cat (Class=cat), a dog (Class=dog), or something different (Class=other)
- computation (Naïve Bayes)
  - $\text{Class} = \arg \max_{c \in \text{Classes}} P(\text{Class}=c|o)$
  - $P(\text{Class} = c|o) = \frac{P(o|\text{Class}=c) \times P(\text{Class}=c)}{P(o)}$

- Diagnosis

- probability of an illness  $I = 1$  given results of analysis  $o$ ,  
 $P(I = 1|o)$

# Independence

- $A$  and  $B$  are **independent** iff  $P(A, B) = P(A)P(B)$
- In that case, it also holds:  $P(A|B) = P(A)$

# Independence

- $A$  and  $B$  are **independent** iff  $P(A, B) = P(A)P(B)$
- In that case, it also holds:  $P(A|B) = P(A)$
- $P(\text{RobotX}, \text{Orientation}) = P(\text{RobotX})P(\text{Orientation})$
- **Reduction** in the size of the probability distribution:

# Independence

- $A$  and  $B$  are **independent** iff  $P(A, B) = P(A)P(B)$
- In that case, it also holds:  $P(A|B) = P(A)$
- $P(\text{RobotX}, \text{Orientation}) = P(\text{RobotX})P(\text{Orientation})$
- **Reduction** in the size of the probability distribution:

$$100 \times 360 = 36000 \rightsquigarrow 100 + 360 = 460$$

- **Smaller description** implies
  - more **efficient** algorithms
  - **less data** (probabilities) to be specified

# Summary

- Discrete probabilities can be understood as assigning weights to all possible assignments of a set of variables
- Probability is a rigorous formalism to handle uncertainty
- Joint probabilities specify the probability of each atomic event
- Questions can be answered summing atomic events
- For some interesting problems we can reduce the number of parameters to represent the joint probability
- We need tools for expressive representations that also allow us efficient reasoning
- Independence will be crucial

# Credits

Material based on:

- Previous material of UC3M
- Book and teaching notes of *Artificial Intelligence: A Modern Approach*. Russell&Novig. 2nd edition
- Teaching material by Héctor Geffner

# Outline

- 1 Introduction
- 2 Probabilistic reasoning
- 3 Bayesian networks**
- 4 Markov Models
- 5 Fuzzy logic

# Outline

- 1 Introduction
- 2 Probabilistic reasoning
- 3 Bayesian networks
- 4 Markov Models**
- 5 Fuzzy logic



# Outline

- 1 Introduction
- 2 Probabilistic reasoning
- 3 Bayesian networks
- 4 Markov Models
- 5 Fuzzy logic**

# References



Lotfi A. Zadeh.

Outline of a new approach to the analysis of complex systems and decision processes.

*Transactions on Systems, Man and Cybernetics*, 1(1), 1973.