

Package ‘behavr’

August 9, 2017

Title Canonical Data Structure for Behavioural Data

Date 2017-07-25

Version 0.3.0.9003

Description

Implements an S3 class based on data.table to store and process efficiently ethomics (high-throughput behavioural) data.

Imports data.table,
hms,
methods

Suggests testthat

License GPL-3

Encoding UTF-8

LazyData true

URL <https://github.com/rethomics/behavr>

BugReports <https://github.com/rethomics/behavr/issues>

RoxygenNote 6.0.1

Roxygen list(markdown = TRUE)

R topics documented:

behavr	2
bind_behavr_list	3
bin_apply	4
meta	5
print.behavr	6
rejoin	7
time_conversion	8
toy_activity_data	8
xmv	10
Index	12

behavr	<i>todo</i>
--------	-------------

Description

todo

Usage

```
behavr(x, metadata)
```

```
is.behavr(x)
```

Arguments

x [data.table](#) containing all measurments

metadata [data.table](#) containing the metadata

Details

Both x and metadata should have a **column as a key** with **the same name** (typically named id).

Examples

```
set.seed(1)
met <- data.table::data.table(id = 1:5,
                             condition=letters[1:5],
                             sex=c("M","M","M","F", "F"),
                             key="id")

data <- met[ ,
             list(t=1L:100L,
                  x=rnorm(100),
                  y=rnorm(100),
                  eating=runif(100) > .5 ),
             by="id"]

d <- behavr(data,met)
print(d)
summary(d)
```

bind_behavr_list	<i>Put together a list of behavr tables</i>
------------------	---

Description

Bind rows of both data and metadata of all [behavr](#) tables in a list. It checks keys, number and names of columns are the same across all data. In addition, it forbids to bind metadata if it generates duplicates (same id in two different metadata)

Usage

```
bind_behavr_list(l)
```

Arguments

l list of [behavr](#)

Value

a single [behavr](#) object

Examples

```
met <- data.table::data.table(id = 1:5,
                              condition=letters[1:5],
                              sex=c("M", "M", "M", "F", "F"),
                              key="id")
data <- met[,list(t=1L:100L,
                 x=rnorm(100),
                 y=rnorm(100),
                 eating=runif(100) > .5 ),
           by="id"]
d1 <- behavr(data,met)

met[,id:= id+5]
data[,id:= id+5]
data.table::setkeyv(met, "id")
data.table::setkeyv(data, "id")
d2 <- behavr(data,met)

d_all <- bind_behavr_list(list(d1, d2))
print(d_all)
```

bin_apply

*Bin a variable (typically time) and compute an aggregate for each bin***Description**

This function is typically used to summarise (i.e. computing an aggregate of) a variable (y) for bins of a another variable x (typically time).

Usage

```
bin_apply(data, y, x = t, x_bin_length = mins(30), wrap_x_by = NULL,
  FUN = mean, string_xy = FALSE, ...)
```

```
bin_apply_all(data, ...)
```

Arguments

data	data.table or behavr table (see details)
y	variable to be aggregated
x	variable to be binned
x_bin_length	length of the bins (same using as 'x')
wrap_x_by	numeric value defining wrapping period. NULL means no wrapping
FUN	function used to aggregate (e.g. mean , median , sum and so on)
string_xy	logical whether the names of the variables are quoted
...	additional arguments to be passed to FUN

Details

bin_apply expects data from a single individual. bin_apply_all works on multiple individuals identifies by a unique key. wrapping is typically used to compute averages accros several periods. For instance, `wrap_x_by = days(1)`, means bins will aggregate values accross several days. The resulting x can be interpreted as "time relative to the onset of the day" (i.e. ZT).

Examples

```
query <- data.frame(experiment_id="toy_experiment",
  region_id=1:5)
dt <- toy_activity_data(query, duration=days(4))

# average by 30min time bins, default
dt_binned <- bin_apply_all(dt,moving)
# equivalent to
dt_binned <- dt[, bin_apply(.SD, moving),by="id"]

# More advanced usage
dt <- toy_dam_data(query, duration=days(4))
```

```
# nsum activity per 60minutes
dt_binned <- bin_apply_all(dt,
                           activity,
                           x=t,
                           x_bin_length = mins(60),
                           FUN=sum)

#' # average activity. time in ZT
dt_binned <- bin_apply_all(dt,
                           activity,
                           x=t,
                           wrap_x_by=days(1)
                           )
```

meta

*Retreive metadata***Description**

This function returns the meta data from a [behavr](#) object

Usage

```
meta(x)
```

```
setmeta(x, new)
```

Arguments

x	a behavr object
new	a new metadata table

Value

a [data.table](#) representing the metadata in x

See Also

[behavr](#) to generate a behavr object, [xmv](#) to map metavariables to data

Examples

```
set.seed(1)
met <- data.table::data.table(id = 1:5,
                              condition=letters[1:5],
                              sex=c("M", "M", "M", "F", "F"),
                              key="id")
```

```

data <- met[ ,
             list(t=1L:100L,
                  x=rnorm(100),
                  y=rnorm(100),
                  eating=runif(100) > .5 ),
             by="id"]

d <- behavr(data,met)
## show metadata
meta(d)
# same as:
d[meta=TRUE]
## set metadata
m <- d[meta=TRUE]
# only id > 2 is kept
setmeta(d, m[id < 3])
meta(d)

```

print.behavr

Print and summarise a [behavr](#) table

Description

Print and summarise a [behavr](#) table

Usage

```

## S3 method for class 'behavr'
print(x, ...)

## S3 method for class 'behavr'
summary(object, ...)

```

Arguments

x, object [behavr](#) table

... arguments passed on to further method

See Also

[behavr](#), [print.default](#), [summary.default](#)

rejoin	<i>Join data and metadata</i>
--------	-------------------------------

Description

This function joins the data of a [behavr](#) object to its metadata

Usage

```
rejoin(x)
```

Arguments

x a [behavr](#) object

Value

a [data.table](#)

See Also

[behavr](#) to generate a behavr object

Examples

```
set.seed(1)
met <- data.table::data.table(id = 1:5,
                              condition=letters[1:5],
                              sex=c("M", "M", "M", "F", "F"),
                              key="id")

data <- met[ ,
             list(t=1L:100L,
                  x=rnorm(100),
                  y=rnorm(100),
                  eating=runif(100) > .5 ),
             by="id"]

d <- behavr(data,met)
summary_d <- d[, .(test=mean(x)), by=id]
rejoin(summary_d)
```

time_conversion	<i>Time conversion utilities</i>
-----------------	----------------------------------

Description

Trivial functions to convert time to seconds – as rethomics uses second as a conventionnal unit of time.

Usage

days(x)

hours(x)

mins(x)

Arguments

x Numerical vector to be converted in second

Details

Given an dummy function that takes time in second like: myFunction(t), it is always preferable to call myFunction(days(1.5)) rather than myFunction(60*60*24*1.5).

Value

Number of seconds corresponding to x (1d = 86400s, 1h = 3600s and 1min = 60s)

toy_activity_data	<i>Generate toy activity and sleep data mimiking Drosophila behaviour in tubes</i>
-------------------	--

Description

This function generates random data that emulates some of the features of fruit fly activity and sleep. This is designed **exclusively to provide material for examples and tests** since it generates "realistic" datasets of arbitrary length.

Usage

```
toy_activity_data(query = NULL, seed = 1, rate_range = 1/c(60, 10),
  duration = days(5), sampling_period = 10, ...)
```

```
toy_ethoscope_data(...)
```

```
toy_dam_data(...)
```


Arguments

query	query (i.e. a dataframe where every row defines an animal). Typically queries have, at least, the columns <code>experiment_id</code> and <code>region_id</code> . The default value (NULL), will generate data for a single animal.
seed	Random seed used.
rate_range	a parameter defining the boundaries of rate at which animals wake up. It will be uniformly distributed between animals, but fixed for each animal.
duration	Length (in second) of the data to generate.
sampling_period	sampling period (in second) of the resulting data.
...	Additional arguments to be passed to <code>simulateAnimalActivity</code>

Value

A [behav](#) table with the query columns as meta variables. In addition to `id` and `t` columns different method will output different variables:

- `toy_activity_data` will have `asleep` and `moving` (1/10s)
- `toy_dam_data` will have `activity` (1/60s)
- `toy_ethoscope_data` `xy_dist_log10x1000` `has_interacted` x (2/1s)

Examples

```
# just one animal, no query needed
dt <- toy_ethoscope_data(duration=days(3))

# advanced, using a query
query<- data.frame(experiment_id="toy_experiment",
                   region_id=1:10,
                   condition=c("A","B"))

# Data that could come from loadEthoscopeData:
dt <- toy_ethoscope_data(query,duration=days(1))
print(dt)

# Some DAM-like data
dt <- toy_dam_data(query,seed=2,duration=days(3))
print(dt)

# some data that would come from `sleepAnnotation` or `sleepDAMAnnotation`
dt <- toy_activity_data(query,3)
print(dt)
```

xmv

*Extract a metavariable and map it against the data***Description**

This function eXpands a MetaVariable from a parent `behavr` object. That is it matches this variable (from metadata) to the data *by id*.

Usage

```
xmv(var)
```

Arguments

`var` the variable to be extracted

Details

This function *can only be called within between the [] of a parent `behavr` object*. It is intended to facilitate operations between data and metadata. For instance, when one wants to modify a column of the data according a metavariable.

Value

a vector of the same type as `var`, but of the same length as the number of row in the parent data. As each row of data is matched against metadata for this specific variable.

Examples

```
library(data.table)
set.seed(1)
data <- data.table(
  id = rep(c("A", "B"), times=c(10,26)),
  t = c(1:10, 5:30),
  x = rnorm(36), key="id"
)

metadata = data.table(id=c("A", "B"), treatment=c("w", "z"), lifespan=c(19,32), ref_x=c(1,0),key="id")
dt <- behavr(data,metadata)
summary(dt)

#### Subsetting using metadata
dt[xmv(treatment) == "w"]
dt[xmv(treatment) == "w"]
dt[xmv(lifespan) < 30]

#### Allocating new columns using metavariable
# Just joining lifespan (not necessary)
dt[, lif := xmv(lifespan)]
```

```
print(dt)
# Anonymously (more useful)
dt[, x2 := x-xmv(ref_x)]
print(dt)
```

Index

behavr, [2](#), [3–7](#), [9](#), [10](#)
bin_apply, [4](#)
bin_apply_all(bin_apply), [4](#)
bind_behavr_list, [3](#)

data.table, [2](#), [4](#), [5](#), [7](#)
days(time_conversion), [8](#)

hours(time_conversion), [8](#)

is.behavr(behavr), [2](#)

mean, [4](#)
median, [4](#)
meta, [5](#)
mins(time_conversion), [8](#)

print.behavr, [6](#)
print.default, [6](#)

rejoin, [7](#)

setmeta(meta), [5](#)
sum, [4](#)
summary.behavr(print.behavr), [6](#)
summary.default, [6](#)

time_conversion, [8](#)
toy_activity_data, [8](#)
toy_dam_data(toy_activity_data), [8](#)
toy_ethoscope_data(toy_activity_data),
 [8](#)

xmv, [5](#), [10](#)