systemd - Exploring the updated deploy script

Investigate the Docker service on the staging server

```
ssh you@192.168.1.99 cat /lib/systemd/system/docker.service
```

```
<Replace you with your username, or omit this if it's the same>
```

```
<Replace 192.168.1.99 with your server's IP if it is different>
```

Copy over the unit files to the staging server

```
./deploy.sh -c
```

Enable the base unit files

```
./deploy.sh -b
```

SSH into the staging server and check out the Docker containers you just started

```
ssh you@192.168.1.99
```

```
<Replace you with your username, or omit this if it's the same>
```

```
<Replace 192.168.1.99 with your server's IP if it is different>
docker ps
```

While still on the staging server check out the iptables rules

```
sudo iptables -L
```

While still on the staging server verify the swap file exists

```
ls /
```

While still on the staging server initiate a reboot

```
sudo reboot --reboot
```

```
[you may need to hit CTRL+C after ~30 seconds]
```

SSH into the staging server and check out the iptables rules again

```
ssh you@192.168.1.99
```

```
<Replace you with your username, or omit this if it's the same>
```

```
<Replace 192.168.1.99 with your server's IP if it is different>
sudo iptables -L
```

While still on the staging server verify the Docker containers are running

```
docker ps
```

While still on the staging server drop into a root prompt

```
su
<Enter in your root password>
```

While still on the staging server look at the help menu for systemctl

```
systemctl --help
```

While still on the staging server investigate Postgres' status

```
systemctl status postgres.service
```

While still on the staging server reload the systemd daemon

```
systemctl daemon-reload
```

While still on the staging server take a look at the docker ps output

```
docker ps
```

While still on the staging server stop the redis service

```
docker stop <container id of Redis>
```

While still on the staging server look at the docker ps output and check the created time

```
docker ps
```

While still on the staging server investigate the journal logs for Redis

```
journalctl -u redis
```

While still on the staging server take a look at all of the system's logs in reverse

```
journalctl --reverse
```

While still on the staging server look at the help menu for journalctl

```
journalctl --help
```

While still on the staging server take a look at all of the system's logs

```
journalctl
```