

```

user www www;

worker_processes 2;

pid /var/run/nginx.pid;

# [ debug | info | notice | warn | error | crit ]

error_log /var/log/nginx.error_log info;

events {
    worker_connections 2000;

    # use [ kqueue | epoll | /dev/poll | select | poll ];
    use kqueue;
}

http {
    include conf/mime.types;
    default_type application/octet-stream;

    log_format main '$remote_addr - $remote_user [$time_local] '
        '"$request" $status $bytes_sent '
        '"$http_referer" "$http_user_agent" '
        '"$gzip_ratio"';

    log_format download '$remote_addr - $remote_user [$time_local] '
        '"$request" $status $bytes_sent '
        '"$http_referer" "$http_user_agent" '
        '"$http_range" "$sent_http_content_range"';

    client_header_timeout 3m;
    client_body_timeout 3m;
    send_timeout 3m;

    client_header_buffer_size 1k;
    large_client_header_buffers 4 4k;

    gzip on;
    gzip_min_length 1100;
    gzip_buffers 4 8k;
    gzip_types text/plain;

    output_buffers 1 32k;
    postpone_output 1460;

    sendfile on;
    tcp_nopush on;
    tcp_nodelay on;
    send_lowat 12000;

    keepalive_timeout 75 20;

    #lingering_time 30;
    #lingering_timeout 10;
    #reset_timedout_connection on;

    server {
        listen one.example.com;
        server_name one.example.com www.one.example.com;
    }
}

```

```

access_log    /var/log/nginx.access_log  main;

location / {
    proxy_pass      http://127.0.0.1/;
    proxy_redirect  off;

    proxy_set_header    Host            $host;
    proxy_set_header    X-Real-IP       $remote_addr;
    #proxy_set_header    X-Forwarded-For $proxy_add_x_forwarded_for;

    client_max_body_size      10m;
    client_body_buffer_size   128k;

    client_body_temp_path     /var/nginx/client_body_temp;

    proxy_connect_timeout     70;
    proxy_send_timeout        90;
    proxy_read_timeout        90;
    proxy_send_lowat          12000;

    proxy_buffer_size         4k;
    proxy_buffers              4 32k;
    proxy_busy_buffers_size   64k;
    proxy_temp_file_write_size 64k;

    proxy_temp_path           /var/nginx/proxy_temp;

    charset koi8-r;
}

error_page 404 /404.html;

location = /404.html {
    root /spool/www;
}

location /old_stuff/ {
    rewrite ^/old_stuff/(.*)$ /new_stuff/$1 permanent;
}

location /download/ {

    valid_referers none blocked server_names *.example.com;

    if ($invalid_referer) {
        #rewrite ^/ http://www.example.com/;
        return 403;
    }

    #rewrite_log on;

    # rewrite /download/*/mp3/*.any_ext to /download/*/mp3/*.mp3
    rewrite ^/(download/.*)/mp3/(.*)\..*$
        /$1/mp3/$2.mp3 break;

    root /spool/www;
    #autoindex on;
    access_log /var/log/nginx-download.access_log download;
}

location ~* \.(jpg|jpeg|gif)$ {
    root /spool/www;
    access_log off;
    expires 30d;
}

```

} } }