



# UNIVERSITÀ DEGLI STUDI DI PADOVA

## Image histogram and equalization

Stefano Ghidoni






- Image histograms
- Working on the histogram of an image
  - Histogram equalization



- What is a histogram?
- How can a histogram be evaluated from an image?



1	8	4	3	4
1	1	1	7	8
8	8	3	3	1
2	2	1	5	2
1	1	8	5	2




- Histograms of the grayscale values

$$p(r_k) = \frac{h(r_k)}{MN} = \frac{n_k}{MN}$$

# of pixels  
whose  
intensity is  
 $r_k$

- Can be treated as a probabilistic density function (PDF)




- Cumulative Distribution Function (CDF)

$$F_X(x) = P(X \leq x)$$

- Probability Density Function (PDF)

$$f_X(x) = \frac{d}{dx} F_X(x)$$

$$F_X(x) = \int_{-\infty}^x f_X(t) dt$$






- Histograms are widely used for:
  - Evaluating image statistics
  - Compression
  - Segmentation
  - Image enhancement
- Is it meaningful to "modify the histogram"?
  - Which operations could we apply?







- No spoiler 😊



- Histogram equalization is a process that flattens the histogram




- Histogram equalization
- Based on a equalization function
  - How to find this function?



- The function  $T(r)$  capable of equalizing the histogram is the CDF


$$s = T(r) = (L-1) \int_0^r p_r(w) dw$$

$$s_k = T(r_k) = (L-1) \sum_{j=0}^k p_r(r_j)$$



Cumulative  
Distribution  
Function (CDF)  
of the RV  $r$

- $T(r)$  is monotonically non-decreasing
  - The inverse function is available
- The function is bounded
$$0 \leq T(r) \leq L - 1$$
$$0 \leq r \leq L - 1$$
- $T(r)$  continuous and differentiable





- Now consider an example
  - An image with 8 gray levels
  - Gray level distribution is given by

$r_k$	$n_k$	$p_r(r_k) = n_k/MN$
$r_0 = 0$	790	0.19
$r_1 = 1$	1023	0.25
$r_2 = 2$	850	0.21
$r_3 = 3$	656	0.16
$r_4 = 4$	329	0.08
$r_5 = 5$	245	0.06
$r_6 = 6$	122	0.03
$r_7 = 7$	81	0.02



- Now consider an example
  - The CDF is given by:

$$s_i = 7 \sum_{j=0}^i p_r(r_j)$$

- How can we apply this formula to equalize the image?

- Using the info about pixels and the CDF formula we can fill this table

$r_k$	$n_k$	$p_r(r_k) = n_k/MN$
$r_0 = 0$	790	0.19
$r_1 = 1$	1023	0.25
$r_2 = 2$	850	0.21
$r_3 = 3$	656	0.16
$r_4 = 4$	329	0.08
$r_5 = 5$	245	0.06
$r_6 = 6$	122	0.03
$r_7 = 7$	81	0.02

$$s_i = 7 \sum_{j=0}^i p_r(r_j)$$

r		$s_i$	round
0	S <sub>0</sub>	1.33	1
1	S <sub>1</sub>	3.08	3
2	S <sub>2</sub>	4.55	5
3	S <sub>3</sub>	5.67	6
4	S <sub>4</sub>	6.23	6
5	S <sub>5</sub>	6.65	7
6	S <sub>6</sub>	6.86	7
7	S <sub>7</sub>	7.00	7


Input values

Output values

$r_k$	$n_k$	$p_r(r_k) = n_k/MN$
$r_0 = 0$	790	0.19
$r_1 = 1$	1023	0.25
$r_2 = 2$	850	0.21
$r_3 = 3$	656	0.16
$r_4 = 4$	329	0.08
$r_5 = 5$	245	0.06
$r_6 = 6$	122	0.03
$r_7 = 7$	81	0.02

$$s_i = 7 \sum_{j=0}^i p_r(r_j)$$

$r$		$s_i$	round
0	$S_0$	1.33	1
1	$S_1$	3.08	3
2	$S_2$	4.55	5
3	$S_3$	5.67	6
4	$S_4$	6.23	6
5	$S_5$	6.65	7
6	$S_6$	6.86	7
7	$S_7$	7.00	7




a b c


**FIGURE 3.19** Illustration of histogram equalization of a 3-bit (8 intensity levels) image. (a) Original histogram. (b) Transformation function. (c) Equalized histogram.





- The output is not perfectly flat
  - Caused by the discrete nature of data



**FIGURE 3.19** Illustration of histogram equalization of a 3-bit (8 intensity levels) image. (a) Original histogram. (b) Transformation function. (c) Equalized histogram.



- Here you can see the corresponding input and output images
- Compare the source images
- Compare the equalized images
- What do you observe?



Equalization functions

# Histograms in OpenCV





- Your duty: check the `calcHist` function and tutorial

§ `calcHist()` [1/3]

```
void cv::calcHist ( const Mat *   images,  
                   int           nimages,  
                   const int *   channels,  
                   InputArray    mask,  
                   OutputArray   hist,  
                   int           dims,  
                   const int *   histSize,  
                   const float ** ranges,  
                   bool          uniform = true,  
                   bool          accumulate = false  
                   )
```

Python:

```
hist = cv.calcHist( images, channels, mask, histSize, ranges[, hist[, accumulate]] )
```



## Parameters

- images** Source arrays. They all should have the same depth, CV\_8U, CV\_16U or CV\_32F , and the same size. Each of them can have an arbitrary number of channels.
- nimages** Number of source images.
- channels** List of the dims channels used to compute the histogram. The first array channels are numerated from 0 to images[0].channels()-1 , the second array channels are counted from images[0].channels() to images[0].channels() + images[1].channels()-1, and so on.
- mask** Optional mask. If the matrix is not empty, it must be an 8-bit array of the same size as images[i] . The non-zero mask elements mark the array elements counted in the histogram.
- hist** Output histogram, which is a dense or sparse dims -dimensional array.
- dims** Histogram dimensionality that must be positive and not greater than CV\_MAX\_DIMS (equal to 32 in the current OpenCV version).
- histSize** Array of histogram sizes in each dimension.
- ranges** Array of the dims arrays of the histogram bin boundaries in each dimension. When the histogram is uniform ( uniform =true), then for each dimension i it is enough to specify the lower (inclusive) boundary  $L_0$  of the 0-th histogram bin and the upper (exclusive) boundary  $U_{\text{histSize}[i]-1}$  for the last histogram bin histSize[i]-1 . That is, in case of a uniform histogram each of ranges[i] is an array of 2 elements. When the histogram is not uniform ( uniform=false ), then each of ranges[i] contains histSize[i]+1 elements:  $L_0, U_0 = L_1, U_1 = L_2, \dots, U_{\text{histSize}[i]-2} = L_{\text{histSize}[i]-1}, U_{\text{histSize}[i]-1}$  . The array elements, that are not between  $L_0$  and  $U_{\text{histSize}[i]-1}$  , are not counted in the histogram.
- uniform** Flag indicating whether the histogram is uniform or not (see above).
- accumulate** Accumulation flag. If it is set, the histogram is not cleared in the beginning when it is allocated. This feature enables you to compute a single histogram from several sets of arrays, or to update the histogram in time.



```
#include <opencv2/imgproc.hpp>
#include <opencv2/highgui.hpp>

using namespace cv;

int main( int argc, char** argv )
{
    Mat src, hsv;
    if( argc != 2 || !(src=imread(argv[1], 1)).data )
        return -1;

    cvtColor(src, hsv, COLOR_BGR2HSV);

    // Quantize the hue to 30 levels
    // and the saturation to 32 levels
    int hbins = 30, sbins = 32;
    int histSize[] = {hbins, sbins};
    // hue varies from 0 to 179, see cvtColor
    float hranges[] = { 0, 180 };
    // saturation varies from 0 (black-gray-white) to
    // 255 (pure spectrum color)
    float sranges[] = { 0, 256 };
    const float* ranges[] = { hranges, sranges };
    MatND hist;
    // we compute the histogram from the 0-th and 1-st channels
    int channels[] = {0, 1};

    calcHist( &hsv, 1, channels, Mat(), // do not use mask
              hist, 2, histSize, ranges,
              true, // the histogram is uniform
              false );
    double maxVal=0;
    minMaxLoc(hist, 0, &maxVal, 0, 0);
```










```
int scale = 10;
Mat histImg = Mat::zeros(sbins*scale, hbins*10, CV_8UC3);

for( int h = 0; h < hbins; h++ )
for( int s = 0; s < sbins; s++ )
{
    float binVal = hist.at<float>(h, s);
    int intensity = cvRound(binVal*255/maxVal);
    rectangle( histImg, Point(h*scale, s*scale),
        Point( (h+1)*scale - 1, (s+1)*scale - 1),
        Scalar::all(intensity),
        CV_FILLED );
}

namedWindow( "Source", 1 );
imshow( "Source", src );

namedWindow( "H-S Histogram", 1 );
imshow( "H-S Histogram", histImg );
waitKey();
}
```

- Recap of the transformations analyzed so far
  - Negative
  - Logarithm
  - Gamma
  - Contrast stretching
  - Thresholding
  - Histogram equalization





# UNIVERSITÀ DEGLI STUDI DI PADOVA

## Image histogram and equalization

Stefano Ghidoni

