1 Fluids as energy carriers

1.1 Fluid state variables and properties

Formulas

1.1.1 State variables

Density

$$\rho \triangleq \frac{m}{V} \left[\frac{kg}{m^3}\right] \tag{1}$$

Specific volume

$$v \triangleq \frac{V}{m} = \frac{1}{\rho} \left[\frac{m^3}{kg}\right] \tag{2}$$

1.1.2 Viscosity

Kinematic viscosity

$$\nu \triangleq \frac{\eta}{\rho} \left[\frac{m^2}{s}\right] \tag{3}$$

Dynamic viscosity

$$\eta \triangleq \nu \cdot \rho \left[Pa \cdot s = \frac{Ns}{m^2} = \frac{kg}{m \cdot s}\right] \tag{4}$$

1.1.3 Real and ideal fluid

Real fluid	**Ideal fluid**
variable density ($\Delta\rho \neq 0$)	incompressible ($\Delta\rho = 0$)
friction ($\eta > 0, \nu > 0$)	frictionless ($\eta = 0, \nu = 0$)

1.1.4 Compressibility

Mach number

$$M \triangleq \frac{u}{c} \tag{5}$$

where:
- M is the Mach number [-]
  $M \lesssim 0.3$: incompressible flow
- u is the flow velocity [m/s]
- c is the speed of sound in the fluid [m/s]

and:
- $c_{\mathrm{w}}^{20°} = 1484$ m/s
- $c_{\mathrm{a}}^{20°} = 343$ m/s

1.2 Laminar and turbulent flow

Reynolds number

$$Re = \frac{v \cdot L}{\nu} = \frac{\rho \cdot v \cdot L}{\eta} [-] \tag{6}$$

where:
- v is the mean flow velocity [m/s]
- L is the characteristic length [m]

Re values

- $Re < 2000$: laminar flow
- $Re \simeq 2300$: critical point
- $2000 < Re < 4000$: transitional regime
- $Re \geq 4000$: turbulent flow

1.3 Pressure and velocity

Pressure

1.3.1 Total pressure

In addition to the static pressure p_{stat}, there is also the dynamic pressure p_{dyn} and the total pressure p_{tot}:

$$p_{\text{tot}} = p_{\text{stat}} + p_{\text{dyn}} \tag{7}$$

1.3.2 Absolute pressure

Absolute pressure p_{abs} refers to the pressure in a vacuum $p_{\text{vaacum}} = 0Pa$ while relative pressure p_{rel} can refer to any chosen reference pressure p_{ref}.

$$p_{\text{abs}} = p_{\text{rel}} - p_{\text{ref}} \tag{8}$$

1.3.3 Velocity

Velocity is a vector quantity:

$$\vec{v} = (v_x v_y v_z) \tag{9}$$

The magnitude is given by:

$$v = \sqrt{v_x^2 + v_y^2 + v_z^2} \tag{10}$$

1.4 Curvature pressure formula

Deflection motion of a fluid element around a blunt body



$$\frac{dp}{dn} = -\rho \cdot \frac{v^2}{R} \tag{11}$$

2 Mass conservation

2.1 Continuity equation / Mass conservation

Continuity equation



2.1.1 Steady mass-flow

$$\dot{m}_{\text{in}} = \dot{m}_{\text{out}} \tag{12}$$

2.1.2 Incompressible fluid

$$\dot{m} = \rho \dot{V} \quad \Longrightarrow \quad \dot{V}_{\text{in}} = \dot{V}_{\text{out}} \tag{13}$$

2.1.3 Streamline theory

$$\dot{V} = \bar{v} A \quad \Longrightarrow \quad \bar{v}_{\text{in}} A_{\text{in}} = \bar{v}_{\text{out}} A_{\text{out}} \tag{14}$$

3 Energy conservation

3.1 Fluid mechanical energy conservation

Derivation of the Bernoulli equation

$$\dot{m}_1 \left(\frac{p_1}{\rho} + \frac{v_1^2}{2} + g z_1 \right) = \dot{m}_2 \left(\frac{p_2}{\rho} + \frac{v_2^2}{2} + g z_2 \right) \tag{15}$$

3.1.1 Energy flow

$$\begin{aligned} \frac{dE}{dt} = & \underbrace{\sum P + \sum \dot{Q}}_{\substack{\text{Energy flow} \\ \text{across system boundary}}} \\ & \underbrace{+ \sum_{in} \left[\dot{m}^{\swarrow} \cdot \left(h^{\swarrow} + \frac{v^{2\swarrow}}{2} + g z^{\swarrow} \right) \right]}_{\substack{\text{Energy transfer} \\ \text{mass in}}} \\ & \underbrace{- \sum_{out} \left[\dot{m}^{\nearrow} \cdot \left(h^{\nearrow} + \frac{v^{2\nearrow}}{2} + g z^{\nearrow} \right) \right]}_{\substack{\text{Energy transfer} \\ \text{mass out}}} \end{aligned} \tag{16}$$

ciao