

# CS 544 Exam 3 (19%) - Spring 2025

Instructor: Tyler Caraza-Harter

First/Given Name: \_\_\_\_\_. Last/Surname: \_\_\_\_\_

Net ID: \_\_\_\_\_@wisc.edu

Fill in these fields (left to right) on the scantron form (use pencil):

1. LAST NAME (surname) and FIRST NAME (given name), fill in bubbles
2. IDENTIFICATION NUMBER is your Campus ID number, fill in bubbles
3. Under A of SPECIAL CODES, tell us about the nearest person (if any) to your left. 0=no person to the left in your row, 1=somebody you do not know is there, 2=somebody you do know is there.
4. Under B of SPECIAL CODES, do the same as B, but for the person to your right
5. **Under C of SPECIAL CODES, write 2 and fill in bubble 2.** This is very important!

Make sure you fill all the special codes above accurately in order to get graded.

You have 2 hours to take the exam. Use a #2 pencil to mark all answers. When you're done, please hand in these sheets in addition to your filled-in scantron. You may not sit adjacent to your friends or other people you know in the class (having only one empty seat is considered "adjacent"). You may only reference your notesheet. You may not use books, your neighbors, calculators, or other electronic devices on this exam. Please turn off and put away portable electronics now.

If multiple answers are correct, choose the best answer.

Do not communicate with anybody besides the teaching team about questions or answers until exam grades have been posted.

(Blank Page for You to Do Scratch Work)

**Q1. How many hits are there for a FIFO cache of size 4 for the following workload?  
6, 3, 1, 7, 6, 1, 6, 1**

- (A) 0   (B) 1   (C) 2   (D) 3   (E) 4

**Q2. Say you want to run a streaming Spark query over a Kafka topic. The topic is partitioned by column X, but the query is grouping by a different column, Y. What will happen?**

- (A) Spark will refuse to run the query  
(B) Spark will produce incorrect outputs  
(C) Spark will be able to group correctly by column Y

**Q3. A Kafka topic has a replication factor of 3. How will new data be written to the replicas?**

- (A) The client will write the message directly to the leader and both followers.  
(B) The client will write the message to the leader, and the followers will later fetch it.  
(C) The client will write the message to the leader, which will actively send it to both followers.  
(D) The client will send the data to the leader, the leader will send it to the first follower, and the first follower will send it to the second follower.  
(E) The client will send the data to the first follower, the first follower will send it to the second follower, and the second follower will send it to the leader, at which point it will be committed.

**Q4. For Cassandra, R=6 and W=6. Readers are guaranteed to see previous writes. What can we infer about RF?**

If multiple answers are correct, choose the answer that provides the tightest bound on RF.

- (A)  $RF < 13$    (B)  $RF \geq 12$    (C)  $RF > 12$    (D)  $RF \geq 13$    (E)  $RF < 12$

**Q5. You have 8 million floating point operations to do on a device capable of 16 GFLOPS. How many seconds will it take to do the operations?**

- (A) 0.0005   (B) 1   (C) 2.0   (D) 2000.0   (E) 2000000.0

**Q6. If you do a correlated cross join between columns y and z (after unnesting each), how many rows will you get?**

x	y	z
1	[2, 3]	[4]
5	[6, 7]	[8, 9, 10]

- (A) 2   (B) 4   (C) 7   (D) 8   (E) 16

**Q7. You want to connect from a browser on your laptop to Jupyter running in a container on your VM. You take the following steps:**

1. Write a command in the Dockerfile to launch Jupyter on port 2325
2. Use `-L localhost:4334:localhost:3658` to establish the SSH tunnel
3. Use `-p ????:2325` in the `docker run ...` command
4. Enter `http://localhost:4334/` in the browser

What should `????` be in step 3?

- (A) 3658 (B) 5000 (C) 4334 (D) 8888 (E) 2325

**Q8. What Linux command provides documentation about how to use a given program?**

- (A) wget (B) which (C) cat (D) du (E) man

**Q9. Assuming 2x replication, which node(s) are responsible a new row being inserted?**

Row: `x="red", y="green", z="blue"`. The primary key is (`"x", "y"`).

Assume `hash("red")=3`, `hash("green")=-5`, `hash("blue")=0`, `hash("<"red", "green">")=-7`, and `hash("<"red", "green", "blue">")=-8`.

Token map:

`token(n1) = [-1, 5]`, `token(n2) = [1]`, `token(n3) = [-7, 7, 0]`

Feel free to annotate the following if it is helpful:

-8 | -7 | -6 | -5 | -4 | -3 | -2 | -1 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7

- (A) only n1 (B) only n2 (C) n1+n2 (D) n1+n3 (E) n2+n3

**Q10. What are two systems that inspired the design of Cassandra?**

- (A) BigTable and Dynamo  
 (B) BigTable and MapReduce  
 (C) BigQuery and Dynamo  
 (D) BigQuery and MapReduce

**Q11. A Kafka partition leader fails, and there are three followers. Which are eligible to become the new leader?**

- Follower 1: in-sync, and has all messages that the old leader had
- Follower 2: in-sync, but is missing 10 messages that the old leader had
- Follower 3: lagging, but is missing 1 message that the old leader had

- (A) only 1 (B) 1 or 2 (C) 1 or 3 (D) 1, 2, or 3

**Q12. The query engine for BigQuery is internally based on what system?**

- (A) GFS   (B) Dremel   (C) Spark   (D) MapReduce

**Q13. Which Spark caching levels will use the JVM types to represent data?**

- (A) MEMORY\_ONLY and MEMORY\_ONLY\_2  
(B) MEMORY\_ONLY\_SER and MEMORY\_ONLY\_SER\_2  
(C) MEMORY\_ONLY AND MEMORY\_ONLY\_SER  
(D) MEMORY\_ONLY\_2 AND MEMORY\_ONLY\_SER\_2

**Q14. Consider the following Kafka messages. What can we guarantee about which messages will go to the same partition?**

1. topic="green", key="purple", value="green"
2. topic="red", key="purple", value="red"
3. topic="purple", key="red", value="green"

- (A) 1 and 2 will go to the same partition  
(B) 1 and 3 will go to the same partition  
(C) 2 and 3 will go to the same partition  
(D) We can't guarantee anything

**Q15. To connect to an HDFS cluster, what does a client need, at a minimum?**

- (A) address of any DataNode  
(B) addresses of all the DataNodes  
(C) address of the NameNode  
(D) addresses of NameNode and all DataNodes

**Q16. Which join algorithm uses hash partitioning to bring rows from each table that could potentially match with each other together on the same machine?**

- (A) SMJ   (B) BHJ

**Q17. Which BigQuery billing model uses "leftover" CPU and memory resources?**

- (A) capacity   (B) on-demand   (C) rollover   (D) spare

**Q18. What kind of service is EC2?**

- (A) IaaS   (B) PaaS

**Q19. In Docker, if you want a file/directory location on the host machine to be visible within a container, what flag should you pass to run?**

- (A) `-d`   (B) `-f`   (C) `-p`   (D) `-v`

**Q20. There are 3 Kafka groups, each with 1 consumer(s). All the groups are subscribed to the same topic, T. A new message in T will be consumed how many times?**

- (A) 7   (B) 5   (C) 3   (D) 2   (E) 1

**Q21. You write 25 MB to a 2x replicated file in HDFS, then later read it back. How much data will be read and written to disks across the cluster?**

- (A) 50 MB written, 25 MB read  
(B) 25 MB written, 50 MB read  
(C) 25 MB written, 25 MB read  
(D) 50 MB written, 50 MB read

**Q22. In an HDFS cluster, load is poorly balanced across DataNodes. What is most likely to help improve balance?**

- (A) using smaller blocks   (B) using bigger blocks

**Q23. A Spark streaming query is maintaining a count for an interval starting at 1pm. At what time could Spark reasonably discard the running count for events occurring in this interval?**

```
(animals.withWatermark("timestamp", "1 hours")  
  .groupBy(window("timestamp", "4 hours"))  
  .count())
```

- (A) 1pm   (B) 2pm   (C) 5pm   (D) 6pm   (E) 10pm

**Q24. You are developing a library for generating unique IDs. You don't want to rely solely on random number generation because you don't want any chance (however small) of different computers using the same library to produce the same ID. What information about the machine where the code is running would be most helpful for generating a truly unique ID?**

- (A) IP address   (B) MAC address   (C) port number of current process   (D) free disk space

**Q25. For the below Spark SQL query, over which column(s) will hash values be calculated for hash partitioning?**

```
SELECT AVG(R), S FROM mytable GROUP BY L, S;
```

- (A) R   (B) R and S   (C) S   (D) L   (E) S and L

**Q26. Which clause related to machine-learning does BigQuery add to SQL?**

- (A) TEST   (B) TRAIN   (C) TRANSFORM   (D) TRANSPOSE

**Q27. For RAM, what is the finest granularity at which every piece of memory has its own address?**

- (A) bit    (B) byte    (C) cacheline    (D) page    (E) block

**Q28. What value(s) could possibly be printed?**

```
x = 6
def task():
    global x
    x += 1
t = threading.Thread(target=task)
t.start()
t.join()
print(x)
```

- (A) 6 or 7    (B) only 7    (C) only 1    (D) 6 or 1    (E) only 6

**Q29. How do "free tiers" usually work for cloud services?**

- (A) you are not charged for initial operations up to some limit  
(B) you are not charged for additional operations after exceeding some limit

**Q30. Which format inspired Parquet?**

- (A) Arrow    (B) Capacitor    (C) ColumnIO    (D) Protocol Buffers