

6.047 Problem Set 4 Writeup

Matthew Feng

November 4, 2018

1 Simulated GWAS

(a) β_i and SNP odds ratio

(b)

See `simulated_gwas.py`.

(c)

(d)

(e)

2 Finding eQTLs

(a) Principle Components Analysis

(b) Finding eQTLs via Linear Regression

For every SNP x_i , we find the mean and variance (μ_i, σ_i^2) of the correlation coefficients r_{ij} that x_i has with expression of gene y_j . In this way, we are determining the “typical” contribution of SNP x_i to any gene. We then select the SNP and gene pairs (x_i, e_j) for which r_{ij} is statistically significant under the null hypothesis $H_0 : \rho_{ij} = \mu_i$ (i.e. contribution of x_i to y_j is typical).

To implement the Bonferroni correction, we test each hypothesis that SNP x_i contributes to the expression of gene y_j with significance of $\alpha/5000$, where $\alpha = 0.05$ (since we are testing 5000 different genes corresponding to 5000 different hypotheses).

(c) Additional Datasets

3 Convolutional Neural Networks

(a) Implementation

```
#!/usr/bin/env python

from keras.models import *
from keras.layers import *
import keras

import numpy as np

from datetime import datetime

import argparse

BATCH_SIZE = 10
NUM_EPOCHS = 20
KERNEL_SIZE = (4, 4)
POOL_SIZE = (4, 6)
HIDDEN_UNITS = 32
CONV_FILTERS = 32

def get_x_y_data():
    negative_data = []
    with open('negativedata.txt') as f:
        for line in f:
            final_mat = np.zeros((4, len(line)-1, 1))
            for i in range(len(line)):
                char = line[i]
                if char == 'a':
                    final_mat[:, i, :] = np.array([[1], [0], [0], [0]])
                if char == 'c':
                    final_mat[:, i, :] = np.array([[0], [1], [0], [0]])
                if char == 'g':
                    final_mat[:, i, :] = np.array([[0], [0], [1], [0]])
                if char == 't':
                    final_mat[:, i, :] = np.array([[0], [0], [0], [1]])
            negative_data.append(final_mat)

    positive_data = []
    with open('positivedata.txt') as f:

        for line in f:
```

```

        final_mat = np.zeros((4, len(line)-1, 1))
        for i in range(len(line)):
            char = line[i]
            if char == 'a':
                final_mat[:, i, :] = np.array([[1], [0], [0], [0]])
            if char == 'c':
                final_mat[:, i, :] = np.array([[0], [1], [0], [0]])
            if char == 'g':
                final_mat[:, i, :] = np.array([[0], [0], [1], [0]])
            if char == 't':
                final_mat[:, i, :] = np.array([[0], [0], [0], [1]])
        positive_data.append(final_mat)

X = np.array(negative_data + positive_data)
y = np.array([0] * len(negative_data) + [1] * len(positive_data))
y = keras.utils.to_categorical(y)

X_neg = X[:len(negative_data), ...]
X_pos = X[len(negative_data):, ...]
y_neg = y[:len(negative_data), ...]
y_pos = y[len(negative_data):, ...]

return X_neg, X_pos, y_neg, y_pos

def create_model():
    model = Sequential()
    model.add(Conv2D(CONV_FILTERS,
                     input_shape=(4, 100, 1),
                     kernel_size=KERNEL_SIZE,
                     activation="relu",
                     padding="same"))
    model.add(MaxPool2D(pool_size=POOL_SIZE))
    model.add(Flatten())
    model.add(Dense(HIDDEN_UNITS, activation="relu"))
    model.add(Dense(2, activation="softmax")) # same as 1 output sigmoid
    return model

def main():
    np.random.seed(1)

    TRAIN_TEST_FRAC = 0.9
    DATASET_SIZE = 5000
    # 10000 x (4, 100, 1) images total (5000 examples each)
    SPLIT = int(TRAIN_TEST_FRAC * DATASET_SIZE)

    Xn, Xp, yn, yp = get_x_y_data()

```

```

shuffled_order = np.arange(0, DATASET_SIZE)
np.random.shuffle(shuffled_order)
Xn, Xp = Xn[shuffled_order, ...], Xp[shuffled_order, ...]
yn, yp = yn[shuffled_order, ...], yp[shuffled_order, ...]

X_train = np.vstack((Xn[:SPLIT, ...], Xp[:SPLIT, ...]))
y_train = np.vstack((yn[:SPLIT, ...], yp[:SPLIT, ...]))

X_test = np.vstack((Xn[SPLIT:, ...], Xp[SPLIT:, ...]))
y_test = np.vstack((yn[SPLIT:, ...], yp[SPLIT:, ...]))

print(X_train.shape)

# define model
model = create_model()
model.compile(loss="categorical_crossentropy",
              optimizer="adam",
              metrics=["accuracy"])

start = datetime.now()
model.fit(X_train, y_train, epochs=NUM_EPOCHS, batch_size=BATCH_SIZE)
end = datetime.now()

scores = model.evaluate(X_test, y_test)

print("\n{:} {:.2f}%".format(model.metrics_names[1], scores[1] * 100))
print("elapsed: {}".format(str(end - start)))

if __name__ == "__main__":
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "-b", "--batch_size",
        help="Number of examples per batch",
        type=int)
    parser.add_argument(
        "-e", "--epochs",
        help="Number of epochs to train over",
        type=int)
    parser.add_argument(
        "-k", "--kernel",
        help="(height, width) tuple representing size of kernel.",
        type=tuple)
    parser.add_argument(
        "-p", "--pool",
        help="(height, width) tuple representing size of pool.",
        type=tuple)

```

```

parser.add_argument(
    "-u", "--hidden_units",
    help="Number of hidden units for the Dense layer",
    type=int)
parser.add_argument(
    "-f", "--num_filters",
    help="Number of filters for the Conv layer",
    type=int)

args = parser.parse_args()

if args.batch_size:
    BATCH_SIZE = args.batch_size

if args.epochs:
    NUM_EPOCHS = args.epochs

if args.kernel:
    height, width = map(int, args.kernel.split(","))
    KERNEL_SIZE = (height, width)

if args.pool:
    height, width = map(int, args.pool.split(","))
    POOL_SIZE = (height, width)

if args.hidden_units:
    HIDDEN_UNITS = args.hidden_units

if args.num_filters:
    CONV_FILTERS = args.num_filters

main()

# acc: 94.70%
# elapsed: 0:00:56.455801

```

(b) Layers

(c) Hyperparameters

Model	Hyperparameters	Train Accuracy	Test Accuracy	Training Time
(1)	epochs = 300	100.00%	94.80%	00:13:02
	batch_size = 10			
	kernel_size = (4, 4)			
	pool_size = (4, 6)			
	hidden_units = 32			
(2)	num_filters = 32	99.32%	95.60%	00:35:37
	epochs = 50			
	batch_size = 10			
	kernel_size = (4, 4)			
	pool_size = (4, 6)			
(3)	hidden_units = 32	97.56%	93.50%	00:02:34
	num_filters = 1024			
	epochs = 50			
	batch_size = 10			
	kernel_size = (4, 4)			
(3)	pool_size = (4, 24)			
	hidden_units = 512			
	num_filters = 32			

(d) Architectures