```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git --version
git version 2.54.0 (Apple Git-157)
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git config user.name
matthcab
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git config user.email
156714188+matthcab@users.noreply.github.com
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is up to date with 'origin/matthieu_lacoste'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   src/main.py

no changes added to commit (use "git add" and/or "git commit -a")
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff
diff --git a/src/main.py b/src/main.py
index 854db11..75448fc 100644
--- a/src/main.py
+++ b/src/main.py
@@ -3,6 +3,7 @@ import csv
 import json


+
 DATA_DIR = Path("data/sample")

 # These starter values mirror config/settings.yml.
matthieulacoste@lacoste esilv-marketpulse-g01-t3M %
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff
diff --git a/src/main.py b/src/main.py
index 854db11..75448fc 100644
--- a/src/main.py
+++ b/src/main.py
@@ -3,6 +3,7 @@ import csv
 import json


+
 DATA_DIR = Path("data/sample")

 # These starter values mirror config/settings.yml.
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff
diff --git a/src/main.py b/src/main.py
index 854db11..147ec5e 100644
--- a/src/main.py
+++ b/src/main.py
@@ -2,6 +2,7 @@ from pathlib import Path
 import csv
 import json

+#test

 DATA_DIR = Path("data/sample")

matthieulacoste@lacoste esilv-marketpulse-g01-t3M %
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff
diff --git a/src/main.py b/src/main.py
index 854db11..d9b4b77 100644
--- a/src/main.py
+++ b/src/main.py
@@ -2,7 +2,6 @@ from pathlib import Path
 import csv
 import json

-
 DATA_DIR = Path("data/sample")

 # These starter values mirror config/settings.yml.
@@ -51,8 +50,6 @@ def display_market_summary(asset, prices, show_currency=True):
         print(f"First close  : {first_close:.2f}")
         print(f"Last close   : {last_close:.2f}")

-
-

 def main():
     instruments = load_instruments()
matthieulacoste@lacoste esilv-marketpulse-g01-t3M %
```

Which files are modified? src/main.py
Which lines were added? empty line in the first exemple and “#test” in the second one
Which lines were removed? 2 empty lines removed in the third exemple
Does the diff match the work you intended? yes
Is there temporary debugging output that should be removed before committing? There are no temporary debugging messages to remove before committing

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is up to date with 'origin/matthieu_lacoste'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   src/main.py

no changes added to commit (use "git add" and/or "git commit -a")
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status --short
 M src/main.py
```

“M src/main.py” means the file src/main.py has been modifed

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git add src/main.py
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is up to date with 'origin/matthieu_lacoste'.

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   src/main.py

matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff --staged
diff --git a/src/main.py b/src/main.py
index 854db11..d9b4b77 100644
--- a/src/main.py
+++ b/src/main.py
@@ -2,7 +2,6 @@ from pathlib import Path
 import csv
 import json

-
 DATA_DIR = Path("data/sample")

 # These starter values mirror config/settings.yml.
@@ -51,8 +50,6 @@ def display_market_summary(asset, prices, show_currency=True):
         print(f"First close  : {first_close:.2f}")
         print(f"Last close   : {last_close:.2f}")

-
-

 def main():
     instruments = load_instruments()
matthieulacoste@lacoste esilv-marketpulse-g01-t3M %
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % python3 src/main.py
=== MarketPulse ===

Instrument
AAPL - Apple Inc.
Observations : 21
First close  : 250.00 USD
Last close   : 266.20 USD

Benchmark
SP500 - S&P 500
Observations : 21
First close  : 6600.00 USD
Last close   : 6742.00 USD

Period: 1 month
Interval: Daily
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git commit -m "test modifying for git diff understanding"
[matthieu_lacoste c09dbec] test modifying for git diff understanding
 1 file changed, 3 deletions(-)
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is ahead of 'origin/matthieu_lacoste' by 1 commit.
  (use "git push" to publish your local commits)

nothing to commit, working tree clean
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git log --oneline
c09dbec (HEAD -> matthieu_lacoste) test modifying for git diff understanding
2c16b63 (origin/matthieu_lacoste) result td02
568ebdb result td01
b925509 suppression
c095ac7 add test file
95f33db Delete Team.md
3949d2b Create Team.md with team and project details
5207db8 first td session
ba5c9f4 Update Readme
9fd6c8a Update Readme
bfb94a6 init projecttemplate
```

we can see the identifier “c09dbec” and the message associated “test modifying for git diff understanding”

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git show head
commit c09dbec2b4caaaf04fcd903102259f934909e1dd (HEAD -> matthieu_lacoste)
Author: matthcab <156714188+matthcab@users.noreply.github.com>
Date:   Fri Nov 13 14:24:16 2026 +0100

    test modifying for git diff understanding

diff --git a/src/main.py b/src/main.py
index 854db11..d9b4b77 100644
--- a/src/main.py
+++ b/src/main.py
@@ -2,7 +2,6 @@ from pathlib import Path
 import csv
 import json

-
 DATA_DIR = Path("data/sample")

 # These starter values mirror config/settings.yml.
@@ -51,8 +50,6 @@ def display_market_summary(asset, prices, show_currency=True):
         print(f"First close  : {first_close:.2f}")
         print(f"Last close   : {last_close:.2f}")

-
-

 def main():
     instruments = load_instruments()
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git show c09dbec
commit c09dbec2b4caaaf04fcd903102259f934909e1dd (HEAD -> matthieu_lacoste)
Author: matthcab <156714188+matthcab@users.noreply.github.com>
Date:   Fri Nov 13 14:24:16 2026 +0100

    test modifying for git diff understanding

diff --git a/src/main.py b/src/main.py
index 854db11..d9b4b77 100644
--- a/src/main.py
+++ b/src/main.py
@@ -2,7 +2,6 @@ from pathlib import Path
 import csv
 import json

-
 DATA_DIR = Path("data/sample")

 # These starter values mirror config/settings.yml.
@@ -51,8 +50,6 @@ def display_market_summary(asset, prices, show_currency=True):
         print(f"First close  : {first_close:.2f}")
         print(f"Last close   : {last_close:.2f}")

-
-

 def main():
     instruments = load_instruments()
```

which files changed; src/main.py
what the diff represents; represents elements that has been modified
why the commit message is appropriate; to recall what has been done when we come back on the projet later or for the people we are working with to allow them understand quickly what we did
who is recorded as the author. we can see
Author: matthcab <156714188+matthcab@users.noreply.github.com>

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % touch td03_notes.txt
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is ahead of 'origin/matthieu_lacoste' by 1 commit.
  (use "git push" to publish your local commits)

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        td03_notes.txt

nothing added to commit but untracked files present (use "git add" to track)
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % rm td03_notes.txt
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is ahead of 'origin/matthieu_lacoste' by 1 commit.
  (use "git push" to publish your local commits)

nothing to commit, working tree clean
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is ahead of 'origin/matthieu_lacoste' by 1 commit.
  (use "git push" to publish your local commits)

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   requirements.txt
        modified:   src/main.py

no changes added to commit (use "git add" and/or "git commit -a")
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff
diff --git a/requirements.txt b/requirements.txt
index 665b359..f9eff90 100644
--- a/requirements.txt
+++ b/requirements.txt
@@ -1,2 +1,3 @@
+
 # External dependencies will be added progressively during the labs.
 # TD01/TD02 intentionally use only the Python standard library.
diff --git a/src/main.py b/src/main.py
index d9b4b77..c2260fe 100644
--- a/src/main.py
+++ b/src/main.py
@@ -4,6 +4,8 @@ import json

 DATA_DIR = Path("data/sample")

+
+
 # These starter values mirror config/settings.yml.
 # settings.yml is a human-readable configuration contract in the CORE.
 # Parsing YAML is optional and is not required by the 18-hour lab sequence.
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git add requirements.txt
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git status
On branch matthieu_lacoste
Your branch is ahead of 'origin/matthieu_lacoste' by 1 commit.
  (use "git push" to publish your local commits)

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   requirements.txt

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   src/main.py

matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff
diff --git a/src/main.py b/src/main.py
index d9b4b77..c2260fe 100644
--- a/src/main.py
+++ b/src/main.py
@@ -4,6 +4,8 @@ import json

 DATA_DIR = Path("data/sample")

+
+
 # These starter values mirror config/settings.yml.
 # settings.yml is a human-readable configuration contract in the CORE.
 # Parsing YAML is optional and is not required by the 18-hour lab sequence.
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git diff --staged
diff --git a/requirements.txt b/requirements.txt
index 665b359..f9eff90 100644
--- a/requirements.txt
+++ b/requirements.txt
@@ -1,2 +1,3 @@
+
 # External dependencies will be added progressively during the labs.
 # TD01/TD02 intentionally use only the Python standard library.
```

```
matthieulacoste@lacoste esilv-marketpulse-g01-t3M % git log --oneline -- src/main.py
c09dbec (HEAD -> matthieu_lacoste) test modifying for git diff understanding
2c16b63 (origin/matthieu_lacoste) result td02
bfb94a6 init projecttemplate
```

affiche les commit en une ligne ou le fichier main.py a ete affecte