MAE 200 Final project

Matthew Stringer

Based on code from github.com/matthew-d-stringer/Mae200-Final-Project

Step 1: Computing $u(t)$ on $t \in [0, T]$

For step 1, we must use adjoint-based optimization in order to compute the optimal input u_k. To do this, we use the provided code from Numerical Renaissance to calculate a more optimal input given a previous "guess" input. In order to get a satisfactory input, 2 things were done: First, an initial optimal input was generated given no input at all. Second, several more inputs were generated based on the previous computed optimal input. This results in a more optimal input. While generating inputs, I found that it was easier to generate satisfactory system responses when given a larger time horizon of 5 seconds rather than the default 3 second time horizon. This program in contained in `Dual_Pendulum_Input.m`



Step 2

Step 3

Step 4: State Estimation based on α-horizon

I began with constructing my model of my system based on the linearized model around equation 22.34 of Numerical Renaissance.

Since E is invertible around $\vec{q} = \vec{0}$, we can solve for the A and B matrices from the standard form,

$$\dot{q} = Aq + Bu,$$

by inverting the E matrix.

After inputting these matrices into matlab, we are left with the following system:

```
sys =
    A =
             x1         x2         x3         x4         x5         x6
    x1        0          0          0          1          0          0
```

```
x2       0       0       0       0       1       0
x3       0       0       0       0       0       1
x4       0   0.491   0.982       0       0       0
x5       0   5.175  0.9428       0       0       0
x6       0  0.9428    20.7       0       0       0

B =
        u1
x1       0
x2       0
x3       0
x4  0.1044
x5  0.1002
x6  0.2004

C =
    x1  x2  x3  x4  x5  x6
y1   1   0   0   0   0   0
y2   0   1   0   0   0   0
y3   0   0   1   0   0   0

D =
    u1
y1   0
y2   0
y3   0

Continuous-time state-space model.
```

Setting our Q matrix to 1, and our R matrix to 1, we create a Kalman filter using the `kalman` function. This results in an L matrix

```
L =
    0.4575    0.3394    0.3830
    0.3394    4.5172    0.2583
    0.3830    0.2583    9.0800
    0.2356    0.9622    1.9510
    0.8249   10.2934    1.8422
    1.7895    1.7995   41.3303
```

Step 5: Optimal Control

Using the linearized model described in Step 5, it is possible to utilize MATLAB's `lqr` function. Since we primarily care about the positional states of our system, we set their weights to be twice as large as their derivatives.

```
Q = diag([1 1 1 0.5 0.5 0.5]);
```

Since we only have one input, we can set its weight to 1.

```
R = 1;
```

This results in the following K matrix:

```
K =
    1.0000 -376.2629  680.7842    6.1759 -175.6396  154.7618
```