

MAE 200 Final project

Matthew Stringer

Step 1

Step 2

Step 3

Step 4: State Estimation based on α -horizon

I began with constructing my model of my system based on the linearized model around equation 22.34 of Numerical Renaissance. This resulted in the following code:

```
E = [  
    mc+m1+m2  -m1*l1      -m2*l1;  
    -m1*l1    I1+m1*l1^2    0  ;  
    -m2*l2     0          (I2 + m2*l2^2);  
];  
  
E = [  
    eye(3) zeros(3)  
    zeros(3) E  
];  
  
A_bar = [  
    0  0  0  
    0 m1*g*l2  0  
    0  0  m2*g*l2  
];  
  
A_bar = [  
    zeros(3) eye(3)  
    A_bar zeros(3)  
];  
  
B_bar = [  
    0  
    0  
    0  
    1  
    0  
    0  
];
```

Since E is invertible around $\vec{q} = \vec{0}$, we can solve for the A and B matrices from the standard form,

$$\dot{q} = Aq + Bu,$$

by inverting the E matrix. Thus, we create the following code

```

A = inv(E)*A_bar;
B = inv(E)*B_bar;

C = eye(3, 6);
D = 0;

sys = ss(A,B,C,D);

```

After running this code, we are left with the following system

```

sys =
  A =
      x1      x2      x3      x4      x5      x6
  x1      0      0      0      1      0      0
  x2      0      0      0      0      1      0
  x3      0      0      0      0      0      1
  x4      0    0.491    0.982      0      0      0
  x5      0    5.175    0.9428      0      0      0
  x6      0    0.9428    20.7      0      0      0

  B =
      u1
  x1      0
  x2      0
  x3      0
  x4    0.1044
  x5    0.1002
  x6    0.2004

  C =
      x1  x2  x3  x4  x5  x6
  y1    1  0  0  0  0  0
  y2    0  1  0  0  0  0
  y3    0  0  1  0  0  0

  D =
      u1
  y1    0
  y2    0
  y3    0

```

Continuous-time state-space model.

Step 5