



No.:

Date: 11-SEP-2020

Customer :

TECHNICAL PROPOSAL

Three-phase induction motor - Squirrel cage rotor

Product line : TEFC - W22 NEMA Premium Efficiency

Catalog Number :

List Price : \$

Notes:

Performed by:

Checked:



No.:

Date: 11-SEP-2020

DATA SHEET**Three-phase induction motor - Squirrel cage rotor**

Customer :
Product line : TEFC - W22 NEMA Premium Efficiency

Frame : 445/7T
Output : 150 HP
Frequency : 60 Hz
Poles : 6
Full load speed : 1187 rpm
Slip : 1.08 %
Voltage : 575 V
Rated current : 141 A
Locked rotor current : 873 A
Locked rotor current (I_L/I_n) : 6.2
No-load current : 56.0 A
Full load torque : 655 lb.ft
Locked rotor torque : 240 %
Breakdown torque : 250 %
Design : B
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 20 s (hot)
Service factor : 1.15
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 2042 lb
Moment of inertia : 133.62 sq.ft.lb
Noise level : 69 dB(A)

	D.E.	N.D.E.
Bearings	6319 C3	6316 C3
Regreasing interval	13000 h	16000 h
Grease amount	45 g	34 g

Load	Power factor	Efficiency (%)
100%	0.82	95.8
75%	0.78	95.4
50%	0.67	95.0

Notes:

Performed by

Checked




No.:

Date: 11-SEP-2020

PERFORMANCE CURVES RELATED TO RATED OUTPUT

Three-phase induction motor - Squirrel cage rotor



Customer :
Product line : TEFC - W22 NEMA Premium Efficiency

Frame	: 445/7T	Locked rotor current (I _L /I _n)	: 6.2
Output	: 150 HP	Duty cycle	: S1
Frequency	: 60 Hz	Service factor	: 1.15
Full load speed	: 1187 rpm	Design	: B
Voltage	: 575 V	Locked rotor torque	: 240 %
Rated current	: 141 A	Breakdown torque	: 250 %
Insulation class	: F		

Notes:

Performed by

Checked




No.:

Date: 11-SEP-2020

CHARACTERISTIC CURVES RELATED TO SPEED

Three-phase induction motor - Squirrel cage rotor



Customer :
Product line : TEFC - W22 NEMA Premium Efficiency

Frame	: 445/7T	Locked rotor current (I _L /I _n)	: 6.2
Output	: 150 HP	Duty cycle	: S1
Frequency	: 60 Hz	Service factor	: 1.15
Full load speed	: 1187 rpm	Design	: B
Voltage	: 575 V	Locked rotor torque	: 240 %
Rated current	: 141 A	Breakdown torque	: 250 %
Insulation class	: F		

Notes:

Performed by

Checked

