

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11679361

Frame	: 588/9TS	Locked rotor time	: 59s (cold) 33s (hot)
Output	: 600 HP (440 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 636 A	Protection degree	: IP55
L. R. Amperes	: 6042 A	Cooling method	: IC411 - TEFC
LRC	: 9.5x(Code K)	Mounting	: F-1
No load current	: 142 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3586 rpm	Noise level ²	: 89.0 dB(A)
Slip	: 0.39 %	Starting method	: Direct On Line
Rated torque	: 879 ft.lb	Approx. weight ³	: 4746 lb
Locked rotor torque	: 300 %		
Breakdown torque	: 320 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 155 sq.ft.lb		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	95.9	96.0	96.5	96.5	Max. traction	: 4227 lb
Power Factor	0.62	0.84	0.89	0.90	Max. compression	: 8973 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
3.8	2.4	1.8	2.5	1.3	1.1	0.5

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	:	4000 h	4000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 6 Revision		
Checked by				
Date	09/07/2025			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	09/07/2025				

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679361



Performance : 460 V 60 Hz 2P

Rated current	: 636 A	Moment of inertia (J)	: 155 sq.ft.lb
LRC	: 9.5	Duty cycle	: Cont.(S1)
Rated torque	: 879 ft.lb	Insulation class	: F
Locked rotor torque	: 300 %	Service factor	: 1.00
Breakdown torque	: 320 %	Temperature rise	: 80 K
Rated speed	: 3586 rpm		

Locked rotor time : 59s (cold) 33s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	09/07/2025			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679361



Performance : 460 V 60 Hz 2P

Rated current : 636 A
LRC : 9.5
Rated torque : 879 ft.lb
Locked rotor torque : 300 %
Breakdown torque : 320 %
Rated speed : 3586 rpm

Moment of inertia (J) : 155 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 6	
Date					

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679361



Performance : 460 V 60 Hz 2P

Rated current : 636 A
LRC : 9.5
Rated torque : 879 ft.lb
Locked rotor torque : 300 %
Breakdown torque : 320 %
Rated speed : 3586 rpm

Moment of inertia (J) : 155 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 6Revision		
Checked by				
Date	09/07/2025			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679361



Performance : 460 V 60 Hz 2P

Rated current	: 636 A	Moment of inertia (J)	: 155 sq.ft.lb
LRC	: 9.5	Duty cycle	: Cont.(S1)
Rated torque	: 879 ft.lb	Insulation class	: F
Locked rotor torque	: 300 %	Service factor	: 1.00
Breakdown torque	: 320 %	Temperature rise	: 80 K
Rated speed	: 3586 rpm		

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 6 / 6 Revision		
Checked by				
Date	09/07/2025			

