

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11679237

Frame	: 586/7T	Locked rotor time	: 28s (cold) 16s (hot)
Output	: 600 HP (440 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 665 A	Protection degree	: IP55
L. R. Amperes	: 4722 A	Cooling method	: IC411 - TEFC
LRC	: 7.1x(Code G)	Mounting	: F-1
No load current	: 210 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1790 rpm	Noise level ²	: 78.0 dB(A)
Slip	: 0.56 %	Starting method	: Direct On Line
Rated torque	: 1760 ft.lb	Approx. weight ³	: 4335 lb
Locked rotor torque	: 229 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 235 sq.ft.lb		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	96.2	96.4	96.5	Max. traction	: 7014 lb
Power Factor	0.00	0.74	0.82	0.86	Max. compression	: 11349 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6322 C3	6319 C3
Sealing	:	Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	:	6000 h	8000 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 6 Revision		
Checked by				
Date	09/07/2025			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	09/07/2025				

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679237



Performance : 460 V 60 Hz 4P

Rated current	: 665 A	Moment of inertia (J)	: 235 sq.ft.lb
LRC	: 7.1	Duty cycle	: Cont.(S1)
Rated torque	: 1760 ft.lb	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.15
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 1790 rpm		

Locked rotor time : 28s (cold) 16s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	09/07/2025			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679237



Performance : 460 V 60 Hz 4P

Rated current : 665 A
LRC : 7.1
Rated torque : 1760 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 250 %
Rated speed : 1790 rpm

Moment of inertia (J) : 235 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 6	
Date					

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679237



Performance : 460 V 60 Hz 4P

Rated current : 665 A
LRC : 7.1
Rated torque : 1760 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 250 %
Rated speed : 1790 rpm

Moment of inertia (J) : 235 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 6 Revision		
Checked by				
Date	09/07/2025			

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11679237



Performance : 460 V 60 Hz 4P

Rated current : 665 A
LRC : 7.1
Rated torque : 1760 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 250 %
Rated speed : 1790 rpm

Moment of inertia (J) : 235 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 6Revision			
Checked by					
Date	09/07/2025				

