

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 14882464

Frame	: 588/9T	Locked rotor time	: 41s (cold) 23s (hot)
Output	: 700 HP (515.20 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 630 A	Protection degree	: IP55
L. R. Amperes	: 4098 A	Cooling method	: IC411 - TEFC
LRC	: 6.5x(Code H)	Mounting	: F-1
No load current	: 192 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1790 rpm	Noise level ²	: 81.0 dB(A)
Slip	: 0.56 %	Starting method	: Direct On Line
Rated torque	: 2050 ft.lb	Approx. weight ³	: 5610 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 220 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 335 sq.ft.lb		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	96.2	96.5	96.6	Max. traction	: 6621 lb
Power Factor	0.76	0.81	0.85	Max. compression	: 12231 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.2	3.2	2.5	2.6	1.8	1.4	0.8

	Drive end	Non drive end
Bearing type	: 6322 C3	6319 C3
Sealing	: Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	: 6000 h	8000 h
Lubricant amount	: 60 g	45 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	09/07/2025			

Page 1 / 6
Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 110 - 127 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	09/07/2025				

TORQUE AND CURRENT VS SPEED CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 14882464



Performance : 575 V 60 Hz 4P

Rated current	: 630 A	Moment of inertia (J)	: 335 sq.ft.lb
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 2050 ft.lb	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.00
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 1790 rpm		

Locked rotor time : 41s (cold) 23s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	09/07/2025			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 14882464

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 4P

Rated current	: 630 A	Moment of inertia (J)	: 335 sq.ft.lb
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 2050 ft.lb	Insulation class	: F
Locked rotor torque	: 250 %	Service factor	: 1.00
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 1790 rpm		

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 4 / 6Revision		
Checked by				
Date	09/07/2025			

THERMAL LIMIT CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 14882464



Performance : 575 V 60 Hz 4P

Rated current : 630 A
LRC : 6.5
Rated torque : 2050 ft.lb
Locked rotor torque : 250 %
Breakdown torque : 220 %
Rated speed : 1790 rpm

Moment of inertia (J) : 335 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 6Revision		
Checked by				
Date	09/07/2025			

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

Subject to change without notice

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 14882464



Performance : 575 V 60 Hz 4P

Rated current : 630 A
LRC : 6.5
Rated torque : 2050 ft.lb
Locked rotor torque : 250 %
Breakdown torque : 220 %
Rated speed : 1790 rpm

Moment of inertia (J) : 335 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 6 / 6 Revision		
Checked by				
Date	09/07/2025			

