STRATA: Conformal Prediction with Heterogeneous Message-Passing Calibration for Infrastructure Risk Assessment

Matt Powell MATTHEW.A.POWELL@OUTLOOK.COM
Lottly AI
GIS and Machine Learning Research
United States

Abstract

Quantifying uncertainty in node-level risk predictions across coupled infrastructure systems—power grids, water networks, and telecommunications—requires prediction intervals that are both distribution-free and topology-aware. Standard split conformal prediction provides marginal coverage guarantees but produces uniformly-sized intervals that ignore the heterogeneous difficulty landscape induced by infrastructure coupling. We introduce STRATA (Spatially-Typed Risk-Aware Topology Adaptation), a framework that combines heterogeneous graph neural networks with a novel Conformal Heterogeneous Message-Passing (CHMP) calibration scheme. CHMP normalizes conformal nonconformity scores using frozen training-set residuals propagated through cross-utility coupling edges, producing locally adaptive prediction intervals while preserving finite-sample coverage guarantees without distributional assumptions. We further develop four advanced calibrator architectures—MetaCalibrator (learned normalization), AttentionCalibrator (neighbor-weighted difficulty), LearnableLambdaCalibrator (per-type optimal scaling), and a heterogeneous CQR variant—alongside an ensemble-based epistemic uncertainty decomposition. Evaluated on synthetic multi-utility graphs and a real-world 200-bus Central Illinois power grid (ACTIVSg200), STRATA maintains nominal 90% marginal coverage (0.908 ± 0.030) across all calibrator variants while providing a principled framework for per-type coverage guarantees on heterogeneous infrastructure graphs. An ensemble-based calibrator achieves the narrowest intervals (0.743 ± 0.052), and a Friedman test over ECE reveals highly significant calibration differences across methods ($p < 10^{-4}$), while coverage differences remain statistically indistinguishable ($p = 0.93$)—consistent with conformal theory.

Keywords: conformal prediction, graph neural networks, heterogeneous graphs, uncertainty quantification, calibration

1 Introduction

Critical infrastructure systems—electric power, water distribution, and telecommunications—form interdependent networks where failures cascade across utility boundaries (Rinaldi et al., 2001; Buldyrev et al., 2010). A transformer outage at a power substation can disable water treatment pumps, which in turn disrupts telecom cooling systems at co-located facilities (Ouyang, 2014). Predicting node-level risk scores in such coupled systems requires not only accurate point predictions but also reliable uncertainty quantification: operators need to know
emphhow wrong a risk estimate might be at each infrastructure node, and that uncertainty is inherently non-uniform across the heterogeneous graph.

©2026 Matthew Powell.

License: CC-BY 4.0, see https://creativecommons.org/licenses/by/4.0/.



Figure 1: Method comparison — marginal coverage (20 seeds).



Figure 2: Method comparison — mean interval width (20 seeds).

Conformal prediction (Vovk et al., 2005; Shafer and Vovk, 2008; Angelopoulos and Bates, 2023) offers distribution-free prediction intervals with finite-sample coverage guarantees, making it attractive for safety-critical infrastructure applications where parametric assumptions may be violated. However, standard split conformal prediction produces inter-



Figure 3: Method comparison — ECE (20 seeds).

vals of uniform width across all nodes, ignoring the topology-dependent difficulty structure that arises from infrastructure coupling.

Graph neural networks (GNNs) (Kipf and Welling, 2017; Gilmer et al., 2017; Hamilton et al., 2017) have emerged as powerful tools for node-level prediction on relational data, and recent work has extended conformal prediction to graph-structured settings (Zargarbashi et al., 2023; Huang et al., 2024; Clarkson, 2023). However, all existing graph conformal prediction methods target *node classification*—producing prediction *sets*—and operate on homogeneous, single-type graphs. To date, no framework provides distribution-free prediction *intervals* for node-level *regression* on heterogeneous multi-type graphs, nor does any prior method exploit graph-propagated residuals to adapt interval widths while preserving finite-sample coverage guarantees.

We address these gaps with **STRATA**, the first conformal prediction framework for heterogeneous graph regression, integrating three key innovations:

1. **Conformal Heterogeneous Message Passing (CHMP)**: A propagation-aware calibration scheme that normalizes nonconformity scores using frozen training-set residuals propagated through the infrastructure coupling topology. Rather than reducing aggregate interval width, CHMP *redistributes* width across nodes—giving wider intervals to nodes in high-difficulty neighborhoods and narrower intervals to low-difficulty nodes.

2. **A family of advanced calibrators** that learn the normalization function from data: a MetaCalibrator using heteroscedastic Gaussian NLL (Kendall and Gal, 2017), an AttentionCalibrator using learned neighbor weights, a LearnableLambdaCalibrator with per-type grid-search, and a heterogeneous CQR variant (Romano et al., 2019). An



Figure 4: ACTIVSg200 spatial site map.



Figure 5: Per-type interval width map.

ensemble-based calibrator using epistemic variance (Lakshminarayanan et al., 2017) achieves the strongest width reduction (6.4% narrower than Mondrian CP).

3. **Spatial diagnostics** including Moran's I autocorrelation tests (Moran, 1950), Getis-Ord G_i^* hotspot detection (Getis and Ord, 1992), and conformal kriging surfaces (Cressie, 1993) that bridge infrastructure risk assessment with geostatistical analysis.

2 Related Work

2.1 Conformal Prediction

Conformal prediction, developed by Vovk et al. (2005), provides distribution-free prediction regions with finite-sample coverage guarantees under the exchangeability assumption. The inductive (split) conformal framework (Papadopoulos et al., 2002) partitions data into training, calibration, and test sets. Lei et al. (2018) established distribution-free inference guarantees for regression. Mondrian conformal prediction (Vovk, 2012) extends coverage guarantees to group-conditional settings.

Recent extensions have relaxed the exchangeability requirement. Barber et al. (2023) proved finite-sample coverage results beyond exchangeability, directly motivating our use of normalized scores on graph-structured data. Gibbs and Candès (2021) proposed adaptive conformal inference for streaming settings with distribution shift. Prior impossibility results for exact conditional coverage without strong distributional assumptions motivate STRATA's approximate type-conditional approach via Mondrian splits combined with propagation-aware normalization.

2.2 Conformal Prediction on Graphs

Zargarbashi et al. (2023) introduced DAPS, a diffusion-based approach for conformal prediction *sets* on GNNs for node classification. Clarkson (2023) provided distribution-free coverage guarantees for node classification under graph dependence, and Huang et al. (2024) developed CF-GNN for node-level uncertainty quantification, also in the classification setting. Most recently, Song et al. (2024) proposed SNAPS, using similarity-navigated scores for graph conformal classification (NeurIPS'24). Notably, **all prior graph conformal prediction work targets classification**—producing prediction *sets*—and operates on homogeneous, single-type graphs. STRATA differs by (i) targeting *regression* with prediction *intervals*, (ii) modeling heterogeneous multi-typed infrastructure graphs with per-type Mondrian coverage, and (iii) introducing propagation-aware normalization (CHMP) using frozen training-set residuals.

2.3 Graph Neural Networks for Heterogeneous Data

Heterogeneous GNNs extend message passing to multi-typed graphs: R-GCN (Schlichtkrull et al., 2018) introduces relation-specific weight matrices, HAN (Wang et al., 2019) applies hierarchical attention, and HGT (Hu et al., 2020) uses transformer-style attention. STRATA's message passing layer follows the R-GCN design with per-edge-type linear transforms, residual connections, and dropout.

2.4 Uncertainty Quantification

Deep ensembles (Lakshminarayanan et al., 2017) provide calibrated epistemic uncertainty. Kendall and Gal (2017) decomposed uncertainty into aleatoric and epistemic components via heteroscedastic loss—directly inspiring STRATA's MetaCalibrator. Conformalized quantile regression (CQR) (Romano et al., 2019) combines neural network quantile regression

(Koenker and Bassett, 1978) with conformal calibration. STRATA extends CQR to heterogeneous graphs with propagation-aware normalization.

3 Methods

3.1 Problem Formulation

Consider a heterogeneous infrastructure graph $G = (V, E, \tau_V, \tau_E)$ where $V = V_{\text{power}} \cup V_{\text{water}} \cup V_{\text{telecom}}$ with type function $\tau_V : V \to \{\text{power}, \text{water}, \text{telecom}\}$. Each node v_i has features $\mathbf{x}_i \in \mathbb{R}^d$ and a scalar risk label $y_i \in [0, 1]$.

Given a trained GNN with point predictions $\hat{y}_i$, we seek prediction intervals $C_i = [\ell_i, u_i]$ such that:

$$\Pr(y_i \in C_i) \geq 1 - \alpha \tag{1}$$

for a user-specified miscoverage level α, ideally with the additional type-conditional guarantee:

$$\Pr(y_i \in C_i \mid \tau_V(i) = t) \geq 1 - \alpha, \quad \forall t \in \{\text{power}, \text{water}, \text{telecom}\} \tag{2}$$

3.2 Heterogeneous GNN Architecture

STRATA's GNN backbone extends the R-GCN framework (Schlichtkrull et al., 2018) with residual connections. Each `HeteroMessagePassingLayer` ℓ computes:

$$\mathbf{h}_i^{(\ell)} = \text{ReLU}\big(\mathbf{W}_{\text{self}}\mathbf{h}_i^{(\ell-1)} + \sum_{r \in \mathcal{R}} \frac{1}{|\mathcal{N}_r(i)|} \sum_{j \in \mathcal{N}_r(i)} \mathbf{W}_r \mathbf{h}_j^{(\ell-1)}\big) + \mathbf{h}_i^{(\ell-1)} \tag{3}$$

where $\mathcal{R}$ is the set of edge types and $\mathbf{W}_r$ are per-relation weight matrices. Per-type output heads project final representations to scalar risk predictions.

3.3 Conformal Heterogeneous Message Passing (CHMP)

CHMP introduces propagation-aware normalization:

Step 1. After training, compute residuals $r_j = |y_j - \hat{y}_j|$ for all training nodes $j \in \mathcal{D}_{\text{train}}$.

Step 2. Aggregate neighbor difficulty:

$$\bar{r}_{\mathcal{N}(i)} = \text{agg}_{j \in \mathcal{N}(i) \cap \mathcal{D}_{\text{train}}}(r_j) \tag{4}$$

Step 3. Compute normalization signal: $\sigma_i = 1 + \lambda \cdot \bar{r}_{\mathcal{N}(i)}$

Step 4. Calibration scores: $s_i = |y_i - \hat{y}_i|/\sigma_i$

Step 5. Prediction intervals:

$$C_i = [\hat{y}_i - \hat{q}_{\tau(i)} \cdot \sigma_i,\ \hat{y}_i + \hat{q}_{\tau(i)} \cdot \sigma_i] \tag{5}$$

Theorem 1 (CHMP Coverage Guarantee) *Let $\{(X_i, Y_i)\}_{i=1}^{n+1}$ be exchangeable random variables, let $\hat{f}$ be trained on $\mathcal{D}_{train}$ (disjoint from calibration and test sets), and let $\sigma_i = 1 + \lambda \cdot \bar{r}_{\mathcal{N}(i)}$ where $\bar{r}_{\mathcal{N}(i)}$ is computed exclusively from frozen training-set residuals. Define normalized scores $s_i = |Y_i - \hat{f}(X_i)|/\sigma_i$ for $i \in \mathcal{D}_{cal} \cup \{n+1\}$. Let $\hat{q}$ be the $\lceil (1-\alpha)(|\mathcal{D}_{cal}| + 1)\rceil / |\mathcal{D}_{cal}|$ quantile. Then:*

$$\Pr\big(Y_{n+1} \in [\hat{f}(X_{n+1}) - \hat{q} \cdot \sigma_{n+1},\ \hat{f}(X_{n+1}) + \hat{q} \cdot \sigma_{n+1}]\big) \geq 1 - \alpha \tag{6}$$

Proof [Proof sketch] Since σ_i is a deterministic function of training data, the normalized scores s_i inherit exchangeability from the original variables (Barber et al., 2023). The result follows from the standard split conformal guarantee (Papadopoulos et al., 2002; Lei et al., 2018). The Mondrian extension to per-type quantiles similarly preserves type-conditional coverage (Vovk, 2012). ■

Assumption 1 *(A1) Exchangeability of calibration and test data conditioned on the training set. (A2) The normalization signal $\sigma_i \geq 1$ is computed solely from training-set quantities. (A3) For Mondrian type-conditional coverage, exchangeability holds within each infrastructure type.*

3.4 Advanced Calibrator Variants

MetaCalibrator. A lightweight MLP predicts σ_i from node-level features including the point prediction, neighbor residual statistics, and node degree, trained with heteroscedastic Gaussian NLL.

AttentionCalibrator. Learns attention weights over neighbors for difficulty aggregation via a small MLP.

LearnableLambdaCalibrator. Optimizes λ per type through a 50/50 calibration-tune split with grid search.

CQR with Propagation. Extends conformalized quantile regression (Romano et al., 2019) to heterogeneous graphs with optional σ_i normalization. Quantile heads predict $q_{\alpha/2}(\mathbf{h}_i)$ and $q_{1-\alpha/2}(\mathbf{h}_i)$ using pinball loss.

3.5 Ensemble Uncertainty Decomposition

M independent GNNs with different random seeds provide: $\hat{y}_i = \frac{1}{M}\sum_m \hat{y}_i^{(m)}$, $\mathrm{Var}_i = \frac{1}{M}\sum_m (\hat{y}_i^{(m)} - \hat{y}_i)^2$. The EnsembleCalibrator uses $\sigma_i = 1 + \lambda\sqrt{\mathrm{Var}_i}$.

4 Experimental Setup

4.1 Synthetic Infrastructure Data

We generate heterogeneous infrastructure graphs with 200 power nodes (tree topology), 150 water nodes (grid/mesh), 100 telecom nodes (star-hub), 8-dimensional features, and cross-utility coupling probability 0.3.

4.2 Real Infrastructure Data: ACTIVSg200

We use the ACTIVSg200 200-bus Central Illinois power grid (Birchfield et al., 2017), constructing a three-layer heterogeneous graph with power (200 nodes), water (∼108 nodes derived from demand centers), and telecom (∼80 hub nodes).

4.3 Additional Public Benchmark: IEEE 118

To reduce the risk that conclusions depend on a single real-network topology, we also evaluate STRATA on the public IEEE 118-bus MATPOWER case. As with ACTIVSg200, we retain the real transmission-layer graph and derive water and telecom layers from demand centres, yielding a second public heterogeneous benchmark with a distinct topology and degree distribution.

4.4 Evaluation Protocol

All experiments use 20 random seeds with 60/20/20 train/cal/test splits. Metrics: marginal coverage, type-conditional coverage, mean interval width, ECE (Guo et al., 2017), paired Wilcoxon tests (Wilcoxon, 1945), and Friedman test (Friedman, 1937).

5 Results

5.1 Baseline Comparison

Table 1: Baseline comparison (20 seeds, $\alpha = 0.10$).

Method	Coverage	Width	ECE
Mondrian CP	0.908 ± 0.032	0.794 ± 0.072	0.057 ± 0.022
CHMP (mean)	0.908 ± 0.030	0.793 ± 0.071	0.080 ± 0.020
CHMP (median)	0.908 ± 0.030	0.794 ± 0.071	0.078 ± 0.021
CHMP (med.+floor)	0.908 ± 0.032	0.794 ± 0.072	0.067 ± 0.023

All methods achieve the nominal 90% coverage target. Coverage is statistically indistinguishable (Friedman $p = 0.93$), confirming CHMP preserves the conformal guarantee. CHMP's primary effect is width *redistribution* rather than aggregate reduction.

5.2 Advanced Calibrator Comparison

Table 2: Full method comparison (20 seeds, $\alpha = 0.10$). Best width in **bold**.

Method	Coverage	Width	ECE
Mondrian CP	0.908 ± 0.032	0.794 ± 0.072	**0.057**
CHMP (mean)	0.908 ± 0.030	0.793 ± 0.071	0.080
CHMP (median)	0.908 ± 0.030	0.794 ± 0.071	0.078
CHMP (med.+floor)	0.908 ± 0.032	0.794 ± 0.072	0.067
MetaCalibrator	0.916 ± 0.027	0.792 ± 0.069	0.075
AttentionCalibr.	0.914 ± 0.027	0.790 ± 0.070	0.070
LearnableLambda	0.914 ± 0.026	0.788 ± 0.064	0.065
CQR + propagation	0.900 ± 0.034	0.838 ± 0.063	0.083
Ensemble (M=3)	0.920 ± 0.030	$\mathbf{0.743 \pm 0.052}$	0.073

The ensemble-based calibrator achieves the narrowest intervals (0.743), a 6.4% reduction from Mondrian CP, while maintaining valid coverage (0.920). CQR with propagation produces the widest intervals (0.838), suggesting that quantile head training on frozen representations is insufficiently expressive for this heterogeneous graph structure.

5.3 Lambda Sensitivity

Table 3: Lambda sensitivity (20 seeds, $\alpha = 0.10$).

λ	Coverage	Width	ECE
0.0	0.916 ± 0.033	0.792 ± 0.078	0.056
0.1	0.916 ± 0.032	0.791 ± 0.077	0.069
0.3	0.916 ± 0.029	0.789 ± 0.075	0.067
0.5	0.915 ± 0.029	0.788 ± 0.073	0.069
1.0	0.912 ± 0.029	0.791 ± 0.071	0.071

Coverage remains stable across all λ values (within 0.4%). Width shows minimal sensitivity ($< 0.5\%$ variation), confirming robustness to hyperparameter misspecification.

5.4 Statistical Significance

Friedman test (coverage). Across all nine methods and 20 seeds: $\chi^2 = 3.05$, $p = 0.93$. We fail to reject the null hypothesis of equal coverage performance.

Friedman test (ECE). $\chi^2 = 34.3$, $p < 10^{-4}$, indicating highly significant differences in calibration quality. Pairwise Wilcoxon tests confirm Mondrian CP achieves significantly lower ECE than CHMP variants ($p < 0.01$).

Width. Only CQR ($p = 0.024$, wider) and Ensemble ($p = 0.019$, narrower) differ significantly from Mondrian CP.

5.5 Public Real-Data Benchmarks

Beyond the main synthetic benchmark, we evaluated Mondrian and CHMP on two public MATPOWER-derived heterogeneous graphs using three seeds each. On ACTIVSg200, both methods achieved average marginal coverage of 0.935; CHMP slightly reduced mean width relative to Mondrian (0.564 vs. 0.568) but had slightly higher ECE (0.073 vs. 0.068). On IEEE 118, both methods again achieved average marginal coverage of 0.898, while CHMP was marginally wider (0.805 vs. 0.803) and less well calibrated by ECE (0.105 vs. 0.069). The main conclusion from these public-network runs is therefore conservative: STRATA transfers across more than one real topology, but CHMP does not yet demonstrate a consistent out-of-sample advantage over the simpler Mondrian baseline on these datasets.

5.6 Alpha Ablation and Fairness Audit

The alpha ablation confirms the expected conformal tradeoff: average marginal coverage decreases from 0.974 at $\alpha = 0.05$ to 0.829 at $\alpha = 0.20$, while average width decreases from 1.166 to 0.604. This monotone trend is important because it demonstrates that STRATA's

implementation respects the intended width–coverage control surface rather than producing unstable behavior under retuning. A representative group-wise audit at $\alpha = 0.10$ produced an overall coverage of 0.965 and a worst-group coverage gap of 0.035 across the three infrastructure types, suggesting mild but measurable group disparity that should be monitored in deployment.

6 Discussion

6.1 Width Redistribution vs. Aggregate Reduction

Because all prior graph conformal methods target classification on homogeneous graphs (§2), STRATA is, to our knowledge, the first framework to provide distribution-free prediction intervals for node-level regression on multi-typed graphs. CHMP's primary design goal is not to shrink intervals in aggregate but to *redistribute* interval width according to local graph difficulty: nodes in high-residual neighborhoods receive wider intervals while low-difficulty nodes receive narrower ones. Across 20 synthetic seeds, CHMP and Mondrian CP produce nearly identical mean widths (~ 0.794), but the spatial distribution differs meaningfully—confirmed by significant Moran's I autocorrelation ($p < 0.01$) in the residual field under CHMP. The real-data comparisons make clear that this redistribution is not automatically beneficial in aggregate: the width effect is slightly favorable on ACTIVSg200 and slightly unfavorable on IEEE 118. The strongest claim supported by the current evidence is therefore mechanistic: CHMP changes *where* interval budget is allocated, which is valuable in infrastructure settings where spatially non-uniform risk demands non-uniform uncertainty coverage.

6.2 Limitations

1. **No significant aggregate width improvement.** CHMP does not produce narrower intervals than Mondrian CP ($p > 0.50$). Only the ensemble method achieves significant width reduction (6.4%, $p = 0.019$) at $3\times$ training cost.

2. **Lambda insensitivity.** Width varies $< 0.5\%$ across $\lambda \in [0, 1]$, suggesting the normalization signal is weak relative to the conformal quantile correction.

3. **CQR underperformance.** CQR produces the widest intervals (0.838) and lowest coverage (0.900).

4. **ECE trade-off.** CHMP variants exhibit higher ECE than Mondrian CP (0.067–0.080 vs. 0.057, $p < 0.01$).

5. **Synthetic data dominance.** The water and telecom layers in ACTIVSg200 and IEEE 118 are derived from power demand heuristics rather than independent utility datasets. This makes the public real-data evaluation useful for topology transfer, but not a full validation on independently measured multi-utility networks.

6. **Mixed real-data evidence.** On the two MATPOWER-based benchmarks, CHMP matches Mondrian coverage but does not produce a consistent width or ECE improvement. The method's empirical advantage over simpler baselines therefore remains benchmark-dependent.

7. **Scalability.** Current evaluation on graphs with ∼400 nodes.

8. **Static analysis.** STRATA provides static risk intervals; streaming infrastructure monitoring requires online conformal updates (Gibbs and Candès, 2021).

9. **Residual group disparity.** The fairness audit shows a worst-group coverage gap of roughly 0.035 in a representative run. This is not catastrophic, but it indicates that type-conditional monitoring should remain part of the evaluation and deployment workflow.

7 Conclusion

We introduced STRATA, the first framework for distribution-free uncertainty quantification via conformal prediction on heterogeneous graph regression. While prior graph conformal methods address node *classification* on homogeneous graphs (DAPS, NAPS, SNAPS, CF-GNN), STRATA targets node-level *regression* with per-type Mondrian coverage guarantees. The core contribution—Conformal Heterogeneous Message Passing—provides locally adaptive prediction intervals by propagating frozen training-set difficulty signals through the infrastructure coupling topology, preserving finite-sample coverage guarantees. Experiments across 20 random seeds demonstrate that all calibrator variants maintain valid marginal and type-conditional coverage (Friedman $p = 0.93$).

CHMP's primary effect is spatial redistribution of interval widths rather than aggregate width reduction. Among all calibrators, the ensemble approach achieves the only statistically significant width improvement (6.4%, $p = 0.019$). STRATA establishes a principled framework for applying conformal prediction to heterogeneous graph-structured data with per-type coverage guarantees, spatial diagnostics, and a family of normalization strategies. The current evidence supports CHMP as a plausible mechanism for difficulty-aware width redistribution, while also indicating that simpler baselines remain competitive on public real-data benchmarks.

Acknowledgments and Disclosure of Funding

This work was conducted independently without external funding. The author declares no competing interests. The author consents to publication and confirms that this manuscript is not under simultaneous review elsewhere. Code, tests, examples, benchmark scripts, and a supplementary reproducibility bundle are provided at `https://github.com/matthew-lottly/strata`.

Software. Code is available at `https://github.com/matthew-lottly/strata` under the MIT License.

References

Anastasios N Angelopoulos and Stephen Bates. Conformal prediction: A gentle introduction. *Foundations and Trends in Machine Learning*, 16(4):494–591, 2023.

Rina Foygel Barber, Emmanuel J Candès, Aaditya Ramdas, and Ryan J Tibshirani. Conformal prediction beyond exchangeability. *Annals of Statistics*, 51(2):816–845, 2023.

Adam B Birchfield, Ti Xu, Kathleen M Gegner, Komal S Shetye, and Thomas J Overbye. Grid structural characteristics as validation criteria for synthetic power grids. *IEEE Transactions on Power Systems*, 32(4), 2017.

Sergey V Buldyrev, Roni Parshani, Gerald Paul, H Eugene Stanley, and Shlomo Havlin. Catastrophic cascade of failures in interdependent networks. *Nature*, 464:1025–1028, 2010.

Jase Clarkson. Distribution-free prediction sets for node classification. In *International Conference on Artificial Intelligence and Statistics*, volume 206 of *PMLR*, 2023.

Noel AC Cressie. *Statistics for Spatial Data*. Wiley, revised edition, 1993.

Milton Friedman. The use of ranks to avoid the assumption of normality implicit in the analysis of variance. *Journal of the American Statistical Association*, 32(200):675–701, 1937.

Arthur Getis and J Keith Ord. The analysis of spatial association by use of distance statistics. *Geographical Analysis*, 24(3):189–206, 1992.

Isaac Gibbs and Emmanuel J Candès. Adaptive conformal inference under distribution shift. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International Conference on Machine Learning*, volume 70 of *PMLR*, 2017.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning*, volume 70 of *PMLR*, 2017.

William L Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Ziniu Hu, Yuxiao Dong, Kuansan Wang, and Yizhou Sun. Heterogeneous graph transformer. In *The World Wide Web Conference*, pages 2704–2710, 2020.

Kexin Huang, Ying Jin, Emmanuel Candes, and Jure Leskovec. Uncertainty quantification over graph with conformalized graph neural networks. In *Advances in Neural Information Processing Systems*, volume 36, 2024.

Alex Kendall and Yarin Gal. What uncertainties do we need in Bayesian deep learning for computer vision? In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations*, 2017.

Roger Koenker and Gilbert Bassett. Regression quantiles. *Econometrica*, 46(1):33–50, 1978.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Jing Lei, Max G'Sell, Alessandro Rinaldo, Ryan J Tibshirani, and Larry Wasserman. Distribution-free predictive inference for regression. *Journal of the American Statistical Association*, 113(523):1094–1111, 2018.

Patrick AP Moran. Notes on continuous stochastic phenomena. *Biometrika*, 37:17–23, 1950.

Min Ouyang. Review on modeling and simulation of interdependent critical infrastructure systems. *Reliability Engineering & System Safety*, 121:43–60, 2014.

Harris Papadopoulos, Kostas Proedrou, Volodya Vovk, and Alex Gammerman. Inductive confidence machines for regression. In *European Conference on Machine Learning*, pages 345–356. Springer, 2002.

Steven M Rinaldi, James P Peerenboom, and Terrence K Kelly. Identifying, understanding, and analyzing critical infrastructure interdependencies. *IEEE Control Systems Magazine*, 21(6):11–25, 2001.

Yaniv Romano, Evan Patterson, and Emmanuel J Candès. Conformalized quantile regression. In *Advances in Neural Information Processing Systems*, volume 32, pages 3543–3553, 2019.

Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne van den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *European Semantic Web Conference*. Springer, 2018.

Glenn Shafer and Vladimir Vovk. A tutorial on conformal prediction. *Journal of Machine Learning Research*, 9:371–421, 2008.

Jianqing Song, Jianguo Cao, and Rui Chen. Similarity-navigated conformal prediction for graph neural networks. In *Advances in Neural Information Processing Systems*, volume 37, 2024.

Vladimir Vovk. Conditional validity of inductive conformal predictors. In *Asian Conference on Machine Learning*, volume 25 of *PMLR*, pages 475–490, 2012.

Vladimir Vovk, Alex Gammerman, and Glenn Shafer. *Algorithmic Learning in a Random World*. Springer, 2005.

Xiao Wang, Houye Ji, Chuan Shi, Bai Wang, Yanfang Ye, Peng Cui, and Philip S Yu. Heterogeneous graph attention network. In *The World Wide Web Conference*, pages 2022–2032, 2019.

Frank Wilcoxon. Individual comparisons by ranking methods. *Biometrics Bulletin*, 1(6): 80–83, 1945.

Soroush H Zargarbashi, Simone Antonelli, and Aleksandar Bojchevski. Conformal prediction sets for graph neural networks. In *International Conference on Machine Learning*, volume 202 of *PMLR*, 2023.