Text

- **<h1>** heading1 **</h1>**
- **<h2>** heading1 **</h2>**
- **<h3>** heading1**</h3>**
- **<h4>** heading1 **</h4>**
- **<h5>** heading1 **</h5>**
- **<h6>** heading1 **</h6>**
- **<p>** paragraph **</p>**
- **** bold ****
- **<i>** italic **</i>**
- **^{** superscript **}**
- **_{** subscript **}**
- **</br>** new line
- **</hr>** line separator
- **** strong importance****
- **** indicates emphasis, subtly changing of meaning ****
- **<blockquote><p>**used for longer quotes that take up an entire paragraph, indented content. ==//notice the paragraph elements used inside the blockquote element== **</p></blockquote>**
- **<p><q>**smaller quote, notice the paragraph elements on either side of the quote element. ==//technically browsers are supposed to put quotation marks around <q> elements but internet explorer doesn't so just avoid it==**</q></p>**
- **<abbr title = "**Professor**">** Prof **</abbr>**
- **<acronym title = "**National Aeronautics and Space Administration**">** NASA **</acronym>**
- **<cite>** when you reference a book, film, research paper. Indicate where citation is from. ==//do not cite a name== **</cite>**
- **<dfn>** jargon //new term**</dfn>**

Author details:
- **<address> <p> < a** href"mailto: matt@example.org>
  matt@example.com**</p> <p>**6231 Pembroke drive. San Diego. ==//browsers display addresses in italics== **</p> </address>**

Changes to Content:
- **<ins>** underlined text **</ins>**
- **~~** text with line through ==//single word use== **~~**
- **<s>** whole line getting crossed through ==//content irrelevant but shouldn't get deleted==**</s>**