Layers

- BatchNorm
- Convolution
- Dropout
- Linear
- LSTM
- Pooling
- RNN

BatchNorm

BatchNorm accelerates convergence by reducing internal covariate shift inside each batch. If the individual observations in the batch are widely different, the gradient updates will be choppy and take longer to converge.

The batch norm layer normalizes the incoming activations and outputs a new batch where the mean equals 0 and standard deviation equals 1. It subtracts the mean and divides by the standard deviation of the batch.

Code

Code example from Agustinus Kristiadi

```
def BatchNorm():
# From https://wiseodd.github.io/techblog/2016/07/04/batchnorm/
 # TODO: Add doctring for variable names. Add momentum to init.
 def __init__(self):
     pass
 def forward(self, X, gamma, beta):
     mu = np.mean(X, axis=0)
     var = np.var(X, axis=0)
     X_{norm} = (X - mu) / np.sqrt(var + 1e-8)
     out = gamma * X_norm + beta
     cache = (X, X norm, mu, var, gamma, beta)
     return out, cache, mu, var
 def backward(self, dout, cache):
     X, X_norm, mu, var, gamma, beta = cache
     N, D = X.shape
     X mu = X - mu
     std_inv = 1. / np.sqrt(var + 1e-8)
     dX norm = dout * gamma
     dvar = np.sum(dX_norm * X_mu, axis=0) * -.5 * std_inv**3
     dmu = np.sum(dX_norm * -std_inv, axis=0) + dvar * np.mean(-2. * X_mu, axis=0)
     dX = (dX_norm * std_inv) + (dvar * 2 * X_mu / N) + (dmu / N)
     dgamma = np.sum(dout * X_norm, axis=0)
     dbeta = np.sum(dout, axis=0)
     return dX, dgamma, dbeta
```

Further reading

- Original Paper
- Implementing BatchNorm in Neural Net
- Understanding the backward pass through Batch Norm

Convolution

Be the first to contribute!

Dropout

Be the first to contribute!

Linear

Be the first to contribute!

LSTM

Be the first to contribute!

Pooling

Max and average pooling layers.

Be the first to contribute!

RNN

Be the first to contribute!

References

[1] http://www.deeplearningbook.org/contents/convnets.html