

```
● (base) matthewbosworth@Matthews-Laptop-4 OS-Group-Assignment2 % cd "/Users/matthewbosworth/Desktop/OS-Group-Assignment2/" && javac BankersAlgorithm.java && java BankersAlgorithm
```

```
=====
| Initial State of the Banker's Algorithm. |
=====
```

Allocation Matrix:				Max Matrix:			
	A	B	C	A	B	C	
T0	0	1	0	7	5	3	
T1	2	0	0	3	2	2	
T2	3	0	2	9	0	2	
T3	2	1	1	2	2	2	
T4	0	0	2	4	3	3	

Need Matrix:			
	A	B	C
T0	7	4	3
T1	1	2	2
T2	6	0	0
T3	0	1	1
T4	4	3	1

Available: (3, 3, 2)

Initial Safe Sequence:

T1 -> T3 -> T4 -> T0 -> T2

```
=====
Case 1 - Request that should be GRANTED
=====
```

```
=====
Request: Threat T1 requests (1, 0, 2)
=====
```

✓ GRANTED - Request is safe.

Safe sequence:

T1 -> T3 -> T4 -> T0 -> T2

Need Matrix:			
	A	B	C
T0	7	4	3
T1	0	2	0
T2	6	0	0
T3	0	1	1
T4	4	3	1

Available: (2, 3, 0)

```
=====
Case 2 - Request that should be DENIED
=====
```

```
=====
Request: Threat T0 requests (0, 2, 0)
=====
```

X DENIED - Granting this request would lead to an unsafe state.