

F3ildCrypt: End-to-End Protection of Sensitive Information in Web Services

Matthew Burnside and Angelos D. Keromytis

Department of Computer Science
Columbia University
{mb, angelos}@cs.columbia.edu

ISC 2009

Motivation

- Identity-related information is valuable
- You must provide such information when using an online merchant
- This information is vulnerable to disclosure at many points
- Can we protect this information end-to-end without revealing details of the logical corporate architecture?

Outline

- 1 Introduction
- 2 Related work
- 3 Architecture
- 4 Evaluation
- 5 Conclusion

Introduction

- Users have to trust online merchants:
- Merchant is not malicious
- Merchant site is maintained by diligent sysadmins
- Merchant will protect always sensitive information

SOA trust

- In Service Oriented Architectures, users have to trust:
- Merchant *and peer* SOAs are not malicious
- Merchant *and peer* SOAs are maintained by diligent sysadmins
- Merchant *and peer* SOAs will always protect sensitive information

Data in transit

- In this work, we focus on data in transit
- We protect the data from the web browser to the back-end database

Example

- XXX: Diagram showing web browser, merchant, and SOA doing credit-card transactions. Even with SSL, only protected from web browser to merchant.

Pair-wise key distribution

- Generate and distribute a key for each potential target host in the SOA pipeline.
- Naive – doesn't work! XXX

Proxy re-encryption

For all plaintext P , Alice $\langle pk_A, sk_A \rangle$, Bob $\langle pk_B, sk_B \rangle$:

$$pk_B(p) = rk_{A \rightarrow B}(pk_A(P))$$

- [Blaze et al., 1998]
- [Ateniese et al., 2005]

- Introduced end-to-end encryption in web pipelines
- Firefox plugin for application-level crypto
- Requires disclosure of corporate network details

Architecture

- Design goals
- F3ieldCrypt architecture
- Example session

Network model

- SOA-style network
- Each SOA may have multiple child SOAs
- SOAs wish to prevent disclosure of logical architecture and peering

Threat model

- XXX

Design goals

- End-to-end protection of XML fields – even across SOA boundaries
- Confidentiality of logical architecture of each SOA must be respected

Do not provide protection against compromise or failure of entities with legitimate access to sensitive information.

F3ieldCrypt architecture

- Each SOA s publishes a public key pk_{E_s}
- Browser b generates plaintext P
- b sends $C = pk_{E_s}(P)$
- At s , proxy re-encrypt C to internal hosts and child SOAs $0...n$

Key generation

- Key pair $\langle pk_{E_s}, sk_{E_s} \rangle$ generated at the external-key holder
- Public keys of applications $pk_{I_0} \dots pk_{I_n}$ are collected
- Used in conjunction with sk_{E_s} to generate $rk_{E \rightarrow I_0} \dots rk_{E \rightarrow I_n}$

F3ieldCrypt architecture (cont.)

- By proxy re-encryption:

$$pk_{I_j}(P) = rk_{E \rightarrow I_j}(pk_E(P))$$

- Keys $rk_{E \rightarrow I_0} \dots rk_{E \rightarrow I_n}$ stored at **proxy re-encryption engine**

Proxy re-encryption engine

- Fields arrive at PRE encrypted under pk_{E_s}
- Each field f is re-encrypted under $pk_{E \rightarrow I_j}$
- The mapping $f \rightarrow j$ is determined from a XACML policy

Client policy and crypto engines

Web clients receive a re-cryptography engine and a policy engine.

- **Policy engine** uses a XACML policy to determine which fields to encrypt
- **Re-crypto engine** encrypts XML fields as directed by the policy engine.

Architecture summary

- XXX: insert image

Implementation

- Java-based Re-crypto engine based on JHU-MIT Proxy Re-cryptography Library for each web client
- Python-based XML proxy for each internal application to store keys and unwrap XML
- XML gateway at the SOA stores the re-encryption engine

Testbed servers

Dell PowerEdge 2650 Servers


- 2.0GHz Intel Zeon processor, 1GB RAM, Gigabit Ethernet
- OpenBSD 4.2
- OpenBSD PF firewall, Apache 1.3.29, PHP 4.4.1, MySQL 5.0.45

Testbed client


Macbook Pro

- 2.4 GHz Intel Core 2 Duo, 2GB RAM, Gigabit Ethernet
- OS X 10.5.2, Darwin kernel 9.2.2, Mozilla Firefox 2.0.0.13


Block encryption on the client



Re-encryption rate at an XML gateway



Decryption rate at an XML proxy



Conclusion

- End-to-end protection to users and SOAs
- XXX



G. Ateniese, K. Fu, M. Green, and S. Hohenberger.

Improved proxy re-encryption schemes with applications to secure distributed storage.

In Proceedings of the 12th Annual Network and Distributed Systems Security Symposium (NDSS 2005), 2005.



Matt Blaze, G. Bleumer, and M. Strauss.

Divertible protocols and atomic proxy cryptography.

In Proceedings of Eurocrypt '98, pages 127–144, 1998.



Angelos Stavrou, Michael Locasto, and Angelos Keromytis.

W3bcrypt: Encryption as a stylesheet.

In Proceedings of the 4th Applied Cryptography and Network Security Conference (ACNS 2006), pages 349–364, 2006.