CS186 Discussion 4

(Buffer Management, Heap Files, File Organization)

Matthew Deng

Buffer Management

Buffer Management

- Buffer pool
 - In-memory cache for database tables
- Not all data can fit in memory at once
- Which data should we keep?
 - Buffer replacement policies
 - Least Recently Used (LRU)
 - Most Recently Used (MRU)
 - Clock

Least Recently Used (LRU)

- Evict page that has been least recently used
- Must keep track of when pages were used
- Prone to sequential flooding
- Example: A, B, C, D, E, A, B, C, D

1	А						
2		В					
3			С				
4				D			

Hit Rate:

Least Recently Used (LRU)

- Evict page that has been least recently used
- Must keep track of when pages were used
- Prone to sequential flooding
- Example: A, B, C, D, E, A, B, C, D

1	А				Е				D
2		В				A			
3			С				В		
4				D				С	

Hit Rate: 0/9

Most Recently (LRU)

- Evict page that has been most recently used
- Must keep track of when pages were used
- Solves sequential flooding
- Example: A, B, C, D, E, A, B, C, D

1	Α						
2		В					
3			С				
4				D			

Hit Rate:

Most Recently (LRU)

- Evict page that has been most recently used
- Must keep track of when pages were used
- Solves sequential flooding
- Example: A, B, C, D, E, A, B, C, D

1	А					*			
2		В					*		
3			С					*	D
4				D	Е				

Hit Rate: 3/9

Clock

- Approximation for LRU
- Use reference bits
- Each page gets a second chance
- Example: A, B, C, D, E, A, B, C, D

1	Α						
2		В					
3			С				
4				D			

Hit Rate:

Clock

```
if HIT:
    reference bit = 1
else:
    while reference bit != 0:
        reference bit = 0
        move hand
    replace page
    reference bit = 1
    move hand
```

Clock

- Approximation for LRU
- Use reference bits
- Each page gets a second chance
- Example: A, B, C, D, E, A, B, C, D

1	А				Е				D
2		В				A			
3			С				В		
4				D				С	

Hit Rate: 0/9

Buffer Replacement Worksheet

Fill in the following tables for the given buffer replacement policies. You have 4 buffer pages, with the access pattern ABCDAFADGDGEDF

1. Least Recently Used (LRU)

1	А								
2		В							
3			С						
4				D					

Hit Rate:

Fill in the following tables for the given buffer replacement policies. You have 4 buffer pages, with the access pattern ABCDAFADGDGEDF

1. Least Recently Used (LRU)

1	А				*		*							F
2		В				ш						E		
3			U						G		*			
4				D				*		*			*	

Hit Rate: 6/14

Fill in the following tables for the given buffer replacement policies. You have 4 buffer pages, with the access pattern ABCDAFADGDGEDF

2. Most Recently Used (MRU)

1	Α								
2		В							
3			С						
4				D					

Hit Rate:

Fill in the following tables for the given buffer replacement policies. You have 4 buffer pages, with the access pattern ABCDAFADGDGEDF

2. Most Recently Used (MRU)

1	А				*	F	Α							
2		В												
3			С											
4				D				*	G	D	G	Е	D	F

Hit Rate: 2/14

Fill in the following tables for the given buffer replacement policies. You have 4 buffer pages, with the access pattern ABCDAFADGDGEDF

3. Clock

1	Α								
2		В							
3			С						
4				D					

Hit Rate:

Fill in the following tables for the given buffer replacement policies. You have 4 buffer pages, with the access pattern ABCDAFADGDGEDF

3. Clock

1	Α				*	F							D	
2		В					A							F
3			С						G		*			
4				D				*		*		Е		

Hit Rate: 4/14

When is LRU the worst possible replacement policy?

When is LRU the worst possible replacement policy?

Sequential Scans – Flooding


Why would we use a clock replacement policy over LRU?

Why would we use a clock replacement policy over LRU?

Efficiency (Clock approximates LRU)


Heap Files

Record Formats: Fixed Length




use this when you can!

Record Formats: Variable Length



symbols can cause problems


Page Formats: Fixed Length



record id = <page id, slot number>

moving records in packed changes rid free space in unpacked spread out

Page Formats: Variable Length



can move records without changing rid

Heap Files Worksheet

1. What can we do to support variable length records (over fixed length records)?

1. What can we do to support variable length records (over fixed length records)?

Delimit with special symbols or use an array of field offsets

2. What are the advantages and disadvantages of using slotted pages or bitmaps versus tightly packing records together?

2. What are the advantages and disadvantages of using slotted pages or bitmaps versus tightly packing records together?

advantages: can move records without changing rid supports variable length records

disadvantages: needs a page directory

- 3. You have a slotted page with 80 bytes of free space, and it costs 4 bytes to store a directory entry.
 - a. What is the size of the largest record you can insert?

- 3. You have a slotted page with 80 bytes of free space, and it costs 4 bytes to store a directory entry.
 - a. What is the size of the largest record you can insert?

$$80 - 4 = 76$$
 bytes

3. You have a slotted page with 80 bytes of free space, and it costs 4 bytes to store a directory entry.

b. At most, how many 1 byte large records can you insert?

- 3. You have a slotted page with 80 bytes of free space, and it costs 4 bytes to store a directory entry.
 - b. At most, how many 1 byte large records can you insert?

$$80/(4+1) = 16$$
 records

File Organization

File Organization

	Heap File	Sorted File
Scan All		
Equality Search		
Range Search		
Insertion		
Deletion		

File Organization

	Heap File	Sorted File
Scan All	В	В
Equality Search	.5B	log ₂ (B)
Range Search	В	log ₂ (B) + num_matches
Insertion	2	log ₂ (B) + 2 * .5B
Deletion	.5B + 1	log ₂ (B) + 2 * .5B

File Organization Worksheet

Consider the table Enrolled(sid, course, grade) with 6,000 tuples spread evenly over 500 pages, and the query SELECT * FROM Enrolled WHERE sid > 4500.

a. How many I/Os would this query take if the table was stored in a heap file?

Consider the table Enrolled(sid, course, grade) with 6,000 tuples spread evenly over 500 pages, and the query SELECT * FROM Enrolled WHERE sid > 4500.

a. How many I/Os would this query take if the table was stored in a heap file?

$$I/Os = B = 500$$

Consider the table Enrolled(sid, course, grade) with 6,000 tuples spread evenly over 500 pages, and the query SELECT * FROM Enrolled WHERE sid > 4500.

b. If the table was stored in a file sorted on grade?

Consider the table Enrolled(sid, course, grade) with 6,000 tuples spread evenly over 500 pages, and the query SELECT * FROM Enrolled WHERE sid > 4500.

b. If the table was stored in a file sorted on grade?

$$I/Os = B = 500$$

Consider the table Enrolled(sid, course, grade) with 6,000 tuples spread evenly over 500 pages, and the query SELECT * FROM Enrolled WHERE sid > 4500.

c. If the table was stored in a file sorted on sid?

Consider the table Enrolled(sid, course, grade) with 6,000 tuples spread evenly over 500 pages, and the query SELECT * FROM Enrolled WHERE sid > 4500.

c. If the table was stored in a file sorted on sid?

$$I/Os = log_2(B) + [# matching pages]$$

= $log_2(500) + 500/4$
= 134

Or...
$$I/OS = B = 125$$