# DIANA Fellowship Proposal Matthew Feickert

#### Abstract

The statistical software used for the last several years in particle physics is facing scalability challenges. In addition to processing speed, which is being addressed with GPU-based fitting approaches, we also face memory limitations as the combined statistical models grow in size. Thus, it is critical to investigate more distributed models for these computations.

The rapid development of software libraries for numerical computations through data flow graphs (e.g., TensorFlow and Theano) has led to a fundamental change of paradigm in machine learning software. While originally developed for the purpose of deep learning research, these libraries are general enough to be applicable in a wide variety of other domains, including particle physics statistical models. Under the mentorship of Gilles Louppe and Vince Croft, Matthew Feickert will investigate the pros and cons of implementing the statistical models used in particle physics with a different computational graph framework. In particular, we will assess their capabilities and limits, and determine how those frameworks would scale in terms of data and model parallelism.

## 1 Project Description

One of the focus areas for DIANA [1] is to "establish infrastructure for a higher-level of collaborative analysis, building on the successful patterns used for the Higgs boson discovery". A large component of this focus is statistical software. RooFit [2] is one of the primary tools used now, but it is facing scalability challenges. In addition to processing speed, which is being addressed with GPU-based fitting approaches, we also face memory limitations as the combined statistical models grow in size. Thus, it is critical to investigate more distributed models.

Within only a couple of years, the rapid development of software libraries for numerical computations through data flow graphs (e.g., TensorFlow [3], Theano [4], and MXNet [5]) has led to a fundamental change of paradigm in machine learning software. These libraries are designed around the concept that a numerical program can often equivalently be expressed as a graph — where nodes represent mathematical operations and edges represent the data communicated between them. Most notably, these libraries allow one to automatically deploy computation over one or more CPUs or GPUs within a single API. This makes it easy to maximize performance without specialized software expertise.

While these frameworks were originally developed for the purpose of deep learning research, they are usually general enough to be applicable in a wide variety of other domains. For this reason, the objective of this DIANA project — conducted by Matthew Feickert under the mentorship of Gilles Louppe and Vince Croft — is to investigate the pros and cons of implementing the statistical models used in particle physics with a different computational graph framework. As these models are typically built with RooFit and HistFactory [6], we first wish to establish reference benchmarks in these frameworks. Later in the project, we will assess the capabilities and limits of different frameworks and determine how they would scale in terms of data and model parallelism. In addition, the study should also determine whether existing probabilistic programming framework based data flow graphs (e.g., Edward [7] and tensorprob [8]) are applicable for particle physics statistical models. Where appropriate, the study should finally identify shortcomings on which further software efforts could be dedicated.

Chien-Chin Huang is a computer science Ph.D. student supported via DIANA. He is investigating the model and data parallelism in systems such as TensorFlow. A bottle neck in the current work is a set of benchmark physics problems that he can use for these scalability tests. This DIANA fellowship would help remove that bottleneck and accelerate work to connect other DIANA projects like Histogrammar [9].

#### 2 Deliverables

- A public GitHub repository with the benchmark model code and instructions for use.
- A document providing the implementation-independent definition of the binned benchmark template that is representative of particle physics use cases.
- Scripts preparing the benchmarks using HistFactory to establish the RooFit benchmark.
- A technical report investigating the potential and limits of data flow graph frameworks for particle physics statistical models.
- A tutorial on data flow graphs targeted for physicists.
- Contributions to a probabilistic framework (if time permits).

### 3 Roadmap

- May, 2017
  - Design of representative benchmarks models:
    - \* A template for binned models that is parametrized in terms of number of events, number of bins, number of channels, number of signal/background components, and number of parameters of interest and nuisance parameters.
    - \* Establish a precise mathematical formulation that is implementation-independent. This will be based on the HistFactory schema.
    - \* Document the template model.
  - Implementation of this template for the benchmark models with a HistFactory script (probably in Python). This will provide the RooFit benchmark.
  - Study of data flow graph frameworks (e.g., TensorFlow, Theano, MXNet) or of probabilistic programming frameworks (e.g., Edward, tensorprob).
- June, 2017
  - Implementation of the benchmark models in one of the studied frameworks.
  - Benchmarks evaluating their data and model parallelism.
- July, 2017
  - Technical report and recommendations for particle physics use cases.
  - Upstream software contributions to address the identified limitations (if any).
  - Development of/Contribution to a probabilistic framework (if time permits).

# 4 Proposed Timeline

• May 8th through May 21st:
☐ Create a GitHub repository for the project.
□ Design a template for binned models that is parametrized in terms of number of events, number of bins, number of channels, number of signal/background components, and number of parameters of interest and nuisance parameters.
$\hfill\square$ Begin documentation of the template model on the GitHub repository.
• May 22nd through June 4th:
$\hfill\Box$ Establish a precise mathematical formulation that is implementation-independent based on the <code>HistFactory</code> schema.
$\hfill \square$ Begin study of data flow graph frameworks or of probabilistic programming frameworks.
$\hfill\square$ Implement the template for the benchmark models with a ${\tt HistFactory}$ script.
• June 5th through June 18th:
$\Box$ Conclude from study of data flow graph frameworks or of probabilistic programming frameworks which framework to pursue.
$\hfill\square$ Begin implementation of the benchmark models in the selected framework.
$\square$ Begin to write technical report.
• June 19th through July 2nd:
$\hfill\square$ Finish implementation of the benchmark models in the selected framework.
$\hfill\square$ Apply benchmarks evaluating framework data and model parallelism.
• July 3rd through July 16th:
☐ Finish technical report.
$\hfill \square$ Create tutorial on data flow graphs targeted for physicists.
• July 17th through August 8th:
<ul> <li>□ Upstream software contributions to address the identified limitations (if any).</li> <li>□ Development of/Contribution to a probabilistic framework (if time permits).</li> </ul>

### References

- [1] P. Elmer, K. Cranmer, M. Sokolof and B. Bockelman, *Data-Intensive Analysis for High Energy Physics (DIANA/HEP)*, June, 2014.
- [2] W. Verkerke and D. P. Kirkby, *The RooFit toolkit for data modeling*, eConf C0303241 (2003) MOLT007, [physics/0306116].
- [3] M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro et al., *TensorFlow: Large-scale machine learning on heterogeneous systems*, 2015.
- [4] Theano Development Team collaboration, R. Al-Rfou, G. Alain, A. Almahairi, C. Angermueller, D. Bahdanau, N. Ballas et al., *Theano: A Python framework for fast computation of mathematical expressions, arXiv e-prints* abs/1605.02688 (May, 2016).
- [5] T. Chen, M. Li, Y. Li, M. Lin, N. Wang, M. Wang et al., Mxnet: A flexible and efficient machine learning library for heterogeneous distributed systems, CoRR abs/1512.01274 (2015) .
- [6] ROOT collaboration, K. Cranmer, G. Lewis, L. Moneta, A. Shibata and W. Verkerke, *HistFactory: A tool for creating statistical models for use with RooFit and RooStats*, 2012.
- [7] D. Tran, A. Kucukelbir, A. B. Dieng, M. Rudolph, D. Liang and D. M. Blei, *Edward: A library for probabilistic modeling, inference, and criticism, arXiv preprint arXiv:1610.09787* (2016).
- [8] I. Babuschkin, "tensorprob: A probabilistic programming framework based on TensorFlow." https://github.com/tensorprob/tensorprob, 2016.
- [9] J. Pivarski and A. Svyatkovskiyi, "Histogrammar." https://github.com/histogrammar, 2017.