Code Verification in Rust with Verus

Matt Grimes

Oct 30 2026

What is code verification

Z3

Verus

Verification as LLM Guardrails

What does it mean for code to be "correct?"

To ask if code is "correct," we have to formulate a formal claim about what the code does.

Taking a max

If *max* returns the max of two integers, x and y, we expect the following properties:

- $max(x, y) \in \{x, y\}$
- $max(x, y) \geq x$
- $max(x, y) \geq y$

Taking the max of two integers

We can state the logical claim that the implementation is correct as

$$\forall x, y, m \in \mathbb{Z},\ m = \max(x, y) \implies (m = x \vee m = y) \wedge m \geq x \wedge m \geq y$$

In general, $a \implies b$ is equivalent to $\neg a \vee b$. We can thus rewrite

$$\forall x, y, m \in \mathbb{Z},\ \neg(m = \max(x, y)) \vee ((m = x \vee m = y) \wedge m \geq x \wedge m \geq y)$$

Equivalently, the implementation of max has a bug if and only if

$$\exists x, y, m \in \mathbb{Z},\ (m = \max(x, y)) \wedge \neg ((m = x \vee m = y) \wedge m \geq x \wedge m \geq y)$$

The general formulation

Let s and s' denote program states, and let $C(s, s')$ mean that program C can terminate in s' when started in s.

$$\forall s, s',\ P(s) \wedge C(s, s') \Longrightarrow Q(s') \quad := \quad \{P\}\ C\ \{Q\}$$

- P: a predicate on the initial state (the precondition).
- Q: a predicate on the final state (the postcondition).
- Initial values can be retained in the state to express input–output relations.

Applied to max

In our example we have

- P: x and y are integers
- C: m is given by the implementation of max
- Q: $m \geq x \wedge m \geq y \wedge (m = y \vee m = x)$

What about the implementation?

In pseudo-code, we can define a naive implementation of max:

```
fn max(x: int, y: int) -> (m: int)
{
    if x > y
    {
        return x;
    } else
    {
        return y;
    }

}
```

Logically, this implementation can be expressed by

$$m = \max(x, y) := ((x > y) \wedge (m = x)) \vee (\neg(x > y) \wedge (m = y))$$

Putting it all together

We can combine everything on the prior slides into the following statement: our implementation of max is *incorrect* if and only if $\exists x, y, m \in \mathbb{Z}$ such that

$$\underbrace{[((x > y) \wedge (m = x)) \vee (\neg(x > y) \wedge (m = y))]}_{m \text{ given by } \max(x,y)} \wedge \neg \underbrace{[(m = x \vee m = y) \wedge m \geq x \wedge m \geq y]}_{m \text{ satisfies definition of max}}$$

We can see by inspection that the claim is false, there is no counter-example, and the implementation is proven correct.

Z3: satisfiability relative to a theory

In the last section, we asked whether or not $\exists x, y, m \in \mathbb{Z}$ such that

$$\underbrace{[((x > y) \wedge (m = x)) \vee (\neg(x > y) \wedge (m = y))]}_{m \text{ given by } \max(x,y)} \wedge \neg \underbrace{[(m = x \vee m = y) \wedge m \geq x \wedge m \geq y]}_{m \text{ satisfies definition of max}}$$

This is exactly the type of statement the SMT/SAT solver Z3 is designed to answer.

SMT: satisfiability modulo theories

Given a formula and a background "theory", is the formula satisfiable?

- Boolean combinations of constraints in supported theories.
- Examples: integer arithmetic, fixed-width bit-vectors, arrays.
- The theory determines the meaning of symbols such as $+$ and $\leq$.

For our example: linear constraints over the integers.

Source: Microsoft's Z3 Guide

Prove a property by searching for its violation

$$\exists s, s' : \; P(s) \wedge C(s, s') \wedge \neg Q(s').$$

Ask whether the existential counterexample formula is satisfiable.



- `sat`: a violation exists in this encoding.
- `unsat`: no such violation exists in this encoding.
- `unknown`: the solver could not decide; no proof obtained.

Source: Z3 Guide: Basic Commands

Ask Z3 to find any bugs

```
(define-fun is_max ((m Int) (x Int) (y Int)) Bool
    (and
        (>= m x)
        (>= m y)
        (or
            (= m x)
            (= m y)
        )
    )
)
(define-fun max ((x Int) (y Int)) Int
    (ite (> x y) x y)
)

(declare-const x Int)
(declare-const y Int)
(declare-const m Int)
(assert
    (and
        (= m (max x y))
        (not (is_max m x y))
    )
)
(check-sat)
(get-model)
```

Result: `unsat`

Verus connects Rust code to proof obligations



- Write specifications and proofs alongside executable code.
- Verify supported Rust code with annotations and library specifications.
- Erase specification/proof code when compiling the executable.

Source: Verus project

Source: Verus Guide: code modes

Three modes, three jobs

Mode	Purpose	Example
`exec`	Actual computation	Update a counter
`spec`	Mathematical definitions	Describe the desired result
`proof`	Establish logical facts	Supply a lemma or assertion

- Think: computation, definition, and lemma.
- Specifications can use mathematical `int` and `nat`.
- Ghost code is reasoning-only code, erased before execution.

Source: Verus Guide: code modes

Implementing max in Rust

```
fn max(x: i64, y: i64) -> i64
{
    if x>y {x} else {y}
}
```

Decorating our implementation with Verus

```
fn max(x: i64, y: i64) -> (m: i64)
    requires
    ensures
        m>=x,
        m>=y,
        (m==x) || (m==y)
{
    if x>y {x} else {y}
}
```

- `requires`: what callers must establish.
- `ensures`: what callers may rely on afterward.

Source: Verus Guide: contracts

What must be established?

1. **Safe addition:** $x < \mathit{limit} \leq$ `u32::MAX` gives room to increment.
2. **Bounded result:** each branch returns at most the limit.
3. **Exact behavior:** increment below the limit, stay put at the limit.

Try the original bug

Replace `x < limit` with `x <= limit` in the body.
The same contract should reject the implementation.

Using a verified function is applying a lemma

Suppose we have established

$$\forall x, L \in \{0, \ldots, 2^{32} - 1\}, \quad x \leq L \implies \text{advance}(x, L) = \min(x + 1, L).$$

- Instantiate at $(x, L) = (4, 5)$ to deduce the result is 5.
- Instantiate at $(x, L) = (5, 5)$ to deduce the result is again 5.
- At $(x, L) = (6, 5)$, the hypothesis fails; the theorem gives no guarantee.

Modular proof

Subsequent arguments use the function's contract as a lemma.
They need not repeat the proof about its implementation.

A loop invariant is an induction hypothesis

For `while` B `do` C, choose a predicate I on states.

$$\underbrace{P \Rightarrow I}_{\text{base case}}, \qquad \underbrace{\{I \wedge B\}\ C\ \{I\}}_{\text{inductive step}}, \qquad \underbrace{I \wedge \neg B \Rightarrow Q}_{\text{conclusion at exit}}.$$

For repeated bounded successor, take $I(x) \equiv 0 \leq x \leq L$.

- Initially: $0 \leq x_0 \leq L$ is assumed.
- If $x < L$, then $x' = x + 1 \leq L$; the invariant is preserved.
- At exit: $x \leq L$ and $\neg(x < L)$ imply $x = L$.

Termination uses well-foundedness

$V(x) = L - x \in \mathbb{N}$ decreases strictly on every iteration.

Loops need an invariant

```
fn fill_to_limit(start: u32, limit: u32) -> (r: u32)
    requires start <= limit,
    ensures r == limit,
{
    let mut x = start;
    while x < limit
        invariant x <= limit,
        decreases limit - x,
    {
        x = advance(x, limit);
    }
    x
}
```

Invariant: we stay within the limit. Variant: the remaining distance shrinks.

Source: Verus Guide: Loops and invariants


What is being trusted?

- The specification captures the intended theorem.
- The translation from code to logical obligations is sound.
- The solver's result and any assumed lemmas are correct.
- Compilation and execution preserve the verified meaning.

Distinguish proof search from proof checking

Here we rely on the Verus/Z3 verification pipeline.
We are not presenting an independently checked proof certificate.

An LLM proposes a construction; verification checks it



Plausibility is not a proof: check the generated construction against a fixed claim.

A concrete revision loop

1. Freeze the counter contract and allowed input domain.
2. Ask the LLM to implement the function and discharge obligations.
3. Reject the <= candidate when verification fails.
4. Revise the body to use <; check the same contract again.
5. Inspect the changed argument and test the surrounding program.

Helpful prompt constraint

"Keep the contract unchanged. Do not introduce assumptions or bypass verification. Explain any remaining obligations."

Do not let a proof attempt change the theorem

- **Weaken the conclusion:** replace $r = \min(x + 1, L)$ by $r \leq L$.
- **Strengthen the hypotheses:** exclude the failing boundary case.
- **Assume the claim:** introduce an unproved premise that implies it.

The guardrail must preserve the statement

Fix the contract, audit new assumptions, and require all intended obligations to pass.

The guardrail has a defined reach

Can establish, when specified

- Results satisfy a contract.
- Arithmetic stays in range.
- A modeled invariant is preserved.

Still needs separate evidence

- The contract matches user intent.
- External systems match the model.
- The algorithm is efficient enough to use.

Stronger acceptance criteria make generated code easier to evaluate.

Start with one property worth keeping true

1. Write the contract before polishing the implementation.
2. Use Z3's counterexample-search model to understand proof obligations.
3. Let Verus connect those obligations to Rust code.
4. Make verification a required check for LLM-generated changes.

Which theorem about an algorithm would you want its implementation to carry?

References and demo files

- Verus Tutorial and Reference

  `https://verus-lang.github.io/verus/guide/`

- Verus source and installation instructions

  `https://github.com/verus-lang/verus`

- Microsoft's Z3 Guide

  `https://microsoft.github.io/z3guide/`

Local examples: `examples/counter.rs`, `examples/counter-bug.smt2`, `examples/counter-fixed.smt2`.