

Hardware Group No. 097

Provide each DE door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
2	EA	ELEC FIRE EXIT HARDWARE	RX-LC-QEL-9827-EO-F- LBR/LBRAFL-499F-CON-SNB 24 VDC (RX-LC-QEL-9827-EO- F-LBRAFL-499F-CON-SNB-24 VDC) [BULLETIN 023, 251218]		✓ 630	VON
1	EA	DELAYED EGRESS MAG	M490DEP MTG BRKT & VOLTAGE AS REQ		✓ 628	SCE
1	EA	AUTOMATIC OPERATOR	BY RELATED SECTION 08 71 13		✓	B/O
1	EA	WAVE ACTUATOR	BY RELATED SECTION 08 71 13		✓	B/O
2	EA	MOTION SENSOR	FURNISHED BY SECTION 08 71 13		✓	B/O
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
2	EA	WALL STOP	WS406/407CCV		630	IVE
2	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
2	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
4	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28		✓	B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
2	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28		✓	B/O
1	EA	POWER SUPPLY	PS904 900-4RL-FA 900-BBK 120/240 VAC [BULLETIN 023, 251218]		✓	VON
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE [BULLETIN 023, 251218]			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 098

Provide each DE door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F-SNB (9827-EO-F-LBRAFL-499F-SNB) [BULLETIN 023, 251218]		626	VON
2	EA	MAGNETIC LOCK	M490P ATS/LED 12/24 VDC X PLATES X BKTS - AS REQUIRED		✓ 628	SCE
1	EA	FIRE/LIFE HOLDER	4040SEH SEH TBWMS120V AC/DC		✓ 689	LCN
1	EA	SURFACE CLOSER	4040XP CUSH		689	LCN
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V		✓ 689	LCN
2	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
2	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
2	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	POWER SUPPLY	PS904 900-4RL-FA 900-BBK 120/240 VAC [BULLETIN 023, 251218]		✓	VON

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		

Hardware Group No. 099

Provide each DE door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
6 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
2 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
2 EA	ELEC FIRE EXIT HARDWARE	RX-LC-QEL-9827-EO-F-LBRAFL-499F-CON-SNB 24 VDC (RX-LC-QEL-9827-EO-F-LBRAFL-499F-CON-SNB 24 VDC) [BULLETIN 023, 251218]	✓ 630	VON
1 EA	DELAYED EGRESS MAG	M490DEP MTG BRKT & VOLTAGE AS REQ	✓ 628	SCE
1 EA	MAGNETIC LOCK	M490P ATS/LED 12/24 VDC X PLATES X BKTS - AS REQUIRED	✓ 628	SCE
2 EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED	689	LCN
2 EA	KICK PLATE	8400 10" HIGH LDW B-CS	630	IVE
2 EA	WALL STOP	WS406/407CCV	630	IVE
2 EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
2 EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1 EA	REQUEST TO EXIT / MOTION SENSOR	FURNISHED BY DIVISION 28	✓	B/O
4 EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28 [BULLETIN 023, 251218]	✓	B/O
2 EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED	✓ BLK	SCE
2 EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓	B/O

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	POWER SUPPLY	PS906 900-4RL-FA 900-BBK 120/240 VAC [BULLETIN 023, 251218]		✓	VON
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 100

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
2	EA	ELEC FIRE EXIT HARDWARE	RX-LC-9827-EO-F-LBRAFL-499F-SNB		✓ 626	VON
1	EA	MAGNETIC LOCK	M490P ATS/LED 12/24 VDC X PLATES X BKTS - AS REQUIRED		✓ 628	SCE
2	EA	DELAYED SURFACE CLOSER	4041 DEL REG TBSRT/ 4041 DEL EDA TBSRT - AS REQUIRED		689	LCN
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
2	EA	WALL STOP	WS401/402CCV		626	IVE
2	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
2	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
4	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28 [BULLETIN 023, 251218]	✓		B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
2	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓		B/O
1	EA	POWER SUPPLY	PS904 900-4RL-FA 900-BBK 120/240 VAC [BULLETIN 023, 251218]		✓	VON

Hardware Group No. 102

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
2	EA	ELEC FIRE EXIT HARDWARE	RX-LC-QEL-9827-EO-F- LBR/LBRAFL-499F-CON-SNB 24 VDC (RX-LC-QEL-9827-EO- F-LBRAFL-499F-CON-SNB-24 VDC) [BULLETIN 023, 251218]		✓ 630	VON
1	EA	AUTOMATIC OPERATOR	BY RELATED SECTION 08 71 13		✓	B/O
2	EA	WAVE ACTUATOR	BY RELATED SECTION 08 71 13		✓	B/O
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
2	EA	WALL STOP	WS406/407CCV		630	IVE
2	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
2	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY	PS904 900-4RL-FA 900-BBK 120/240 VAC		✓	VON
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE [BULLETIN 023, 251218]			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED [BULLETIN 023, 251218]			

Hardware Group No.103 [BULLETIN 023, 251218]

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F- SNB		626	VON
2	EA	MAGNETIC LOCK	M490P ATS/LED 12/24 VDC X PLATES X BKTS - AS REQUIRED		✓ 628	SCE
1	EA	FIRE/LIFE HOLDER	4040SEH SEH TBWMS120V AC/DC		✓ 689	LCN
1	EA	SURFACE CLOSER	4040XP CUSH		689	LCN
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V		✓ 689	LCN
2	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
2	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
2	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	REMOTE RELEASE	BY DIVISION 28		✓	B/O
1	EA	POWER SUPPLY	PS904 900-4RL-FA 900-BBK 120/240 VAC		✓	VON
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 104

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F-SNB (9827-EO-F-LBRAFL-499F-SNB) [BULLETIN 023, 251218]		626	VON
2	EA	SURFACE CLOSER	4040XP SCUSH TBSRT		689	LCN
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 105

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F-SNB (9827-EO-F-LBRAFL-499F-SNB) [BULLETIN 023, 251218]		626	VON
2	EA	FIRE/LIFE HOLDER	4040SEH SEH TBWMS120V AC/DC	 ✈	689	LCN
2	EA	SURFACE CLOSER	4040XP CUSH		689	LCN
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 106

Provide each DE door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F- SNB (9827-EO-F-LBRAFL-499F- SNB) [BULLETIN 023, 251218]		626	VON
2	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
2	EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V		✓ 689	LCN
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 107

Provide each DE door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F-SNB (9827-EO-F-LBRAFL-499F-SNB) [BULLETIN 023, 251218]		626	VON
1	EA	FIRE/LIFE HOLDER	4040SEH SEH TBWMS120V AC/DC	 ✎	689	LCN
1	EA	SURFACE CLOSER	4040XP CUSH		689	LCN
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V	 ✎	689	LCN
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 108

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F-SNB (9827-EO-F-LBRAFL-499F-SNB) [BULLETIN 023, 251218]		626	VON
2	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
2	EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V		689	LCN
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 109

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR/LBRAFL-499F-SNB (9827-EO-F-LBRAFL-499F-SNB) [BULLETIN 023, 251218]		626	VON
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	SURFACE CLOSER	4040XP SCUSH TBSRT		689	LCN
2	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

Hardware Group No. 110

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	ELEC FIRE EXIT HARDWARE	RX-LC-98-L-F-M996-06-FSE-CON-SNB		✓ 630	VON
1	EA	RIM CYLINDER	1E SERIES - PROVIDE BRASS CONSTRUCTION CORE [BULLETIN 023, 251218]		626	BES
4	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035-GRN [BULLETIN 023, 251218]			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
4	EA	GASKETING SET	188SBK-PSA [BULLETIN 023, 251218]		BK	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28		✓	B/O
1	EA	MULTITECH CREDENTIAL READER NOTE:	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		✓ BLK	SCE
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS [BULLETIN 023, 251218]			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	ELEC FIRE EXIT HARDWARE	RX-LC-98-EO-F-CON-SNB		✓ 630	VON
1	EA	ELEC EXIT DEVICE TRIM	AD-300-993R-70-MT-RHO-B- LRX 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN [BULLETIN 023, 251218]			SCH
4	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN [BULLETIN 023, 251218]			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
1		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 112

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1	EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1	EA	ELEC FIRE EXIT HARDWARE	RX-LC-98-EO-F-CON-SNB	✓ 630	VON
1	EA	ELEC EXIT DEVICE TRIM	AD-300-993R-70-MT-RHO-B-LRX 12/24 VDC	✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1	EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1	EA	SURFACE CLOSER	4040XP SCUSH TBSRT	689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS	630	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
1	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 113

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	ELEC FIRE EXIT HARDWARE	RX-LC-98-EO-F-CON-SNB	✓ 630	VON
1 EA	ELEC EXIT DEVICE TRIM	AD-300-993R-70-MT-RHO-B-LRX 12/24 VDC	✓ 626	SCE
1 EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED	689	LCN
1 EA	KICK PLATE	8400 10" HIGH LDW B-CS	630	IVE
1 EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V	✓ 689	LCN
1 EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1 EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1 EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
1	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 114

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE	✓ 626	BES
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	ELECTRIC STRIKE	6400 FSE 12/24 VAC/VDC	✓ 630	VON
1 EA	AUTOMATIC OPERATOR	BY RELATED SECTION 08 71 13	✓	B/O
1 EA	WAVE ACTUATOR	BY RELATED SECTION 08 71 13 - INTERIOR	✓	B/O
1 EA	KICK PLATE	8400 10" HIGH LDW B-CS	630	IVE
1 EA	WALL STOP	WS401/402CCV	626	IVE
3 EA	SILENCER	SR64	GRY	IVE
1 EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1 EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1 EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
1 EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED	✓ BLK	SCE
1 EA	REMOTE RELEASE	BY DIVISION 28	✓	B/O
1 EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓	B/O

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
1	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFERENCE DIVISION 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS AND WIRING.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVERRIDE. CREDENTIAL READER TO ACTIVATE AUTO DOOR OPERATOR. INTERIOR ACTUATOR ACTIVATES AUTO OPERATOR. AUTO OPERATOR TO SEQUENCE AND RETRACT ELECTRIC STRIKE ALLOWING DOOR TO OPEN. ALWAYS FREE EGRESS UPON FIRE ALARM ACTIVATION. FAIL SECURE ELECTRIC LOCK. ELECTRIC STRIKE FAIL SECURE. OPTIONAL DOOR CONTROL BY SECURITY SYSTEM.

Hardware Group No. 115

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	689	VON

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	ELECTRIC STRIKE	6400 FSE 12/24 VAC/VDC		✓ 630	VON
1	EA	AUTOMATIC OPERATOR	BY RELATED SECTION 08 71 13		✓	B/O
1	EA	WAVE ACTUATOR	BY RELATED SECTION 08 71 13 - INTERIOR		✓	B/O
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28		✓	B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28		✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
1		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			

REFERENCE DIVISION 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS AND WIRING.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. CREDENTIAL READER TO ACTIVATE AUTO DOOR OPERATOR. INTERIOR ACTUATOR ACTIVATES AUTO OPERATOR. AUTO OPERATOR TO SEQUENCE AND RETRACT ELECTRIC STRIKE ALLOWING DOOR TO OPEN. ALWAYS FREE EGRESS UPON FIRE ALARM ACTIVATION. FAIL SECURE ELECTRIC LOCK. ELECTRIC STRIKE FAIL SECURE. OPTIONAL DOOR CONTROL BY SECURITY SYSTEM.

Hardware Group No. 116

Provide each SGL door(s) with the following:

QT		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
Y						
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	ELECTRIC STRIKE	6400 FSE 12/24 VAC/VDC		✓ 630	VON
1	EA	AUTOMATIC OPERATOR	BY RELATED SECTION 08 71 13		✓	B/O
1	EA	WAVE ACTUATOR	BY RELATED SECTION 08 71 13 - INTERIOR		✓	B/O
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
1	EA	GASKETING SET	188SBK PSA		BK	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28		✓	B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28		✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
1		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			

REFERENCE DIVISION 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS AND WIRING.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. CREDENTIAL READER TO ACTIVATE AUTO DOOR OPERATOR. INTERIOR ACTUATOR ACTIVATES AUTO OPERATOR. AUTO OPERATOR TO SEQUENCE AND RETRACT ELECTRIC STRIKE ALLOWING DOOR TO OPEN. ALWAYS FREE EGRESS UPON FIRE ALARM ACTIVATION. FAIL SECURE ELECTRIC LOCK. ELECTRIC STRIKE FAIL SECURE. OPTIONAL DOOR CONTROL BY SECURITY SYSTEM.

Hardware Group No. 117

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP SCUSH TBSRT		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	GASKETING	188SBK PSA		BK	ZER
1	EA	DOOR BOTTOM	369AA-Z49		AA	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No. 118

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
1		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No. 119

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	DELAYED SURFACE CLOSER	4041 DEL REG TBSRT/ 4041 DEL EDA TBSRT - AS REQUIRED		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No. 120

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	PIVOT SET	7230F SET		630	IVE
1	EA	INTERMEDIATE PIVOT	7230F INT		630	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D LL RQE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
1	EA	GASKETING	188SBK PSA		BK	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28		✓	B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28		✓	B/O
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL PIVOTS AT DOORS 7'6" AND OVER			

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No. 121

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP SCUSH TBSRT		689	LCN

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No.122 [BULLETIN 023, 251218]

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	PIVOT SET	7230F SET		630	IVE
1	EA	INTERMEDIATE PIVOT	7230F INT		630	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SAFE CYLINDRICAL LOCK, RX	9K37DEL 15D LL RQE	✓	626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
1	EA	GASKETING	188SBK PSA		BK	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28	✓	B/O
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
		NOTE:	FURNISH ADDITIONAL PIVOTS AT DOORS 7'6" AND OVER		

DOOR NORMALLY CLOSED AND UNLOCKED.
DOOR LOCKED BY INTERFACE WITH EQUIPMENT.
ENTRY BY LEVER OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS UNLOCKED.

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE CYLINDRICAL LOCK, RX	9K37DEU 15D RQE - PROVIDE BRASS CONSTRUCTION CORE		✓ 626	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	OH STOP	90S X J BKT - AS REQUIRED - STOP TO BE MOUNTED ON ROOM SIDE		630	GLY
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28		✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS [BULLETIN 023, 251218]			

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No. 125

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	DOUBLE CYLINDER FAIL SECURE LOCK	45HW7WEU15S		✓ 626	BES
2	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	ELECTRIC STRIKE	6400 FSE 12/24 VAC/VDC		✓ 630	VON
1	EA	AUTOMATIC OPERATOR	BY RELATED SECTION 08 71 13		✓	B/O
1	EA	GASKETING SET	188SBK PSA		BK	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
2	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28		✓	B/O

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY/EGRESS BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No. 126

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC	✓ 626	SCE
1 EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED	689	LCN
1 EA	WALL STOP	WS401/402CCV	626	IVE
1 EA	GASKETING SET	188SBK PSA	BK	ZER
1 EA	DOOR BOTTOM	369AA-Z49	AA	ZER
1 EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1 EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1 EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 128

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC	✓ 626	SCE
1 EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	OH STOP	90S X J BKT - AS REQUIRED - STOP TO BE MOUNTED ON ROOM SIDE	630	GLY
1 EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED	689	LCN
1 EA	GASKETING SET	188SBK PSA	BK	ZER
1 EA	DOOR BOTTOM	369AA-Z49	AA	ZER
1 EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1 EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1 EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O

QTY	DESCRIPTION	CATALOG NUMBER	FINISH MFR
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE	
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED	
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS	

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVERRIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 129

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	SILENCER	SR64	GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 130

~~IN~~
~~181~~

~~IN~~
~~181~~

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	DELAYED SURFACE CLOSER	4041 DEL REG TBSRT/ 4041 DEL EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	↗		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	↗		SCH
	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	↗		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 131

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED PRIVACY LOCK	AD-300-CY-40-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS FOR POE OPERATION.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 132

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	PIVOT SET	7230F SET		630	IVE
1	EA	INTERMEDIATE PIVOT	7230F INT		630	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	⚡		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	⚡		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	⚡		B/O
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			
		NOTE:	FURNISH ADDITIONAL PIVOTS AT DOORS 7'6" AND OVER			

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-
 RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 133

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		⚡ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		⚡ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4040XP SCUSH TBSRT		689	LCN
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	⚡		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	⚡		SCH
	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	⚡		B/O

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 134

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC	✓ 626	SCE
1 EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	SURFACE CLOSER	4041 DEL SCUSH TBSRT	689	LCN
1 EA	GASKETING SET	188SBK PSA	BK	ZER
1 EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1 EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-
 RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 135

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	OH STOP	90S X J BKT - AS REQUIRED - STOP TO BE MOUNTED ON ROOM SIDE		630	GLY
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 136

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC	✓ 626	SCE
1 EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	OH STOP	90S X J BKT - AS REQUIRED - STOP TO BE MOUNTED ON ROOM SIDE	630	GLY
1 EA	DELAYED SURFACE CLOSER	4041 DEL REG TBSRT/ 4041 DEL EDA TBSRT - AS REQUIRED	689	LCN

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 137

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	SURFACE CLOSER	4041 DEL H		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 138

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1	EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC	✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1	EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1	EA	OH STOP	90S X J BKT - AS REQUIRED - STOP TO BE MOUNTED ON ROOM SIDE	630	GLY
1	EA	DELAYED SURFACE CLOSER	4041 DEL REG TBSRT/ 4041 DEL EDA TBSRT - AS REQUIRED	689	LCN
2	EA	ARMOR PLATE - AS REQUIRED	8400/8402 34" HIGH LDW B-CS	630	IVE
2	EA	EDGE GUARD	7310/7310B W/CUT OUTS AS REQUIRED	630	IVE
3	EA	SILENCER	SR64	GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVERRIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 139

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1	EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC	✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1	EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED	689	LCN
1	EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V	✓ 689	LCN
1	EA	GASKETING SET	188SBK PSA	BK	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 140

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC	✓ 626	SCE
1 EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	DELAYED SURFACE CLOSER	4041 DEL REG TBSRT/ 4041 DEL EDA TBSRT - AS REQUIRED	689	LCN
1 EA	FIRE/LIFE SAFETY MAGNET	SEM7800 SERIES AS REQUIRED - 12V/24V/120V	✓ 689	LCN
3 EA	SILENCER	SR64	GRY	IVE
1 EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓	SCH
1 EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓	SCH
1 EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓	B/O
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-
 RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 142

}

}

}

}

}

}

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28		✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 143

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS	652	IVE
1 EA	POWER TRANSFER	EPT10 CON	✓ 689	VON
1 EA	INTEGRATED PRIVACY LOCK	AD-300-CY-40-MT-RHO-B 12/24 VDC	✓ 626	SCE
1 EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN		SCH
1 EA	PERMANENT CORE - COMBINATED	1C72	626	BES
1 EA	WALL STOP	WS401/402CCV	626	IVE
3 EA	SILENCER	SR64	GRY	IVE
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		
	DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS FOR POE OPERATION.
 OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 144

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	PIVOT SET	7230F SET		630	IVE
1	EA	INTERMEDIATE PIVOT	7230F INT		630	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC - LEAD LINE LOCK - AS REQUIRED		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
2	EA	WALL STOP	WS406/407CCV		630	IVE
1	EA	GASKETING SET	188SBK PSA		BK	ZER
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED DIAGRAMS	BY DIVISION 28 PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS		✓	B/O

LEAD LINED OPENING. COORDINATE ALL HARDWARE WITH DOOR SUPPLIER TO MAINTAIN LEAD SHIELDING.

OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.

Hardware Group No. 145

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	INTEGRATED LOCK	AD-300-CY-70-MT-RHO-B 12/24 VDC		✓ 626	SCE
1	EA	SFIC CONST. CORE - CONSTRUCTION PHASE	80-035 GRN			SCH
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	OH STOP	90S X J BKT - AS REQUIRED - STOP TO BE MOUNTED ON ROOM SIDE		630	GLY
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT	✓		SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY	✓		SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28	✓		B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			
		DIAGRAMS	PROVIDE FACTORY POINT TO POINT WIRING DIAGRAMS			

REFER TO DIV 28 TECHNOLOGY DRAWINGS FOR ADDITIONAL COMPONENTS.
OPERATIONAL DESCRIPTION: ENTRANCE BY CREDENTIAL READER OR MANUAL KEY OVER-
RIDE. ALWAYS FREE EGRESS. FAIL SECURE.

Hardware Group No. 146

Provide each SGL door(s) with the following:

QT Y		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	POWER TRANSFER	EPT10 CON		✓ 689	VON
1	EA	FAIL SECURE BH LOCK	SPSE ML RNN		✓ 630	BES
1	EA	PERMANENT CORE - COMBINATED	1C72		626	BES
1	EA	WALL STOP	WS401/402CCV		626	IVE
3	EA	SILENCER	SR64		GRY	IVE
1	EA	WIRE HARNESS - IN DOOR	CON - LENGTH AS REQUIRED - FROM LOCK TO EPT		✓	SCH
1	EA	WIRE HARNESS CONNECTOR - IN FRAME	CON - 6W - FROM CON TO POWER SUPPLY		✓	SCH
1	EA	POWER SUPPLY - AS REQUIRED	BY DIVISION 28		✓	B/O
1	EA	MULTITECH CREDENTIAL READER	PROVIDED BY DIV 28 - MTB15 OR MTB11 AS REQUIRED		✓ BLK	SCE
1	EA	DOOR POSITION SWITCH - AS REQUIRED	BY DIVISION 28		✓	B/O
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			

DOOR NORMALLY CLOSED AND LOCKED.
ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE.
ALWAYS FREE EGRESS.
UPON LOSS OF POWER, DOOR REMAINS LOCKED.

Hardware Group No. 147

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	FIRE EXIT HARDWARE	98-L-BE-F-06SS-SNB		630	VON
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
4	EA	GASKETING SET	488SBK-PSA [BULLETIN 023, 251218]		BLK	ZER
3	EA	SILENCER	SR64 [BULLETIN 023, 251218]		GRY	IVE
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS [BULLETIN 023, 251218]		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		

Hardware Group No. 148

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS 	652	IVE
1 EA	PASSAGE SET	9K30N 15D 	626	BES
1 EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED 	689	LCN
1 EA	WALL STOP	WS401/402CCV 	626	IVE
3 EA	SILENCER	SR64 	GRY	IVE
	NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE		
	NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS		
	NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED		

Hardware Group No. 149

Provide each SGL door(s) with the following:

QTY	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3 EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS 	652	IVE
1 EA	PASSAGE SET	9K30N 15D 	626	BES

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	DELAYED SURFACE CLOSER	4041 DEL REG TBSRT/ 4041 DEL EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
1	EA	GASKETING SET	188SBK PSA		BK	ZER

Hardware Group No. 152

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	PRIVACY LOCK W/IND	45H0L15S VIN		626	BES
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	KICK PLATE	8400 10" HIGH LDW B-CS		630	IVE
1	EA	WALL STOP	WS401/402CCV		626	IVE
1	EA	GASKETING SET	188SBK PSA		BK	ZER

Hardware Group No. 154

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HEAVYWEIGHT HINGE	5BB1HW 4.5 X 4.5 - NRP AT OUTSWINGING LOCKING DOORS		652	IVE
1	EA	FIRE EXIT HARDWARE	98-EO-F-SNB		630	VON
1	EA	SURFACE CLOSER	4040XP REG TBSRT/ 4040XP EDA TBSRT - AS REQUIRED		689	LCN
1	EA	WALL STOP	WS401/402CCV		626	IVE
		NOTE:	FURNISH 5BB1HW 5" X 4.5" HINGES AT DOORS OVER 3'0" WIDE			
		NOTE:	FURNISH SEALS AS REQUIRED TO MAINTAIN SMOKE/FIRE RATING OR STC RATING AS NOTED ON PLANS			
		NOTE:	FURNISH ADDITIONAL HINGES AS REQUIRED FOR DOORS 7'6" AND OVER AS REQUIRED			