

Lab 02: Governance

Introduction

In this lab, you will start by creating a new workspace, a Warehouse and Lakehouse. Then you will assign users to the various workspace roles and warehouse security features.

Objectives

After completing this lab, you will be better able to:

- Endorsements and Certifying items
- Data Lineage and Impact Analysis
- Scan Fabric Metadata using APIs using Power Shell

Estimated time to complete this lab

60 minutes

Lab Prerequisites

- A Fabric capacity or Fabric trial

Contents

_ab 02: Governance	1
Introduction	
Objectives	
Task 1: Enabling certification on your tenant	
Task 2: Creating a new workspace	
Task 3: Endorsement and certifying items	5
Taks 3.1 - Promoting an item	5
Taks 3.2 – Certifying an item	7
Task 4: Data Linage	g
Task 5 - View the Impact Analysis	11
Task 6 – Scan Microsoft Fabric Metadata using API	13
Task 6.1 – Incremental scans (Optional)	16


Task 1: Enabling certification on your tenant

In this task as a Fabric admin, you're responsible for enabling and setting up the certification process for your organization.

In the Admin portal, go to Tenant settings.

Under the *Export and sharing settings* section, expand the Certification section Set the toggle to Enabled.

Admin portal




You can share the URL of your organization's certification policy. This link will be used as the "Learn more" link in the certification section of the endorsement settings dialog. If you don't provide a link, users interested in certification will be directed to contact their Fabric administrator.

Select Apply.


Task 2: Creating a new workspace

In this task, you will create a new workspace to be used in the remainder of the lab.

Connect to the Microsoft Fabric environment and switch to Data Warehouse experience



Now, select "Workspaces" in the left side menu and click "+ New workspace"



Provide the name as **M02 - Governance**.

Click apply.

Task 3: Endorsement and certifying items


In this task, you will learn how the endorsement and certification features work in Microsoft Fabric and the tenant level settings that are needed for these features.

Let's create some items first.

In the M02 - Governance workspace, switch to Data Warehouse experience

In the data warehouse experience, create a new warehouse named: governance_wh


On the left side menu, click "Home", then click "Sample warehouse" as shown below



Provide a name for the new warehouse: governance_wh

In the M02 - Governance workspace, switch to Data Engineering experience

On the left side menu, click "Home", click in "Lakehouse" and provide a name: governance_lh




Taks 3.1 - Promoting an item


Any content owner or member with write permissions for the item can promote it when they believe it's ready for sharing.

To promote an item, you need to have write permissions for that specific item.

In governance_wh warehouse, click the ellipsis and from the menu, click "Settings"




Click "Endorsement" and then promote it selecting the radio button "Promoted".



Now, let's promote a semantic model.

In governance_lh lakehouse, click the ellipsis and from the menu, click "Settings"


Expand the "Endorsement and discovery"



Select the radio button "Promoted" to promoting the item.

If "Make discoverable" checkbox is selected, this implies that users who don't have access to the semantic model can discover it.

Go back to "M02 - Governance" workspace and you'll notice a tag has been added to those items.




Taks 3.2 – Certifying an item


Make sure you have completed task 1 before starting this task.

To certify an item, you need to have write permissions for that specific item.


In governance_lh warehouse, click the ellipsis and from the menu, click "Settings"



Click "Endorsement" and then promote it selecting the radio button "Certified".



Go back to "M02 – Governance" workspace and you'll notice a tag has been added to the Lakehouse.




Task 4: Data Linage

This task allows you to view the lineage between all the items in a workspace. With this feature, you can answer questions such as "What happens if I change this data?" or "Why isn't this report up to date?" These questions can be challenging to address without Fabric's lineage view.


Before seeing the linage, let's create a report using the default semantic model.

Lineage is accessible from multiple locations. Typically, you can get to it:


From the workspace toolbar




• From an item's option menu




• From the menu items at the top of the item's details page



When you access the lineage view of an item, you'll observe the connections between all items within the workspace where the item is situated. The displayed view is a sample and may vary from the lineage view of your workspace.




• Explore the lineage view to understand various tiles cards, use the "Show lineage" within a card to highlight lineage



• Explore the zoom and Full Screen feature that is available in the right hand bottom corner of the lineage view


Task 5 - View the Impact Analysis

To view the impact analysis, click "Show impact across workspaces" on the card



Examine the impact analysis to comprehend the potential effects the item may have on dependent items.

You have the option to switch between Child Items and All downstream items. Additionally, you can navigate by Item Type or by Workspace.



Task 6 – Scan Microsoft Fabric Metadata using API

Metadata scanning facilitates governance of your organization's Microsoft Fabric data by making it possible to catalog and report on all the metadata of your organization's Fabric items. It accomplishes this using a set of Admin REST APIs that are collectively known as the scanner APIs.


In this task, you will use the REST APIs along with PowerShell (using MicrosoftPowerBIMgmt module) to scan and extract metadata for your workspace(s) using Power Shell ISE.


- Pre-requisites:
 - o Windows PowerShell v3.0 and up with .NET 4.7.1 or above.
 - o PowerShell Core (v6) and up on any OS platform supported by PowerShell Core.

Prior to scanning Fabric using API's there are a two tenant settings control metadata scanning that need to be enabled:

- Enhance admin APIs responses with detailed metadata: This setting turns on Model caching and enhances API responses with low-level dataset metadata (for example, name and description) for tables, columns, and measures.
- Enhance admin APIs responses with DAX and mashup expressions: This setting allows the API response to include DAX expressions and Mashup queries. This setting can only be enabled if the first setting is also enabled.

To enable these settings, go to Admin portal > Tenant settings > Admin API settings





Follow the instructions below and run the commands.

- 1. Open Power Shell ISE ("Run as Administrator" is optional)
- 2. Install the MicrosoftPowerBIMgmt module using the below commands

```
#Install MicrosoftPowerBIMgmt module
Install-Module -Name MicrosoftPowerBIMgmt

#Login
Login-PowerBIServiceAccount

1  #Install MicrosoftPowerBIMgmt module
2  Install-Module -Name MicrosoftPowerBIMgmt
3
4  #Login
5  Login-PowerBIServiceAccount
6

PS C:\WINDOWS\system32> Login-PowerBIServiceAccount

Environment: Public
TenantId: 1-42ddof104902
UserName: 0nmicrosoft.com
```

3. Build URL to exclude Personal Workspaces and get the list of workspaces

```
#Build URL to exclude Personal Workspaces
$url =
"https://api.powerbi.com/v1.0/myorg/admin/workspaces/modified?excludePersonalWorkspaces=True"
#Get list of workspaces
Invoke-PowerBIRestMethod -Url $url -Method Get | ConvertFrom-Json
```

```
#Build URL to exclude Personal Workspaces
Surl = "https://api.powerbi.com/v1.0/myorg/admin/workspaces/modified?excludePersonalWorkspaces=True"

#Get list of workspaces
Invoke-PowerBIRestMethod -Url Surl -Method Get | ConvertFrom-Json|

PS C:\WINDOWS\system32> #Build URL to exclude Personal Workspaces
$\foatil{\text{Surl}} = \text{"https://api.powerbi.com/v1.0/myorg/admin/workspaces/modified?excludePersonalWorkspaces=True"
#Get list of workspaces
Invoke-PowerBIRestMethod -Url $\text{surl} -Method Get | ConvertFrom-Json

id
--

-055df2a28f41
-301d2196a90e
-2173cf098adfs
-464fce210465
-2c0962ifb2d5
-b9883eb5b2eb
-4f1322852c45
-ff178C0630a5
-af09f2138c65
-4f91803d3c6d
-e84ac71aee12
-16261dedf86c
-0ad9fbcc75d1
-da6cfd1e83af
-dc9da8e8e8fd
-6ed78f3acba1
-bd2ec9b59e2b
```

4. Build URL to start a scan against a workspace or set of workspaces. Replace the workspace ID in the \$body variable from the result of the above command. You can use one workspace ID or multiple separated by commas

```
#Build URL to start a scan against a workspace or set of workspaces. Replace
the workspace ID in the $body variable from the result of the above command $url1 = "https://api.powerbi.com/v1.0/myorg/admin/workspaces/getInfo"
$body = @"
      "workspaces": [
                    XXXXXXXXXXX
   ]
}
"@
#Trigger a scan
Invoke-PowerBIRestMethod -Url $url1 -Body $body -Method Post | ConvertFrom-
             #Build URL to start a scan against a workspace or set of workspaces. Replace the workspace ID in the $body variable from the result of the above command Surli = "https://api.powerbi.com/v1.0/myorg/admin/workspaces/getInfo" [$body explanation of the above command property of the start a scan against a workspace or set of workspaces and surliverse of the start a scan against a workspace or set of workspaces. Replace the workspace ID in the $body variable from the result of the above command Surli = "https://api.powerbi.com/v1.0/myorg/admin/workspaces/getInfo" [$body explanation of the start a scan against a workspace or set of workspace ID in the $body variable from the result of the above command Surli = "https://api.powerbi.com/v1.0/myorg/admin/workspaces/getInfo" [$body explanation of the start a scan against a workspace or set of workspaces and surliverse in the start a scan against a workspace or set of workspaces. The start a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces and set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace or set of workspaces are start as a scan against a workspace and workspaces are start as a scan against a workspace and workspaces are start as a scan against a workspace and workspaces are start as a scan against a workspace and workspaces are start as a scan against a workspace and workspaces are start as a scan against a workspace and workspaces are start as a scan against a wor
                #Trigger a scan
Invoke-PowerBIRestMethod -Url $url1 -Body $body -Method Post | ConvertFrom-Json
               \WINDOWS\system32> #Build URL to start a scan against a workspace or set of workspaces. Replace the workspace ID in the $body variable from the result of the above c = "https://api.powerbi.com/v1.0/myorg/admin/workspaces/getInfo" = @"
      "workspaces": [
   #Trigger a scan
Invoke-PowerBIRestMethod -Url $url1 -Body $body -Method Post | ConvertFrom-Json
                                                                                       createdDateTime
                                                                                                                                                         status
     ad844b03-bb07-490b-8db8-132978b99334 2023-11-03T07:58:51.6778162Z NotStarted
```

Notice from the above output that we submitted a scan and got the id, CreateDateTIme in the output. Copy this output as we will use these in the later steps. Also note that the status is reported was "NotStarted". Meaning the scanning is yet to start

5. We will poll using the scan ID that we got from the above step to check the scan status

- 6. When the scan status shows as Succeeded, it means that the scan completed and we can consume the results of the scan in the next step
- 7. Get the result of the scan

The output above has been clipped but, this output can be consumed by various tools for cataloging

Task 6.1 – Incremental scans (Optional)

Incremental scans can be performed by using createdDateTIme from the output of the command that triggered the scan in step 4 above (the output of which you should have saved). But prior to that, you need to make some changes (like adding new items) to the workspace(s) you would like to perform and incremental scan and wait 30 minutes. Then run the below:

The output would provide a list of workspaces that changed since the last full scan. You can then use the workspaces in this list to trigger a new scan (starting from step3).

This is the end of the lab. Congratulations for finishing the lab!