Software Tool Article

cy3sabiork: A Cytoscape app for visualizing kinetic records from SABIO-RK

Matthias König^{'*}

¹Humboldt-University Berlin, Institute for Theoretical Biology, Invalidenstraße 43, 10115 Berlin, Germany

*Corresponding author: konigmatt@googlemail.com

Abstract

Cy3sabiork is a Cytoscape 3 app for the visualization of kinetic records from SABIO-RK, a curated database storing comprehensive information about biochemical reactions and their kinetic properties.

Cy3sabiork reads kinetic information in the Systems Biology Markup Language (SBML) format.

A seamless integration with the SABIO-RK web services is provided which allows direct queries from within Cytoscape. Alternatively advanced queries can be performed on the SABIO-RK web page and the results be exported as SBML which then is imported using cy3sabiork.

This visualization method allows for easy comparison of kinetic data, visual inspection of the elements involved in the kinetic record and simple access to the annotation information of the kinetic record.

Keywords

Data display, Graphical user interfaces, Web service, SABIO-RK, kinetic parameters, SBML

Introduction

Importance of kinetic information for computational modelling.

"The scientific literature contains a tremendous amount of kinetic data describing the dynamic behaviour of biochemical reactions over time. These data are needed for computational modelling to create models of biochemical reaction networks and to obtain a better understanding of the processes in living cells." {Wittig2014}

"In recent years, biological databases for different data types have been developed. The advantages of these databases lie in their unified structure, searchability and the potential for augmented analysis by software, which supports the modelling process. We have developed the SABIO-RK database for biochemical reaction kinetics." {Wittig2014}

"modellers who are trying to integrate published data into simulatable computer models. Both search for kinetic parameters and additional information in databases for enzymatic reaction kinetics" {Wittig2014}

"For dynamic modelling and simulation of biochemical reactions and complex networks, computational methods are used that either describe the reaction dynamics as an approximate estimation applying convenience kinetics [1] or require detailed information on the reactions and their kinetics. This required information includes kinetic parameters with their rate equations that describe the dynamic behaviour of the reactions over time, as well as detailed descriptions of how these were determined" {Wittig2014}

"In recent years, the number of available biological databases has grown, offering the advantage of providing unified structures. Included amongst them are databases that contain enzyme and reaction kinetics data to support the modelling and simulation processes: enzyme databases such as BRENDA {Scheer2011} or protein databases such as UniProtKB {UniProtConsortium2011}, which both also store kinetic parameters." {Wittig2014}

One of the main challenges in kinetic modeling of biochemical systems is the availability of reliable parameters from the literature.

"Especially for computational modelling and computer assisted exchange of knowledge, a definition of standard data exchange formats and a common language are essential [20]. Therefore, the use of existing ontologies and controlled vocabularies for all reaction participants (e.g. small chemical compounds and proteins), as well as for kinetic rate laws, parameters, units, etc., is becoming more and more essential." {Wittig2014}

SABIO-RK

SABIO-RK (http://sabio.h-its.org/) is a manually curated database storing comprehensive information about biochemical reactions and their kinetic properties. SABIO-RK offers standardized data manually extracted from the literature and data directly submitted from lab experiments {Wittig2012, Wittig2014}.

"The SABIO-RK database has been developed to meet these requirements and to support scientists in modelling and understanding of complex biochemical networks by structuring kinetic data and related information from the literature." {Wittig2014}

SBML

The Systems Biology Markup Language (SBML) is a free and open interchange format for computer models of biological processes {Hucka2003}. SABIO-RK provides access to the kinetic information in SBML format either (I) by export of SBML from the SABIO-RK web interface (http://sabiork.h-its.org/) after searching and selecting kinetic records, or (II) by SBML return of kinetic records via RESTful web services (http://sabiork.h-its.org/layouts/content/webservices.gsp).

"SABIORK data can be simply accessed through web-based user interfaces and web services. Various search criteria are selectable to search for biochemical reactions and their kinetics. Beside a free text search, complex and detailed queries can be executed in the advanced search. This may include the combination of several search criteria [e.g. reaction participants (substrates, products, inhibitors, activators etc.), pathways, enzymes, organisms, tissues or cellular locations, kinetic parameters, environmental conditions or literature Sources]." {Wittig2014}

"SABIO-RK stores all of the kinetic information for one specific reaction under specific experimental conditions from a defined biological source in one dataset called the database entry. This information can be viewed and exported as a single dataset." {Wittig2014}

Semantic annotations & Knowledge Integration

The annotation information and semantic layer accessible to the user and linking these data to additional web resources. SBML can be annotated based on Minimum Information Required for the Annotation of Models (MIRIAM; {Laibe2007}), a set of controlled vocabularies in systems biology.

The annotation information in form of RDF-based MIRIAM annotations and XML based SABIO-RK annotations of the kinetic records are made accessible. Hyperlinks to annotated online resources are provided, i.e. via SABIO-RK internal identifiers and identifiers from external databases ChEBI {deMatos2010}, UniProtKB {UniProtConsortium2011}, Pubmed, or KEGG {Kanehisa2010}. In this way, information from a wide range of resources and databases is integrated with the graph visualization of the kinetic records. This allows for instance direct access to the publication from which the kinetic information was retrieved or the Protein for which the kinetic information was measured.

What is problem and what is solution!

Despite the importance of kinetic information for modelling there is no easy way to visualize the kinetic information from kinetic records in SABIO-RK. There is currently no visualization tool enabling the visualization of kinetic records from SABIO-RK. Therefore, we developed the Cytoscape app cy3sabiork, that takes advantage of the web service and SBML export from SABIO-RK for importing and displaying graphs of the kinetic records in Cytoscape.

Cy3sabiork provides access to the following information of SABIO-RK database entries via the graph structure and annotations of nodes: (I) reaction details, enzyme and organism; (II) Kinetic law, formula, parameters; (III) Experimental conditions; (IV) Source

We applied cy3sabiork for the search of kinetic parameters for the galactose metabolism in Human liver.

Methods

Implementation

Cy3sabiork was written in Java as an OSGi bundle. It adds a "cy3sabiork" tab with specific functionality to the Cytoscape "Results Panel". Kinetic records are retrieved in SBML format either via the SABIO-RK web page export or the cy3sabiork web service queries. The data import functionality is implemented as a Cytoscape Task using the registered cy3sbml {Koenig2012} SBMLReaderTask via the Cytoscape LoadNetworkFileTaskFactory. The cy3sbml SBML reader was extended to support the SABIO-RK specific SBML annotations.

Operation

Visualizing kinetic records data with cy3sabiork consists of two steps:

- (I) Searching kinetic records for visualization via either the web services in the cy3sabiork panel (Figure 1) or via the SABIO-RK web interface
 - (II) Loading the kinetic records in SBML format in Cytoscape. In case of searching

All annotation information is available via the cy3sbml panel, providing direct links to additional resources for the kinetic law.

Use Cases

cy3sabiork was used in the modeling of galactose metabolism of the human liver. In the following the workflow for retrieval of single kinetic records (**Figure**

Conclusion

cy3sabiork allows easy visual analysis of kinetic records from SABIO-RK kinetic records. Especially the availability of direct links to the SABIO-RK database and ontology annotations of the kinetic records provide additional knowledge integration.

Data and software availability

cy3sabiork is freely available from the Cytoscape app store http://apps.cytoscape.org/apps/cy3sabiork. The code is open source under GNU General Public License, version 3 (GPL-3.0) license available at https://github.com/matthiaskoenig/cy3sabiork.

Author contributions

MK developed the app and wrote the manuscript. We thank the SABIO-RK team, the SBML community, and Cytoscape community for their support and help.

Competing interests

No competing interests.

Grant information

This work was supported by the Federal Ministry of Education and Research (BMBF, Germany) within the research network Systems Medicine of the Liver (LiSyM) [grant number 031L0054] and the Virtual Liver Network VLN [grant number 0315741].

Supplementary material

Supplementary File S1: SBML file for galactose query

Supplementary File S2: Cytoscape session file for the galactose query

References

De Matos, P., Alcántara, R., Dekker, A., Ennis, M., Hastings, J., Haug, K., et al. (2009). Chemical entities of biological interest: an update. *Nucleic acids research*, gkp886.

Hucka, M., Finney, A., Sauro, H. M., Bolouri, H., Doyle, J. C., Kitano, H., et al. (2003). The systems biology markup language (SBML): a medium for representation and exchange of biochemical network models. *Bioinformatics*, 19(4), 524-531.

Kanehisa, M., Goto, S., Furumichi, M., Tanabe, M., & Hirakawa, M. (2010). KEGG for representation and analysis of molecular networks involving diseases and drugs. *Nucleic acids research*, 38(suppl 1), D355-D360.

König, M., Dräger, A., & Holzhütter, H. (2012). CySBML: a Cytoscape plugin for SBML. *Bioinformatics*, 28(18), 2402-2403. Laibe, C., & Le Novère, N. (2007). MIRIAM Resources: tools to generate and resolve robust cross-references in Systems Biology. *BMC Systems Biology*, 1(1), 58.

Scheer, M., Grote, A., Chang, A., Schomburg, I., Munaretto, C., Rother, M., et al. (2010). BRENDA, the enzyme information system in 2011. *Nucleic acids research*, gkq1089.

UniProt Consortium (2011). Ongoing and future developments at the Universal Protein Resource. *Nucleic acids research*, 39(suppl 1), D214-D219.

Wittig, U., Kania, R., Golebiewski, M., Rey, M., Shi, L., Jong, L., et al. (2012). SABIO-RK—database for biochemical reaction kinetics. *Nucleic acids research*, 40(D1), D790-D796.

Wittig, U., Rey, M., Kania, R., Bittkowski, M., Shi, L., Golebiewski, M., et al. (2014). Challenges for an enzymatic reaction kinetics database. *FEBS Journal*, 281(2), 572-582.

Figures

TODO

Figure 0. Workflow diagram (overview over exchange)

Combine with Figure 2, to show the content of the information.




Figure 1. cy3sabiork GUI for web service queries. In the example the kinetic record 18974 is retrieved (http://sabiork.h-its.org/sabioRestWebServices/kineticLaws/18974). The web service returns the SABIO-RK information in SBML.

Gene	ral info	ormatic	on														
Organ	ism	Oryctolagus cuniculus															
Tissue				muscle ¬													
EC Class				2.4.1.1													
SABIO reaction id				10080													
Variant				wildtype													
Experiment Type				in vitro													
Event Description																	
Subs	trates																
name								location					com	comment			
Maltopentaose														-			
Gluco	se 1-pl	nospha	e					-					-				
Prod	ucts							<u> </u>								=	
name						location				comn			nent				
Phosphate					-			again Color				-				_	
Maltohexaose							-					-					
Modif	fiers															_	
name					locati	on	effec	t			com	ment	pro	tein co	mplex		
_	horylas	e(Enzy	(me)					fier-Cat	fier-Catalyst				_	((P00489 7)*2)*2;			
_	me (pr												335	and an included in	-7 -7 -1	_	
Enzy	me (pre	_		40		nam		mal w	oiah	+ /kD	-		dovi	ation /	kDa)		
uniProtKE subunit P00489				_AU mame n				illor. W	ol. weight (kDa)				uevi	deviation (kDa)			
compl		- 0040	10				-									_	
_	ic Law					_										_	
Kinet			form					-									
type form				uia					annotation								
			<u> </u>													_	
Paran	1000							1									
	type		_	spec				start v	-	end	10000	devia	t. unit		comm	en	
A	concentration 7						hate		1.6		40.0		1		M-		
E Km	Km -		יר נ	Enzy				-	10.0		-		-	μg/	mI- nM -		
Vmax				Gruc	ose 1-p	nospi	nate	-	35.0		- 1			/(min*m		_	
	-			-					00.0		_1		- рич	/(111111 11	9)	_	
Expe	riment	al cond		-													
start value								end value unit									
pH temperature					6.8												
tempe buffer			20 =	M. ale	oront -	onh-	to 1 f	5 mM E		5 -	MDT	т.				088	
comm			20 M	w gry	eropho	s pna	10, 1.0	J MM E	DIA	, o m	IVI DI	1				_	
Omilli			_													_	
	ence									LALIS				N ISSUES	ln	_	
10-15-2								autho	or	yea	jour	rnai	volum	epages	PubMed	1	
Refer title	esis ar																

Figure 2. Overview over SABIO-RK kinetic law entry http://sabiork.h-its.org/kineticLawEntry.jsp?viewData=true&kinlawid=18974




Figure 3. Resulting SBML species-reaction graph (left) and kinetic graph (right) for query /kineticLaws/18974. A single kinetic record is retrieved via the web services and imported using cy3sbml.




Figure 4. Graph of SABIO-RK kinetic records for the Human liver galactokinsase, consisting of 47 entries (query 2016-06-08, Organism="homo sapiens" & Pathway="galactose metabolism" & wildtype=True, SBML and session file in supplement). Three clusters can be seen, depending on the localization of the reported protein. The lysosomal reactions are non-canonical reactions in the galactose pathway.