Rapamycin PBPK model: fit PK

1 Methods: Rapamycin PBPK model: fit PK

1.1 Parameters and data

9 parameters were optimized: Ka_dis [1/hr] dissolution rapamycin (`GU__Ka_dis_rap`), rate of rapamycin metabolism by CYP3A4 (`LI__RAP2RX_k`), tissue/blood partition coefficient rap (`Kp_rap`), tissue distribution rap (`ftissue_rap`), bound/free partition coefficient rap (tissue) (`Kpdeep_rap`), rate of the slow binding rap (tissue) (`kdeep_rap`), fed effect on the fraction absorbed (`GU__FED_f_absorption`), fed effect on the dissolution and gastric emptying (`GU__FED_f_dissolution`) and capacity of CYP3A5 relative to CYP3A4 (`r_cyp3a5`).

A fit mapping is a curve of a study, the data and the observable of the model it is compared with. The fit has 22 fit mappings of training data with 308 data points, whose residuals enter the objective; and 32 fit mappings of validation data with 479 data points, which were simulated and evaluated with the fitted parameters but not fitted. The fit was set up and run with sbmlsim [1].

1.2 Objective function

The parameters were estimated by minimizing the objective function

$$F(\vec{p}) = \frac{1}{2} \sum_k \sum_i \rho\left(w_{i,k} r_{i,k}(\vec{p})^2\right) \tag{1}$$

where k runs over the fit mappings of the training data and i over their data points, $r_{i,k}$ is the residual, $w_{i,k} = w_k w^p_{i,k}$ the weight of the data point and ρ the loss function, applied to the squared weighted residual $z = w_{i,k} r^2_{i,k}$. The loss function is linear, $\rho(z) = z$, i.e. a standard least squares problem.

The residuals are normalized by the mean $\overline{y}_k$ of the data of their curve, which makes curves of different quantities and magnitudes comparable:

$$r_{i,k} = \frac{y_{i,k} - f_{k(x_{i,k},\vec{p})}}{\overline{y}_k} \tag{2}$$

The weight of curve k is $w_k = \frac{n_k}{N_k}$, the weight n_k of its fit mapping (the weight its fit mapping collection assigns, 1 by default, or, for a collection which uses the weights of its mappings, the weight of the mapping, by default the number of subjects of its data) divided by the number N_k of its data points.

A data point is weighted with the inverse of its coefficient of variation, $w^p_{i,k} = |y_{i,k} \frac{|}{\sigma_{i,k}}$, with $\sigma_{i,k}$ the standard deviation of the data point, or its standard error for data without a standard deviation. An error of zero is missing, a missing error of a curve with errors is replaced by the largest error of the curve, and the data points of a curve without errors have the weight $w^p_{i,k} = 2$, the weight of a coefficient of variation of 0.5.

1.3 Optimization

The optimizer searched the parameters in log10 space within their bounds; bounds, values and intervals are given in the units of the fit parameters, the units of the table of the parameters.

The objective was minimized in 3 runs with differential evolution [2] of SciPy [3] within the bounds of the parameters, with the strategy `best1bin`, a population of 15 times the number of parameters, at most 1000 generations, the relative tolerance 0.01 of convergence, the recombination constant 0.7 and a mutation dithered between 0.5 and 1. The initial population of a run was drawn by latin hypercube sampling [4], with a seed of every run derived from the seed 1234 of the fit. The best member of the final population was polished with the L-BFGS-B method of SciPy.

The convergence of the runs was assessed from the traces of their cost and the waterfall plot of their final costs, and the parameter set with the lowest cost was used.

The models were simulated with libRoadRunner [5] and its integrator CVODE [6] with the relative tolerance 10^{-6} and the absolute tolerances 10^{-13} of an amount, 10^{-13} of a concentration and 10^{-6} of the other states, which for a species in a concentration is multiplied by the initial volume of its compartment. It ran with the variable step size of libRoadRunner, i.e. with an output at every step of the integrator. A data point at the time of a change after the start of a simulation, e.g. a dose or the reset of a collection, was compared with the state before the change, except the first data point of a curve with data at later times, which starts a collection and was compared with the state after the change.

1.4 Goodness of fit

The goodness of fit is given per kind of data (training data and validation data) by metrics over its n data points with the residuals $e_i = y_i - f\left(x_i, \hat{\vec{p}}\right)$ at the fitted parameters $\hat{\vec{p}}$, the mean squared error, its root and the root mean squared error normalized by the mean $\overline{y}_{k(i)}$ of the data of the curve of a point:

$$\mathrm{MSE} = \frac{1}{n}\sum_{i=1}^{n} e_i^2, \quad \mathrm{RMSE} = \sqrt{\mathrm{MSE}}, \quad \mathrm{NRMSE} = \sqrt{\frac{1}{n}\sum_{i=1}^{n}\left(\frac{e_i}{\overline{y}_{k(i)}}\right)^2} \tag{3}$$

The root mean square of the residuals of the objective, i.e. what the fit minimizes, and the coefficient of determination:

$$\mathrm{RMSE}_w = \sqrt{\frac{1}{n}\sum_{i=1}^{n}\rho(w_i r_i^2)}, \quad R^2 = 1 - \frac{\sum_i e_i^2}{\sum_i \left(y_i - \overline{y}\right)^2} \tag{4}$$

The predictions of a non-linear model are no linear regression of the data, so R^2 can be negative: the prediction is worse than the mean of the data. The information criteria of Akaike [7] and Schwarz [8] with the number n_p of fitted parameters are those of a least squares fit with normally distributed residuals, up to an additive constant, so only differences between models fitted to the same data are meaningful:

$$\mathrm{AIC} = n\ln(\mathrm{MSE}) + 2n_p, \quad \mathrm{BIC} = n\ln(\mathrm{MSE}) + n_p\ln(n) \tag{5}$$

The percentage of the data points whose prediction $f_i = f\left(x_i, \hat{\vec{p}}\right)$ lies within twofold of the data is taken over the n_+ data points with positive data $y_i > 0$ and a positive prediction $f_i > 0$; the others have no ratio and are not counted, and a kind of data without such a point has no percentage:

$$P_2 = \frac{100}{n_+}\left|\left\{i : \frac{1}{2} \le \frac{f_i}{y_i} \le 2\right\}\right| \tag{6}$$

The goodness of fit plot shows the predictions against the data on logarithmic axes, with the lines of twofold $f = 2y$ and $f = \frac{y}{2}$. The Bland-Altman plot [9] shows the ratio of prediction and data as $d_i = \log_{10}\left(\frac{f_i}{y_i}\right)$ against the geometric mean $\sqrt{f_i y_i}$ for the data points with positive values, with the bias $\overline{d}$ and the limits of agreement $\overline{d} \pm 1.96 s_d$, with the sample standard deviation s_d of d_i, of the training data; they are read as the fold factors $10^{\overline{d}}$ and $10^{\overline{d} \pm 1.96 s_d}$.

1.5 Identifiability

The identifiability of the parameters was analysed with the profile likelihood [10], [11]. The profile of a parameter is the lowest objective with the parameter fixed:

$$\mathrm{PL}(p_j) = \min_{p_{l \ne j}} F(\vec{p}) \tag{7}$$

At every point of a scan the other parameters were re-optimized from the previous point with the least squares optimizer of SciPy with the relative step 0.05. A scan ran from the optimum in both directions in the space of the optimizer, with steps in decades of the parameter, starting at 0.1. A step which raised the objective by more than 0.2 of the distance between the objective at the optimum and the threshold was reduced by the factor 2 and repeated, down to 0.01, and the step after one which raised it by less than that divided by the factor was enlarged by the factor, up to 1. A scan stopped at the threshold, at the bound of the parameter, at a point which failed or after 50 points.

The confidence intervals are the values at which the profile crosses the threshold of the likelihood ratio test

$$F_{\mathrm{thr}} = F_{\mathrm{min}} + \chi^2_\alpha \frac{\mathrm{df}}{2} \tag{8}$$

with F_{min} the lowest objective of the fit and of all profiles and $\chi^2_\alpha(\mathrm{df})$ the quantile of the χ^2 distribution at the confidence level $\alpha = 0.95$ with df = 1 degrees of freedom, i.e. 1.92 above the lowest objective. The threshold has this confidence level if F is the negative log-likelihood of the data up to a constant, i.e. if the weighted residuals are independent and normally distributed with unit variance; otherwise the level is approximate. A crossing is interpolated between two points of the profile, on the logarithm of a parameter on a logarithmic scale. A parameter is identifiable if its profile reaches the threshold within the scan on both sides of the optimum, i.e. its confidence interval is finite; practically non-identifiable towards the lower bound if its profile reaches the threshold above the optimum but not below it within the scan, which ends at the lower bound or after 50 points; practically non-

identifiable towards the upper bound if its profile reaches the threshold below the optimum but not above it within the scan, which ends at the upper bound or after 50 points; practically non-identifiable if its profile reaches the threshold on neither side within the scans, which end at the bounds or after 50 points, and is not flat; and structurally non-identifiable if its profile is flat on both sides. A side of a profile is flat if it rises by less than 0.05 of the distance between the lowest objective and the threshold, and a profile with a point which failed or did not converge is not classified. The profile likelihood is preferred over the intervals of the Fisher information, its intervals are invariant under a transformation of the parameters and can be asymmetric [12].

The Fisher information is the local alternative to the profiles: it is the Gauss-Newton approximation of the curvature of the objective at the optimum, from the Jacobian J of the weighted residuals of the training data with respect to the parameters $\vec{p}$ in the space of the optimizer, computed by central finite differences with the step $h_j = \varepsilon \max\left(|p_j|, 1\right),\ \varepsilon = 10^{-6}$ of the parameter p_j:

$$I = J^{\top} J, \quad \mathrm{cov} = \sigma^2 I^{-1}, \quad \sigma^2 = \frac{2F}{n - n_p} \tag{9}$$

with the number n of data points of the training data and the number n_p of parameters. The information has rank 9 of 9, the number of its eigenvalues above 10^{-8} of the largest one, and the condition number 1020; the covariance of an information of a lower rank is computed with the pseudo-inverse. The Wald intervals are $\hat{p}_j \pm t_{\frac{1+\alpha}{2}, n-n_p} \mathrm{SE}_j$ with the standard errors $\mathrm{SE}_j = \sqrt{\mathrm{cov}_{jj}}$ at the confidence level $\alpha = 0.95$, transformed back into the units of the fit parameters.

1.6 Provenance

The fit PK_20261017_094949__24b18 was run on 2026-10-17 07:49:51 UTC with sbmlsim 0.10.0 [1], libRoadRunner 2.10.0 [5], SciPy 1.18.1 [3], NumPy 2.5.3 [13] and Python 3.14.4 (seed 1234). The models and data were those of commit `138cd5e26b655379e4c34971f8cb649aa6cb81cd` of `/home/mkoenig/git/pkdb_models-rapamycin` their SHA-256 checksums are listed in Table 1.

Table 1: SHA-256 checksums of the models and data of the fit PK_20261017_094949__24b18, their first 12 characters; the full checksums are in the provenance of the result (optimization_result.json).

File	SHA-256
pkdb_models/models/rapamycin/data/rapamycin/BasaDenes2019/.BasaDenes2019_Fig1A.tsv	13006e53327e...
pkdb_models/models/rapamycin/data/rapamycin/BasaDenes2019/.BasaDenes2019_Fig1C.tsv	75f1a06f66cc...
pkdb_models/models/rapamycin/data/rapamycin/BasaDenes2019/.BasaDenes2019_Tab2.tsv	538a078117f8...
pkdb_models/models/rapamycin/data/rapamycin/BasaDenes2019/.BasaDenes2019_TabGroups.tsv	131175414a11...
pkdb_models/models/rapamycin/data/rapamycin/BasaDenes2019/.BasaDenes2019_TabIndividuals.tsv	f924ac035979...
pkdb_models/models/rapamycin/data/rapamycin/BasaDenes2019/.BasaDenes2019_TabInterventions.tsv	49f81db9d585...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_Fig1.tsv	fb4e1d2fb87a...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_Fig2.tsv	07207cba6fe4...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_Fig2A.tsv	08691b58bbb4...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_Fig2B.tsv	fbb5bbb441c8...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_Fig3.tsv	b015ed4f7389...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_Tab1.tsv	0a4267b84efb...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_Tab2.tsv	3d61fb9188dc...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_TabGroups.tsv	bf66a2f415f4...
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_TabIndividuals.tsv	f2a01715e7f8...

File	SHA-256
pkdb_models/models/rapamycin/data/rapamycin/Bottiger2001/.Bottiger2001_TabInterventions.tsv	d97a0a2d7ed9...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_Fig1.tsv	c580613148d3...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_Fig2.tsv	6777cec976ed...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_Fig3.tsv	c680268839fa...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_Tab3.tsv	fb4bd0572679...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_Tab4.tsv	89ad59cb83db...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_TabGroups.tsv	e583f7ad4731...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_TabIndividuals.tsv	811aaf8d038b...
pkdb_models/models/rapamycin/data/rapamycin/Brattstrom2000/.Brattstrom2000_TabInterventions.tsv	294a2affd173...
pkdb_models/models/rapamycin/data/rapamycin/Kelly1999/.Kelly1999_Fig1.tsv	67a785017573...
pkdb_models/models/rapamycin/data/rapamycin/Kelly1999/.Kelly1999_Tab2.tsv	ee4a399e466e...
pkdb_models/models/rapamycin/data/rapamycin/Kelly1999/.Kelly1999_Tab3.tsv	85ae5e50f51f...
pkdb_models/models/rapamycin/data/rapamycin/Kelly1999/.Kelly1999_TabGroups.tsv	1ab69cc2c5d0...
pkdb_models/models/rapamycin/data/rapamycin/Kelly1999/.Kelly1999_TabInterventions.tsv	2662d51a8cf5...
pkdb_models/models/rapamycin/data/rapamycin/KorthBradley2012/.KorthBradley2012_Fig1.tsv	65b0c8650ac5...
pkdb_models/models/rapamycin/data/rapamycin/KorthBradley2012/.KorthBradley2012_Fig2.tsv	924012e8580d...
pkdb_models/models/rapamycin/data/rapamycin/KorthBradley2012/.KorthBradley2012_Tab1.tsv	5243aeeb4d12...
pkdb_models/models/rapamycin/data/rapamycin/KorthBradley2012/.KorthBradley2012_TabGroups.tsv	98eae14b8b4c...
pkdb_models/models/rapamycin/data/rapamycin/KorthBradley2012/.KorthBradley2012_TabInterventions.tsv	ffd8b9f8fc89...
pkdb_models/models/rapamycin/data/rapamycin/Leelahavanichkul2005/.Leelahavanichkul2005_Fig1.tsv	a1d90dac9290...
pkdb_models/models/rapamycin/data/rapamycin/Leelahavanichkul2005/.Leelahavanichkul2005_Tab3.tsv	9c0869686e57...
pkdb_models/models/rapamycin/data/rapamycin/Leelahavanichkul2005/.Leelahavanichkul2005_Tab3A.tsv	9228a4518ca7...
pkdb_models/models/rapamycin/data/rapamycin/Leelahavanichkul2005/.Leelahavanichkul2005_TabGroups.tsv	fce6b139031e...
pkdb_models/models/rapamycin/data/rapamycin/Leelahavanichkul2005/.Leelahavanichkul2005_TabIndividuals.tsv	5a7e18c59123...
pkdb_models/models/rapamycin/data/rapamycin/Leelahavanichkul2005/.Leelahavanichkul2005_TabInterventions.tsv	a583b930eb2b...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Fig1.tsv	cb15f2cb0453...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Fig2.tsv	5a1c52fcf55a...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Tab1.tsv	102ab99e42a9...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Tab1A.tsv	b697031a63f1...

File	SHA-256
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Tab2.tsv	e3d0ffa70b99...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Tab2A.tsv	ba474077480b...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Tab3.tsv	7912c555985f...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_Tab3A.tsv	eb0a81143bf3...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_TabGroups.tsv	46bd4793ec75...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_TabIndividuals.tsv	9a8fe0cfb5ce...
pkdb_models/models/rapamycin/data/rapamycin/Leung2006/.Leung2006_TabInterventions.tsv	6d7aa16fd67a...
pkdb_models/models/rapamycin/data/rapamycin/Renders2007/.Renders2007_Fig3.tsv	0df0bddfe28e...
pkdb_models/models/rapamycin/data/rapamycin/Renders2007/.Renders2007_Fig4.tsv	565d75d1f4d0...
pkdb_models/models/rapamycin/data/rapamycin/Renders2007/.Renders2007_Tab2.tsv	53794ef66237...
pkdb_models/models/rapamycin/data/rapamycin/Renders2007/.Renders2007_Tab3.tsv	40e2060550a0...
pkdb_models/models/rapamycin/data/rapamycin/Renders2007/.Renders2007_TabGroups.tsv	794762a06fe0...
pkdb_models/models/rapamycin/data/rapamycin/Renders2007/.Renders2007_TabInterventions.tsv	dd93d598090e...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Fig1.tsv	c16175688c37...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Fig2.tsv	dde8f3a111ff...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Fig3.tsv	b7f8ad4e6d3b...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Fig4.tsv	2a5a833be9c7...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Tab1.tsv	e5a58b02c2ad...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Tab2.tsv	a2390d3901ab...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Tab3.tsv	d4350ffebca8...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_Tab4.tsv	070098eba6bf...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_TabGroups.tsv	3ad97e0734d5...
pkdb_models/models/rapamycin/data/rapamycin/Rogers2008/.Rogers2008_TabInterventions.tsv	bb78c72e1407...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2013/.Tortorici2013_Fig1.tsv	d8520a4e20c3...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2013/.Tortorici2013_Fig2.tsv	03a53753cdb0...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2013/.Tortorici2013_Tab1.tsv	3f03d7aecac4...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2013/.Tortorici2013_Tab2.tsv	615dd9564327...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2013/.Tortorici2013_TabGroups.tsv	ac44e6798412...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2013/.Tortorici2013_TabInterventions.tsv	4f7df7473aa5...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2014/.Tortorici2014_Fig1.tsv	0c8f186cc2ac...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2014/.Tortorici2014_Tab1.tsv	abba1042c8e5...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2014/.Tortorici2014_TabGroups.tsv	89f51cae990c...
pkdb_models/models/rapamycin/data/rapamycin/Tortorici2014/.Tortorici2014_TabInterventions.tsv	2aee1a655c60...

File	SHA-256
pkdb_models/models/rapamycin/data/rapamycin/Wang2014/.Wang2014_Fig1.tsv	2ace696344df...
pkdb_models/models/rapamycin/data/rapamycin/Wang2014/.Wang2014_Fig3.tsv	d7a7b60f6514...
pkdb_models/models/rapamycin/data/rapamycin/Wang2014/.Wang2014_Tab1.tsv	5e7a49654cdd...
pkdb_models/models/rapamycin/data/rapamycin/Wang2014/.Wang2014_TabGroups.tsv	d158d890c392...
pkdb_models/models/rapamycin/data/rapamycin/Wang2014/.Wang2014_TabIndividuals.tsv	a8be4c361011...
pkdb_models/models/rapamycin/data/rapamycin/Wang2014/.Wang2014_TabInterventions.tsv	386c7de063b1...
pkdb_models/models/rapamycin/data/rapamycin/Zha2022/.Zha2022_Fig2.tsv	f34b0903cc21...
pkdb_models/models/rapamycin/data/rapamycin/Zha2022/.Zha2022_Fig3.tsv	432e4727302b...
pkdb_models/models/rapamycin/data/rapamycin/Zha2022/.Zha2022_Tab1.tsv	b0b5c0c3120a...
pkdb_models/models/rapamycin/data/rapamycin/Zha2022/.Zha2022_Tab2.tsv	8ddf2a7f9e9a...
pkdb_models/models/rapamycin/data/rapamycin/Zha2022/.Zha2022_TabGroups.tsv	35f121debc24...
pkdb_models/models/rapamycin/data/rapamycin/Zha2022/.Zha2022_TabInterventions.tsv	058004c07f72...
pkdb_models/models/rapamycin/data/rapamycin/Zhang2017/.Zhang2017_Fig1A.tsv	67b022e9c0f7...
pkdb_models/models/rapamycin/data/rapamycin/Zhang2017/.Zhang2017_Fig1B.tsv	17bb9402f369...
pkdb_models/models/rapamycin/data/rapamycin/Zhang2017/.Zhang2017_Tab4.tsv	aeebed617f32...
pkdb_models/models/rapamycin/data/rapamycin/Zhang2017/.Zhang2017_Tab6.tsv	9edd0b2873fe...
pkdb_models/models/rapamycin/data/rapamycin/Zhang2017/.Zhang2017_TabGroups.tsv	abb9ad0260c6...
pkdb_models/models/rapamycin/data/rapamycin/Zhang2017/.Zhang2017_TabInterventions.tsv	4b53a9b9f25b...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_Fig1.tsv	5c57542e6fdc...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_Fig2.tsv	482ccc06e7c0...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_Fig3.tsv	d16982579e20...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_Fig4.tsv	1fed866e9a85...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_Tab2.tsv	4495d595e5c7...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_TabGroups.tsv	4fc5ebaae762...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_TabIndividuals.tsv	2bb7f6fce1c4...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1997/.Zimmerman1997_TabInterventions.tsv	794b07c4f898...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1999/.Zimmerman1999_Fig1.tsv	67be37dab38d...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1999/.Zimmerman1999_Fig2.tsv	84c5e98cbe15...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1999/.Zimmerman1999_Tab1.tsv	2f18356303a3...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1999/.Zimmerman1999_TabGroups.tsv	99647fb116b8...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1999/.Zimmerman1999_TabIndividuals.tsv	cc5759fd82ea...

File	SHA-256
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman1999/.Zimmerman1999_TabInterventions.tsv	c8f5ecd371ef...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_Fig1.tsv	ddecd6ef2916...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_Fig2.tsv	0a8154d390c6...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_Fig3.tsv	f8d4e5d95e71...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_Fig4.tsv	b7aa09394894...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_Tab1.tsv	1fe7c403d91a...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_Tab2.tsv	64824d228af5...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_TabGroups.tsv	a2d068c934a5...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_TabIndividuals.tsv	3e5fd6d3d543...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2003/.Zimmerman2003_TabInterventions.tsv	a7402cfb0c65...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2005/.Zimmerman2005_Tab2.tsv	403f1434f473...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2005/.Zimmerman2005_TabGroups.tsv	4356c1f9ddb6...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2005/.Zimmerman2005_TabInterventions.tsv	fd4763f3c6e5...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2008/.Zimmerman2008_Fig1.tsv	3b0b3f20b169...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2008/.Zimmerman2008_Tab2.tsv	1f91affc6218...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2008/.Zimmerman2008_TabGroups.tsv	f5cf2f65304c...
pkdb_models/models/rapamycin/data/rapamycin/Zimmerman2008/.Zimmerman2008_TabInterventions.tsv	38ec39cadeaa...
pkdb_models/models/rapamycin/models/output/models/rapamycin_body_flat.xml	147d4aa9d8ed...

2 Results: Rapamycin PBPK model: fit PK

2.1 Parameters

Table 2: Parameters of the fit PK_20261017_094949__24b18, the parameter set PK_20261017_094949__24b18_0, cost 150, with their bounds in the optimization. The 95% confidence intervals are those of the profile likelihood, LB and UB an interval which is open towards the lower or the upper bound, and the Wald intervals of the Fisher information for a parameter without a profile. Identifiable is the classification of the profile: yes, no (LB) or no (UB) if the profile does not reach the threshold towards the lower or the upper bound, no if it reaches it on neither side, structural if it is flat.

Parameter	Description	Value [95% CI]	Unit	Bounds	Identifiable
GU__Ka_dis_rap	Ka_dis [1/hr] dissolution rapamycin	3.65 [2.13, 7.88]	1/hr	[0.1, 20]	yes
LI__RAP2RX_k	rate of rapamycin metabolism by CYP3A4	0.0262 [LB, 0.0393]	1/min	[0.001, 1]	no (LB)

Parameter	Description	Value [95% CI]	Unit	Bounds	Identifiable
Kp_rap	tissue/blood partition coefficient rap	0.648 [0.551, 0.82]	dimensionless	[0.3, 30]	yes
ftissue_rap	tissue distribution rap	3.72 [1.66, UB]	l/min	[0.001, 10]	no (UB)
Kpdeep_rap	bound/free partition coefficient rap (tissue)	3.5 [1.67, 19.8]	dimensionless	[0.1, 100]	yes
kdeep_rap	rate of the slow binding rap (tissue)	0.000648 [0.000122, 0.00143]	1/min	[1e-05, 0.1]	yes
GU__FED_f_absorption	fed effect on the fraction absorbed	1.2 [1.07, 1.35]	dimensionless	[1, 1.9]	yes
GU__FED_f_dissolution	fed effect on the dissolution and gastric emptying	0.171 [0.082, 0.278]	dimensionless	[0.01, 1]	yes
r_cyp3a5	capacity of CYP3A5 relative to CYP3A4	0.458 [LB, 1.18]	dimensionless	[0.01, 5]	no (LB)

2.2 Data

Table 3: Data of the fit PK_20261017_094949__24b18: the number of fit mappings and, in parentheses, of data points per study and kind. The training data enters the cost, the validation data and the outliers are evaluated only.

Study	Training	Validation	Outlier	Total
BasaDenes2019	-	5 (70)	-	5 (70)
Bottiger2001	1 (15)	1 (15)	-	2 (30)
Brattstrom2000	5 (73)	-	-	5 (73)
Kelly1999	-	4 (32)	-	4 (32)
KorthBradley2012	3 (39)	-	-	3 (39)
Leelahavanichkul2005	1 (11)	-	-	1 (11)
Leung2006	2 (16)	2 (20)	-	4 (36)
Renders2007	-	2 (26)	-	2 (26)
Rogers2008	-	4 (52)	-	4 (52)
Tortorici2013	1 (15)	2 (30)	-	3 (45)
Tortorici2014	1 (14)	1 (14)	-	2 (28)
Wang2014	-	2 (26)	-	2 (26)
Zha2022	1 (22)	1 (31)	-	2 (53)
Zhang2017	3 (42)	-	-	3 (42)
Zimmerman1997	-	5 (119)	-	5 (119)
Zimmerman1999	2 (32)	-	-	2 (32)
Zimmerman2003	1 (13)	2 (28)	-	3 (41)
Zimmerman2008	1 (16)	1 (16)	-	2 (32)
Total	22 (308)	32 (479)	-	54 (787)

2.3 Goodness of fit

Table 4: Goodness of fit of the fit PK_20261017_094949__24b18 per kind of data, the parameter set PK_20261017_094949__24b18_0. The cost is defined on the training data only, 2-fold is the percentage of the data points with a positive value and prediction whose prediction is within twofold of the data.

Kind	n	cost	MSE	RMSE	NRMSE	RMSE_w	R^2	2-fold [%]	AIC	BIC
training	308	124	5.58e-11	7.47e-06	0.572	0.899	0.86	87.3	−7253.5	−7220.0

Kind	n	cost	MSE	RMSE	NRMSE	RMSE_w	R²	2-fold [%]	AIC	BIC
validation	479	-	5.17e-10	2.27e-05	0.758	1.13	0.694	68.6	−10224.4	−10186.8

2.4 Figures




Figure 1: Cost of the optimizers over their steps, fit PK_20261017_094949__24b18. The cost of every optimization run over its steps. Runs which end at the same cost found the same optimum; a run which stops much higher is stuck in a local minimum.




Figure 2: Cost of the optimization runs, ordered, fit PK_20261017_094949__24b18. The final cost of the runs, ordered. A flat plateau at the left is the global optimum found repeatedly, which is the evidence that the multistart converged; steps to the right are local minima.




Figure 3: Prediction against the measured data points, per kind of fit mapping, with the agreement of the training data, the lines of twofold and the metrics of the panel, fit PK_20261017_094949__24b18. Within twofold of the data are 269 of the 308 training data points (87.3%) and 327 of the 477 validation data points (68.6%); only the data points with a positive value and prediction are counted. Prediction against measurement, one point per data point, with a panel per kind of fit mapping. The points scatter around the diagonal when the model describes the data; a systematic deviation from it is a systematic error of the model. The band is the agreement of the training data, i.e. the same band the Bland-Altman plot draws, here as lines parallel to the diagonal. The dark red dotted lines are twofold, prediction = 2 x measurement and prediction = measurement / 2; the caption states the points between them of every kind. A point which is zero or negative is not drawn on the logarithmic axes and not counted, the title of a panel then states the points drawn of all. The validation panel shows how the fit describes data it was not fitted on, the outlier panel the data the fit dropped. The box of a panel carries its R², its normalized RMSE, the RMSE of the residuals of the cost, its fold errors GMFE and AFE and the percentages of its points within twofold and within two standard deviations of the data.




Figure 4: Agreement of prediction and measurement as a ratio, per kind of fit mapping, with the agreement of the training data and the agreement of the panel, fit PK_20261017_094949__24b18. The ratio of prediction and measurement over the geometric mean of the two, i.e. the goodness of fit with the diagonal turned into the horizontal. The band is the same, the bias and the limits of agreement `bias ± 1.96 SD` of the training data as fold factors. A bias away from 1 is a systematic over- or underprediction, wide limits are a large scatter, and a trend over the mean is a model which describes the large or the small values better. The box of a panel carries the bias and the SD of its own points as fold factors and the share of them inside the limits of agreement of the training data.




Figure 5: Profile likelihood of every parameter: the cost with the parameter fixed and the other parameters optimized, the threshold of the confidence level and the confidence interval, fit PK_20261017_094949__24b18. One profile per parameter. A profile which crosses the dashed threshold on both sides gives a finite confidence interval; one which stays below it up to a bound is practically non-identifiable; a flat profile is structurally non-identifiable, the parameter is compensated by the others.

2.5 Provenance

Table 5: Provenance of the fit PK_20261017_094949__24b18: the versions it ran with and the revision of its models and data; the SHA-256 checksums of the models and data are listed in Table 1.

Item	Value
Fit	`PK_20261017_094949__24b18`
Created	2026-10-17 07:49:51 UTC
Seed	1234
Python	3.14.4
sbmlsim	0.10.0
libRoadRunner	2.10.0
SciPy	1.18.1
NumPy	2.5.3
Repository	`/home/mkoenig/git/pkdb_models-rapamycin`
Commit	`138cd5e26b655379e4c34971f8cb649aa6cb81cd`
Uncommitted changes	no

Bibliography

[1] M. König, "sbmlsim: SBML simulation made easy." Zenodo, 2026. doi: 10.5281/zenodo.3597770. Version 0.10.0.

[2] R. Storn and K. Price, "Differential evolution - a simple and efficient heuristic for global optimization over continuous spaces," *Journal of Global Optimization*, vol. 11, pp. 341–359, 1997, doi: 10.1023/A:1008202821328.

[3] P. Virtanen *et al.*, "SciPy 1.0: fundamental algorithms for scientific computing in Python," *Nature Methods*, vol. 17, pp. 261–272, 2020, doi: 10.1038/s41592-019-0686-2. Version 1.18.1.

[4] M. D. McKay, R. J. Beckman, and W. J. Conover, "A comparison of three methods for selecting values of input variables in the analysis of output from a computer code," *Technometrics*, vol. 21, no. 2, pp. 239–245, 1979, doi: 10.2307/1268522.

[5] C. Welsh, J. Xu, L. Smith, M. König, K. Choi, and H. M. Sauro, "libRoadRunner 2.0: a high performance SBML simulation and analysis library," *Bioinformatics*, vol. 39, no. 1, p. btac770, 2023, doi: 10.1093/bioinformatics/btac770. Version 2.10.0.

[6] A. C. Hindmarsh *et al.*, "SUNDIALS: suite of nonlinear and differential/algebraic equation solvers," *ACM Transactions on Mathematical Software*, vol. 31, no. 3, pp. 363–396, 2005, doi: 10.1145/1089014.1089020.

[7] H. Akaike, "A new look at the statistical model identification," *IEEE Transactions on Automatic Control*, vol. 19, no. 6, pp. 716–723, 1974, doi: 10.1109/TAC.1974.1100705.

[8] G. Schwarz, "Estimating the dimension of a model," *The Annals of Statistics*, vol. 6, no. 2, pp. 461–464, 1978, doi: 10.1214/aos/1176344136.

[9] J. M. Bland and D. G. Altman, "Statistical methods for assessing agreement between two methods of clinical measurement," *The Lancet*, vol. 327, no. 8476, pp. 307–310, 1986, doi: 10.1016/S0140-6736(86)90837-8.

[10] A. Raue *et al.*, "Structural and practical identifiability analysis of partially observed dynamical models by exploiting the profile likelihood," *Bioinformatics*, vol. 25, no. 15, pp. 1923–1929, 2009, doi: 10.1093/bioinformatics/btp358.

[11] C. Kreutz, A. Raue, D. Kaschek, and J. Timmer, "Profile likelihood in systems biology," *The FEBS Journal*, vol. 280, no. 11, pp. 2564–2571, 2013, doi: 10.1111/febs.12276.

[12] F.-G. Wieland, A. L. Hauber, M. Rosenblatt, C. Tönsing, and J. Timmer, "On structural and practical identifiability," *Current Opinion in Systems Biology*, vol. 25, pp. 60–69, 2021, doi: 10.1016/j.coisb.2021.03.005.

[13] C. R. Harris *et al.*, "Array programming with NumPy," *Nature*, vol. 585, pp. 357–362, 2020, doi: 10.1038/s41586-020-2649-2. Version 2.5.3.