

ILP 2022 – W2S3

While/Break statements

Matthieu DE MARI – Singapore University of Technology and Design



SINGAPORE UNIVERSITY OF
TECHNOLOGY AND DESIGN

Outline (Week2, Session3 – W2S3)

- While statements
- Infinite loops and how to kill them
- The break statement
- (If time allows, recursion!)

The **while** statement

The **while** statement is another type of **conditional structure**.

The **while** statement

The **while** statement is another type of **conditional structure**.

The **if** statement is the simplest **conditional structure**.

- **How it works:**

- If the Boolean condition specified for the **if** statement is **True**, then execute the block of code inside the **if** statement.
- If the Boolean condition is **False**, ignore the block of code in the **if** statement.
- Once we are done executing the code in **if** (or ignoring it), move on to the next (non-indented) line.

The **while** statement

The **while** statement is another type of conditional structure.

- **How it works:**

- If the Boolean condition specified for the **while** statement is **True**, then execute the block of code inside the **while** statement.
- If the Boolean condition is **False**, ignore the block of code in the **while** statement.



The **if** statement is the simplest conditional structure.

- **How it works:**

- If the Boolean condition specified for the **if** statement is **True**, then execute the block of code inside the **if** statement.
- If the Boolean condition is **False**, ignore the block of code in the **if** statement.
- Once we are done executing the code in **if** (or ignoring it), move on to the next (non-indented) line.

The **while** statement

The **while** statement is another type of conditional structure.

- **How it works:**

- If the Boolean condition specified for the **while** statement is **True**, then execute the block of code inside the **while** statement.
- If the Boolean condition is **False**, ignore the block of code in the **while** statement.
- Once we are done executing the code in **while**, move back to the while statement, and repeat until the condition is no longer True.



The **if** statement is the simplest conditional structure.

- **How it works:**

- If the Boolean condition specified for the **if** statement is **True**, then execute the block of code inside the **if** statement.
- If the Boolean condition is **False**, ignore the block of code in the **if** statement.
- Once we are done executing the code in **if** (or ignoring it), move on to the next (non-indented) line.

The **while** statement

The **while** statement is another type of conditional structure.

- **How it works:**

- If the Boolean condition specified for the **while** statement is **True**, then execute the block of code inside the **while** statement.
- If the Boolean condition is **False**, ignore the block of code in the **while** statement.
- Once we are done executing the code in **while**, move back to the while statement, and repeat until the condition is no longer True.

```
1  # Counting from 1 to 10
2  x = 0
3  print("Counting from 1 to 10...")
4  while(x<10):
5      x = x + 1
6      print(x)
7  print("Done!")
```

Counting from 1 to 10...

1

2

3

4

5

6

7



8

9

10

Done !

Architectures: **if** vs. **while**



Infinite loops

The **while** statement repeats a condition until it is no longer **True**.

Infinite loops

The **while** statement repeats a condition until it is no longer **True**.

This means that there should be a clear process that **makes your condition no longer True**, at some point.

```
1  # Counting from 1 to 10
2  x = 0
3  print("Counting from 1 to 10...")
4  while(x<10):
5      x = x + 1
6      print(x)
7  print("Done!")
```

Counting from 1 to 10...

1
2
3
4
5
6
7
8
9
10
Done !

Infinite loops

The **while** statement repeats a condition until it is no longer **True**.

This means that there should be a clear process that **makes your condition no longer True**, at some point.

Otherwise, the **while** block will keep on repeating indefinitely... This is called an **infinite loop**.

```
In [4]: 1 # Counting from 1 to infinity
        2 x = 0
        3 while(x>=0):
        4     x = x + 1
        5     print(x)
        6 print("Done!")
```

```
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
```

Infinite loops and how to kill them

Infinite loops will keep on executing forever, unless

1. Your computer runs out of resources and performs an emergency shutdown before exploding (**bad thing to do**),

Infinite loops and how to kill them

Infinite loops will keep on executing forever, unless

- ~~1. Your computer runs out of resources and performs an emergency shutdown before exploding (**bad thing to do**),~~

Infinite loops and how to kill them

Infinite loops will keep on executing forever, unless

1. You decide to crash the program on purpose and kill the loop manually.

Infinite loops and how to kill them

Infinite loops will keep on executing forever, unless

1. You decide to crash the program on purpose and kill the loop manually.

This is called a **keyboard interrupt**. It is done with **CTRL+C** (or **CMD+C** on mac), in console mode and most IDEs.

```
Counting from 1 to infinity...
1
2
3
4
5
6
7
8
9
10
Traceback (most recent call last):
  File ".\infinite_loop.py", line 8, in <module>
    time.sleep(1)
KeyboardInterrupt
```

Infinite loops and how to kill them

Infinite loops will keep on executing forever, unless

1. You decide to crash the program on purpose and kill the loop manually.

This is called a **keyboard interrupt**. It is done with **CTRL+C** (or **CMD+C** on mac), in console mode and most IDEs.

Or, by using the **stop button** on Jupyter.

```
Counting from 1 to infinity...
1
2
3
4
5
6
7
8
9
10
Traceback (most recent call last):
  File ".\infinite_loop.py", line 8, in <module>
    time.sleep(1)
KeyboardInterrupt
```



Infinite loops and how to kill them

Infinite loops will keep on executing forever, unless

1. You decide to crash the program on purpose and kill the loop manually.

This is called a **keyboard interrupt**. It is done with **CTRL+C** (or **CMD+C** on mac), if in console mode and most IDEs.

Or, by using the **stop button** on Jupyter.



Matt's Great advice #7

Matt's Great Advice #7: Avoid the infinite loops and dead code, by drawing structural diagrams.

Infinite loops and **dead code**, unless created on purpose, usually follow from a **poor design** in your code.

Drawing a **structural diagram**, **before coding**, greatly helps figuring out the right structure for your code.




Matt's Great advice #7

Matt's Great Advice #7: Avoid the infinite loops and dead code, by drawing structural diagrams.

Infinite loops and **dead code**, unless created on purpose, usually follow from a **poor design** in your code.

Drawing a **structural diagram**, **before coding**, greatly helps figuring out the right structure for your code.



Example: diagram for our while loop, counting from 1 to 10.

Infinite loops and how to kill them

Infinite loops will keep on executing forever, unless

1. You decide to crash the program on purpose and kill the loop manually.

Infinite loops: the **break** statement

Infinite loops will keep on executing forever, unless

2. You use a **break** statement.

Infinite loops: the **break** statement

Infinite loops will keep on executing forever, unless

2. You use a **break** statement.

When encountered, the **break** statement will immediately end the current **while** loop.

Infinite loops: the **break** statement

Infinite loops will keep on executing forever, unless

2. You use a **break** statement.

When encountered, the **break** statement will immediately end the current **while** loop.

The code then resumes its execution with the next line outside of the **while** block.

Infinite loops: the **break** statement

Infinite loops will keep on executing forever, unless

2. You use a **break** statement.

When encountered, the **break** statement will immediately end the current **while** loop.

The code then resumes its execution with the next line outside of the **while** block.

```
1 # Counting from 1 to 10, with a break
2 x = 0
3 while(True):
4     x = x + 1
5     print(x)
6     # If x has reached the value 10, break the while loop
7     if(x>=10):
8         break
9     # Careful!
10    print("This is DEAD CODE, because the break is reached before.")
11 print("Done!")
```

```
1
2
3
4
5
6
7
8
9
10
Done!
```


Standard **while** vs. infinite **while** + **break**

1. Standard **while** loop with condition in the while statement.

```
1 # Counting from 1 to 10
2 x = 0
3 print("Counting from 1 to 10...")
4 while(x<10):
5     x = x + 1
6     print(x)
7 print("Done!")
```

2. Infinite **while** loop with condition in an **if** statement, and **break** in the **if** block.

```
1 # Counting from 1 to 10, with a break
2 x = 0
3 while(True):
4     x = x + 1
5     print(x)
6     # If x has reached the value 10,
7     # break the while loop
8     if(x>=10):
9         break
10 print("Done!")
```

→ Both loops work and do the job, which one is better though?

Matt's Great advice #8

Matt's Great Advice #8: Avoid the infinite loops, if possible.

Relying on an infinite **while** loop with a **break** is risky, and should be avoided when possible.



Matt's Great advice #8

Matt's Great Advice #8: Avoid the infinite loops, if possible.

Relying on an infinite **while** loop with a **break** is risky, and should be avoided when possible.

It is often easily avoided, by using the Boolean expression of the **if** statement used for **break**, as the condition in the **while** statement.

```
1  # Counting from 1 to 10, with a break
2  x = 0
3  while(True):
4      x = x + 1
5      print(x)
6      # If x has reached the value 10,
7      # break the while loop
8      if(x>=10):
9          break
10 print("Done!")
```

```
1  # Counting from 1 to 10
2  x = 0
3  print("Counting from 1 to 10...")
4  while(x<10):
5      x = x + 1
6      print(x)
7  print("Done!")
```

Matt's Great advice #8

Matt's Great Advice #8: Avoid the infinite loops, if possible.

Relying on an infinite **while** loop with a **break** is risky, and should be avoided when possible.

It is often easily avoided, by using the Boolean expression of the **if** statement used for **break**, as the condition in the **while** statement.

Note: a few cases, however, require the use of a **break** statement.
For instance, **emergency shutdowns**.

```
1 while(True):
2     print("All systems normal.")
3     print("Running operations as expected.")
4     if(overheating):
5         print("Overheating detected.")
6         print("Engaging emergency shutdown.")
7         break
```

Practice activities for **while/break**

Let us practice the **while/break** concepts a bit, with two activities.

Activity 1 – How many hits can you take.ipynb

Activity 1 - How many hits can you take

Your main character currently has a number of lifepoints, stored in **lifepoints_number**.

Your mentor gives you the following challenge: he will hit you, for a given number of times ***n***.

- The **first hit** will make you **lose one lifepoint**,
- the **second, two lifepoints**,
- the **third, three lifepoints**,
- and **so on**.
- **If you take too many hits and your lifepoints fall at or below zero, you fail the challenge.**

- Assuming you survive ***n*** hits, your mentor will give you ***n*²** coins.

Write a function, named **maximal_coins_number()**, which

- **receives** your current number of **lifepoints**, as the variable **lifepoints_number**,
- and **returns** the **maximal number of coins** you can hope to obtain from the challenge,
- as well the **number of lifepoints** that will be **remaining after taking this maximal number of hits**.

Activity 2 – Guess the number game v2

Remember the guess the number game in W3S1, Activity 1? Back then, we had defined a function **guess_the_number()**,

- which received a **hidden number that the user had to guess** (passed as input **hidden_number**),
- **asked the user to input a number**, via the **input()** method and would store it in a variable **guessed_number**,
- and based on the two numbers would **display two messages**, reading:
 - "You have found the hidden number: True/False."
 - "Your number in guessed_number is lower than the hidden number: True/False."

Your task is to write a **second version** (v2!) of this function, called **guess_the_number_v2()**.

Activity 2 – Guess the number game v2

This v2 function will have the following features, replacing the previous ones:

- The game will **keep on asking the user to input()** values, **until the right number is found**.
- It will **display the message** "You have found the right number!", **once the user has found the right number**.
- When that happens, it **also displays** "It only took you ... tries!" with the blank filled with the number of times the user had to type a number via input().
- Once the number has been found, the function no longer asks the user for inputs and stops.
- **While the user has not found the right number**, the game will **display either**
 - "Your number is lower than the hidden number." (if the last number entered by the user is lower than the hidden number)
 - or "Your number is higher than the hidden number." (if the last number entered by the user is higher than the hidden number).

Conclusion

- While statements
- Infinite loops and how to kill them
- The break statement
- (If time allows, recursion!)

Up for a challenge?
(in the Extra challenges folder)

Challenge: Activity 1+ - How many hits can you take (extra challenge).ipynb

- Similarly, as in other challenges...
- Do not use any conditional statement (**if/while**)
- **Hint:** use a bit of maths on sequences!