

Brilliance Base

Recruitment Module — API Documentation

Base URL: `http://localhost:5000` (or your ngrok / tunnel URL)
Prefixes: `/api/jobs` · `/api/applications`

Auth header (all endpoints below):
Authorization: Bearer <jwt_token>

Roles: candidate | employee | manager | hr | admin
Success: { success: true, message, data }
Error: { success: false, message, errors? }

Application status (exact strings):
Applied !' Review !' Shortlisted !' Interview !' Selected
Also: Rejected | Withdrawn

Job status: Active | Closed

Public signup allows only candidate | admin.
HR / employee / manager accounts are created by Admin/HR or via Select hire.

1. Business flow (frontend match)

1. HR posts a Job (Active) !' appears in Candidate jobs list
2. Candidate applies !' Application status = Applied
3. HR marks Review / Shortlisted / Rejected
4. Shortlisted list !' HR schedules interview (Onsite | Online)
5. Candidate may request reschedule (note) or withdraw
6. After interview HR Select !' User.role = employee + Employee record (EMP001)
or Reject !' Rejected

2. Jobs API — /api/jobs

POST /api/jobs

Auth: Bearer JWT required

Roles: hr, admin

Headers: Content-Type: application/json | Authorization: Bearer <token>

Body (JSON):

```
{
  "title": "Junior Frontend Developer",           // required
  "company": "Brilliance Base",                   // optional, default Brilliance Base
  "department": "Engineering",                    // required enum:
    // Engineering | Developer | Manager | Design | Product | HR | Finance | Marketing
  "location": "Lahore, PK",                       // required
  "types": ["Full-time"],                          // required "e1:
    // Full-time | Part-time | Contract | Internship
  "salaryMin": 60000,                             // optional number
  "salaryMax": 90000,                             // optional number
  "currency": "PKR",                              // optional, default USD
  "description": "At least 30 characters...",      // required min 30
  "requirements": [                                // required string[] (or newline string)
    "1+ year React Native",
    "REST APIs"
  ],
  "skills": ["React Native", "JS"],                // optional string[]
  "closesAt": "2026-09-30T00:00:00.000Z",         // optional ISO date
  "branch": "Lahore HQ"                           // optional string
}
```

Success response (shape):

```
{ "success": true, "message": "Job posted", "data": { "job": { ...enriched } } }
```

Note: Enriched job includes type (types joined), salaryDisplay, applicantsCount, postedAt.

GET /api/jobs

Auth: Bearer JWT required

Roles: candidate, manager, hr, admin

Headers: Authorization: Bearer <token>

Query: status? (candidates default Active) | search? | department? | page? | limit?

Success response (shape):

```
{ "success": true, "data": { "jobs": [...], "pagination": { page, limit, total, pages } } }
```

GET /api/jobs/:id

Auth: Bearer JWT required

Roles: candidate, employee, manager, hr, admin

Headers: Authorization: Bearer <token>

Success response (shape):

```
{ "success": true, "data": { "job": { ... } } }
```

PATCH /api/jobs/:id

Auth: Bearer JWT required

Roles: hr, admin

Headers: Content-Type: application/json | Authorization: Bearer <token>

Body (JSON):

```
{
  "title": "...",
  "department": "Design",
  "location": "...",
  "types": ["Full-time", "Contract"],
  "requirements": [...],
  "description": "...",
  "salaryMin": 70000,
  "salaryMax": 100000,
  "currency": "PKR",
  "status": "Active",    // or Closed
  "closesAt": "...",
  "branch": "..."
}
```

Note: Send only fields to update.

PATCH /api/jobs/:id/close

Auth: Bearer JWT required

Roles: hr, admin

Headers: Authorization: Bearer <token>

Body (JSON):

(none)

Success response (shape):

```
{ "success": true, "message": "Job closed", "data": { "job": { ... } } }
```

Note: Sets job.status = Closed

3. Applications API — Candidate

POST /api/applications

Auth: Bearer JWT required

Roles: candidate

Headers: Content-Type: multipart/form-data | Authorization: Bearer <token>

Body (multipart/form-data):

```
jobId          = <Job ObjectId>          (required)
phone          = 03001234567
experience     = 2 years
education      = BS Computer Science
expectedSalary= 80000
linkedin       = https://linkedin.com/in/... (optional)
coverLetter    = min 20 characters         (required)
resume         = file (pdf | doc | docx)    (optional if profile resume exists)
```

Success response (shape):

```
{ "success": true, "message": "Application submitted", "data": { "application": { status:
"Applied", ... } } }
```

Note: candidateName / candidateEmail auto-filled from User. Duplicate apply blocked unless previous was Withdrawn.

Resume saved under /uploads/resumes/...

GET /api/applications/me

Auth: Bearer JWT required

Roles: candidate

Headers: Authorization: Bearer <token>

Success response (shape):

```
{ "success": true, "data": { "applications": [ { job: { title, company, ... }, status, interview?, ... } ] } }
```

GET /api/applications/:id

Auth: Bearer JWT required

Roles: candidate (own only), hr, admin

Headers: Authorization: Bearer <token>

Note: Candidate may only fetch own application.

POST /api/applications/:id/reschedule

Auth: Bearer JWT required

Roles: candidate (own)

Headers: Content-Type: application/json | Authorization: Bearer <token>

Body (JSON):

```
{  
  "note": "Please move to next week after 3 PM"  
}
```

Note: Allowed only when status === Interview. Sets rescheduleRequest.

POST /api/applications/:id/withdraw

Auth: Bearer JWT required

Roles: candidate (own)

Headers: Authorization: Bearer <token>

Body (JSON):

(none)

Note: status != Withdrawn. Blocked if already Selected.

4. Applications API — HR / Admin pipeline

GET /api/applications

Auth: Bearer JWT required

Roles: hr, admin

Headers: Authorization: Bearer <token>

Query: jobId? | status? | search? (name/email) | page? | limit?

Success response (shape):

```
{ "success": true, "data": { "applications": [...], "pagination": {...} } }
```

GET /api/applications/shortlisted

Auth: Bearer JWT required

Roles: hr, admin

Headers: Authorization: Bearer <token>

Note: Returns status in [Shortlisted, Interview]

GET /api/applications/job/:jobId

Auth: Bearer JWT required

Roles: hr, admin

Headers: Authorization: Bearer <token>

Note: All applications for one job (pipeline list).

PATCH /api/applications/:id/review

Auth: Bearer JWT required

Roles: hr, admin

Headers: Content-Type: application/json | Authorization: Bearer <token>

Body (JSON):

```
{  
  "note": "Looks promising"    // optional != reviewNote  
}
```

Note: status != Review. Allowed only from Applied.

PATCH /api/applications/:id/shortlist

Auth: Bearer JWT required

Roles: hr, admin

Headers: Content-Type: application/json | Authorization: Bearer <token>

Body (JSON):

```
{
  "note": "Strong portfolio" // optional
}
```

Note: status != Shortlisted. Allowed from Applied or Review.

PATCH /api/applications/:id/reject

Auth: Bearer JWT required

Roles: hr, admin

Headers: Content-Type: application/json | Authorization: Bearer <token>

Body (JSON):

```
{
  "note": "Not a fit for this role" // optional
}
```

Note: status != Rejected. Not allowed if Selected or Withdrawn.

POST /api/applications/:id/schedule-interview

Auth: Bearer JWT required

Roles: hr, admin

Headers: Content-Type: application/json | Authorization: Bearer <token>

Body (JSON):

```
// Online
{
  "mode": "Online",
  "datetime": "2026-08-15T10:00:00.000Z",
  "meetingLink": "https://meet.example.com/abc",
  "note": "Be ready 5 mins early" // optional
}

// Onsite
{
  "mode": "Onsite",
  "datetime": "2026-08-15T10:00:00.000Z",
  "location": "Brilliance HQ, Lahore – Floor 3",
  "note": "Bring CNIC" // optional
}
```

Success response (shape):

application.status = "Interview"

application.interview.message auto-built, e.g.:

"Your interview is scheduled Online on Aug 15, 2026, 3:00 PM. Meeting link: https://..."

Note: Allowed from Shortlisted or Interview (reschedule). Clears rescheduleRequest. Onsite requires location; Online requires meetingLink.

POST /api/applications/:id/select

Auth: Bearer JWT required

Roles: hr, admin

Headers: Authorization: Bearer <token>

Body (JSON):

(none)

Success response (shape):

```
{
  "success": true,
  "message": "Candidate selected and hired",
  "data": {
    "application": { "status": "Selected", ... },
    "employee": { "empId": "EMP001", "designation": "<job.title>", ... },
    "user": { "role": "employee", ... }
  }
}
```

Note: Allowed only when status === Interview. Transaction: Application Selected + User.role=employee + create Employee (EMP001 style).

5. Resume / static files

Uploaded resumes are stored on disk under uploads/resumes/ and served as:

GET http://localhost:5000/uploads/resumes/<filename>

Allowed MIME: application/pdf, application/msword, application/vnd.openxmlformats-officedocument.wordprocessingml.document

Max size: 10 MB (multer).

6. Related auth (recruitment context)

POST /api/auth/register

Auth: No auth

Headers: Content-Type: application/json

Body (JSON):

```
{
  "name": "Ali Khan",
  "email": "ali@example.com",
  "password": "secret12",
  "phone": "0300...",
  "role": "candidate"    // ONLY candidate | admin for public signup
}
```

Note: employee | manager | hr ! 403 from public register.

POST /api/auth/login

Auth: No auth

Headers: Content-Type: application/json

Body (JSON):

```
{
  "email": "ali@example.com",
  "password": "secret12",
  "role": "candidate"    // must match account role
}
```

Success response (shape):

```
{ "success": true, "data": { "user": {...}, "token": "<jwt>" } }
```

7. Quick curl examples

Login (HR)

```
curl -X POST http://localhost:5000/api/auth/login \
  -H "Content-Type: application/json" \
  -d '{"email":"hr@example.com","password":"...","role":"hr"}'
```

List Active jobs (Candidate)

```
curl http://localhost:5000/api/jobs \
  -H "Authorization: Bearer $CAND_TOKEN"
```

Apply with resume

```
curl -X POST http://localhost:5000/api/applications \
  -H "Authorization: Bearer $CAND_TOKEN" \
  -F "jobId=JOB_ID" \
  -F "coverLetter=I am excited to apply for this role at Brilliance Base." \
  -F "phone=03001234567" \
  -F "experience=2 years" \
  -F "education=BS CS" \
  -F "expectedSalary=80000" \
  -F "resume=@./cv.pdf"
```

Schedule Online interview

```
curl -X POST http://localhost:5000/api/applications/APP_ID/schedule-interview \
  -H "Authorization: Bearer $HR_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"mode":"Online","datetime":"2026-08-15T10:00:00.000Z","meetingLink":"https://meet.example.com/x"}'
```

Select / hire

```
curl -X POST http://localhost:5000/api/applications/APP_ID/select \
  -H "Authorization: Bearer $HR_TOKEN"
```

8. Seed sample jobs

Run: npm run seed:jobs

Creates sample Active jobs for UI testing.