

# Improving Duckworth-Lewis: Statistical Methods for Resetting Score Targets in Limited-Overs Cricket

Matthew Knowles

University of York

*mk1320@york.ac.uk*

May 27, 2022

# Plan for the Talk

- 1 Background
- 2 Neural Networks in Cricket
- 3 Resetting Score Targets
- 4 Conclusions

# Cricket

- 2 teams of 11 players. One team bats, the other fields.

# Cricket

- 2 teams of 11 players. One team bats, the other fields.
- Score measured in runs. Aim: Score as many as you can before losing 10 wickets.

# Cricket

- 2 teams of 11 players. One team bats, the other fields.
- Score measured in runs. Aim: Score as many as you can before losing 10 wickets.
- Focus in this project is limited overs cricket. Games last 50 overs, which takes about 3 hours.

# Setting the scene: The need for score resetting

- Cricket is very sensitive to external factors, such as rain and daylight.

## Setting the scene: The need for score resetting

- Cricket is very sensitive to external factors, such as rain and daylight.
- If it gets too dark, the ball becomes very hard to see and so the game is stopped.

# Setting the scene: The need for score resetting

- Cricket is very sensitive to external factors, such as rain and daylight.
- If it gets too dark, the ball becomes very hard to see and so the game is stopped.
- Similarly, if it rains, the game is stopped due to the adverse affect this has on the pitch.



# A motivating example

- To illustrate the issue, consider the following example.

# A motivating example

- To illustrate the issue, consider the following example.

## Example

Team A scores 320 runs in their 50 overs, losing 8 wickets in the process. While team B is batting, it begins to rain, and the umpires call the game off with team B on 118-2 from 34 overs. After the rain stops, there is only time for 6 overs of play.

# A motivating example

- To illustrate the issue, consider the following example.

## Example

Team A scores 320 runs in their 50 overs, losing 8 wickets in the process. While team B is batting, it begins to rain, and the umpires call the game off with team B on 118-2 from 34 overs. After the rain stops, there is only time for 6 overs of play.

- Clearly, at this point it is unfair to expect team B to chase down 222 runs in 6 overs instead of the 16 they should have had. So for this reason, score target adjustment is needed to keep the game fair, despite the loss of time.

# Duckworth, Lewis

- Statisticians Frank Duckworth and Tony Lewis set about a way to reduce score targets appropriately to overcome challenges like the one in the last example.

# Duckworth, Lewis

- Statisticians Frank Duckworth and Tony Lewis set about a way to reduce score targets appropriately to overcome challenges like the one in the last example.
- They introduce the following formula

$$Z(u, w) = Z_0(w)(1e^{-b(w)u})$$

Which gives the runs scored with  $u$  overs remaining and  $w$  wickets lost. Note that the actual value of  $Z_0$  and  $b$ , the decay constant are not given due to commercial agreements.

# Duckworth, Lewis

- Statisticians Frank Duckworth and Tony Lewis set about a way to reduce score targets appropriately to overcome challenges like the one in the last example.
- They introduce the following formula

$$Z(u, w) = Z_0(w)(1e^{-b(w)u})$$

Which gives the runs scored with  $u$  overs remaining and  $w$  wickets lost. Note that the actual value of  $Z_0$  and  $b$ , the decay constant are not given due to commercial agreements.

- Consider the special case at the start of an  $N$ -over innings. I.e  $u = N$  and  $w = 0$ .

$$Z(N, 0) = Z_0(1 - e^{-bN}).$$

# Duckworth and Lewis (Contd.)

- We incorporate the above into a ratio that forms the basis of the Duckworth-Lewis method.

$$P(u, w) = \frac{Z(u, w)}{Z(N, 0)}.$$

## Duckworth and Lewis (Contd.)

- We incorporate the above into a ratio that forms the basis of the Duckworth-Lewis method.

$$P(u, w) = \frac{Z(u, w)}{Z(N, 0)}.$$

- Computing all values for  $P$  with  $1 \leq u \leq 50$  and  $0 \leq w \leq 10$  gives a table of results. It is from this table that the revised score target is calculated.



# Stern

- With the introduction of an even shorter form of the game, “Twenty20”, consisting of only 20 overs instead of 50. The method needed to be updated.

# Stern

- With the introduction of an even shorter form of the game, “Twenty20”, consisting of only 20 overs instead of 50. The method needed to be updated.
- Steven Stern introduced updates in 2015 to account for the new increase in game scores.

# Problems with DLS

- DLS has a tendency to reset score targets that are unrealistic, and as such ruin the competitive nature of a match

# Problems with DLS

- DLS has a tendency to reset score targets that are unrealistic, and as such ruin the competitive nature of a match
- DLS does not account for fielding restrictions that are in place at different points in the game

# Problems with DLS

- DLS has a tendency to reset score targets that are unrealistic, and as such ruin the competitive nature of a match
- DLS does not account for fielding restrictions that are in place at different points in the game
- It is not easy to understand, especially for players and officials without any mathematical education


# Structure of Neural Networks

- Neural Networks are a mathematical model based on neurons in a brain

# Structure of Neural Networks

- Neural Networks are a mathematical model based on neurons in a brain
- To artificially create such a model, we use a system of nodes and synapses

## Example



# Mathematically Representing Neural Networks



# Mathematically Representing Neural Networks

- Layers of nodes (perceptrons).  $k$  “hidden” layers sandwiched by an input layer and an output layer.

# Mathematically Representing Neural Networks

- Layers of nodes (perceptrons).  $k$  “hidden” layers sandwiched by an input layer and an output layer.
- Each node in layer  $j$  connects to each node in layer  $j + 1$ . Connection is defined by a weight and a bias.

# Mathematically Representing Neural Networks

- Layers of nodes (perceptrons).  $k$  “hidden” layers sandwiched by an input layer and an output layer.
- Each node in layer  $j$  connects to each node in layer  $j + 1$ . Connection is defined by a weight and a bias.
- Let the layer  $k_i$  have  $m$  nodes, and the layer  $k_i + 1$  have  $n$  nodes. Then the weights between the layers are given by the matrix

# Mathematically Representing Neural Networks

- Layers of nodes (perceptrons).  $k$  “hidden” layers sandwiched by an input layer and an output layer.
- Each node in layer  $j$  connects to each node in layer  $j + 1$ . Connection is defined by a weight and a bias.
- Let the layer  $k_i$  have  $m$  nodes, and the layer  $k_i + 1$  have  $n$  nodes. Then the weights between the layers are given by the matrix

$$W = \begin{bmatrix} w_{1,1} & w_{1,2} & \cdots & w_{1,m} \\ w_{2,1} & w_{2,2} & \cdots & w_{2,n} \\ \vdots & \vdots & \ddots & \vdots \\ w_{n,1} & w_{n,2} & \cdots & w_{n,m} \end{bmatrix} \quad (1)$$

# Mathematically Representing Neural Networks (contd)

- The values of the nodes in layer  $k + 1$ , denoted  $A_{(k+1)}$  is given by the matrix equation  $A_{(k+1)} = \sigma(WA_{(k)} + b_{(k)})$ . Where  $b$  is the vector containing the biases, and  $\sigma()$  is the *activation function*.

# Mathematically Representing Neural Networks (contd)

- The values of the nodes in layer  $k + 1$ , denoted  $A_{(k+1)}$  is given by the matrix equation  $A_{(k+1)} = \sigma(WA_{(k)} + b_{(k)})$ . Where  $b$  is the vector containing the biases, and  $\sigma()$  is the *activation function*.
- The choice of activation function is pretty much problem dependent, and depends a little bit on the data. In our case, we used the sigmoid activation function  $\sigma : \mathbb{R} \rightarrow \mathbb{R}$  defined by  $\sigma(x) = (1 + \exp(-x))^{-1}$ .

# How do Neural Networks “learn”?

- The idea of learning comes from updating the weights and biases to reduce the error made when predicting a result.

# How do Neural Networks “learn”?

- The idea of learning comes from updating the weights and biases to reduce the error made when predicting a result.
- We start by initialising values of weights, biases, activation values by drawing random samples from a distribution.




# How do Neural Networks “learn”?

- The idea of learning comes from updating the weights and biases to reduce the error made when predicting a result.
- We start by initialising values of weights, biases, activation values by drawing random samples from a distribution.
- We pass training data through the network, and see what the output is. By comparing this output to the actual value for that piece of data, we get an error value.

# How do Neural Networks “learn”?

- The idea of learning comes from updating the weights and biases to reduce the error made when predicting a result.
- We start by initialising values of weights, biases, activation values by drawing random samples from a distribution.
- We pass training data through the network, and see what the output is. By comparing this output to the actual value for that piece of data, we get an error value.
- We then employ the backpropagation algorithm to readjust the values of the weights and biases in accordance with the error. This looks to find a set of weights and biases that give the least error on the training data.

# The Run-Rate Network



## Different Scenarios

- Since the aim is to reset score targets when a full innings cannot be played, we have the issue of having 50 inputs to the network. There are two examples of how we could fix this.

# Different Scenarios

- Since the aim is to reset score targets when a full innings cannot be played, we have the issue of having 50 inputs to the network. There are two examples of how we could fix this.

## Example

Assume 35 overs of play have occurred. Leaving 15 overs without data.

- 1 Assert a value of 0 on the remaining overs and see what the network predicts
- 2 Draw random values based on historical performance of teams in the remaining overs

## Different Scenarios (contd)

- To test which method worked better, we took a test data set, and tested which option worked better.

## Different Scenarios (contd)

- To test which method worked better, we took a test data set, and tested which option worked better.
- As it turns out, trying to fill in the gaps, didn't work at all. The predictions were way off and the correlation between predicted results and actual results was almost 0.

## Different Scenarios (contd)

- To test which method worked better, we took a test data set, and tested which option worked better.
- As it turns out, trying to fill in the gaps, didn't work at all. The predictions were way off and the correlation between predicted results and actual results was almost 0.
- Leaving the unplayed overs blank was much more successful, and had a correlation of 0.49. So not great, but much better.



# World Cup Simulation Study

- To test the method fully, we took the 3 games from the 2019 world cup that used DLS to decide a result, and used our method instead.

# World Cup Simulation Study

- To test the method fully, we took the 3 games from the 2019 world cup that used DLS to decide a result, and used our method instead.
- Of the 3 games, only 1 had the result changed, which meant the final standings of the tournament were virtually unchanged, except Bangladesh finish above South Africa for 7<sup>th</sup> place.

## World Cup Simulation Study

- To test the method fully, we took the 3 games from the 2019 world cup that used DLS to decide a result, and used our method instead.
- Of the 3 games, only 1 had the result changed, which meant the final standings of the tournament were virtually unchanged, except Bangladesh finish above South Africa for 7<sup>th</sup> place.
- The key difference was in the scores set, the score targets were far more attainable by the batting team, which would have led to a more competitive set of games. The India vs Pakistan game was ruined by DLS in this way. Since they needed 27.2 an over at one point.

# Did we improve DLS?

- Not really. Aside from giving slightly more competitive score targets, the method was still lacking.

## Did we improve DLS?

- Not really. Aside from giving slightly more competitive score targets, the method was still lacking.
- From an entertainment point of view, this method is better, but from a pure cricket perspective, DLS is still more reliable

# Did we improve DLS?

- Not really. Aside from giving slightly more competitive score targets, the method was still lacking.
- From an entertainment point of view, this method is better, but from a pure cricket perspective, DLS is still more reliable
- With more data, this method will become more reliable in the future, but this is constrained by the number of cricket games played each year.

# Any Questions?