

Booking Your First Flight

A step-by-step guide to the GDS Trainer terminal simulator

Open `../web/index.html` in a browser to start (or run the `gds-trainer` command-line edition). Everything is typed at the prompt and submitted with **Enter**. Commands aren't case-sensitive, but standard GDS convention is ALL CAPS.

1 Sign in

```
SI
```

Confirms sign-in with a demo agent sine and pseudo city code (PCC). Nothing else works until you're signed in.

2 Shop fares and check the schedule (optional, before booking)

Format: FQ + origin + destination, for an indicative fare quote independent of any booking

```
FQDFWORD
```

Shows a per-class table of indicative base fare, taxes, and total for that city pair — no PNR involved, nothing is booked. Useful for a quick "what would this cost" before searching availability.

Add `/ {CLASS}` to check a class's fare rules instead of its price:

```
FQDFWORD/Y
```

Shows that class's change fee, cancellation fee, refundability, minimum/maximum stay, advance-purchase requirement, and checked-baggage allowance — the same rule data shown after you price an itinerary with WP, but queryable up front for any class on any route, no booking required.

To see what flies a route across a whole week rather than one date — times and equipment only, no booking classes or seat counts, since it's not tied to sellable inventory:

```
S15AUGDFWORD
```

To compare fares across nearby dates before committing to one — a fare-calendar style view, lowest indicative fare per day across a ± 3 day window around the given date, nonstop only:

```
AF15AUGDFWORD
```

This is a shopping tool only — not bookable directly. Once you've picked a date, search it with A (step 3) to see and sell actual flights.

3

Search flight availability

Format: A + day + month + origin + destination (or 1 in place of A — both are real GDS entries)

```
A15AUGDFWORD
```

This requests flights from **DFW** (Dallas/Ft Worth) to **ORD** (Chicago O'Hare) on **August 15**. You'll get back a numbered list of flights, each with airline, flight number, seats open per class (F/J/C/Y/B/M), departure/arrival times. Most lines share the searched city pair, but a few may show a different one — that's a connecting flight's leg (see the next step).

A flight may show an OPERATED BY {AIRLINE} ({CODE}{NUMBER}) line underneath it — that's a codeshare: the listed airline sells and tickets the seat, but another airline actually operates the flight, same as a real GDS display.

A long enough flight departing late in the day lands after midnight — its arrival time shows a +1 suffix (e.g. 1206A+1) to mark that it's the next calendar day, the same convention real Sabre uses. This shows up anywhere an arrival time is printed: availability, schedule display, the PNR, and the itinerary document.

Any real-world IATA airport code works — the simulator ships with data for ~6,000 airports worldwide.

4

Sell a seat from the list

Format: 0 + line number + class letter + number of seats

```
04Y1
```

Sells **1 seat in Y class from line 4** of the availability display you just pulled up. The simulator confirms the segment and shows your PNR so far (currently just that flight segment). Selling reduces that class's remaining seat count for the rest of the session — sell it down to 0 and the next sell in that class waitlists (status HL) instead of being blocked.

You can also sell a specific flight directly, without pulling up availability first (a "long sell"). Format: 0 + airline + flight number + class + date + origin/destination + status code + party size:

```
0AA100Y15AUGDFWORDNN1
```

If two lines' cities and times line up (one line's destination matches another's origin, with a workable connection time), sell them together as a connecting itinerary in one entry: seats, then class + line number for each leg:

```
02Y1M2
```

Sells 2 seats — Y class on line 1, M class on line 2 — as two segments that are **married**: they were sold as one connection, so cancelling one later requires cancelling both together (X1, 2), rather than silently leaving the other leg behind.

"Workable connection time" means the layover clears minimum connect time (MCT) at the connecting airport: **45 minutes** if both legs stay within the same country, **90 minutes** if either leg crosses a border (extra time for immigration, security, or re-check-in). A layover that's too short is rejected with the required and actual minutes shown.

5

Add the passenger's name

Format: – + SURNAME + / + GIVEN NAME + TITLE

```
–SMITH/JOHN MR
```

To add **more than one passenger with the same surname** in a single entry, prefix the surname with a count and chain additional given-name/title pairs with /:

```
–2SMITH/JOHN MR/JANE MRS
```

For passengers with different surnames, add a separate – entry for each. The number of named passengers can't exceed the number of seats sold.

To add a **lap infant** traveling with a passenger, append (INF{SURNAME}/{GIVEN}/{DOB}) to that passenger's name entry (DOB is DDMONYY):

```
–SMITH/JOHN MR( INFSMITH/BABY/12JAN26)
```

To tag one passenger in a multi-name entry as a **child fare** — still a fully named, seat-occupying passenger, just priced at a discount off the adult base fare — append (CHD) to that passenger's given-name/title:

```
–2SMITH/JOHN MR/JOHNNY MSTR( CHD)
```

Unlike a lap infant, a child fare occupies a seat and counts against the party size sold on the itinerary; pricing (WP) automatically splits each segment's fare between adult and child portions.

Booking a group (10 or more passengers): if the names aren't finalized yet, add placeholder passengers in one entry instead of spelling out each one:

```
–12TBA/TBA
```

Adds 12 identical TBA/TBA placeholders — real groups are held this way, with names filled in closer to departure. A group needs a deposit on file before it can be saved:

```
3DEPS
```

To finalize a placeholder later, cancel it and add the real name — the same two entries you'd use to fix any other passenger's name:

```
X5
–SMITH/JOHN MR
```

6

Add passenger travel documents (APIS) (optional)

Format: 3D0CS + document type + / + issuing country + / + number + / + nationality + / + date of birth + / + sex + / + expiry date + - + passenger number

```
3D0CSP/US/123456789/US/12JAN90/M/25DEC30-1
```

This is Advance Passenger Information (APIS) / Secure Flight-style data, tied to a specific passenger by number (-1 above means passenger 1 in the name field). TYPE is P for passport. Dates are DDM0NYY, sex is M or F.

For a **lap infant**, append .{INFANT#} after the passenger number — real GDSs don't give infants their own name-field entry, so they're addressed as a decimal off the adult they travel with (1.1 = the 1st infant travelling with passenger 1):

```
3D0CSP/US/123456789/US/12JAN26/M/25DEC30-1.1
```

7

Add special service requests / other service info (optional)

Format: 3{SSR CODE} for a service request (meals, wheelchair, etc.), optionally with a passenger number and free text: 3{SSR CODE}-{PAX#}/{TEXT}. Format: 3OSI{AIRLINE}{TEXT} for other-service-info free text to a carrier.

```
3VGML
3WCHR-1/AISLE SEAT PREFERRED
3OSIAA VIP PASSENGER
```

Common SSR codes: WCHR/WCHS/WCHC (wheelchair), VGML/BBML/CHML/KSML/MOML/DBML/SPML (meals), BLND/DEAF (accessibility), UMNRR (unaccompanied minor), PETC (pet in cabin), BSCT (bassinet), XBAG (extra baggage), EXST (extra seat purchased), CBBG (extra seat for cabin baggage/instrument), STCR (stretcher case), DEPS (group deposit received — see step 5).

To book an extra seat (a comfort/oversized-passenger purchase, or one held for an instrument), sell one more seat than passengers and tag it with the SSR:

```
04Y2
-SMITH/JOHN MR
3EXST-1
```

Sells 2 seats but names only 1 passenger — the fare quote (WP) automatically prices for both seats, since it charges per seat sold on the segment, not per name.

A frequent flyer number can optionally be tied to a specific passenger and/or carry a loyalty tier:

```
3FQTVAA1234567-1/GLD
```

Tiers: SLV (Silver), GLD (Gold), PLT (Platinum), DIA (Diamond). The passenger number and tier are each optional and independent — 3FQTVAA1234567-1 (no tier) and 3FQTVAA1234567/GLD (no passenger, applies to the PNR generally) both work too.

To add an agency-internal note that isn't sent to the airline (distinct from OSI, which is carrier-facing):

```
5VIP CLIENT - HANDLE WITH CARE
```

8

Assign a seat (optional)

Format: 4{N} to display the seat map for itinerary segment N, then 4{N}--{SEAT} to assign one, optionally tied to a specific passenger with / {PAX#}.

```
41
41-14A
```

With a solo passenger on file, the passenger number can be omitted — it's assigned to them automatically. With more than one name on the PNR, it's required (there's no way to guess whose seat it is):

```
41-14A/1
41-14B/2
```

9

Price the itinerary

Format: WP (once segments and at least one name are on the PNR)

```
WP
```

Prices the itinerary and shows a base fare, itemized taxes, a total, the trip type (one way/round trip/circle trip/open jaw — worked out from how your segments' origins and destinations connect), fare rules (change fee, refundability, advance-purchase requirement), and the checked-baggage allowance for the booked class — this is stored on the PNR as a fare quote and is **required before ticketing**. WPNCs prices the lowest fare regardless of seat availability (informational only).

To apply a negotiated/corporate fare code, append it after a slash:

```
WP/ACME01
```

An unrecognized code is rejected with the list of valid codes; a valid one applies its discount to the base fare and is noted on the quote.

10

Add a contact phone number

Format: 9 + phone number + - + location code (A=Agency, H=Home, B=Business, C/M=Cell, F=Fax, HTL=Hotel)

```
9214555-1234-A
```

11

Add "received from" (who the booking request came from)

Format: 6 + text

```
6JSMITH
```

12

Add a ticketing arrangement

```
7TAW/
```

This means "ticket at will" (no ticketing deadline). There's also 7TAX16AUG/1800 to set a ticketing time limit of Aug 16 at 6:00 PM.

13 Add a form of payment

Format: FPCASH, FPCHECK, or FPCC{TYPE}{CARDNUMBER}/{MMYY} for a credit card (TYPE is VI=Visa, CA=MasterCard, AX=Amex, DC=Diners Club, DS=Discover, JC=JCB).

FPCASH

or

FPCCVI4111111111111111/1225

Just like a real GDS, the PNR can't be saved without a form of payment on file. Card numbers are masked to the last 4 digits once stored.

14 End the transaction (save the booking)

ER

This saves the PNR and gives you a **6-character record locator** — your confirmation code. ER redisplay the saved PNR; ET saves it and clears the screen for a new booking. (A group PNR — 10 or more names — additionally needs a deposit on file; see step 5.)

15 Issue the ticket (optional)

TKTT

This is the step people often assume ER already did — it doesn't. Saving a PNR (ER/ET) and **ticketing** it are two different things: the "ticketing arrangement" you added in step 12 just sets a deadline (or "ticket at will"), it doesn't issue anything. TKTT is the actual ticketing entry — it requires the PNR to already be saved (has a record locator) and to have a fare quote, ticketing arrangement, and form of payment on file, and it generates a real-format ticket number (airline numeric code + serial) per passenger, including infants.

If you change the itinerary after ticketing (sell or cancel a segment), the ticket(s) are automatically voided along with the fare quote — you'll need to WP and TKTT again before saving. Three more entries handle a ticketed PNR from there: TKTV voids the ticket(s) same-day, no penalty, leaving the fare quote in place so TKTT can reissue right away; TKTR refunds them (blocked if the fare basis isn't refundable); WFR{TICKET#} exchanges an already-issued ticket after a later fare/itinerary change — applies its value toward the newly-priced total, shows an additional collection or a residual, and reissues.

16 Print or save the customer a copy of the itinerary/invoice (optional)

EMI

EMI ends the transaction (same requirements as ER/ET) and generates a formatted itinerary/invoice document — passenger names, flights, seats, the fare breakdown, form of payment, and ticket numbers if TKTT has already run. In the browser edition this opens in a new tab you can print or "Save as PDF" from your browser's print dialog; the CLI edition prints the same content directly in the terminal. Two related entries generate narrower documents the same way: EM (itinerary only, no fare/payment) and EMT (ticket-focused, notes "NOT YET TICKETED" if you haven't run TKTT yet). All three clear the work area on success, like ET.

17 Look up the booking again later

```
*ABC123
```

(using the actual locator you were given)

To see the full chronological history of everything that's been added, changed, or cancelled on the PNR:

```
*H
```

18 Divide the PNR into two bookings (optional)

Format: SP + passenger number(s)

```
SP2
```

Splits passenger 2 out of the current PNR into a brand-new, separately-located PNR — the itinerary and contact/ticketing info are copied to both. Needs a saved PNR (ER/ET already run) to work from; both resulting PNRs need a fresh WP (and TKTT if already ticketed) before they can be saved again, since the party size changed on each side — each side's WP prices for its own headcount, not the original combined party. Any seat assignment tied to the divided passenger (see step 8) follows them into the new PNR; seats tied to passengers who stay behind stay with the original.

19 Queue the PNR for follow-up (optional)

Format: QE + queue number (once the PNR has been saved with ER/ET)

```
QE25
```

Places the saved PNR on queue **25** for later work — real agencies route PNRs to numbered queues for things like ticketing follow-up or schedule changes, rather than an agent handling everything in one sitting. Queuing clears the work area, the same as ET.

To see how many PNRs are waiting on each queue:

```
QC
```

Or check one specific queue:

```
QC25
```

To pull the next PNR off a queue and load it into the work area:

```
QN25
```

This works one PNR at a time, first-in-first-out — exactly how an agent works a real queue. An empty or unused queue number just reports there's nothing there.

Three queues populate themselves automatically as you work a PNR, no entry required: queue **1** picks up a PNR whose flight time changed after booking (a schedule change), queue **2** picks up one whose flight was cancelled outright by the carrier, and queue **18** picks up one whose waitlisted segment cleared to confirmed. All three are discovered the same way — checking QC/QN-{N}, or noticing the on-screen note the next time the PNR is redisplayed. A cancelled segment (queue 2) is the strictest of the three: the itinerary can't be re-priced with WP until you cancel that segment (X{n}) and sell a replacement — unlike a schedule change, which just needs a fresh WP.

Quick reference

STEP	COMMAND	EXAMPLE
Sign in	SI	SI
Shop fares by city pair (no PNR needed)	FQ{ORIG}-{DEST}	FQDFWORD
Check a class's fare rules by city pair (no PNR needed)	FQ{ORIG}-{DEST}/{CLASS}	FQDFWORD/Y
Flight schedule, 7-day window (no booking classes/seats)	S{DD}{MON}{ORIG}{DEST}	S15AUGDFWORD
Flexible-date fare calendar, ±3 days (not bookable)	AF{DD}{MON}{ORIG}{DEST}	AF15AUGDFWORD
Search flights	A{DD}{MON}{ORIG}{DEST}	A15AUGDFWORD
Sell from list	Ø{LINE}{CLASS}{SEATS}	Ø4Y1
Sell a connection (two avail lines)	Ø{SEATS}{CLASS}{LINE}{CLASS}{LINE}	Ø2Y1M2
Long/direct sell	Ø{AL}{FLT}{CLASS}{DD}{MON}{ORIG}{DEST}{STATUS}{SEATS}	ØAA1ØØY15AUGDFWORDNN1
Add name	–{SURNAME}/{GIVEN} {TITLE}	–SMITH/JOHN MR
Add multiple passengers	–{N}{SURNAME}/{G1} {T1}/{G2} {T2}	–2SMITH/JOHN MR/JANE MRS
Add lap infant	–... (INF{SURNAME}/{GIVEN}/{DOB})	–SMITH/JOHN MR (INFSMITH/BABY/12JAN26)
Tag a passenger as a child fare	–.../{GIVEN} {TITLE} (CHD)	–2SMITH/JOHN MR/JOHNNY MSTR (CHD)
Add a group of placeholder names (10+ = a group)	–{N}TBA/TBA	–12TBA/TBA
Record a group deposit (required to	3DEPS	3DEPS

STEP	COMMAND	EXAMPLE
save a 10+ name PNR)		
Add travel document (APIS)	3DOCS{TYPE}/{CTY}/{NUM}/{NATL}/{DOB}/{SEX}/{EXP}-{PAX#} [. {INFANT#}]	3D0CSP/US/123456789/US/12JAN90/M/25DEC30-1 or ...-1.1
Add SSR	3{SSRCODE} [-{PAX#}] [/ {TEXT}]	3VGML
Add OSI	30SI{AL}-{TEXT}	30SIAA VIP PASSENGER
Add frequent flyer number (+ pax, tier)	3FQTV{AL}{NUMBER} [-{PAX#}] [/ {TIER}]	3FQTVAA1234567-1/GLD
Add general remark	5{TEXT}	5VIP CLIENT
Seat map / assign seat (+ pax)	4{N} / 4{N}-{SEAT} [/ {PAX#}]	41 / 41-14A or 41-14A/1
Decode airport code	DC{CODE}	DCORD
Search airports by name	DAN{TEXT}	DANCHICAGO
Price itinerary (+ corporate code)	WP [/ {CORPCODE}]	WP or WP/ACME01
Add phone	9{NUMBER}-{LOC}	9214555-1234-A
Add received-from	6{TEXT}	6JSMITH
Add ticketing	7TAW/	7TAW/
Add form of payment	FPCASH, FPCHECK, FPCC{TYPE}{NUM}/{MMYY}	FPCASH
Save booking	ER or ET	ER
Issue ticket	TKTT	TKTT
Void ticket (same-day, no penalty)	TKTV	TKTV
Refund ticket (blocked for nonrefundable fares)	TKTR	TKTR
Exchange ticket after a fare/itinerary change	WFR{TICKET#}	WFR045-1234567890

STEP	COMMAND	EXAMPLE
Print/save itinerary, invoice, or e-ticket document	EM, EMI, EMT	EMI
Redisplay PNR	*R or *	*R
Show PNR activity history	*H	*H
Retrieve saved PNR	*{LOCATOR}	*ABC123
Divide passenger(s) into a new PNR	SP{N} or SP{N},{M}	SP2
Place PNR on a queue	QE{N}	QE25
Show queue counts	QC or QC{N}	QC or QC25
Retrieve next PNR from a queue	QN{N}	QN25 (queue 1 auto-populates on a schedule change, 2 on a flight cancellation, 18 on a waitlist clearing)
Cancel an item	X{N}, X{N}-{M}, X{N},{M}	X2
Cancel entire itinerary	XI	XI
Discard unsaved work	IG	IG
Full command list	HELP	HELP

Full walkthrough, start to finish

```
SI
A15AUGDFWORD
04Y1
-SMITH/JOHN MR
3D0CSP/US/123456789/US/12JAN90/M/25DEC30-1
3VGML
41-14A
WP
9214555-1234-A
6JSMITH
7TAW/
FPCASH
ER
TKTT
```

Command & terminology keymap, by PNR stage

Every command and every piece of jargon from this guide, grouped by where it fits in building a PNR from scratch.

STAGE 01

Sign on

COMMAND	DOES
SI	Sign in
SI{sine}/{pcc}	Sign in with a specific agent sine and pseudo city code
S0	Sign out
HELP	Full in-app command reference

TERMINOLOGY

Sine — the agent's identifying code, shown on every sign-in and stamped on the PNR's activity log

PCC — (Pseudo City Code) the agency/office identifier an agent is signed in under

GDS — (Global Distribution System) the reservation platform itself; PNRs, fares, and inventory all live in it

STAGE 02

Shop for fares & schedules

COMMAND	DOES
FQ{ORG}{DST}	Fare quote shop by city pair — indicative only, no PNR involved
FQ{ORG}{DST}/{CLASS}	Fare rules for that class on that route (change fee, cancellation fee, refundable, min/max stay, advance purchase) — no PNR involved
S{DD}-{MON}-{ORG}{DST}	Flight schedule across a 7-day window — no booking classes or seats
AF{DD}-{MON}-{ORG}{DST}	Flexible-date fare calendar, ±3 days around the given date — not bookable directly

TERMINOLOGY

Fare shop — an indicative, per-class fare check by city pair, independent of any itinerary; distinct from WP, which prices an already-sold itinerary

Fare rules — the change fee, cancellation fee, refundability, minimum/maximum stay, and advance-purchase requirement tied to a booking class; viewable stand-alone via FQ.../{CLASS} or automatically shown after pricing with WP. The cancellation fee is deducted from the refund amount when TKTR is used on a refundable fare.

Baggage allowance — the number of free checked bags tied to a booking class (0 for the lowest discount class up to 3 for first class), shown alongside fare rules via FQ.../{CLASS} or after pricing with WP

Schedule display — a several-day view of what flies a route, independent of sellable inventory; distinct from availability, which shows one date's bookable classes/seats

STAGE 03

Shop for availability

COMMAND	DOES
A{DD}{MON}{ORG}{DST}	Air availability
1{DD}{MON}{ORG}{DST}	Air availability (alternate entry, same result)
DC{CODE}	Decode a 3-letter airport/city code
DAN{TEXT}	Search airports/cities by name

TERMINOLOGY

Availability display — the numbered list of flights returned by an A/1 entry

Line number — the number to the left of each flight on the availability display, used to sell it

Class of service — the single-letter fare class (F First, J/C Business, Y/B/M Economy) shown with a seat count per flight

EQP — the aircraft equipment code (e.g. 738, 320) shown on each flight line

Codeshare — a flight sold under one airline's code but operated by another; shown as an OPERATED BY line under the flight on the availability/schedule display, and carried onto the segment once sold

STAGE 04

Sell the itinerary

COMMAND	DOES
0{LINE}{CLASS}{SEATS}	Sell from an availability line
0{SEATS}{CLASS}{LINE}{CLASS}{LINE}	Sell a connection — both legs in one entry
0{AL}{FLT}{CLASS}{DD}{MON}{ORG}{DST}{STATUS}{SEATS}	Long/direct sell (no availability display needed)
X{N}	Cancel element N
X{N}–{M}, X{N},{M}	Cancel a range or list of elements
XI	Cancel the entire itinerary (all segments)

TERMINOLOGY

Segment — one sold flight on the PNR

Long sell — selling a specific flight directly by airline/flight number, bypassing the availability display

Status code — the two-letter segment status: HK = holds confirmed; HL = waitlisted (a class sold down to 0 remaining sells as a waitlist request instead of being blocked); NN = need/request, used when typing a long-sell entry by hand

Party size — the number of seats requested in a sell entry; caps how many passenger names the PNR can carry

PNR element — any single numbered line on the PNR display (a name, a segment, a phone, etc.) — what X{N} cancels

Married segments — two segments sold together as one connection; the PNR display notes each one's pairing, and cancelling either alone is blocked — both must be cancelled in the same X entry

Minimum connect time (MCT) — the shortest layover a connection sell will accept at the connecting airport: 45 minutes if both legs stay within the same country, 90 minutes if either leg crosses a border. A shorter layover is rejected with the required and actual minutes shown

STAGE 05 Add passenger data (name field & documents)

COMMAND	DOES
–{SURNAME}/{GIVEN} {TITLE}	Add a name
–{N}{SURNAME}/{G1} {T1}/{G2} {T2}	Add multiple passengers sharing a surname in one entry
–... (INF{SURNAME}/{GIVEN}/{DOB})	Attach a lap infant to the name just added
–.../{GIVEN} {TITLE}(CHD)	Tag one passenger (in a multi-name entry) as a child fare — still a fully named, seat-occupying passenger, just priced at a discount off the adult base fare
–{N}TBA/TBA	Add N identical group-placeholder passengers in one entry (N > 1)
3DEPS	Record a group deposit received (required to save a 10+ name PNR)
3DOCS{TYPE}/{CTY}/{NUM}/{NATL}/{DOB}/{SEX}/{EXP}–{PAX#} [. {INFANT#}]	Add a travel document (APIS) for a passenger, or for their infant

TERMINOLOGY

Name field — the passenger name(s) on the PNR; required before pricing

Lap infant — an infant traveling on an adult's lap rather than in their own seat; doesn't count against the party size/seats-sold limit

Child fare — a fully named, seat-occupying passenger (unlike a lap infant), priced at a discount off the adult base fare and tagged with a (CHD) suffix

DOB format — DDMONYY, e.g. 12JAN26

Group — a PNR with 10 or more passengers; typically built with TBA/TBA placeholder names finalized closer to departure, and requires a deposit (3DEPS) on file before it can be saved

APIS — (Advance Passenger Information) passport/nationality/date-of-birth data governments require for international travel, tied to a specific passenger by number — or, for an infant, by {PAX#}.{INFANT#} (Sabre-style decimal notation, since an infant has no name-field entry of its own)

STAGE 06 Special service requests / other service info

COMMAND	DOES
3{SSRCODE} [–{PAX#}] [/ {TEXT}]	Add a special service request
30SI{AL}{TEXT}	Add other-service-info free text to a carrier
3FQTV{AL}{NUMBER} [–{PAX#}] [/ {TIER}]	Add a frequent flyer number, optionally tied to a passenger, optionally with a loyalty tier
5{TEXT}	Add a general remark (agency-internal, not sent to the carrier)

TERMINOLOGY

SSR — (Special Service Request) a coded request to the airline: meals, wheelchair assistance, unaccompanied minor, extra baggage, a group deposit (DEPS), etc.

OSI — (Other Service Info) free-text information sent to a carrier that isn't a coded SSR

FQTV — frequent flyer number, stored as a special kind of SSR; can be tied to a specific passenger by number (like a regular SSR), and can carry a loyalty tier (SLV/GLD/PLT/DIA)

General remark — an agency-internal note on the PNR, distinct from OSI (which the carrier sees)

STAGE 07 Seat selection

COMMAND	DOES
4{N}	Display the seat map for segment N
4{N}--{SEAT} [{PAX#}]	Assign a seat on segment N, optionally tied to a passenger

TERMINOLOGY

Seat map — the row/column grid of open (.) and occupied (X) seats for a segment

Seat/passenger attribution — which specific passenger a seat assignment belongs to; optional and auto-assumed for a solo passenger, required once there's more than one name on the PNR. Matters for SP (divide): only an attributed seat can follow its passenger into a new PNR

STAGE 08 Price the itinerary

COMMAND	DOES
WP	Price the itinerary
WPNCs	Price at the lowest fare, regardless of seat availability (informational only)
WP/{CORPCODE}, WPNCs/{CORPCODE}	Price using a negotiated/corporate fare code

TERMINOLOGY

Fare quote — the stored pricing result on the PNR; required before ticketing, and cleared automatically if the itinerary changes afterward

Fare basis — the short code summarizing the fare's class and trip type (e.g. YOW = Y class, one-way)

Trip type — the itinerary's shape, printed alongside the fare basis and on every PNR display once a segment is sold: one way (a single segment), round trip (out and back on the same city pair), circle trip (multiple stops that return to the origin), or open jaw (the return leg starts or ends at a different city than the outbound)

Base fare — the pre-tax fare amount

Taxes/fees — the itemized government and carrier charges added on top of the base fare

Fare rules — the change fee, refundability, and advance-purchase requirement shown with every fare quote, keyed off the itinerary's class

Baggage allowance — the number of free checked bags shown with every fare quote, keyed off the itinerary's class (higher classes get more; the lowest discount economy class gets none)

Corporate/negotiated fare code — an account code that unlocks a discounted fare tier

STAGE 09 Add contact & booking info

COMMAND	DOES
9{NUMBER}--{LOC}	Add a phone number
9/{CTY}{NUMBER}--{LOC}	Add a phone number, out-of-area (with city code)
6{TEXT}	Add "received from"

TERMINOLOGY

Phone field — the contact number(s) on the PNR; required before end transaction

Location code — the phone type suffix (A=Agency, H=Home, B=Business, C/M=Cell, F=Fax, HTL=Hotel)

Received From (RF) — who requested the booking; required before end transaction, same as a phone field

STAGE 10

Ticketing arrangement & form of payment

COMMAND	DOES
7TAW/	Ticketing at will (no deadline)
7TAW{DD}/{MON}/{HHMM}	Ticketing at will, queued to a date/time
7TAX{DD}/{MON}/{HHMM}	Ticketing time limit
FPCASH	Form of payment: cash
FPCHECK	Form of payment: check
FPCC{TYPE}/{CARDNUM}/{MMYY}	Form of payment: credit card

TERMINOLOGY

Ticketing arrangement — the deadline (or lack of one) by which the PNR must be ticketed; not the same as ticketing itself. In this trainer it also stands in for a group's names-finalization deadline.

Ticket at will — no fixed ticketing deadline

Time limit — a fixed date/time by which the PNR must be ticketed or it's expected to cancel

Form of payment (FOP) — how the ticket will be paid for; required before end transaction. Card numbers are masked to the last 4 digits once stored

STAGE 11

End transaction

COMMAND	DOES
ER	End transaction, redisplay the saved PNR
ET	End transaction, clear the work area for a new booking
IG	Ignore the PNR (discard unsaved work)

TERMINOLOGY

RLOC — (Record Locator) the 6-character confirmation code assigned the first time a PNR is end-transacted

End transaction — saving the PNR; requires a segment, a name, a fare quote, a phone, a received-from, a form of payment, and a ticketing arrangement all on file (plus a deposit on file for a 10+ name group)

STAGE 12 Ticket issuance

COMMAND	DOES
TKTT	Issue ticket number(s)
TKTV	Void issued ticket(s) — same-day, no penalty; the fare quote stays on file
TKTR	Refund issued ticket(s) — blocked for a nonrefundable fare basis
WFR{TICKET#}	Exchange an issued ticket after a fare/itinerary change

TERMINOLOGY

Validating carrier — the airline whose numeric code prefixes the issued ticket number(s); taken from the first segment

Ticketing vs. ticketing arrangement — the arrangement (7TAW/7TAX) only sets a deadline; TKTT is the entry that actually issues ticket numbers, and requires the PNR to already be saved (has an RLOC)

Void — a same-day ticket reversal with no penalty; unlike a refund, the fare quote and ticketing arrangement stay valid, so TKTT can reissue immediately

Refund — cancelling issued ticket(s) and voiding the fare quote with them; blocked outright if the fare basis isn't refundable

Exchange — applying an already-issued ticket's value toward a newly re-priced itinerary, showing either an additional collection (ADCOLL) or a non-refundable residual, then reissuing a new ticket number

STAGE 13 Documents

COMMAND	DOES
EM	End transaction, generate an itinerary document (no fare/payment)
EMI	End transaction, generate an invoice document (adds fare summary, form of payment, ticket numbers if issued)
EMT	End transaction, generate an e-ticket notification document

TERMINOLOGY

Itinerary/invoice document — a customer-facing formatted document (browser: printable page/PDF in a new tab; CLI: formatted terminal block), distinct from the PNR display an agent sees - EM/EMI/EMT are end-transaction entries like ER/ET, requiring the same completeness, and clear the work area on success

STAGE 14 Retrieve & review

COMMAND	DOES
*R or *	Redisplay the current PNR
*H	Show the PNR's chronological activity history
*{LOCATOR}	Retrieve a saved PNR by its record locator

TERMINOLOGY

Activity log / PNR history — the timestamped, sine-stamped record of every action taken on a PNR, viewed with *H, separate from the record-locator lookup done with *{LOCATOR}

STAGE 15 Divide a PNR

COMMAND	DOES
SP{N}	Divide passenger N out of the PNR into a new, separately-located PNR
SP{N}, {M}	Divide multiple passengers out at once

TERMINOLOGY

Divide — splitting one or more passengers out of a PNR into a brand-new PNR; the itinerary and contact/ticketing details are copied to both, but each needs its own fresh fare quote (and reissue, if already ticketed) afterward since the party size changed on both sides — each side prices for its own remaining/moved headcount, not the original combined party. A passenger's own seat assignment (if tied to them) moves with them; an unattributed seat assignment is dropped from both sides

STAGE 16 Queues

COMMAND	DOES
QE{N}	Place the saved PNR on queue N; clears the work area
QC	Show a count of PNRs on every non-empty queue
QC{N}	Show the count of PNRs on queue N specifically
QN{N}	Retrieve the next (first-in) PNR off queue N into the work area

TERMINOLOGY

Queue — a numbered bucket of PNRs awaiting follow-up work; the backbone of real-world agent workflow, distinct from *{LOCATOR} retrieval which requires already knowing the exact record locator

Queue count — how many PNRs are currently sitting on a given queue, shown by QC

Working a queue — repeatedly entering QN{N} to pull PNRs off a queue one at a time, in the order they were placed there

Schedule change — an airline-side change to a booked segment's time, discovered automatically: it auto-queues the PNR to queue 1 and shows a note on its next redisplay until re-priced

Flight cancellation — the airline drops a booked, confirmed (HK) flight entirely; the segment's status flips to UN and the PNR auto-queues to queue 2. Unlike a schedule change, WP refuses to re-price while the dead segment is still on file — cancel it with X{n} and sell a replacement first

Waitlist clearing — a waitlisted (HL) segment clearing to confirmed (HK), discovered the same way via queue 18 — no re-pricing needed, since the fare and flight are unchanged