

S * A * B * R * E *

Booking & Modification Guide

A complete reference for building, pricing, ticketing,
retrieving, and modifying PNRs in the Sabre GDS
Terminal Simulator

TRAINING / EDUCATIONAL USE · SYNTHETIC DATA · NO NETWORK CALLS

Part 1 — Booking a New Flight

Everything in the simulator is typed at the `>` prompt and submitted with **Enter**. Entries are not case-sensitive, but Sabre convention is ALL CAPS — the terminal echoes your input in caps regardless of how you type it.

1 Sign In

Nothing else works until you're signed in.

```
> SI
SABRE SYSTEM ONE - SIGN IN COMPLETE
AGENT SINE: 9TAA   PCC: DFW1   ...
```

You can optionally supply your own sine and PCC: `SI{SINE}/{PCC}`.

2 Search Flight Availability

Format: `A{DD}{MON}{ORIG}{DEST}` — day, three-letter month, origin airport, destination airport. `1{DD}{MON}{ORIG}{DEST}` is an accepted alternate entry (both are authentic Sabre mnemonics).

```
> A15AUGDFWORD
** AIR AVAILABILITY **  DFW-ORD  15AUG2026  SAT
DALLAS-FORT WORTH DFW  TO  CHICAGO ORD

LN  FLT      F  J  C  Y  B  M  DEP    ARR    EQP
1   AA 2265   F5 J1 C5 Y4 B5 M5 539A   720A   E75
2   NK 2561   F1 J7 C2 Y6 B4 M5 649A   941A   73G
...
```

Any real IATA airport code works — the simulator ships with data for roughly 6,000 airports worldwide. Flight numbers, times, and seat counts are deterministic: the same route + date always returns the same results.

3 Sell a Seat

From an availability display

Format: `0{LINE}{CLASS}{SEATS}`

```
> 01Y1
SEGMENT SOLD - AA2265 Y 15AUG DFWORD HK1  539A 720A
```

Direct / long sell (no availability display needed)

Format: `0{AIRLINE}{FLIGHT#}{CLASS}{DD}{MON}{ORIG}{DEST}{STATUS}{SEATS}`

```
> 0AA100Y15AUGDFWORDNN1
SEGMENT SOLD - AA100 Y 15AUG DFWORD NN1 646P 929P
```

Status	Meaning
HK	Holding confirmed (used automatically when selling from availability)
NN	Need / requested, not yet confirmed
GK	Confirming without request
LL	Waitlisted
DS	Open / unconfirmed date segment

Sell as many segments as the itinerary needs (connections, return flights, multi-city) by repeating either sell entry.

4 Add Passenger Name(s)

Format: `-{SURNAME}/{GIVEN} {TITLE}`

```
> -SMITH/JOHN MR
NAME ADDED - SMITH/JOHN MR
```

For **multiple passengers with the same surname**, prefix the surname with a headcount and chain additional given-name/title pairs with `/`:

```
> -2SMITH/JOHN MR/JANE MRS
NAMES ADDED - SMITH/JOHN MR SMITH/JANE MRS
```

Passengers with **different surnames** each get their own `-` entry. Every named passenger becomes its own numbered `NM` element in the PNR.

5 Price the Itinerary

Format: `WP` — requires at least one sold segment and one name on the PNR.

```
> WP
** ITINERARY PRICING - WP **
1 AA2265 Y 15AUG DFWORD HK1 539A 720A

FARE BASIS: YOW
BASE FARE          USD 140.00
  XF   USD 6.94    PASSENGER FACILITY CHARGE
  US   USD 15.14    U.S. TRANSPORTATION TAX
TAXES/FEES         USD 22.08
TOTAL              USD 162.08

FARE QUOTE STORED - REQUIRED PRIOR TO TICKETING
```

WPNC prices the lowest fare regardless of seat availability (informational only — same pricing engine, different label).

Pricing is required before ticketing. Ending the transaction (**ER / ET**) without a stored fare quote fails with **PNR INCOMPLETE - NEED FARE QUOTE (ENTRY: WP)** .

6 Add a Contact Phone Number

Format: **9{NUMBER}-{LOC}** or, for an out-of-area number, **9/{CITY}{NUMBER}-{LOC}** .

```
> 9214555-1234-A
PHONE ADDED - 9214555-1234-A
```

Code	Location
A	Agency
H	Home
B	Business
C / M	Cell / Mobile
F	Fax
HTL	Hotel

7 Add "Received From"

Format: **6{TEXT}** — who the booking request came from.

```
> 6JSMITH
RECEIVED FROM ADDED - JSMITH
```

8 Add a Ticketing Arrangement

Entry	Meaning
7TAW/	Ticket at will — no deadline, ticket any time before departure
7TAW{DD}-{MON}/{HHMM}	Ticket at will, queued to a specific date/time
7TAX{DD}-{MON}/{HHMM}	Time limit — must ticket by this date/time

```
> 7TAW/  
TICKETING ARRANGEMENT ADDED - 7TAW/
```

9 End the Transaction

This is what actually saves the PNR and generates a record locator. All five required elements — segment, name, fare quote, phone, received-from, ticketing — must be present, or **ER / ET** will reject with an **PNR INCOMPLETE** error naming the missing piece.

```
> ER  
END OF TRANSACTION COMPLETE  
30JUL 236P RLOC: CUA9SU
```

Entry	Behavior
ER	End + Retrieve — saves the PNR and keeps it loaded in the work area, redisplayed. Use this if you plan to keep editing (e.g. immediately price/ticket a second itinerary variation, or review before moving on).
ET	End Transaction — saves the PNR and clears the work area completely, ready for the next booking from scratch.

Part 2 — Retrieving & Modifying an Existing PNR

1 Retrieve the Booking

Format: `*{LOCATOR}` — the 6-character record locator returned by `ER / ET`. This loads a full copy of the saved PNR back into the work area and displays it.

```
> *CUA9SU
PNR CUA9SU RETRIEVED

RLOC: CUA9SU
1  NM1  SMITH/JOHN MR
2  SEG1 AA2265 Y 15AUG DFWORD HK1  539A 720A SAT
3  FQ   WP  YOW  BASE USD140.00 TAX USD22.08 TTL USD162.08
4  CTC  214555-1234-A
5  RF   JSMITH
6  TK   7TAW/ (TICKETING AT WILL - TICKET ON OR BEFORE DEPARTURE)
```

To redisplay the PNR already in the work area (no retrieval needed) use `*R` or `*` alone.

2 Add or Change Elements

Once retrieved, the PNR is fully live and editable — every entry from Part 1 works exactly the same way against a retrieved booking as it does against a brand-new one:

- **Add another passenger:** `-JONES/MARY MRS`
- **Add another segment** (connection, return flight, multi-city): sell from a fresh availability display or with a direct/long sell entry, same as Part 1 Step 3.
- **Add/replace a phone or received-from:** entering a new one adds it as an additional element — cancel the old one first (see below) if you want a clean replacement.
- **Change the ticketing arrangement:** entering a new `7TAW/` or `7TAX...` overwrites the existing ticketing element.

3 Cancel Elements

Every line in the PNR display is numbered. Cancel by that number:

Entry	Effect
X{N}	Cancel a single numbered element, e.g. <code>X2</code>
X{N}–{M}	Cancel a contiguous range, e.g. <code>X1–3</code>
X{N}, {M}, {K}	Cancel a specific list, e.g. <code>X1,3,5</code>
XI	Cancel the entire itinerary — every sold segment at once

```
> X1,3  
ELEMENTS 1,3 CANCELLED
```

Element numbers always refer to the most recently displayed PNR. If you add or cancel something, the numbering shifts — always check the latest `*R` display before issuing another `X` entry rather than reusing numbers from an earlier screen.

4 Re-price After an Itinerary Change

Selling a new segment or cancelling an existing one automatically invalidates any stored fare quote — this mirrors real Sabre, where changing the itinerary states out the priced fare:

```
> 0DL200Y16AUGORDLAXNN1  
SEGMENT SOLD - DL200 Y 16AUG ORDLAX NN1 719A 1134A  
FARE QUOTE INVALIDATED - ITINERARY CHANGED, RE-PRICE WITH WP
```

Run `WP` again before you can successfully `ER / ET` — the completeness check will reject the save otherwise, exactly as it does for a brand-new PNR missing a fare quote.

5 Save the Modified PNR

Once the PNR is complete again (segment, name, fare quote, phone, received-from, ticketing), save with `ER` or `ET` exactly as in Part 1. Because the PNR was retrieved with its original locator already attached, the **same record locator is reused** — this updates the saved booking rather than creating a new one.

```
> ER  
END OF TRANSACTION COMPLETE  
30JUL 241P RLOC: CUA9SU
```

6 Discarding Changes

Format: `IG` — discards whatever is currently in the work area.

Important simulator-specific behavior: `IG` clears the work area to a completely blank PNR — it does *not* restore the last-saved version of a retrieved booking. If you want to abandon in-progress edits to a retrieved PNR and get back its last-saved state, re-retrieve it with `*{LOCATOR}` instead of using `IG`.

Part 3 — Full Command Reference

Sign On / Off

Entry	Description
SI	Sign in with a default demo sine/PCC
SI{SINE}/{PCC}	Sign in with a specific agent sine and pseudo city code
SO	Sign out

Availability

Entry	Description
A{DD}{MON}{ORIG}{DEST}	Air availability display
1{DD}{MON}{ORIG}{DEST}	Air availability display (alternate real Sabre entry)

Sell

Entry	Description
0{LINE}{CLASS}{SEATS}	Sell from the most recent availability display
0{AL}{FLT}{CLASS}{DD}{MON}{ORIG}{DEST}{STATUS}{SEATS}	Direct/long sell — no prior availability display needed

PNR Build

Entry	Description
—{SURNAME}/{GIVEN} {TITLE}	Add one passenger name
—{N}{SURNAME}/{G1} {T1}/{G2}{T2}...	Add multiple passengers sharing a surname
WP	Price the itinerary as booked (required before ticketing)
WPNC	Price the lowest fare regardless of availability (informational)
9{NUMBER}—{LOC}	Add a contact phone number
9/{CITY}{NUMBER}—{LOC}	Add an out-of-area contact phone number
6{TEXT}	Add "received from"
7TAW/	Ticketing: at will, no deadline
7TAW{DD}{MON}/{HHMM}	Ticketing: at will, queued to date/time
7TAX{DD}{MON}/{HHMM}	Ticketing: time limit by date/time

PNR Management

Entry	Description
*R or *	Redisplay the PNR currently in the work area
*{LOCATOR}	Retrieve a saved PNR by its 6-character record locator
X{N}	Cancel a single numbered element
X{N}–{M}	Cancel a contiguous range of elements
X{N},{M},{K}	Cancel a specific list of elements
XI	Cancel the entire itinerary (all sold segments)
IG	Discard everything in the work area (does not restore a prior save)
ER	End transaction, save, and keep the PNR loaded/redisplayed
ET	End transaction, save, and clear the work area
HELP	Show the in-terminal command reference

Part 4 — Worked Example

Start to finish: book a one-passenger itinerary, save it, retrieve it later, add a second passenger and a connecting segment, re-price, and re-save.

Booking

```
SI
A15AUGDFWORD
01Y1
-SMITH/JOHN MR
WP
9214555-1234-A
6JSMITH
7TAW/
ER                                     -- note the RLOC returned, e.g. CUA9SU
```

Modifying later

```
*CUA9SU                               -- retrieve the saved PNR
-JONES/MARY MRS                       -- add a second passenger
A16AUGORDLAX                           -- pull a connecting flight
02Y1                                   -- sell it (fare quote auto-invalidates)
WP                                     -- re-price the now two-segment itinerary
ER                                     -- save back to the same RLOC: CUA9SU
```

Cancelling a segment and re-pricing

```
*CUA9SU
X4                                     -- cancel just the SEG element numbered 4 on the current
display
WP                                     -- required again before ER/ET will succeed
ER
```

Sabre GDS Terminal Simulator — training/educational tool. All flight, fare, and airport data in this simulator is either synthetic (deterministically generated) or drawn from the public OpenFlights airport dataset; nothing in this application makes network calls or represents real-time airline inventory.