

S * A * B * R * E *

Booking & Modification Guide

A complete reference for building, pricing, ticketing,
retrieving, and modifying PNRs in the Sabre GDS
Terminal Simulator

TRAINING / EDUCATIONAL USE · SYNTHETIC DATA · NO NETWORK CALLS

Part 1 — Booking a New Flight

Everything in the simulator is typed at the `>` prompt and submitted with **Enter**. Entries are not case-sensitive, but Sabre convention is ALL CAPS — the terminal echoes your input in caps regardless of how you type it.

1 Sign In

Nothing else works until you're signed in.

```
> SI
SABRE SYSTEM ONE - SIGN IN COMPLETE
AGENT SINE: 9TAA   PCC: DFW1   ...
```

You can optionally supply your own sine and PCC: `SI{SINE}/{PCC}`.

2 Search Flight Availability

Format: `A{DD}{MON}{ORIG}{DEST}` — day, three-letter month, origin airport, destination airport. `1{DD}{MON}{ORIG}{DEST}` is an accepted alternate entry (both are authentic Sabre mnemonics).

```
> A15AUGDFWORD
** AIR AVAILABILITY **  DFW-ORD  15AUG2026  SAT
DALLAS-FORT WORTH DFW  TO  CHICAGO ORD

LN  FLT      F  J  C  Y  B  M  DEP    ARR    EQP
1   AA 2265  F5 J1 C5 Y4 B5 M5 539A   720A   E75
2   NK 2561  F1 J7 C2 Y6 B4 M5 649A   941A   73G
...
```

Any real IATA airport code works — the simulator ships with data for roughly 6,000 airports worldwide. Flight numbers, times, and seat counts are deterministic: the same route + date always returns the same results. Don't know a code? See `DC` / `DAN` in Step 6 below.

3 Sell a Seat

From an availability display

Format: `0{LINE}{CLASS}{SEATS}`

```
> 01Y1
SEGMENT SOLD - AA2265 Y 15AUG DFWORD HK1  539A 720A
```

Direct / long sell (no availability display needed)

Format: `0{AIRLINE}{FLIGHT#}{CLASS}{DD}{MON}{ORIG}{DEST}{STATUS}{SEATS}`

```
> 0AA100Y15AUGDFWORDNN1  
SEGMENT SOLD - AA100 Y 15AUG DFWORD NN1 646P 929P
```

Status	Meaning
HK	Holding confirmed (used automatically when selling from availability)
NN	Need / requested, not yet confirmed
GK	Confirming without request
LL	Waitlisted
DS	Open / unconfirmed date segment

Sell as many segments as the itinerary needs — connections, return flights, multi-city — by repeating either sell entry. There's no separate "trip type" step: a round trip is just two sells (outbound, then a return-date search and sell); multi-city is the same pattern repeated. The fare quote in Step 7 automatically labels the result **OW** , **RT** , **CT** , or **OJ** based on whatever segments end up on the PNR.

4 Add Passenger Name(s)

Format: **-{SURNAME}/{GIVEN} {TITLE}**

```
> -SMITH/JOHN MR  
NAME ADDED - SMITH/JOHN MR
```

For **multiple passengers with the same surname**, prefix the surname with a headcount and chain additional given-name/title pairs with **/** :

```
> -2SMITH/JOHN MR/JANE MRS  
NAMES ADDED - SMITH/JOHN MR SMITH/JANE MRS
```

Passengers with **different surnames** each get their own **-** entry. Every named passenger becomes its own numbered **NM** element in the PNR.

To add a **lap infant** traveling with a passenger, append **(INF{SURNAME}/{GIVEN}/{DOB})** to that passenger's name entry (**DOB** is **DDMONYY**):

```
> -SMITH/JOHN MR(INFSMITH/BABY/12JAN26)  
NAME ADDED - SMITH/JOHN MR  
INFANT ADDED - SMITH/BABY DOB 12JAN26 (TRAVELS WITH SMITH/JOHN MR)
```

5 Special Service Requests, Other Service Info & Frequent Flyer (optional)

Format: **3{SSRCODE}[-{PAX#}] [/ {TEXT}]** for a service request — optionally tied to a specific passenger number, with free text after a slash.

> 3VGML

SSR ADDED – VGML VEGETARIAN MEAL

> 3WCHR-1/AISLE SEAT

SSR ADDED – WCHR WHEELCHAIR – CAN WALK TO/FROM SEAT PAX 1 (SMITH/JOHN MR) /AISLE SEAT

Code	Meaning
WCHR / WCHS / WCHC	Wheelchair — can walk / must be carried / immobile
VGML / BBML / CHML / KSML / MOML / DBML / SPML	Meal requests — vegetarian, baby, child, kosher, muslim, diabetic, special (free text)
BLND / DEAF	Blind / deaf passenger
UMNR	Unaccompanied minor
PETC	Pet in cabin
BSCT	Bassinet request
XBAG	Extra baggage

Format: 30SI{AIRLINE}{TEXT} for other-service-info free text sent to a carrier (not an actionable request, just information):

> 30SIAA VIP PASSENGER

OSI ADDED – AA VIP PASSENGER

Format: 3FQTV{AIRLINE}{NUMBER} to add a frequent flyer number (stored as its own SSR element):

> 3FQTVAA1234567

SSR ADDED – FQTV AA FREQUENT FLYER NUMBER AA1234567

6 Assign a Seat & Look Up Airports (optional)

Format: 4{N} to display the seat map for itinerary segment N, then 4{N}–{SEAT} to assign one. The map is deterministic per segment — the same flight always shows the same open/occupied layout.

```

> 41
SEAT MAP - AA2265 E75 15AUG DFW-ORD

      A B C      D E F
1      . X .      X . X
2      X . X      . . X
3      . X .      X . X
...

. OPEN   X OCCUPIED   * YOUR ASSIGNMENT
ASSIGN WITH: 41-{SEAT}   e.g. 41-14A
> 41-1A
SEAT ASSIGNED - SEG1 1A

```

Don't know an airport's 3-letter code? Format: `DC{CODE}` decodes a code you have; `DAN{TEXT}` searches by city/airport name:

```

> DCORD
ORD CHICAGO O'HARE INTERNATIONAL AIRPORT
  CHICAGO, UNITED STATES
> DANCHICAGO
CITY/AIRPORT NAME SEARCH - "CHICAGO" (8 MATCHES)

CGX CHICAGO MEIGS AIRPORT          CHICAGO          UNITED STATES
MDW CHICAGO MIDWAY INTERNATIONAL AIRPORT CHICAGO      UNITED STATES
ORD CHICAGO O'HARE INTERNATIONAL AIRPORT CHICAGO      UNITED STATES
...

```

7 Price the Itinerary

Format: `WP` — requires at least one sold segment and one name on the PNR.

```

> WP
** ITINERARY PRICING - WP **
1 AA2265 Y 15AUG DFWORD HK1 539A 720A

FARE BASIS: YOW
BASE FARE          USD 140.00
XF   USD 6.94   PASSENGER FACILITY CHARGE
US   USD 15.14   U.S. TRANSPORTATION TAX
TAXES/FEES          USD 22.08
TOTAL              USD 162.08

FARE QUOTE STORED - REQUIRED PRIOR TO TICKETING

```

The fare basis suffix reflects the shape of the itinerary at the time you price it:

Suffix	Meaning
OW	One way — a single segment
RT	Round trip — exactly two segments, second mirrors the first city pair
CT	Circle trip — three or more segments that return to the origin
OJ	Open jaw / multi-city — doesn't return to the origin city

WPNC prices the lowest fare regardless of seat availability (informational only — same pricing engine, different label).

Pricing is required before ticketing. Ending the transaction (**ER / ET**) without a stored fare quote fails with **PNR INCOMPLETE – NEED FARE QUOTE (ENTRY: WP)** .

8 Add a Contact Phone Number

Format: **9{NUMBER}--{LOC}** or, for an out-of-area number, **9/{CITY}{NUMBER}--{LOC}** .

```
> 9214555-1234-A
PHONE ADDED – 9214555-1234-A
```

Code	Location
A	Agency
H	Home
B	Business
C / M	Cell / Mobile
F	Fax
HTL	Hotel

9 Add "Received From"

Format: **6{TEXT}** — who the booking request came from.

```
> 6JSMITH
RECEIVED FROM ADDED – JSMITH
```

10 Add a Ticketing Arrangement

Entry	Meaning
7TAW/	Ticket at will — no deadline, ticket any time before departure
7TAW{DD}/{MON}/{HHMM}	Ticket at will, queued to a specific date/time
7TAX{DD}/{MON}/{HHMM}	Time limit — must ticket by this date/time

```
> 7TAW/  
TICKETING ARRANGEMENT ADDED - 7TAW/
```

This entry only sets a *deadline or queue instruction* — it does not actually issue a ticket. See Step 13.

11 Add a Form of Payment

Format: `FPCASH`, `FPCHECK`, or `FPCC{TYPE}/{CARDNUMBER}/{MMYY}` for a credit card (`TYPE` is `VI` =Visa, `CA` =MasterCard, `AX` =Amex, `DC` =Diners Club, `DS` =Discover, `JC` =JCB).

```
> FPCASH  
FORM OF PAYMENT ADDED - CASH  
> FPCCVI4111111111111111/1225  
FORM OF PAYMENT ADDED - CC VI XXXXXXXXXXXX1111 EXP 12/25 (VISA)
```

Card numbers are masked to the last 4 digits once stored. Re-entering a form of payment replaces the one on file rather than adding a second.

Required before end transaction. Just like real Sabre, the PNR can't be saved without a form of payment on file.

12 End the Transaction

This is what actually saves the PNR and generates a record locator. All six required elements — segment, name, fare quote, phone, received-from, form of payment, ticketing — must be present, or `ER` / `ET` will reject with a `PNR INCOMPLETE` error naming the missing piece.

```
> ER  
END OF TRANSACTION COMPLETE  
30JUL 236P RLOC: CUA9SU
```

Entry	Behavior
ER	End + Retrieve — saves the PNR and keeps it loaded in the work area, redisplayed. Use this if you plan to keep editing (e.g. immediately price/ticket a second itinerary variation, or review before moving on).
ET	End Transaction — saves the PNR and clears the work area completely, ready for the next booking from scratch.

13 Issue the Ticket (optional)

Format: `TKTT` — this is the step people often assume `ER` already did. It didn't: saving a PNR and ticketing it are two separate things in real Sabre, exactly like here. `TKTT` requires the PNR to already be saved (has a record locator) and to have a fare quote, ticketing arrangement, and form of payment on file, and it refuses to double-ticket an already-ticketed PNR.

> TKTT

** ELECTRONIC TICKET ISSUED **

SMITH/JOHN MR 001-6243662235

VALIDATING CARRIER: AA FORM OF PAYMENT: CASH

One ticket number is generated per passenger (adults and infants both), in the real 13-digit airline format: a 3-digit IATA airline numeric code for the validating carrier (the first segment's airline) followed by a 10-digit serial.

Changing the itinerary after ticketing voids the ticket(s). Selling or cancelling a segment after **TKTT** clears both the stored fare quote and any issued tickets — you'll need to run **WP** then **TKTT** again before the PNR can be saved as ticketed.

Part 2 — Retrieving & Modifying an Existing PNR

1 Retrieve the Booking

Format: `*{LOCATOR}` — the 6-character record locator returned by `ER / ET`. This loads a full copy of the saved PNR back into the work area and displays it.

```
> *CUA9SU
PNR CUA9SU RETRIEVED

RLOC: CUA9SU
1  NM1  SMITH/JOHN MR
2  SEG1 AA2265 Y 15AUG DFWORD HK1  539A 720A SAT
3  FQ   WP  YOW  BASE USD140.00 TAX USD22.08 TTL USD162.08
4  CTC  214555-1234-A
5  RF   JSMITH
6  FP   CASH
7  TK   7TAW/ (TICKETING AT WILL – TICKET ON OR BEFORE DEPARTURE)
8  TKT  SMITH/JOHN MR 001-6243662235
```

To redisplay the PNR already in the work area (no retrieval needed) use `*R` or `*` alone.

2 Add or Change Elements

Once retrieved, the PNR is fully live and editable — every entry from Part 1 works exactly the same way against a retrieved booking as it does against a brand-new one:

- **Add another passenger:** `-JONES/MARY MRS`
- **Add another segment** (connection, return flight, multi-city): sell from a fresh availability display or with a direct/long sell entry, same as Part 1 Step 3.
- **Add SSR/OSI, assign a seat, add a frequent flyer number:** same entries as Part 1 Steps 5–6.
- **Add/replace a phone or received-from:** entering a new one adds it as an additional element — cancel the old one first (see below) if you want a clean replacement.
- **Change the ticketing arrangement or form of payment:** entering a new `7TAW/ / 7TAX...` or `FP...` overwrites the existing element.

3 Cancel Elements

Every line in the PNR display is numbered — including SSR/OSI, seats, form of payment, and ticket lines, not just names and segments. Cancel by that number:

Entry	Effect
X{N}	Cancel a single numbered element, e.g. X2
X{N}–{M}	Cancel a contiguous range, e.g. X1–3
X{N},{M},{K}	Cancel a specific list, e.g. X1,3,5
XI	Cancel the entire itinerary — every sold segment at once

```
> X1,3
ELEMENTS 1,3 CANCELLED
```

Element numbers always refer to the most recently displayed PNR. If you add or cancel something, the numbering shifts — always check the latest *R display before issuing another X entry rather than reusing numbers from an earlier screen.

4 Re-price (and Re-ticket) After an Itinerary Change

Selling a new segment or cancelling an existing one automatically invalidates any stored fare quote — **and any issued tickets along with it** — this mirrors real Sabre, where changing the itinerary stales out both the priced fare and anything already ticketed against it:

```
> 0DL200Y16AUGORDLAXNN1
SEGMENT SOLD - DL200 Y 16AUG ORDLAX NN1 719A 1134A
FARE QUOTE INVALIDATED - ITINERARY CHANGED, RE-PRICE WITH WP
TICKETS VOIDED - ITINERARY CHANGED, REISSUE WITH TKTT AFTER RE-PRICING
```

Run WP again before you can successfully ER / ET — the completeness check will reject the save otherwise, exactly as it does for a brand-new PNR missing a fare quote. If the PNR had already been ticketed, run TKTT again too once it's re-priced.

5 Save the Modified PNR

Once the PNR is complete again (segment, name, fare quote, phone, received-from, form of payment, ticketing), save with ER or ET exactly as in Part 1. Because the PNR was retrieved with its original locator already attached, the **same record locator is reused** — this updates the saved booking rather than creating a new one.

```
> ER
END OF TRANSACTION COMPLETE
30JUL 241P RLOC: CUA9SU
```

6 Discarding Changes

Format: IG — discards whatever is currently in the work area.

Important simulator-specific behavior: `IG` clears the work area to a completely blank PNR — it does *not* restore the last-saved version of a retrieved booking. If you want to abandon in-progress edits to a retrieved PNR and get back its last-saved state, re-retrieve it with `*{LOCATOR}` instead of using `IG`.

7 View PNR History

Format: `*H` — shows a full chronological, timestamped log of every change made to the PNR (sell, name, price, phone, SSR/OSI, seat, form of payment, ticketing, cancellations, saves), not just its current state. The log travels with the PNR across save/retrieve cycles.

```
> *H
PNR ACTIVITY HISTORY  RLOC: CUA9SU

30JUL/1733  9TAA  SEGMENT SOLD - AA2265 Y 15AUG DFWORD HK1  539A 720A
30JUL/1733  9TAA  NAME ADDED - SMITH/JOHN MR
30JUL/1733  9TAA  PRICED - WP  YOW  BASE USD140.00  TAX USD22.08  TTL USD162.08
30JUL/1733  9TAA  PHONE ADDED - 9214555-1234-A
30JUL/1733  9TAA  RECEIVED FROM ADDED - JSMITH
30JUL/1733  9TAA  TICKETING ARRANGEMENT ADDED - 7TAW/
30JUL/1733  9TAA  FORM OF PAYMENT ADDED - CASH
30JUL/1733  9TAA  PNR SAVED (ER) - RLOC CUA9SU
30JUL/1733  9TAA  TICKETED - 1 TICKET(S) ISSUED, VALIDATING CARRIER AA
```

Part 3 — Full Command Reference

Sign On / Off

Entry	Description
SI	Sign in with a default demo sine/PCC
SI{SINE}/{PCC}	Sign in with a specific agent sine and pseudo city code
SO	Sign out

Availability

Entry	Description
A{DD}{MON}{ORIG}{DEST}	Air availability display
1{DD}{MON}{ORIG}{DEST}	Air availability display (alternate real Sabre entry)

Sell

Entry	Description
0{LINE}{CLASS}{SEATS}	Sell from the most recent availability display
0{AL}{FLT}{CLASS}{DD}{MON}{ORIG}{DEST}{STATUS}{SEATS}	Direct/long sell — no prior availability display needed

PNR Build

Entry	Description
–{SURNAME}/{GIVEN} {TITLE}	Add one passenger name
–{N}{SURNAME}/{G1} {T1}/{G2}{T2}...	Add multiple passengers sharing a surname
–... (INF{SURNAME}/{GIVEN}/{DOB})	Add a lap infant tied to the passenger just added
3{SSRCODE} [–{PAX#}] [/ {TEXT}]	Add a special service request
30SI{AL}{TEXT}	Add other service info for a carrier
3FQTV{AL}{NUMBER}	Add a frequent flyer number
4{N}	Display the seat map for itinerary segment N
4{N}–{SEAT}	Assign a seat on segment N
DC{CODE}	Decode a 3-letter airport/city code
DAN{TEXT}	Search airports/cities by name
WP	Price the itinerary as booked (required before ticketing)
WPNC	Price the lowest fare regardless of availability (informational)
9{NUMBER}–{LOC}	Add a contact phone number
9/{CITY}{NUMBER}–{LOC}	Add an out-of-area contact phone number
6{TEXT}	Add "received from"
7TAW/	Ticketing: at will, no deadline
7TAW{DD}{MON}/{HHMM}	Ticketing: at will, queued to date/time
7TAX{DD}{MON}/{HHMM}	Ticketing: time limit by date/time
FPCASH / FPCHECK	Form of payment — cash / check
FPCC{TYPE}{CARDNUM}/{MMYY}	Form of payment — credit card (TYPE: VI CA AX DC DS JC)
TKTT	Issue ticket(s) — requires a saved PNR with fare quote, ticketing arrangement, and form of payment

PNR Management

Entry	Description
*R or *	Redisplay the PNR currently in the work area
*H	Display the PNR's chronological activity history
*{LOCATOR}	Retrieve a saved PNR by its 6-character record locator
X{N}	Cancel a single numbered element
X{N}–{M}	Cancel a contiguous range of elements
X{N},{M},{K}	Cancel a specific list of elements
XI	Cancel the entire itinerary (all sold segments)
IG	Discard everything in the work area (does not restore a prior save)
ER	End transaction, save, and keep the PNR loaded/redisplayed
ET	End transaction, save, and clear the work area
HELP	Show the in-terminal command reference

Part 4 — Worked Examples

Start to finish: book a one-passenger itinerary, price it, pay for it, save it, and ticket it.

Booking and Ticketing

```
SI
A15AUGDFWORD
01Y1
-SMITH/JOHN MR
3VGML          -- optional: meal request
41-14A         -- optional: seat assignment
WP
9214555-1234-A
6JSMITH
7TAW/
FPCASH
ER             -- note the RLOC returned, e.g. CUA9SU
TKTT          -- issue the ticket
```

Retrieving and Modifying Later

```
*CUA9SU        -- retrieve the saved, ticketed PNR
-JONES/MARY MRS -- add a second passenger
A16AUGORDLAX   -- pull a connecting flight
02Y1           -- sell it (fare quote AND ticket auto-invalidate)
WP             -- re-price the now two-segment (OJ) itinerary
TKTT          -- reissue the ticket
ER            -- save back to the same RLOC: CUA9SU
```

Cancelling a Segment and Re-pricing

```
*CUA9SU
X4          -- cancel just the SEG element numbered 4 on the current
display
WP          -- required again before ER/ET will succeed
TKTT
ER
```

Sabre GDS Terminal Simulator — training/educational tool. All flight, fare, and airport data in this simulator is either synthetic (deterministically generated) or drawn from the public OpenFlights airport dataset; nothing in this application makes network calls or represents real-time airline inventory.