



Applied Deep Learning

Dr. Philippe Blaettchen
Bayes Business School (formerly Cass)

www.bayes.city.ac.uk

Learning objectives of today

Goals:

- Anomaly detection: understand what anomalies are, why we would want to detect them, and how we can do so
- CNNs: Understand how convolution works and how it can be implemented in TensorFlow

How will we do this?


- We will start by discussing anomaly detection and the different techniques used to perform it in different settings
- We will use this to lead over into the student presentations
- We then turn to computer vision, and the fundamental architectural innovation that makes it work: convolutional layers






Anomaly detection

What color are swans?



Source: Alla

What color are swans?




Source: Alla



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

Outliers and anomalies



Outliers:

- Data points that are distinctly different from other data points
- Can be caused by unavoidable random errors or by systematic errors relating to how data was sampled

Anomalies:

- Outliers or other values that are not expected to exist
- Can be context- or pattern-based:
 - Context: exceptionally high credit card spending on Black Friday versus near-simultaneous spending in New York and London
 - Pattern: high credit card spending every Saturday versus high spending on a day where spending is low in other weeks



What are possible anomalies and how would we detect them?

Consider the following situations:

- A machine produces thousands of screws per minute, every few days the type of screw is changed
- A software developer for a bank downloads a large number of entries from a customer database
- An intermediary supplies fair trade coffee beans

What is the expected outcome in each case?

What is an anomalous outcome?

What data do we observe?



Detecting anomalies

Supervised anomaly detection:

- A fancy way of saying classification – learn to differentiate between two classes
- We can use the standard toolbox
- Upside: When feasible, usually the most failsafe method
- Downside: only works if we know how normal and anormal data looks like

Semi-supervised anomaly detection:


- Learn an efficient representation of normal data and then try to apply this to new data coming in
- We can use autoencoders and other tools
- Upside: we don't need to know how anormal data looks like
- Downside: still need to be sure that our normal data is actually normal

Unsupervised anomaly detection:


- Learn “how far” datapoints are from each other and recognize the ones that are far away from anything else
- We can use isolation forests and other tools
- Upside: we can work with any kind of data
- Downside: we don't have many guarantees



Anomaly detection with an autoencoder




Feeding in normal data




Feeding in anormal data

An “anomalous” instance



What we should be observing



Your turn – what did you find?



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON



Computer vision and convolutional layers

Importance of computer vision in business processes



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

Typical computer vision problems


Image classification



Semantic segmentation



Object detection



Neural style transfer



Source: Lin, reiinakano.com




BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

Challenges to deep learning using large images



150x100x3





Say we have 100 neurons at the first layer.

Then we need $100 \cdot (45000 + 1) = 4.5$ mio parameters, just for the first layer!



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

From fully connected to locally connected



Source: Dieleman

An image filter

| | | | | | |
|----|----|----|---|---|---|
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |

*

| | | |
|---|---|----|
| 1 | 0 | -1 |
| 1 | 0 | -1 |
| 1 | 0 | -1 |

=

| | | | |
|---|--|--|--|
| 0 | | | |
| | | | |
| | | | |



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

An image filter

| | | | | | |
|----|----|----|---|---|---|
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |

*

| | | |
|---|---|----|
| 1 | 0 | -1 |
| 1 | 0 | -1 |
| 1 | 0 | -1 |

=

| | | | |
|---|----|--|--|
| 0 | 30 | | |
| | | | |
| | | | |



An image filter

| | | | | | |
|----|----|----|---|---|---|
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |

*

| | | |
|---|---|----|
| 1 | 0 | -1 |
| 1 | 0 | -1 |
| 1 | 0 | -1 |

=

| | | | |
|---|----|----|--|
| 0 | 30 | 30 | |
| | | | |
| | | | |



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

An image filter

| | | | | | |
|----|----|----|---|---|---|
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |

*

| | | |
|---|---|----|
| 1 | 0 | -1 |
| 1 | 0 | -1 |
| 1 | 0 | -1 |

=

| | | | |
|---|----|----|---|
| 0 | 30 | 30 | 0 |
| | | | |
| | | | |



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

An image filter

| | | | | | |
|----|----|----|---|---|---|
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |
| 10 | 10 | 10 | 0 | 0 | 0 |

*


| | | |
|---|---|----|
| 1 | 0 | -1 |
| 1 | 0 | -1 |
| 1 | 0 | -1 |

=

| | | | |
|---|----|----|---|
| 0 | 30 | 30 | 0 |
| 0 | 30 | 30 | 0 |
| 0 | 30 | 30 | 0 |



Convolutional layers: learning the filter




*

| | | |
|-----------|-----------|-----------|
| $w_{1,1}$ | $w_{1,2}$ | $w_{1,3}$ |
| $w_{2,1}$ | $w_{2,2}$ | $w_{2,3}$ |
| $w_{3,1}$ | $w_{3,2}$ | $w_{3,3}$ |

+

b

=





Activation function

Source: Dieleman





BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

Less parameters required




Source: Goodfellow

Parameters are shared




Source: Goodfellow

Translation invariance



Source: Bhaskhar

Hierarchical setup



Source: Goodfellow

With convolution, the center matters more

| | | | |
|---|---|---|---|
| 1 | 3 | 1 | 2 |
| 6 | 1 | 5 | 4 |
| 5 | 4 | 2 | 5 |
| 3 | 3 | 1 | 2 |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | |
|----|----|----|
| 20 | 12 | 19 |
| 22 | 21 | 22 |
| 22 | 15 | 16 |



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

The convolution operator with padding

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | | | |
|---|--|--|--|--|
| 1 | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

The convolution operator with padding

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | | | |
|---|---|--|--|--|
| 1 | 4 | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

The convolution operator with padding

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | | | |
|---|---|---|--|--|
| 1 | 4 | 7 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |



The convolution operator with padding

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | | | |
|----|----|----|----|----|
| 1 | 4 | 7 | 4 | 4 |
| 8 | 20 | 12 | 19 | 10 |
| 17 | 22 | 21 | 22 | 14 |
| 13 | 22 | 15 | 16 | 9 |
| 6 | 9 | 5 | 5 | 2 |



The convolution operator with padding and stride

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | |
|---|--|--|
| 1 | | |
| | | |
| | | |

The convolution operator with padding and stride

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | |
|---|---|--|
| 1 | 7 | |
| | | |
| | | |

The convolution operator with padding and stride

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

=

| | | |
|---|---|---|
| 1 | 7 | 4 |
| | | |
| | | |



The convolution operator with padding and stride

| | | | | | |
|--|---|---|---|---|--|
| | | | | | |
| | 1 | 3 | 1 | 2 | |
| | 6 | 1 | 5 | 4 | |
| | 5 | 4 | 2 | 5 | |
| | 3 | 3 | 1 | 2 | |
| | | | | | |

4x4
 $(n_H^{[0]}, n_W^{[0]})$

*

| | |
|---|---|
| 1 | 2 |
| 2 | 1 |

2x2 with padding 1x1 and stride 2x2
 (f_H, f_W) with (p_H, p_W) and (s_H, s_W)

=

| | | |
|----|----|----|
| 1 | 7 | 4 |
| 17 | 21 | 14 |
| 6 | 5 | 2 |

3x3
 $(n_H^{[1]}, n_W^{[1]})$

$$n_H^{[1]} = \left\lfloor \frac{n_H^{[0]} + 2p_H - f_H}{s_H} + 1 \right\rfloor \quad n_W^{[1]} = \left\lfloor \frac{n_W^{[0]} + 2p_W - f_W}{s_W} + 1 \right\rfloor$$




BAYES
 BUSINESS SCHOOL
 CITY, UNIVERSITY OF LONDON




The same, just in 3D


Convolution on a 3D array




*



=




Convolution on a 3D array



4x4x3

*




2x2x3

=

| | | |
|----|--|--|
| 20 | | |
| | | |
| | | |


3x3

Multiple 3D convolutions




4x4x3
 $(n_H^{[0]}, n_W^{[0]}, n_C^{[0]})$


*





=



*



=



3x3x2
 $(n_H^{[1]}, n_W^{[1]}, n_C^{[1]})$

$n_C^{[1]}$ = number of filters




Additional architectural considerations

Objective of pooling layers

- Subsample (i.e., summarize) the input
 - Reduced computational load
 - Reduced memory usage
 - Fewer parameters (and, thus, less overfitting)



Max pooling



Source: Géron



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

Max pooling in practice

| | | | |
|---|---|---|---|
| 1 | 3 | 1 | 2 |
| 6 | 1 | 5 | 4 |
| 5 | 4 | 2 | 5 |
| 3 | 3 | 1 | 2 |

*

| | |
|--|--|
| | |
| | |

=

| | | |
|---|--|--|
| 6 | | |
| | | |
| | | |

Source: Géron

Max pooling in practice

| | | | |
|---|---|---|---|
| 1 | 3 | 1 | 2 |
| 6 | 1 | 5 | 4 |
| 5 | 4 | 2 | 5 |
| 3 | 3 | 1 | 2 |

*

| | |
|--|--|
| | |
| | |

=

| | | |
|---|---|--|
| 6 | 5 | |
| | | |
| | | |

Source: Géron

Max pooling in practice

| | | | |
|---|---|---|---|
| 1 | 3 | 1 | 2 |
| 6 | 1 | 5 | 4 |
| 5 | 4 | 2 | 5 |
| 3 | 3 | 1 | 2 |

*

| | |
|--|--|
| | |
| | |

=

| | | |
|---|---|---|
| 6 | 5 | 5 |
| | | |
| | | |

Source: Géron

Max pooling in practice

| | | | |
|---|---|---|---|
| 1 | 3 | 1 | 2 |
| 6 | 1 | 5 | 4 |
| 5 | 4 | 2 | 5 |
| 3 | 3 | 1 | 2 |

*


| | |
|--|--|
| | |
| | |

=

| | | |
|---|---|---|
| 6 | 5 | 5 |
| 6 | 5 | 5 |
| 5 | 4 | 5 |

Source: Géron

Typical architecture



Source: Géron



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON

ConvNets in practice






Starting with object detection – non-sequential models

Typical computer vision problems


Image classification



Semantic segmentation



Object detection





Neural style transfer




Source: Lin, reiinakano.com

Before detection: classification + localization



Source: Géron

A look at creating non-sequential models



BAYES
BUSINESS SCHOOL
CITY, UNIVERSITY OF LONDON



See you next week!

Sources

- Alla & Kalyan Adari, 2019, Beginning Anomaly Detection Using Python-Based Deep Learning, Apress
- Bhaskhar, 2021, Introduction to Deep Learning: <https://cs229.stanford.edu/syllabus.html>
- DeepLearning.AI, n.d.: deeplearning.ai
- Dieleman, 2020, Lecture 3: Convolutional Neural Networks: https://storage.googleapis.com/deepmind-media/UCLxDeepMind_2020/L3%20-%20UCLxDeepMind%20DL2020.pdf
- Géron, 2019, Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow
- Goodfellow, Bengio, Courville, 2016, The Deep Learning Book: <http://www.deeplearningbook.org>
- Liang, 2016, Introduction to Deep Learning: <https://www.cs.princeton.edu/courses/archive/spring16/cos495/>
- Lin et al., 2014, Microsoft COCO: Common Objects in Context: <https://arxiv.org/pdf/1405.0312.pdf>

