

TT8XTA	749-7,693	1-1/2	23.37 lb	8.98 in	12.83 in	3.54 in	5.28 in	1.84 in
TT10XTA	1,113-11,130	1-1/2	28.44 lb	9.33 in	13.23 in	3.94 in	5.67 in	2 in
TT15XTA	1,431-14,315	2-1/2	44.09 lb	10.75 in	15.39 in	4.33 in	6.46 in	2.24 in
TT20XTA	1,847-19,506	2-1/2	55.12 lb	11.3 in	17.05 in	4.72 in	7.36 in	2.35 in
TT25XTA	2,441-25,539	2-1/2	74.52 lb	12.72 in	18.27 in	5.43 in	8.11 in	2.79 in
TT35XTA	3,497-34,971	2-1/2	94.8 lb	13.82 in	19.45 in	6.02 in	8.54 in	3.02 in
TT50XTA	5,108-51,074	2-1/2	114.64 lb	14.8 in	20.79 in	6.38 in	8.9 in	3.1 in

Source: ToughTorq canonical manufacturer data. Max working pressure 10,000 psi / 700 bar where published.

TT14LCT	1,272-11,982	14XT	14LC-115	37.26 lb	14.17 in	8.86 in	8.03 in	2.52 in	3.9 in
TT18LCT	1,657-16,889	18XT	18LC-135	50.49 lb	15.28 in	10.39 in	9.09 in	2.8 in	4.29 in
TT30LCT	2,779-29,196	30XT	30LC-155	83.78 lb	16.93 in	11.93 in	10.71 in	3.35 in	5.16 in

Source: ToughTorq canonical manufacturer data. Max working pressure 10,000 psi / 700 bar where published.