

ToughTorq 3/4-Inch Drive Sockets

Socket dimensions and published compatible hydraulic wrench models

Model	Wrench	Bolt	AF mm	AF in	L1	L2	D1	D2
TX-75-24	TT1XTA	M16	24 mm	0.94 in	2.13 in	1.26 in	1.57 in	1.57 in
TX-75-27	TT1XTA	M18	27 mm	1.06 in	2.13 in	1.26 in	1.65 in	1.65 in
TX-75-30	TT1XTA	M20	30 mm	1.18 in	2.13 in	1.3 in	1.81 in	1.73 in
TX-75-34	TT1XTA	M22	34 mm	1.34 in	2.13 in	1.26 in	1.89 in	1.73 in
TX-75-36	TT1XTA	M24	36 mm	1.42 in	2.24 in	1.26 in	2.09 in	1.73 in
TX-75-41	TT1XTA	M27	41 mm	1.61 in	2.28 in	1.3 in	2.36 in	1.73 in
TX-75-46	TT1XTA	M30	46 mm	1.81 in	2.48 in	1.5 in	2.6 in	1.73 in
TX-75-50	TT1XTA	M33	50 mm	1.97 in	2.56 in	1.57 in	2.8 in	1.73 in
TX-75-55	TT1XTA	M36	55 mm	2.17 in	2.76 in	1.77 in	3.03 in	2.13 in

ToughTorq 1-Inch Drive Sockets

Socket dimensions and published compatible hydraulic wrench models

Model	Wrench	Bolt	AF mm	AF in	L1	L2	D1	D2
TX-100-30	TT3XTA	M20	30 mm	1.18 in	2.32 in	1.26 in	2.13 in	2.13 in
TX-100-34	TT3XTA	M22	34 mm	1.34 in	2.32 in	1.26 in	2.28 in	2.28 in
TX-100-36	TT3XTA	M24	36 mm	1.42 in	2.44 in	1.26 in	2.32 in	2.32 in
TX-100-41	TT3XTA	M27	41 mm	1.61 in	2.56 in	1.5 in	2.64 in	2.13 in
TX-100-46	TT3XTA	M30	46 mm	1.81 in	2.56 in	1.5 in	2.91 in	2.13 in
TX-100-50	TT3XTA	M33	50 mm	1.97 in	2.76 in	1.69 in	3.11 in	2.36 in
TX-100-55	TT3XTA	M36	55 mm	2.17 in	3.15 in	2.05 in	3.31 in	2.36 in
TX-100-60	TT3XTA	M39	60 mm	2.36 in	3.35 in	2.24 in	3.5 in	2.36 in
TX-100-65	TT3XTA	M42	65 mm	2.56 in	3.35 in	2.28 in	3.86 in	2.76 in
TX-100-70	TT3XTA	M45	70 mm	2.76 in	3.54 in	2.44 in	4.09 in	2.76 in
TX-100-75	TT3XTA	M48	75 mm	2.95 in	3.74 in	2.56 in	4.25 in	2.76 in

ToughTorq 1-1/2-Inch Drive Sockets - 1

Socket dimensions and published compatible hydraulic wrench models

Model	Wrench	Bolt	AF mm	AF in	L1	L2	D1	D2
TX-150-36	TT5XTA / TT8XTA / TT1~	M24	36 mm	1.42 in	3.35 in	1.73 in	2.91 in	2.91 in
TX-150-41	TT5XTA / TT8XTA / TT1~	M27	41 mm	1.61 in	3.35 in	1.73 in	2.91 in	2.91 in
TX-150-46	TT5XTA / TT8XTA / TT1~	M30	46 mm	1.81 in	3.35 in	1.73 in	2.91 in	2.91 in
TX-150-50	TT5XTA / TT8XTA / TT1~	M33	50 mm	1.97 in	3.54 in	1.77 in	3.11 in	3.11 in
TX-150-55	TT5XTA / TT8XTA / TT1~	M36	55 mm	2.17 in	3.54 in	1.77 in	3.31 in	3.31 in
TX-150-60	TT5XTA / TT8XTA / TT1~	M39	60 mm	2.36 in	3.94 in	1.77 in	3.7 in	3.7 in
TX-150-65	TT5XTA / TT8XTA / TT1~	M42	65 mm	2.56 in	3.94 in	1.77 in	3.86 in	3.15 in
TX-150-70	TT5XTA / TT8XTA / TT1~	M45	70 mm	2.76 in	4.13 in	1.97 in	4.09 in	3.15 in
TX-150-75	TT5XTA / TT8XTA / TT1~	M48	75 mm	2.95 in	4.33 in	1.97 in	4.65 in	3.35 in
TX-150-80	TT5XTA / TT8XTA / TT1~	M52	80 mm	3.15 in	4.53 in	2.17 in	4.65 in	3.54 in
TX-150-85	TT5XTA / TT8XTA / TT1~	M56	85 mm	3.35 in	4.92 in	2.36 in	5.04 in	3.54 in
TX-150-90	TT5XTA / TT8XTA / TT1~	M60	90 mm	3.54 in	4.92 in	2.36 in	5.47 in	3.54 in

ToughTorq canonical manufacturer data. Final reaction geometry is application-specific and must be verified at the joint.

ToughTorq 1-1/2-Inch Drive Sockets - 2

Socket dimensions and published compatible hydraulic wrench models

Model	Wrench	Bolt	AF mm	AF in	L1	L2	D1	D2
TX-150-95	TT5XTA / TT8XTA / TT1~	M64	95 mm	3.74 in	5.12 in	2.56 in	5.47 in	3.54 in
TX-150-100	TT5XTA / TT8XTA / TT1~	M68	100 mm	3.94 in	5.31 in	2.76 in	5.67 in	3.54 in
TX-150-105	TT5XTA / TT8XTA / TT1~	M72	105 mm	4.13 in	5.31 in	2.76 in	5.87 in	3.54 in
TX-150-110	TT5XTA / TT8XTA / TT1~	M76	110 mm	4.33 in	5.31 in	2.76 in	6.22 in	3.54 in
TX-150-115	TT5XTA / TT8XTA / TT1~	M80	115 mm	4.53 in	5.31 in	2.76 in	6.26 in	3.54 in
TX-150-120	TT5XTA / TT8XTA / TT1~	M85	120 mm	4.72 in	5.31 in	2.76 in	6.61 in	3.74 in
TX-150-130	TT5XTA / TT8XTA / TT1~	M90	130 mm	5.12 in	6.1 in	3.66 in	7.44 in	3.54 in

ToughTorq Reaction Arm Application Guidance

Reaction equipment is selected around the actual bolting geometry

Confirm the torque tool model and required output torque.

Identify a structurally suitable reaction point before operating the tool.

Keep the reaction interface stable and aligned with the tool's reaction path.

Confirm clearance around the fastener, wrench body, socket, and reaction arm.

Standard square-drive hydraulic reaction arms can be positioned through 360 degrees.

Custom reaction equipment may be required where standard geometry is unsuitable.

Do not select a generic reaction arm category without checking the actual application.

Match square drive, socket size, fastener size, and wrench compatibility as one system.