

ToughTorq Portable Valve Actuation - Power Platforms

Portable actuator platforms for battery, pneumatic, gas, and water-network operation

Platform	Power	Max Torque	Operating Concept	Use
MC89	Battery	740 ft-lb	Portable, smoke-free battery op~	General PVA platform
JA73	Battery	740 ft-lb	High-output portable battery op~	General PVA platform
HL83	Pneumatic	740 ft-lb	Compressed-air drive	General PVA platform
PY68	Gas	740 ft-lb	Independent fuel-powered operat~	General PVA platform
H2O KIT	Battery-based water~	630 ft-lb	Underground water-distribution ~	Dedicated water-network~

ToughTorq PVA - Actuator Heads

Head compatibility is platform- and torque-dependent

Head	Description	Selection Note

Straight Head	Straight actuator geometry for direct valve access.	Published configuration
Right-Angle Head	Right-angle configuration for restricted inline acc~	Variant and torque limits app~
Standard-Duty Banjo Head	Hollow/banjo head for compatible rising-stem valve ~	Variant and torque limits app~
Heavy-Duty Banjo Head	Higher-capacity hollow/banjo head for compatible ri~	Variant and torque limits app~

ToughTorq PVA - Valve Adaptors

Valve interfaces selected to match the handwheel or drive geometry

Adaptor	Function
Fixed Finger Adaptor	Fixed interface for compatible valve handwheel configurations.
Self-Centering Spoke Adaptor	Self-centering interface for handwheel spoke configurations.
Square Drive Adaptor	Socket-driven interface for square-drive valve operation.
Variable Valve Adaptor	Adjustable interface for varying handwheel and valve configurations.
Flat-Spoke Adaptor	Adaptor for compatible flat-spoke valve handwheels.
Tapered-Spoke Adaptor	Adaptor for compatible tapered-spoke valve handwheels.

ToughTorq PVA - Reaction Management

Reaction equipment selected around valve position, access, and required torque

Component	Function

Reaction Arm	Reaction support for controlled portable valve operation.
Bipod	Supported reaction configuration for demanding valve positions.
Reaction Finger	Compact reaction interface for specific valve and access configurations.
Articulated Reaction Arm	Articulated reaction support for applications requiring flexible positi-
Custom Mounting Flange	Made-to-order mounting interface for application-specific valve configu-

ToughTorq PVA - Options & Accessories

Power-platform and application-specific accessory selection

Accessory	Platform / Use	Function
Torque Limiter	Application dependent	Torque-control option used where the actuator/hea-
Extension	Application dependent	Extension component for applications requiring ad-
Air Hose	HL83	Air-supply hose for pneumatic PVA systems.
Counter	Application dependent	Revolution/counting option for supported actuator-
Storage Case	Application dependent	Protective transport and storage case for PVA com-
Battery Pack	MC89 / JA73 / H20 kit confi-	Battery power accessory for compatible battery-op-
Universal Joint	Application dependent	Angular-flexibility accessory for supported valve-
Safety Unit	Application dependent	Safety accessory for supported portable valve act-

ToughTorq PVA - Published Compatibility Matrix

Compatible = published pairing; Conditional = variant/head/torque limits must be checked

Platform	Component	Status	Note
MC89	Straight Head	compatible	Straight-head configurations are published for the MC~
JA73	Straight Head	compatible	Straight-head configurations are published for the JA~
HL83	Straight Head	compatible	Straight-head configurations are published for the HL~
PY68	Straight Head	compatible	Straight-head configurations are published for the PY~
MC89	Right-Angle Head	conditional	Supported with actuator/torque limits; use the applic~
JA73	Right-Angle Head	conditional	Supported with actuator/torque limits; high-torque va~
HL83	Right-Angle Head	conditional	Supported on published HL83 variants; highest-output ~
PY68	Right-Angle Head	conditional	Supported with actuator/torque limits; highest-output~
MC89	Standard-Duty Banjo Head	conditional	Published hollow-head configuration with a maximum he~
JA73	Standard-Duty Banjo Head	conditional	Published on selected variants; maximum head torque l~
HL83	Standard-Duty Banjo Head	conditional	Published only for selected HL83 variants.
PY68	Standard-Duty Banjo Head	conditional	Published only for selected PY68 variants.
MC89	Heavy-Duty Banjo Head	conditional	Published hollow-head configuration; model and torque~
JA73	Heavy-Duty Banjo Head	conditional	Published on selected variants; model and torque limi~
HL83	Heavy-Duty Banjo Head	conditional	Published on selected variants; model and torque limi~
PY68	Heavy-Duty Banjo Head	conditional	Published on selected variants; model and torque limi~
HL83	Air Hose	compatible	Pneumatic supply accessory.
MC89	Battery Pack	compatible	Battery-platform accessory.
JA73	Battery Pack	compatible	Battery-platform accessory.
H20 KIT	Battery Pack	compatible	H20 is a battery-based water-network kit configuratio~

ToughTorq PVA - System Selection

Build the complete portable valve actuation package around the application

Selection Sequence

1. Select the power platform for the environment and available utilities.
2. Select the actuator head for the valve geometry and required torque.
3. Match the valve adaptor to the handwheel, stem, socket, or drive interface.
4. Select the reaction method for the actual valve position and surrounding structure.
5. Add extensions, batteries, air supply, counters, storage, and safety options as required.

Important Limits

Right-angle and banjo-head configurations are conditional on actuator variant and torque limits.

H2O is a configured water-network package rather than a general-purpose actuator/head platform.

Variant-level speed, weight, battery, air-consumption, fuel, and dimension data are not published until confirmed.

Select the complete actuator, head, adaptor, reaction, and option package for the specific valve application.