

Bearing Heater Series

Plate and induction heating systems for controlled bearing installation.

Plate Bearing Heaters

Conductive plate heaters for controlled preheating of small bearings and suitable workpieces.

Model	Voltage	Power	Temp Range	Accuracy	Plate Size	Overall Size
KHG-12	220 V	1.32 kW	60-320 deg C	+/-3 deg C	390 x 190 mm	400 x 220 x 145 mm
KHG-12P	110/220 V	1.32 kW	30-350 deg C	+/-3 deg C	390 x 190 mm	400 x 220 x 145 mm

Plate Heater Notes

- Integrated heating surface allows multiple workpieces to be heated within the available plate area.
- Select the model around available voltage, required temperature range, and workpiece size.
- Published temperature limits and electrical ratings must be observed during operation.

Series Selection

Match heater type and model to workpiece ID, OD, width, weight, temperature target, and electrical supply.

KHG Series Induction Heaters

Electromagnetic induction heaters with temperature and timing control.

Induction Heater Technical Data

Constant-temperature and timed heating with heat preservation, demagnetization, and overheat protection.

Model	Voltage	Power	Max Bearing	Max OD	Min ID Hang	Min ID Level	Max Temp	Weight
KHG-22	220 V	2.2 kW	15 kg	220 mm	15 mm	60 mm	245 deg C	35.3 lb
KHG-40	220 V	4 kW	50 kg	480 mm	20 mm	120 mm	245 deg C	57.3 lb
KHG-100	2ph 380 V	10 kW	150 kg	720 mm	45 mm	140 mm	245 deg C	88.2 lb
KHG-120	2ph 380 V	12 kW	350 kg	860 mm	45 mm	110 mm	245 deg C	396.8 lb
KHG-150	2ph 380 V	15 kW	450 kg	1020 mm	60 mm	180 mm	245 deg C	606.3 lb

Selection Guidance

- Workpiece limits vary by hanging or level orientation.
- Confirm workpiece inner diameter, outer diameter, width, weight, and target temperature.
- Confirm voltage, current, frequency, and phase requirements for the selected model before operation.

Source: ToughTorq / Kashon manufacturer catalog. Specifications shown are manufacturer-published values.