

ToughTorq Mechanical & Integral Hydraulic Nut Splitters

Nut removal systems selected by nut A/F size, bolt diameter, and available access

Model	Series	Capacity	Nut A/F	Bolt	Operation	Weight
NT-1	Mechanical	-	9â 12 mm	-	Mechanical	3.5 lb
NT-2	Mechanical	-	12â 16 mm	-	Mechanical	3.5 lb
NT-3	Mechanical	-	16â 22 mm	-	Mechanical	3.5 lb
NT-4	Mechanical	-	19â 24 mm	-	Mechanical	3.5 lb
NI2432	Integral Hyd.	15 ton	24â 32 mm	M16â 22	Integral hydraulic	-
NI3241	Integral Hyd.	20 ton	32â 41 mm	M22â 27	Integral hydraulic	-
NI4150	Integral Hyd.	35 ton	41â 50 mm	M27â 33	Integral hydraulic	-

ToughTorq Separated & Heavy-Duty Hydraulic Nut Splitters

700 bar / 10,153 psi hydraulic systems where published

Model	Series	Capacity	Nut A/F	Bolt	Pressure	Weight
NC-1319	Separated	5 ton	10â 19 mm	M6â 12	10,153 psi	2.6 lb
NC-1924	Separated	10 ton	19â 24 mm	M12â 16	10,153 psi	5.7 lb
NC-2432	Separated	15 ton	24â 32 mm	M16â 22	10,153 psi	8.8 lb
NC-3241	Separated	20 ton	32â 41 mm	M22â 27	10,153 psi	11.9 lb
NC-4150	Separated	35 ton	41â 50 mm	M27â 33	10,153 psi	22 lb
NC-5060	Separated	50 ton	50â 60 mm	M33â 39	10,153 psi	37.5 lb
NC-6075	Separated	90 ton	60â 75 mm	M39â 48	10,153 psi	75.2 lb
NS-7080	Heavy Duty	103 ton	70â 80 mm	M45â 52	10,153 psi	81.6 lb
NS-7085	Heavy Duty	103 ton	70â 85 mm	M45â 56	10,153 psi	81.6 lb
NS-7095	Heavy Duty	103 ton	70â 95 mm	M45â 64	10,153 psi	86 lb
NS-70105	Heavy Duty	103 ton	70â 105 mm	M45â 72	10,153 psi	88.2 lb
NS-110115	Heavy Duty	193 ton	110â 115 mm	M76â 80	10,153 psi	152.1 lb
NS-110130	Heavy Duty	193 ton	110â 130 mm	M76â 90	10,153 psi	158.7 lb

ToughTorq Adjustable Hydraulic Gear Pullers

Integrated hydraulic pullers with 2/3-jaw configurations where published

Model	Capacity	Spread	Stroke	Jaws	Pressure	Weight
UKA-3	3 ton	5.91 in	2.36 in	2/3	10,153 psi	7.7 lb
UKA-5	5 ton	7.87 in	2.36 in	2/3	10,153 psi	15.4 lb
UKA-10	10 ton	9.84 in	3.15 in	2/3	10,153 psi	26.5 lb
UKA-15	15 ton	13.78 in	3.15 in	2/3	10,153 psi	39.7 lb
UKA-20	20 ton	15.75 in	3.15 in	2/3	10,153 psi	52.9 lb
UKA-30	30 ton	17.72 in	3.54 in	2/3	10,153 psi	61.7 lb
UKA-40	40 ton	19.69 in	3.94 in	2/3	10,153 psi	77.2 lb
UKA-50	50 ton	23.62 in	3.94 in	2/3	10,153 psi	99.2 lb
UKA-60	60 ton	27.56 in	4.72 in	3	10,153 psi	220.5 lb
UKA-80	80 ton	31.5 in	4.72 in	3	10,153 psi	264.6 lb

ToughTorq Hydraulic Coupler Pullers

Controlled coupling removal with matched connector specification

Model	Capacity	Pressure	Oil Cap.	Stroke	Cylinder L	Modules	Weight
TTLTC-20T	20 ton	10,153 psi	450 cm3	2.95 in	11.97 in	M27, M30, M32, M36, M42, M~	22 lb
TTLTC-50T	50 ton	10,153 psi	530 cm3	3.54 in	14.69 in	M42, M48, M56, M60, M64	39.7 lb

ToughTorq Grip Puller Sets

Matched hydraulic puller systems with pump, cylinder, hose, gauge, and pulling components

Model	Capacity	Cylinder	Hand Pump	Pressure	Set Weight
BHP-152	8 ton	RCH-121	P-392	10,153 psi	48.5 lb
BHP-251G	20 ton	RCH-202	P-392	10,153 psi	123.5 lb
BHP-351G	30 ton	RCH-302	P-392	10,153 psi	200.6 lb
BHP-551G	50 ton	RCH-603	P-80	10,153 psi	352.7 lb

ToughTorq Cross-Bearing Puller Sets

Matched hydraulic puller systems with pump, cylinder, hose, gauge, and pulling components

Model	Capacity	Cylinder	Hand Pump	Pressure	Set Weight
BHP-162	8 ton	RCH-121	P-392	10,153 psi	57.3 lb
BHP-261G	20 ton	RCH-202	P-392	10,153 psi	136.7 lb
BHP-361G	30 ton	RCH-302	P-392	10,153 psi	266.8 lb
BHP-561G	50 ton	RCH-603	P-80	10,153 psi	407.9 lb

ToughTorq Master Puller Sets

Matched hydraulic puller systems with pump, cylinder, hose, gauge, and pulling components

Model	Capacity	Cylinder	Hand Pump	Pressure	Set Weight
BHP-1752	8 ton	RCH-121	P-392	10,153 psi	81.6 lb
BHP-2751G	20 ton	RCH-202	P-392	10,153 psi	198.4 lb
BHP-3751G	30 ton	RCH-302	P-392	10,153 psi	379.2 lb
BHP-5751G	50 ton	RCH-603	P-80	10,153 psi	657 lb

ToughTorq Removal Tool Selection Guidance

Choose the removal method around the actual component and available access

Nut splitters: match nut A/F size, bolt diameter, tool access, and operating method.

Hydraulic nut splitters: match pump, hose, coupler, and tool pressure ratings.

Adjustable pullers: confirm required force, maximum spread, stroke, and jaw engagement.

For applicable adjustable pullers using two jaws, manufacturer guidance limits force to 60% of rated load.

Coupler pullers: match connector thread/specification to the coupling being removed.

Matched puller sets: keep cylinder, pump, hose, gauge, adaptor, and puller components together.

Do not exceed published capacity when a seized component does not release.

Move to a higher-capacity system rather than overloading the selected puller.