

ToughTorq General Purpose Single Acting - 1

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRC-50	5 ton	10,153 psi	0.63 in	1.61 in	2.24 in	2.28 in	-	2.2 lb
TTRC-51	5 ton	10,153 psi	0.98 in	4.33 in	5.31 in	2.28 in	-	2.2 lb
TTRC-53	5 ton	10,153 psi	2.99 in	6.5 in	9.49 in	2.28 in	-	3.3 lb
TTRC-55	5 ton	10,153 psi	5 in	8.46 in	13.46 in	2.28 in	-	4.2 lb
TTRC-57	5 ton	10,153 psi	6.97 in	10.75 in	17.72 in	2.28 in	-	5.3 lb
TTRC-59	5 ton	10,153 psi	9.13 in	12.72 in	21.85 in	2.28 in	-	6.2 lb
TTRC-101	10 ton	10,153 psi	1.02 in	3.5 in	4.53 in	2.24 in	-	4 lb
TTRC-102	10 ton	10,153 psi	2.13 in	4.76 in	6.89 in	2.24 in	-	5.1 lb
TTRC-104	10 ton	10,153 psi	4.13 in	6.73 in	10.87 in	2.24 in	-	7.3 lb
TTRC-106	10 ton	10,153 psi	6.14 in	9.72 in	15.87 in	2.24 in	-	9.7 lb
TTRC-108	10 ton	10,153 psi	7.99 in	11.73 in	19.72 in	2.24 in	-	11.9 lb

ToughTorq General Purpose Single Acting - 2

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRC-1010	10 ton	10,153 psi	10.12 in	13.74 in	23.86 in	2.24 in	-	14.1 lb
TTRC-1012	10 ton	10,153 psi	11.97 in	15.75 in	27.72 in	2.24 in	-	15 lb
TTRC-1014	10 ton	10,153 psi	14.02 in	17.72 in	31.73 in	2.24 in	-	18.1 lb
TTRC-151	15 ton	10,153 psi	0.98 in	4.88 in	5.87 in	2.72 in	-	7.3 lb
TTRC-152	15 ton	10,153 psi	2.01 in	5.87 in	7.87 in	2.72 in	-	9 lb
TTRC-154	15 ton	10,153 psi	3.98 in	7.87 in	15.79 in	2.72 in	-	11 lb
TTRC-156	15 ton	10,153 psi	5.98 in	10.67 in	16.65 in	2.72 in	-	15 lb
TTRC-158	15 ton	10,153 psi	7.99 in	12.68 in	20.67 in	2.72 in	-	18.1 lb
TTRC-1510	15 ton	10,153 psi	10 in	14.69 in	24.69 in	2.72 in	-	20.9 lb
TTRC-1512	15 ton	10,153 psi	12.01 in	16.65 in	28.66 in	2.72 in	-	24 lb
TTRC-1514	15 ton	10,153 psi	14.02 in	18.66 in	32.68 in	2.72 in	-	26 lb

ToughTorq General Purpose Single Acting - 3

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRC-251	25 ton	10,153 psi	1.02 in	5.47 in	6.5 in	3.35 in	-	13 lb
TTRC-252	25 ton	10,153 psi	1.97 in	6.5 in	8.46 in	3.35 in	-	14.1 lb
TTRC-254	25 ton	10,153 psi	4.02 in	8.46 in	12.48 in	3.35 in	-	18.1 lb
TTRC-256	25 ton	10,153 psi	6.22 in	10.75 in	16.97 in	3.35 in	-	22 lb
TTRC-258	25 ton	10,153 psi	8.27 in	12.72 in	20.98 in	3.35 in	-	26.9 lb
TTRC-2510	25 ton	10,153 psi	10.28 in	14.72 in	25 in	3.35 in	-	31.1 lb
TTRC-2512	25 ton	10,153 psi	12.24 in	16.73 in	28.98 in	3.35 in	-	35.9 lb
TTRC-2514	25 ton	10,153 psi	14.25 in	18.74 in	32.99 in	3.35 in	-	39 lb
TTRC-308	30 ton	10,153 psi	8.23 in	15.24 in	23.46 in	3.98 in	-	39.9 lb
TTRC-502	50 ton	10,153 psi	2.01 in	6.93 in	8.94 in	5 in	-	33.1 lb
TTRC-504	50 ton	10,153 psi	3.98 in	8.94 in	12.91 in	5 in	-	42.1 lb

ToughTorq General Purpose Single Acting - 4

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRC-506	50 ton	10,153 psi	6.26 in	11.1 in	17.36 in	5 in	-	50.9 lb
TTRC-5013	50 ton	10,153 psi	13.27 in	18.11 in	31.38 in	5 in	-	82.9 lb
TTRC-756	75 ton	10,153 psi	6.14 in	11.22 in	17.36 in	5.75 in	-	65 lb
TTRC-7513	75 ton	10,153 psi	13.11 in	19.37 in	32.48 in	5.75 in	-	130.1 lb
TTRC-1006	100 ton	10,153 psi	6.61 in	14.06 in	20.67 in	6.97 in	-	130.1 lb
TTRC-10010	100 ton	10,153 psi	10.24 in	17.68 in	27.91 in	6.97 in	-	160.1 lb

ToughTorq RSM Low Height

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRSM-50	5 ton	10,153 psi	0.24 in	1.26 in	1.5 in	-	-	2.2 lb
TTRSM-100	10 ton	10,153 psi	0.47 in	1.65 in	2.13 in	-	-	3.1 lb
TTRSM-200	20 ton	10,153 psi	0.43 in	2.01 in	2.44 in	-	-	6.8 lb
TTRSM-300	30 ton	10,153 psi	0.51 in	2.28 in	2.8 in	-	-	9.9 lb
TTRSM-500	45 ton	10,153 psi	0.63 in	2.6 in	3.23 in	-	-	15 lb
TTRSM-750	75 ton	10,153 psi	0.63 in	3.11 in	3.74 in	-	-	24.9 lb
TTRSM-1000	100 ton	10,153 psi	0.63 in	3.35 in	3.98 in	-	-	32 lb
TTRSM-1500	150 ton	10,153 psi	0.63 in	3.94 in	4.57 in	-	-	58 lb

ToughTorq RCS Low Height

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRCS-101	10 ton	10,153 psi	1.5 in	3.46 in	4.96 in	2.72 in	-	9 lb
TTRCS-201	20 ton	10,153 psi	1.77 in	3.86 in	5.63 in	3.62 in	-	11 lb
TTRCS-302	30 ton	10,153 psi	2.44 in	4.61 in	7.05 in	3.98 in	-	15 lb
TTRCS-502	50 ton	10,153 psi	2.36 in	4.8 in	7.17 in	4.88 in	-	24 lb
TTRCS-1002	100 ton	10,153 psi	2.24 in	5.55 in	7.8 in	6.5 in	-	50 lb

ToughTorq Single-Acting Hollow Plunger

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRCH-120	13 ton	10,153 psi	0.31 in	2.17 in	2.48 in	2.72 in	0.77 in	3.3 lb
TTRCH-121	13 ton	10,153 psi	1.65 in	4.72 in	6.38 in	2.72 in	0.77 in	6.2 lb
TTRCH-1211	13 ton	10,153 psi	1.65 in	4.72 in	6.38 in	2.72 in	0.77 in	6.2 lb
TTRCH-123	13 ton	10,153 psi	2.99 in	7.24 in	10.24 in	2.72 in	0.77 in	9.7 lb
TTRCH-202	20 ton	10,153 psi	1.93 in	6.38 in	8.31 in	3.86 in	1.06 in	17 lb
TTRCH-206	20 ton	10,153 psi	6.1 in	12.05 in	18.15 in	3.86 in	1.06 in	31.1 lb
TTRCH-302	30 ton	10,153 psi	2.52 in	7.01 in	9.53 in	4.49 in	1.31 in	24 lb
TTRCH-306	30 ton	10,153 psi	6.1 in	12.99 in	19.09 in	4.49 in	1.31 in	48.1 lb
TTRCH-603	60 ton	10,153 psi	2.99 in	9.72 in	12.72 in	6.26 in	2.12 in	61.9 lb
TTRCH-606	60 ton	10,153 psi	6.02 in	12.72 in	18.74 in	6.26 in	2.12 in	78 lb
TTRCH-1003	100 ton	10,153 psi	2.99 in	10 in	12.99 in	8.35 in	3.11 in	138.9 lb

ToughTorq Double-Acting Hollow Plunger

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTRRH-307	30 ton	10,153 psi	7.01 in	12.99 in	20 in	4.49 in	1.31 in	46.3 lb
TTRRH-3010	30 ton	10,153 psi	10.16 in	16.97 in	27.13 in	4.49 in	1.31 in	59.5 lb
TTRRH-603	60 ton	10,153 psi	3.5 in	9.72 in	13.23 in	6.26 in	2.12 in	61.7 lb
TTRRH-606	60 ton	10,153 psi	6.54 in	12.72 in	19.25 in	6.26 in	2.12 in	77.2 lb
TTRRH-6010	60 ton	10,153 psi	10.12 in	17.24 in	27.36 in	6.26 in	2.12 in	99.2 lb
TTRRH-1001	100 ton	10,153 psi	1.5 in	6.5 in	7.99 in	8.35 in	3.12 in	72.8 lb
TTRRH-1003	100 ton	10,153 psi	2.99 in	10 in	12.99 in	8.35 in	3.12 in	134.5 lb
TTRRH-1006	100 ton	10,153 psi	6.02 in	13.46 in	19.49 in	8.35 in	3.12 in	174.2 lb
TTRRH-10010	100 ton	10,153 psi	10.12 in	18.11 in	28.23 in	8.35 in	3.12 in	233.7 lb
TTRRH-1508	150 ton	10,153 psi	7.99 in	13.74 in	21.73 in	9.72 in	3.12 in	244.7 lb

ToughTorq Ultra Low Height 1500 Bar

Ultra-low-height cylinders with published 1,500 bar / 21,756 psi working pressure

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTTC-00510	5 ton	21,756 psi	0.39 in	1.18 in	1.57 in	2.36 in	-	7.9 lb
TTTC-01010	10 ton	21,756 psi	0.39 in	1.18 in	1.57 in	2.76 in	-	9 lb
TTTC-02510	25 ton	21,756 psi	0.39 in	1.18 in	1.57 in	3.54 in	-	10.1 lb
TTTC-05510	50 ton	21,756 psi	0.39 in	1.18 in	1.57 in	4.53 in	-	9.9 lb
TTTC-10010	100 ton	21,756 psi	0.39 in	1.18 in	1.57 in	5.67 in	-	11.5 lb
TTTC-12010	120 ton	21,756 psi	0.39 in	1.18 in	1.57 in	6.3 in	-	13 lb
TTTC-15010	150 ton	21,756 psi	0.39 in	1.22 in	1.61 in	6.93 in	-	18.7 lb
TTTC-20010	200 ton	21,756 psi	0.39 in	1.26 in	1.65 in	8.03 in	-	20.9 lb

ToughTorq Pancake Lock Nut

Hydraulic cylinder model selection data

Model	Capacity	Pressure	Stroke	Collapsed	Extended	OD	Special	Weight
TTCLP-602	60 ton	10,153 psi	1.97 in	4.92 in	6.89 in	5.51 in	Mechanical lock nut	33.1 lb
TTCLP-1002	100 ton	10,153 psi	1.97 in	5.39 in	7.36 in	6.89 in	Mechanical lock nut	57.3 lb
TTCLP-1602	160 ton	10,153 psi	1.77 in	5.83 in	7.6 in	8.66 in	Mechanical lock nut	97 lb
TTCLP-2002	200 ton	10,153 psi	1.77 in	6.1 in	7.87 in	9.65 in	Mechanical lock nut	125.7 lb
TTCLP-2502	260 ton	10,153 psi	1.77 in	6.26 in	8.03 in	10.83 in	Mechanical lock nut	163.1 lb
TTCLP-4002	400 ton	10,153 psi	1.77 in	7.01 in	8.78 in	13.78 in	Mechanical lock nut	295.4 lb
TTCLP-5002	520 ton	10,153 psi	1.77 in	7.56 in	9.33 in	15.75 in	Mechanical lock nut	416.7 lb

ToughTorq Hydraulic Cylinder Selection

Select the complete cylinder and hydraulic system around the load and available space

Confirm required lifting/pushing/pulling capacity and apply the appropriate engineering safety factor.

Confirm stroke, collapsed height, extended height, outside diameter, and available working clearance.

Select single-acting, double-acting, hollow-plunger, low-height, or lock-nut configuration as required.

Hollow-plunger models add a center-hole requirement for tensioning, pulling, or pass-through applications.

Lock-nut cylinders provide mechanical load-holding capability where published.

Ultra-low-height 1500 bar models require hydraulic components rated for their published system pressure.

Match pump, hose, couplers, gauge, control valves, and fittings to the selected cylinder pressure and connections.

Avoid unsupported side loading unless the selected cylinder explicitly publishes a side-load capability.