

Manual Torque Multiplier Series

Planetary mechanical torque multiplication for high-output industrial bolting.

Z Type - compact confined-space multiplier

Model	Max Torque	Nut A/F	Bolt Dia.	Ratio	Input	Output	Weight
TTM10W-4.5	738 ft-lb	S30-46	M20-30	4.5:1	1/2 in	1 in	5.7 lb
TTM20W-12	1,475 ft-lb	S32-55	M22-36	12:1	1/2 in	1 in	8.6 lb
TTM35W-15	2,581 ft-lb	S46-70	M30-45	15:1	1/2 in	1 in	12.1 lb
TTM55W-18.5	4,057 ft-lb	S55-80	M36-52	18.5:1	1/2 in	1-1/2 in	16.5 lb
TTM75W-20	5,532 ft-lb	S65-90	M42-60	20:1	1/2 in	1-1/2 in	22 lb
TTM100W-26.5	7,376 ft-lb	S80-105	M52-72	26.5:1	1/2 in	1-1/2 in	37.5 lb

L Type - offset multiplier geometry

Model	Max Torque	Nut A/F	Bolt Dia.	Ratio	Input	Output	Weight
TTM10F-5	738 ft-lb	S30-46	M20-30	5:1	1/2 in	1 in	5.7 lb
TTM20F-13.3	1,475 ft-lb	S32-55	M22-36	13.3:1	1/2 in	1 in	8.6 lb
TTM35F-16	2,581 ft-lb	S46-70	M30-45	16:1	1/2 in	1 in	12.1 lb
TTM55F-21.5	4,057 ft-lb	S55-80	M36-52	21.5:1	1/2 in	1-1/2 in	16.5 lb
TTM75F-24	5,532 ft-lb	S65-90	M42-60	24:1	1/2 in	1-1/2 in	22 lb
TTM100F-32	7,376 ft-lb	S80-105	M52-72	32:1	1/2 in	1-1/2 in	37.5 lb
TTM150F-50	11,063 ft-lb	S90-115	M60-80	50:1	1/2 in	2 in	55.1 lb
TTM200F-72	14,751 ft-lb	S105-135	M72-95	72:1	1/2 in	2 in	68.3 lb

Selection

Match required output torque, available input torque, fastener size, square drive, and reaction point.

Accessories

Input torque wrench | Impact-rated sockets | Reaction equipment | Storage and transport accessories