

PT Series Pneumatic Torque Guns

Continuous non-impact torque for repetitive industrial bolting.

AIR PRESSURE 6 bar	AIR CONSUMPTION 600 L/min max	NOISE <80 dBA	ACCURACY +/-5% std.	REPEATABILITY +/-1%
-----------------------	----------------------------------	------------------	------------------------	------------------------

Model	Torque Range (ft-lb)	Square (in)	Max Speed (rpm)	Weight (lb)	L (in)	E (in)	D (in)
PT05-350SS	74-369	3/4	50	8.8	6.7	7.3	2.4
PT10-700SS	111-738	3/4	28	10.6	9.8	7.3	2.9
PT15-1000SS	148-1,106	1	21	11.5	10.2	7.3	3.0
PT20-1500SS	221-1,475	1	15	12.1	10.2	7.3	3.0
PT30-2200SS	369-2,213	1	10	16.5	13.4	7.3	3.7
PT40-2900SS	516-2,950	1-1/2	7	20.9	13.4	7.3	3.8
PT60-4400SS	738-4,426	1-1/2	5	30.9	15.0	7.3	4.1
PT80-6000SS	1,475-5,900	1-1/2	4	39.7	15.0	7.3	4.4

Key features

- Continuous non-impact torque output
- Compact planetary gearbox
- Seven-vane high-performance air motor
- Single-hand forward/reverse control
- Full reverse torque for loosening
- Optional digital regulation:
- +/-3% accuracy, +/-1% repeatability

Typical applications

- Industrial flange bolting
- Power generation maintenance
- Oil & gas service
- Manufacturing and assembly
- Heavy equipment maintenance
- Shutdown and turnaround work