

# Data-Centric Approach For Blood Vessel Segmentation

Matthew Li

# Introduction

- Vasculature Common Coordinate Framework (VCCF)
- Manual label annotation is difficult!
- Current ML approaches do not generalize well (scan quality, variability in human anatomy)
- We propose a data processing pipeline that demonstrates strong generalization to unseen test data
- All visuals are original unless indicated otherwise

# Data

- Hierarchical Phase-Contrast Tomography (HiP-CT)

- Kidney 1 - **50 um/voxel**, densely segmented, 2278 slices
- Kidney 3 - **50.16 um/voxel**, densely segmented, 501 slices

Train

- Kidney 2 - **50 um/voxel**, sparsely segmented, 2217 slices

Validation

- Kidney 5 - **25.14 -> 50.28 um/voxel**, approx. 1000 slices
- Kidney 6 - **15.77 -> 63.08 um/voxel**, approx. 500 slices

Test

# Visualization


Kidney 3 – (1008, 9520)

[1]



Image

Label

Stacked



# Exploratory Data Analysis




# Key Takeaways

- Many fluctuations within each kidney (background noise, intensity)
- Kidneys are of different distribution (different resolution, scanning method)
- Very imbalanced dataset, hard to detect small vessels

# Preprocessing



[1]



# Architecture

- Model: Unet with SE-ResNeXt\_32x4d encoder
- Loss: Dice Loss
- Optimizer: AdamW
- LR Scheduler: OneCycleLR with max LR = 8e-5
- Epochs: 40

$$\text{Dice Loss} = 1 - \frac{2 \cdot y_{true} \cap y_{pred}}{y_{true} \cup y_{pred}} = \frac{2TP}{2TP + FN + FP}$$






# Inference/Postprocessing

- Test Time Augmentation (4 Rot, 2 Flip)
- Algorithmically determined 3D connected components to remove disconnected vessel predictions
- Then apply 3D flood fill to fix sparse predictions

Image



Truth



Prediction



Postprocessed



# Results

- Due to limited resources, we were not able to complete a full ablation study
- Strong augmentation and normalization were critical components in our pipeline, postprocessing provided small improvements
- After incorporating our pipeline, we got a final surface dice metric of 0.6017 on the test set

# Citations

1. Yashvardhan Jain, et al. (2023). SenNet + HOA - Hacking the Human Vasculature in 3D.
2. Ronneberger, O., Fischer, P., & Brox, T. (2015). U-Net: Convolutional Networks for Biomedical Image Segmentation.
3. Hu, J., Shen, L., Albanie, S., Sun, G., & Wu, E. (2019). Squeeze-and-Excitation Networks.
4. Xie, S., Girshick, R., Dollár, P., Tu, Z., & He, K. (2017). Aggregated Residual Transformations for Deep Neural Networks.
5. Sudre, C. H., Li, W., Vercauteren, T., Ourselin, S., & Jorge Cardoso, M. (2017). Generalised Dice Overlap as a Deep Learning Loss Function for Highly Unbalanced Segmentations
6. Van der Walt, S. et al., 2014. scikit-image: image processing in Python. PeerJ, 2, p.e453.
7. Seung Lab, (2024). Connected Components 3D.
8. Monigatti, L. (2023, December 4). A visual guide to learning rate schedulers in PyTorch. Medium. <https://towardsdatascience.com/a-visual-guide-to-learning-rate-schedulers-in-pytorch-24bbb262c863>