Evolve®



CUSTOMER NAME _____

PROJECT NAME _____

DATE _____ TYPE _____

CATALOG NUMBER _____

EALS Series
LED Outdoor Area Light

The EALS Area Light luminaire offers a wide range of optical patterns, color temperatures, lumen packages and mounting configurations to optimize area light applications, as well as provide versatility in lighting design within one form-factor. They are ideal for commercial property site-lighting applications such as retail and commercial exteriors.

Construction

Housing:	Aluminum die cast enclosure. Integral heat sink for maximum heat transfer
Lens:	Impact resistant tempered glass
Paint:	Corrosion resistant polyester powder paint, minimum 2.0 mil thickness Standard = Black, Dark Bronze Gray, White (RAL & custom colors available) Optional = Coastal Finish
Weight:	27 lbs

Optical System

Lumens:	7,000 - 50,000
Photometry:	Type II, III, IV & V
Efficacy:	118-177LPW
CCT:	2700K, 3000K, 4000K, 5000K
CRI:	≥70
Upward Light Output Ratio (ULOR):	0 Horizontal Orientation

Electrical

Input Voltage:	120-277V, 277-480V & 347-480V
Input Frequency:	50/60 Hz
Power Factor (PH):	≥ 0.9 at rated watts
Total Harmonic Distortion (THD):	≤ 20% at rated watts

Surge Protection

☐ 6kV/3kA ☐ 10kV/5kA ☐ 20kV/10kA

Per ANSI C136.2-2023

Lumen Maintenance

Projected Lxx per IES TM-21-11 at 25°C

OPTICS	LXX/50K) @ HOURS		
	25,000 HR	50,000 HR	60,000 HR
C2, C3, C4, C5 D2, D3, D4, D5 F2, F3, F4, F5	L99	L97	L96
H2, H3, H4, H5 J2, J3, J4, J5 K2, K3, K4, K5	L98	L96	L96
L2, L3, L4, L5 M2, M3, M4, M5	L96	L93	L91
N2, N3, N4, N5	L94	L85	L82

Note: Projected Lxx based on LM80 (> 17,000 hour testing). Accepted industry tolerances apply to initial luminous flux and lumen maintenance measurements

Luminaire Ambient Temperature Factor

AMBIENT TEMP (°C)	INITIAL FLUX FACTOR	AMBIENT TEMP (°C)	INITIAL FLUX FACTOR
10	1.02	30	0.99
20	1.01	40	0.98
25	1.00		

Ratings

Operating Temperature:	-40°C to 50°C (Nx Optic Codes are -40°C to 40°C)
Vibration: LM-79:	3G per ANSI C136.31-2010 Testing in accordance with IESNA Standards

Controls

Dimming:	Standard – 0-10V ☐ Optional – DALI (Option U) ☐
Sensors:	Photo Electric Sensors (PE) available LightGrid+™ and Daintree Compatible

Warranty

☐ 5 Year (Standard) ☐ 10 Year (Optional)

IP66 IK07

© 2025 Current Lighting Solutions, LLC. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

Evolve®

EALS Series
LED Outdoor Area Light

CUSTOMER NAME _____

PROJECT NAME _____

DATE _____ TYPE _____

CATALOG NUMBER _____

Ordering Information

EALS 04 _ _ _ _ _ _ _ _ 7 _ _ _ _ _ _ _ _ _ _ _ _

PRODUCT ID	GENERATION	VOLTAGE	OPTICAL CODE	DISTRIBUTION	CRI	CCT	DIMMING[1]	CONTROLS	MOUNTING ARM	COLOR	OPTIONS
E= Evolve ALs= Area Light S = Standard	04	0*=120-277V H* = 347-480V E*[2] = 277-480V 1 = 120V 2 = 208V 3 = 240V 4 =277V D = 347V 5 = 480V	Cx =7500K[3,19] Dx = 10000 lm/ft[4,19] Fx = 15000 lm Hx = 20000 lm Jx = 25000 lm Kx = 30000 lm Lx = 35000 lm Mx = 40000 lm Nx = 50000 lm	SM = Symmetric Medium SW = Symmetric Wide SH = Symmetric High Angle AF = Asymmetric Forward AH = Asymmetric High Angle AW = Asymmetric Wide AN = Asymmetric Narrow/Auto	7 = 70 (min)	27* = 2700K 30* = 3000K 40 = 4000K 50 = 5000K	N = Dimming thru PE receptacle D = External Dimming 18/2 3 ft Cable	A = ANSI C136.41 7-Pin Receptacle (No Control) D = ANSI C136.41 7-Pin Receptacle with Shorting Cap E* = ANSI C136.41 7-pin with Non-Dimming PE Control	C** = Integral Slipfitter: Standard D** = Universal Mounting Arm: Fitted for round or square pole mounting 4" min. square poles. K**,* = Knuckle Slipfitter: For 1.9 in. - 2.3 in OD Tenon S**,* = Knuckle Slipfitter: For 2.3 in. - 3.0 in OD Tenon V**,* = Knuckle Wall Mount	BLCK = Black GRAY = Gray WHTE = White DKBZ = Dark Bronze	F= Fusing H2 = Daintree (WHS-1120) enabled motion sensor.*,16 H4 = Motion Sensor (WattStopper) L = Tool-Less Entry J = cUL/Canada R = Enhanced Surge Protection (10kV/5kA) SL** = Rotated Left SR** = Rotated Right T = Extreme Surge Protection (20kV/10kA) UF = DALI Programmable V0 = 3 Position Terminal Block V** = Coastal Finish XXX = Special Options

1 Not Available with Fusing, Must Choose a Discrete Voltage with "F" Option Code
2 Note Standard Dimming is 0-10V
3 Not available in 277-480V
4 Supplied with 3ft leads
5 Supplied with 16/3 ft Cable
6 Restricted Aiming Angle of 0-45°
7 Compatible with LightGrid+™ Wireless Control Nodes, Not Compatible with Motion Sensor Control
8 Not available in 347V, 480V or 347-480V
9 Only available with F, H, J, K, L, M, N option
10 Recommended for installations within 750 feet from coast. Lead time varies, check with factory.
11 Select 2700K or 3000K CCT for DarkSky Approved fixtures.
12 For aimed left or right light distribution orientation, as assembled in manufacturing. Not applicable for Symmetric Distributions
13 DALI option not available with 347V, 480V, or 347-480V
14 Not available with 20kV/10kA SPD
15 When mounting fixtures at 90 degrees, round pole must be 3.5" OD minimum

© 2025 Current Lighting Solutions, LLC. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

Evolve®

EALS Series
LED Outdoor Area Light

CUSTOMER NAME _____

PROJECT NAME _____

DATE _____ TYPE _____

CATALOG NUMBER _____

TYPE	OPTIC CODE	DISTRIBUTION	TYPICAL INITIAL LUMENS			TYPICAL SYSTEM WATTAGE		BUG RATINGS		
			2700K	3000K	4000K & 5000K	120-277	347-480V	2700K	3000K	4000 & 5000K
TYPE V	C5	Symmetric Medium (SM)	6800	7340	7730	45	47	B3-U0-G1	B3-U0-G1	B3-U0-G1
	D5		9060	9790	10300	61		B3-U0-G2	B3-U0-G2	B3-U0-G2
	F5		13600	14680	15450	91		B4-U0-G2	B4-U0-G2	B4-U0-G2
	H5		18130	19570	20600	123		B4-U0-G2	B4-U0-G2	B4-U0-G2
	J5		22660	24460	25750	156		B4-U0-G2	B5-U0-G3	B5-U0-G3
	K5		27190	29360	30900	191		B5-U0-G3	B5-U0-G3	B5-U0-G3
	L5		31720	34250	36050	231		B5-U0-G3	B5-U0-G4	B5-U0-G4
	M5		36260	39140	41200	273		B5-U0-G4	B5-U0-G4	B5-U0-G4
	N5		45320	48930	51500	372		B5-U0-G4	B5-U0-G4	B5-U0-G4
	C5	Symmetric Wide (SW)	6930	7480	7880	45	47	B3-U0-G1	B3-U0-G1	B3-U0-G1
	D5		9240	9980	10500	61		B3-U0-G1	B3-U0-G1	B3-U0-G1
	F5		13860	14960	15750	91		B3-U0-G2	B3-U0-G2	B3-U0-G2
	H5		18480	19950	21000	123		B4-U0-G2	B4-U0-G2	B4-U0-G2
	J5		23100	24940	26250	156		B4-U0-G2	B4-U0-G2	B5-U0-G2
	K5		27720	29930	31500	191		B4-U0-G2	B4-U0-G2	B5-U0-G2
	L5		32340	34910	36750	231		B5-U0-G2	B5-U0-G3	B5-U0-G3
	M5		36960	39900	42000	273		B5-U0-G3	B5-U0-G3	B5-U0-G3
	N5		46200	49880	52500	372		B5-U0-G3	B5-U0-G4	B5-U0-G4
	C5	Symmetric High Angle (SH)	6600	7130	7500	45	47	B3-U0-G1	B3-U0-G2	B3-U0-G2
	D5		8800	9500	10000	61		B3-U0-G2	B3-U0-G2	B4-U0-G2
	F5		13200	14250	15000	91		B4-U0-G2	B4-U0-G2	B4-U0-G2
	H5		17600	19000	20000	123		B4-U0-G3	B4-U0-G3	B5-U0-G3
	J5		22000	23750	25000	156		B5-U0-G3	B5-U0-G3	B5-U0-G3
	K5		26400	28500	30000	191		B5-U0-G3	B5-U0-G3	B5-U0-G4
	L5		30800	33250	35000	231		B5-U0-G4	B5-U0-G4	B5-U0-G4
	M5		35200	38000	40000	273		B5-U0-G4	B5-U0-G4	B5-U0-G4
	N5		44000	47500	50000	372		B5-U0-G4	B5-U0-G5	B5-U0-G5

For additional information on Non-Shielded and Shielded EALS files, please refer to LED.com

© 2025 Current Lighting Solutions, LLC. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

PRAXIS3

100 Peachtree St NW
Suite 1450
Atlanta, GA 30303

404-875-4500 tel
www.praxis3.com

GEORGIA REGISTERED No. 043508 PROFESSIONAL ENGINEER RAHN ONEAL WILLIAMS

Copyright (c) 2024 Praxis3, LLC

All reports, plans, specifications, computer files, field data, notes and other documents and instruments prepared by Praxis3 shall retain all common law, statutory and other reserved rights, including copyright thereto.

This drawing may not be reproduced in whole or in part without written permission of Praxis3. It is to be returned upon request. Scales as stated are valid on the original drawings.

Rev	Date	Comments
	07/02/2026	PERMIT SET

Client:

FIFTH THIRD BANK

Project Number: 26032
Project Name:

FIFTH THIRD BANK WATSON 1,900 SF

2711 WATSON BOULEVARD
WARNER ROBBINS, GA 31093

Key Plan:

Sheet Title:

EXTERIOR LIGHTING CUTSHEETS

Sheet Number:

E-601

6/30/2026 2:32:08 PM