
Project Name _____ Qty _____

Type _____ Catalog / Part Number _____







## Photometric Summary

| | Delivered output (lm) | Intensity (peak cd) |
|---|---|---|
| **WW** | 3,634 | 10,795 |
| **8"x8"** | 4,512 | 59,238 |
| **10"x10"** | 4,410 | 33,872 |
| **10"x30"** | 4,586 | 25,296 |
| **10"x60"** | 3,876 | 12,062 |
| **10"x90"** | 4,077 | 6,927 |
| **15"x25"** | 4,346 | 19,773 |
| **30"x30"** | 4,730 | 16,886 |
| **30"x60"** | 4,035 | 5,317 |
| **35"x35"** | 4,612 | 11,616 |
| **50"x80"** | 4,656 | 3,904 |
| **60"x60"** | 3,868 | 3,368 |
| **80"x80"** | 4,548 | 2,992 |
| **90"x90"** | 4,070 | 2,132 |

Based on HO 40K full output, 4ft [1219mm].
DMX/RDM configuration.
2.5° factory-set tilt setting for WW optic, 0° tilt setting for all other optics.
Photometric performance is measured in compliance with IESNA LM-79-08.

## Optics




## Description

The Lumenfacade Inground is an LED luminaire designed for ground-recessed lighting applications, including asymmetric wall washing, grazing, and linear wayfinding. An innovative, plug and play design simplifies installation, protecting the system from water infiltration and ensuring long-lasting performance. Featuring second generation LED technology, the Lumenfacade Inground is available in four different sizes (12 in, 24 in, 36 in or 48 in), with a wide choice of outputs, color temperatures, color-mixing systems, optics and controls. A unique asymmetric wallwash distribution is also available, providing exceptional uniformity and brightness for walls and signage.

## Features

| | |
|---|---|
| **Construction** | Walk over compliant up to 500 kg in any type of ground, Walk over compliant up to 1000 kg in concrete |
| **Color and Color Temperature** | 2200K, 2700K, 3000K, 3500K, 4000K, Red, Green, Blue |
| **Length (nominal)** | 12 in, 24 in, 36 in, 48 in |
| **Optics** | Asymmetric wallwash, 8° x 8°, 10° x 10°, 10° x 30°, 10° x 60°, 10° x 90°, 15° x 25°, 30° x 30°, 30° x 60°, 35° x 35°, 50° x 80°, 60° x 60°, 80° x 80°, 90° x 90° |
| **Tilt Setting (factory set)** | 0 degrees, 2.5 degrees, 5 degrees, 20 degrees |
| **Optical Option** | Internal louver |
| **Options** | Anti-slip lens, CE (certification covers European Economic Area) |
| **Power Consumption** | 5 W/ft (meets ASHRAE standards for linear lighting on building facades - not available for 12 in fixture lengths), 8.5 W/ft (RO version), 15.25 W/ft (HO version). Typically 20% higher for 12 in fixture lengths |
| **Warranty** | 5-year limited warranty |



Specification Sheet

lumenfacade
Inground
LOI

WHITE AND STATIC COLORS

## Colors and Color Temperatures

2200K 2700K 3000K 3500K 4000K

Red Green Blue

## Controls

ON/OFF 0-10V DALI

lumentalk DMXrdm EcoSystem Enabled

## Ratings

IP68 IK10

## Certifications

## Performance

| | |
|---|---|
| **Maximum Delivered Output** | 4,730 lm (48 in fixture, 4000K, 30° x 30°, 0° tilt setting, DMX/RDM) |
| **Maximum Delivered Intensity** | 59,238 cd at nadir (48 in fixture, 4000K, 8° x 8°, 0° tilt setting, DMX/RDM) |
| **Illuminance at Distance** | Minimum 1 fc at 243 ft (48 in fixture, 4000K, 8° x 8°, 0° tilt setting, DMX/RDM) |
| **Color Consistency** | 2 SDCM, 3 SDCM (2200K) |
| **Color Rendering** | Minimum CRI 80 |
| **Lumen Maintenance** | L70 280,000 hrs, L95 35,000 hrs |

## Physical

| | |
|---|---|
| **Optical Chamber Material** | Aluminum |
| **Blockout Material** | Polymer recycled PVC reinforced with a stainless steel frame |
| **Trim Material** | Anodized aluminum |
| **Lens Material** | Tempered glass |
| **End Cap Material** | Die cast aluminum |
| **Hardware Material** | Stainless steel |
| **Weight** | 12 in: 7.5 lbs, 24 in: 15.3 lbs, 36 in: 21.4 lbs, 48 in: 27 lbs |

## Electrical and control

| | |
|---|---|
| **Voltage** | 120 to 277 volts |
| **Fixture Cable** | Power and data in one cable |
| **Leader Cable Conductor** | 5C #16-5 |
| **Connectors** | IP68 push-lock |
| **Control** | On/Off control, Lumentalk, 0-10V dimming, DALI dimming, Lutron® EcoSystem® Enabled dimming, DMX/RDM enabled |
| **Resolution (DMX/RDM)** | Per foot or per fixture (configured with LumenID V3 software), 8-bit or 16-bit |

## Environmental

| | |
|---|---|
| **Storage Temperature** | -40 °F to 185 °F (device must reach start-up temperature value before operating) |
| **Start-up Temperature** | -13 °F to 122 °F |
| **Operating Temperature** | -40 °F to 122 °F |
| **Ingress Protection Rating** | IP68 rated for up to 1 ft, not suitable for permanent immersion applications |
| **Impact Resistance Rating** | IK10 |

## Accessories (order separately)

| | |
|---|---|
| **Cables** | Lumenfacade Inground Leader Cable, Lumenfacade Inground Jumper Cable |
| **Electrical Accessories** | Lumenfacade Inground Junction Box |

lumenpulse™ 1220 Marie-Victorin Blvd., Longueuil, QC, J4G 2H9, CA info@lumenpulse.com www.lumenpulse.com T United States 617.307.5700 | Canada 1.877.937.3003 | 514.937.3003 www.lumenpulse.com/products/2556 F 514.937.6289

LMPG Inc., reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately
2022.12.19 copyright © 2022 LMPG Inc.
EM - R24



PRAXIS3

100 Peachtree St NW
Suite 1450
Atlanta, GA 30303

404-875-4500 tel
www.praxis3.com

GEORGIA REGISTERED No. 044560 PROFESSIONAL ENGINEER RAHN ONEAL WILLIAMS

Copyright (c) 2024 Praxis3, LLC

All reports, plans, specifications, computer files, field data, notes and other documents and instruments prepared by Praxis3 shall retain all common law, statutory and other reserved rights, including copyright thereto.

This drawing may not be reproduced in whole or in part without written permission of Praxis3. It is to be returned upon request. Scales as stated are valid on the original drawings.

| Rev | Date | Comments |
|---|---|---|
| | 07/02/2026 | PERMIT SET |

Client:

**FIFTH THIRD BANK**

Project Number: 26032
Project Name:

**FIFTH THIRD BANK WATSON 1,900 SF**

2711 WATSON BOULEVARD
WARNER ROBBINS, GA 31093

Key Plan:

Sheet Title:

**EXTERIOR LIGHTING CUTSHEETS**

Sheet Number:

**E-603**

6/30/2026 2:32:09 PM